**TECHNISCHE
UNIVERSITÄT
DRESDEN**

Fakultät Wirtschaftswissenschaften Lehrstuhl für BWL, insbes. Industrielles Management, Prof. Dr. Udo Buscher

Railway crew scheduling problems with attendance rates

Dissertation

to achieve the academic degree

Doctor rerum politicarum

(Dr. rer. pol.)

submitted to the Faculty of Business and Economics

Technische Universität Dresden

submitted by

Kirsten Hoffmann

Supervisor and first reviewer: Prof. Dr. rer. pol. Udo Buscher

Second reviewer: Prof. Dr. rer. pol. Rainer Lasch

Dresden, December 10th, 2019

Contents

List of Figures	IV
List of Tables	V
List of Algorithms	VII
List of Abbreviations	VIII
List of Symbols	X
1 Introduction	1
1.1 Motivation	1
1.2 Basics of railway crew scheduling	3
1.3 Purpose and research questions	5
1.4 Structure of this work	6
1.5 Research design	10
2 Large-scale optimization techniques	16
2.1 Column generation	16
2.2 Dantzig-Wolfe decomposition for linear programs	18
3 Railway crew scheduling: models, methods and applications	22
3.1 Introduction	23
3.2 Crew planning in railway operations	25
3.2.1 Crew management in strategic and tactical planning	25
3.2.2 Crew scheduling in operational planning	25
3.2.3 Real-time crew re-scheduling in disruption management	27
3.2.4 Technical terms of crew scheduling	28
3.2.5 Special characteristics of transportation modes	29
3.3 Overview of RCSP literature	32
3.3.1 Planning stage	32
3.3.2 Mode	33
3.3.3 Crew type	33

3.3.4	Model	34
3.3.5	Objective	34
3.3.6	Solution method	34
3.3.7	Country	35
3.4	Model formulations, objectives and constraints of RCSP	40
3.4.1	Model formulations	40
3.4.2	Objectives	44
3.4.3	Constraints	48
3.5	Solution methods	50
3.5.1	Integer programming methods	51
3.5.2	Heuristics	54
3.5.3	Column generation	56
3.5.4	Meta-heuristics	64
3.6	Conclusion and further research opportunities	67
3.7	Decision support tools and railway crew scheduling in practice	69
4	Schichtplanung von Zugbegleitpersonal unter Berücksichtigung von Prüf-	
	quoten	74
4.1	Einleitung	75
4.2	Planungsprozesse im Schienenpersonennahverkehr	76
4.3	Problembeschreibung	78
4.3.1	Klassifikation	79
4.3.2	Betriebliche und rechtliche Rahmenbedingungen	80
4.4	Modellierung als Set-Covering-Problem	81
4.5	Modellierung der Schichtplanung der Zugbegleiter mit Prüfquoten	83
4.6	Beispiel	84
4.7	Zusammenfassung und Ausblick	88
5	A hybrid solution approach for railway crew scheduling problems with at-	
	tendance rates	89
5.1	Introduction	90
5.2	Crew scheduling problem with attendance rates	90
5.3	Hybrid solution approach	92
5.4	Computational results	94
5.5	Conclusions and further research	95
6	Solving practical railway crew scheduling problems with attendance rates	97
6.1	Introduction	98
6.2	Related work	100

6.3	The crew scheduling problem with attendance rates	102
6.3.1	Analytics-based design	102
6.3.2	Problem description and practical requirements	103
6.3.3	Problem formulation	104
6.4	Solution approaches for the MCSPAR	107
6.4.1	A multi-period column generation algorithm	107
6.4.2	Solving the pricing problem	109
6.5	Artifact evaluation	112
6.5.1	Considered transport networks and experimental design	112
6.5.2	Evaluation and comparison of algorithms	114
6.6	Conclusions and further research	116
7	Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates	118
7.1	Introduction	119
7.2	Related work	121
7.3	Problem description and practical requirements	122
7.4	Arc flow formulation	124
7.5	Valid inequalities	130
7.5.1	Model specific valid inequalities	130
7.5.2	Symmetry breaking constraints	131
7.5.3	Parallel arcs	132
7.5.4	Fixed arcs	132
7.6	Computational results	133
7.6.1	Small-sized instances	134
7.6.2	Bounds for real-world instances	138
7.6.3	Improve heuristic solution	139
7.7	Conclusion	140
8	Conclusion	144
8.1	Summary	144
8.2	Future research	148
A	Declarations of authorship	151
	Bibliography	155

List of Figures

1.1	Number of passengers and transport performance in regional rail transport	1
1.2	Tactical planning process in regional rail passenger transport	4
1.3	Structure of this thesis	7
1.4	Research onion adapted from SAUNDERS/LEWIS/THORNHILL (2016)	14
3.1	Number of publications on RCSP by year	24
3.2	Number of publications on RCSP by journal or type	25
3.3	Operational planning process in passenger railway transportation	26
3.4	Number of publications by model formulation for RCSP	40
3.5	Number of publications on RCSP by solution methods	51
4.1	Verkehrsaufkommen in Deutschland (Quelle: DEUTSCHES INSTITUT FÜR WIRTSCHAFTSFORSCHUNG DIW BERLIN (2013))	75
4.2	Planungsprozess im Schienenpersonennahverkehr	77
4.3	Klassifikation der Trips in Quotenklassen	80
4.4	Beispielnetz mit Strecken- und Zeitdistanzen	85
4.5	Schichtplan für Regionalexpresszüge des Beispielfalls	87
4.6	Schichtplan für Regionalbahnzüge des Beispielfalls	87
4.7	Schichtplan für Beispielfall unter Zuhilfenahme des neuen Modells	88
5.1	Hybrid solution approach	93
6.1	Planning process	99
6.2	Flowchart of proposed multi-period column generation algorithm	108
6.3	One-point crossover	111
6.4	Structure and size of the considered regional transport networks	113
7.1	Planning process	119
7.2	Example graph with trip, source, sink, waiting and sink-source arcs	126
7.3	Arc with resource parameters and variables	126
7.4	Mean computation times depending on selected sets of inequalities	135

List of Tables

1.1	Number of passengers in millions, transport performance in billions of passenger-kilometers, number of train drivers and conductors of DB Regio AG from 2012 to 2018.	2
1.2	Design-science research guidelines by HEVNER et al. (2004, p. 83)	12
3.1	Special characteristics of different railway transportation modes	30
3.2	Overview of RCSP literature	36
3.3	Overview of integer programming methods in RCSP	53
3.4	Overview of column generation approaches in RCSP	61
3.5	Overview of meta-heuristics in RCSP	65
4.1	Mögliche rechtliche und tarifliche Restriktionen der Schichtplanung	81
4.2	Beispielfahrplan mit Regionalexpress- und Regionalbahnlinien	85
5.1	Computational results of the two-phase approach	94
5.2	Computational results of the hybrid approach (selection)	95
6.1	Legal and contractual requirements concerning duties	104
6.2	Sets, decision variables and parameters used	105
6.3	Computational results for Transport Networks I and II	115
6.4	Analysis of average computation times for Network III	116
7.1	Legal and contractual requirements	123
7.2	Definition of resources t_{ij} , s_{ij} , b_{ij} depending on the type of arc	125
7.3	Sets and parameters	127
7.4	Sets of valid inequalities	133
7.5	Instances	134
7.6	Small-sized instances	136
7.7	Computation times for small-sized instances (extract)	137
7.8	Best computation times for small-sized instances	138
7.9	Deviation of the linear relaxation value and computation times without and with valid inequalities	139

7.10	Best objective values, best bounds and gaps at the beginning and after 24 h	139
7.11	Mean computation times for all small-sized instances	141

List of Algorithms

2.1	Column generation	17
6.1	Genetic algorithm	110

List of Abbreviations

ACO	Ant colony optimization
B&B	Branch-and-bound
B&P	Branch-and-price
C	Conductor
CB	Crew bases
CEwIPM	Complete enumeration of all duties with integer programming methods
CG	Column generation
CR	Crew rostering
CP	Constraint programming
CS	Crew scheduling
CSP	Crew scheduling problem
CSPAR	Crew scheduling problem with attendance rates
CUS	Cuckoo search
D	Driver
DG	Duty generation
DP	Dynamic programming
DSP	Duty set pricing
EA	Evolutionary algorithm
F	Freight transportation
F&R	Fit-and-relax
GA	Genetic algorithm
H	Heuristics
IPM	Integer programming methods
IP	Integer programming
IT	Idle time
Iter	Iterations
LD	Long distance transportation
LP	Linear programming
MCSPAR	Multi-period crew scheduling problem with attendance rates
MH	Meta-heuristics

MP	Master problem
na	not available
ND	Number of duties
NFP	Network flow problem
NS	Neighborhood search
Obj.	Objective value
PP	Pricing problem
R	Regional transportation
RB	Regionalbahn
RCSP	Railway crew scheduling problem
RE	Regionalexpress
RMP	Restricted master problem
Rob.	Robustness
RP	Relief points
RSS	Rolling stock scheduling
S	Simulation
SA	Simulated annealing
Satisf.	Employee satisfaction
Schedule eff.	Schedule efficiency
SCP	Set covering problem
SD	Standard deviation
SE	Simulated evolution algorithms
SG	Security guard
SPNV	Schienenpersonennahverkehr
SPP	Set partitioning problem
SPPRC	Shortest path problem with resource constraints
TC	Total cost
Trans.	Transition time
TS	Tabu search
TT	Train timetabling
U	Urban transportation
VI	Valid inequalities
VRP	Vehicle routing problem
WRO	Window of relief opportunities

List of Symbols

Chapter 2

A	Constraint matrix
$\mathcal{A}$	Set of columns
a_{ij}	Coefficient of constraint matrix A in row i and column j
a^j	j -th column of A
a^p	Vector, $a^p = Ax^p$
a^r	Vector, $a^r = Ax^r$
$\mathcal{B}$	Convex polyhedron
b	Vector, right hand side of constraints
b_i	Right hand side of constraint i
$c(a)$	Cost function, function of column a
c_j	Cost coefficients of x_j
$\bar{c}_p$	Reduced cost of variable λ_p
$\bar{c}^*$	Least reduced cost
D	Constraint matrix
$\mathcal{D}$	Convex polyhedron
d	Vector, right hand side of constraints
k_p	Cost coefficient of λ_p
k_r	Cost coefficient of μ_r
M	Set of constraints
m_1	Integer, dimension of first constraint set
m_2	Integer, dimension of second constraint set
N	Set of variables
N'	Subset of N
n	Integer, dimension of variable set
P	Set of extreme points
R	Set of extreme rays
x	Vector of decision variables, primal solution
x_j	Decision variable, $j \in N$

x^p	Extreme point p
x^r	Extreme ray r
x_s	Variable with least negative reduced cost
λ_p	Decision variable, $p \in P$
μ_r	Decision variable, $r \in R$
π	Vector of decision variables, dual solution
π_0	Dual value
π_i	Dual value of constraint i

Chapter 3

A	Binary matrix
a_{ij}	Binary parameter such that $a_{ij} = 1$, if duty j covers trip i , 0 otherwise
$C_{\text{deadheading}}$	Cost for deadheading
$C_{\text{idle time}}$	Cost for idle time
C_{layover}	Cost for layover
$C_{\text{paid break time}}$	Cost for paid break time
C_{total}	Total cost
$C_{\text{working time}}$	Cost for working time
c_{ij}	Cost associated with arc (i, j)
c_j	Cost of duty j
D	Set of driver
(i, j)	Arc
M	Set of trips
N	Set of duties
$\tilde{N}$	Set of nodes
s	Source node, $s \in N$
t	Sink node, $t \in N$
x_{ij}^d	Binary decision variable such that $x_{ij}^d = 1$, if arc (i, j) is served by driver d , 0 otherwise
x_j	Binary decision variable such that $x_j = 1$, if duty j is part of the solution schedule, 0 otherwise
y_i^d	Binary decision variable such that $y_i^d = 1$, if node i is served by driver d , 0 otherwise

Chapter 4

A	Adjazenzmatrix
a_{ij}	Binärer Parameter, der beschreibt ob Trip i in Schicht j enthalten ist ($a_{ij} = 1$) oder nicht
c_{fix}	Fixkosten je Schicht
c_{var}	Kosten je Arbeitsminute
d_i^g	Streckenkilometer des Trips i in der Klasse g
G	Menge der Quotenklassen
M	Menge der Trips
N	Menge aller zulässigen Schichten
q^g	Quote der Quotenklasse g
s^g	Kumulierte Streckenkilometer aller Trips der Klasse g
t_j	Arbeitsminuten der Schicht j
x_j	Binäre Entscheidungsvariable, die beschreibt ob Schicht j in der Lösung ist ($x_j = 1$) oder nicht
y_i	Binäre Entscheidungsvariable, die beschreibt ob Trip i in der Lösung ist ($y_i = 1$) oder nicht

Chapter 5

A	Binary matrix
a_{ij}	Binary parameter such that $a_{ij} = 1$, if duty j covers trip i , 0 otherwise
c_j	Costs of duty j
d_{ig}	Distance of trip i with attendance rate g
G	Set of attendance rates
M	Set of trips
N	Set of duties
x_j	Binary decision variable such that $x_j = 1$, if duty j is part of the solution schedule, 0 otherwise
y_i	Binary decision variable such that $y_i = 1$, if trip i is covered in solution schedule, 0 otherwise

Chapter 6

a_{ij}	Assignment parameter such that $a_{ij} = 1$, if duty j covers trip i , 0 otherwise
b_{je}	Assignment parameter, such that $b_{je} = 1$ if duty j starts at crew base e , 0 otherwise
C_e	Maximum number of duties starting at crew base e
c_j	Costs of duty j
$\bar{c}_j$	Reduced costs of duty j
d_{ig}	Distance of trip i with attendance rate g
E	Set of crew bases
G	Set of attendance rates
K	Set of all days of the planning horizon
M	Set of trips
M_k	Subset of M with all trips i valid on day k
N	Set of duties
N_k	Subset of N with all duties j on day k
O	Set of mandatory trips i on day k as pair (i, k)
q_g	Attendance rate g
t_j	Paid time of duty j
t_{CPU}	Computation time
$t^{\max}$	Maximum average paid time of all duties
$t^{\min}$	Minimum average paid time of all duties
x_j	Binary decision variable such that $x_j = 1$, if duty j is in solution, 0 otherwise
y_{ik}	Binary decision variable such that $y_{ik} = 1$, if trip i on day k is in solution, 0 otherwise
Δ_{Obj}	Percentage deviation of the solution values
π_{ik}	Dual value of trip i on day k
ρ_1, ρ_2	Dual values
σ_e	Dual value of crew base capacity constraint e

Chapter 7

A	Set of arcs of G
b_{ij}	Possible break time of arc (i, j)
ba_{ic}	Accumulated break time at node i for conductor c
C	Set of conductors
C_q	Maximum number of duties starting at crew base q
c^{fix}	Fixed costs per duty
c^{var}	Variable costs per minute
D	Set of attendance rates
d_{ijg}	distance of trip arc (i, j) with attendance rate g
E	Set of crew bases
F	Set of trip arcs
G	Graph
(i, j)	Arc
M	Set of unique trips
$P_1, \dots, P_L$	Set of trip arcs with attendance rate 100% running parallel
$P_1, \dots, P_N$	Set of trip arcs running parallel
$\bar{P}$	Set of $P_1, \dots, P_L$ with maximum cardinality
Q	Set of sources
R	Set of sink-source arcs
S	Set of sinks
$S1, \dots, S7$	Sets of valid inequalities
s_{ij}	Protected working time of arc (i, j)
s^{max}	Maximum protected working time
sa_{ic}	Accumulated protected working time without break times at node i for conductor c
$t_1^{\text{end}}, t_2^{\text{end}}$	End time of arc 1 or 2
$t_1^{\text{start}}, t_2^{\text{start}}$	Start time of arc 1 or 2
t_{ij}	Duty time of arc (i, j)
t^{max}	Maximum duty time
$\bar{t}^{\text{max}}$	Maximum average paid time of all duties
$\bar{t}^{\text{min}}$	Minimum average paid time of all duties
ta_{ic}	Accumulated duty time at node i for conductor c
u_c	Binary decision variable such that $u_c = 1$, if protected working time of conductor c is > 360 , 0 otherwise
V	Set of nodes of G

v_c	Binary decision variable such that $v_c = 1$, if protected working time of conductor c is > 540 , 0 otherwise
w_{ijc}	Binary decision variable such that $w_{ijc} = 1$, if conductor c takes a break between node i and j , 0 otherwise
x_{ijc}	Binary decision variable such that $x_{ijc} = 1$, if conductor c uses arc (i, j) , 0 otherwise
y_{ij}	Binary decision variable such that $y_{ij} = 1$, if trip arc (i, j) is in solution, 0 otherwise
τ_1, τ_2	Trips

1 Introduction

1.1 Motivation

In Germany, the number of passengers and the transport performance in regional and long-distance rail passenger transport increase constantly over the last decades (see Figure 1.1 for regional rail transport). For example, the number of passengers carried in regional rail passenger transport rose from 1.96 billion in 2004 to 2.72 billion in 2018. This represents an increase of almost 39%. However, it is becoming increasingly difficult for railway companies to cover the required transport services by drivers and conductors due to the shortage of skilled workers. This implies that a greater transport performance must be achieved with fewer resources, thus resource-saving and at the same time cost-efficient planning of personnel is essential.

Figure 1.1: Number of passengers and transport performance in regional rail transport¹

DB Regio AG, subsidiary of Deutsche Bahn (the biggest German railway operator), operates passenger trains on short and medium distances in Germany and holds a market share of 74% of the transport performance (in passenger-kilometers) in 2017 (see

¹ Figure is based on data extracted from STATISTISCHES BUNDESAMT (DESTATIS) (2019, p. 8).

BUNDESNETZAGENTUR (2019, p.115)). Table 1.1 illustrates that from 2012 to 2018 an increasing number of passengers transported by DB Regio AG from 1.393 billion to 1.426 billion is offset by a decreasing number of train drivers from 9,788 to 9,542 and conductors from 4,520 to 4,205 respectively.

Table 1.1: Number of passengers in millions, transport performance in billions of passenger-kilometers, number of train drivers and conductors of DB Regio AG from 2012 to 2018.²

Year	Passengers (in billions)	Number of	
		train drivers	conductors
2012	1.393	9,788	4,520
2013	1.410	9,726	4,395
2014	1.425	9,619	4,307
2015	1.400	9,550	4,271
2016	1.383	9,471	4,246
2017	1.426	9,490	4,303
2018	1.426	9,542	4,205

Another reason to focus on railway crew scheduling is the share of personnel costs in the total expenditure of a railway company. Based on the profit and loss account of the area of transport (providing transport services) of DB Regio AG for 2018 (see DB REGIO AG (2018), p. 52), it is evident that the cost of materials, at EUR 4,257 million, is the largest cost item before personnel expenses at EUR 1,089 million, depreciation at EUR 494 million as well as other operating expenses at EUR 425 million. In descending order of magnitude, the cost of materials is comprises the cost of purchased services such as infrastructure, cleaning, security and winter services at EUR 3,008 million, maintenance at EUR 783 million as well as energy at EUR 466 million. The cost item depreciation relates 99% to passenger transport vehicles. Accordingly, the biggest cost driver for DB Regio AG is the use of infrastructure followed in descending order by personnel costs, maintenance, depreciation for vehicles and energy. Despite the fact that these values are company-specific, the ratio of cost factors will be similar for other railway operators. Since the costs for infrastructure, vehicles and energy can only be influenced by the company to a limited degree, personnel costs are an important factor for corporate success.

In addition to the increasing cost pressure and a growing number of competitors in the railway sector, the elimination of operational tasks in shift schedules of conductors due to progressive automation is leading to the introduction of attendance rates. This means

² Figures are based on data extracted from the annual reports of DB Regio AG from 2012 to 2018 (DB REGIO AG (2012), DB REGIO AG (2013), DB REGIO AG (2014), DB REGIO AG (2015), DB REGIO AG (2016a), DB REGIO AG (2017), DB REGIO AG (2018)).

that it is no longer necessary or reasonable to assign a conductor to each train. Therefore, only a certain proportion of trains or train kilometers of the transport network is required to be attended. The definition also allows attendance rates of, for example, 200%, i.e. each train is attended by two conductors (e.g. due to high passenger volume or safety aspects). As described in this paragraph, these rates are indispensable in practice for conductors of regional trains, which is why the focus of this work is on crew scheduling for conductors in regional rail passenger transport. However, train drivers can also be represented with rates of 100%.

Due to the size and complexity of crew scheduling problems for train drivers and conductors, practice planning is supported by suitable software tools. Usually, experienced personnel planners provide the required data and make necessary manual adjustments. However, attendance rates for conductors have not yet been integrated into any solution method or planning tool known to us. Therefore, high manual planning effort necessitates the definition of a suitable model and implementation of a solution algorithm with the help of operations research methods.

1.2 Basics of railway crew scheduling

Railway crew scheduling is one of the major planning steps in regional rail passenger transport. The general tactical planning process is illustrated in Figure 1.2 and starts with the specification of offered services (*requirements determination*). On the basis of predicted travel demand, *line planning* designs lines, groups them to different transport networks and specifies the frequencies of trains that run on different lines (CAPRARA et al. (2007, pp.133–134)). Thereafter the *timetabling* process determines departure and arrival times at each track section and station ensuring all relevant safety constraints (KASPI/RAVIV (2013, pp.295–296)). The assignment of train journeys derived from the timetable to anonymous trains in a conflict-free and resource-efficient way is the key task of *rolling stock scheduling*. The required type and capacity of rolling stock units play an important role here. Closely related and often integrated in the previous step is *maintenance planning*, where services like cleaning, vehicle repair and refueling are considered. Finally, *crew scheduling* aims for generating crew duties for train drivers and conductors. The goal is to assign all trips (smallest unit of a train journey) of a given transport network to anonymous crew members at minimum costs.

Among others, rolling stock scheduling and crew scheduling are refined in the following operational planning process. Rolling stock scheduling is followed by *rolling stock circulation*, in which vehicle rotations are assigned to specified trains fulfilling operational and contractual requirements. *Vehicle disposition* includes short-term changes related

to, e.g., vehicle breakdown, construction sites or bad weather. Similarly, *crew rostering* assigns anonymous duties to individual crew members considering their working time accounts and vacancies. Unpredictable or short-term changes, like sickness notifications or operational interruptions, are managed in *crew disposition*.

Figure 1.2: Tactical planning process in regional rail passenger transport

In Germany, a division of these planning tasks can be observed due to the rail reform in 1994 (REINHARDT (2018, pp.126–143), SCHWEDES (2018, pp.349–352)). Since the beginning of 1996, regional rail passenger transport has been regionalized, i.e. the responsibility for tasks and finances for regional, suburban and urban passenger transport has been transferred from the federal government to the federal states. This means that the public authorities, such as federal states or subsidiary transportation authorities, invite to tender for rail passenger transport services for which railway companies can submit an offer. Therefore, requirements determination, line planning and timetabling is the responsibility of transport associations (light coloring in Figure 1.2), whereas the tasks of rolling stock scheduling, maintenance planning and crew scheduling are carried out by the railway company (dark coloring in Figure 1.2).

This work focuses on crew scheduling for conductors, in which trips have to be combined to form anonymous duties for conductors. Thereby a *trip* is the smallest unit of a certain train journey from one relief point to the subsequent one characterized by a departure time, a departure station, an arrival time as well as an arrival station. *Relief points*, usually a subset of all stations in the transport network, are stations where a change of trains is viable for conductors. Combining single trips leads to a *duty* that must satisfy several conditions. First of all, there are legal requirements and specifications from labor contracts, such as the maximum and average paid duty time, maximum working time and very complex break regulations. Furthermore, operating conditions including the symmetry of duties, compatibility of two consecutive trips concerning time as well as place and capacity of home depots must be observed. The last group of requirements are claims under the concluded transportation contract of the specific transport network. In addition to, e.g., frequencies of trips and vehicle types, the transportation contract regulates the attendance rates. These *attendance rates* are usually calculated as the ratio between the cumulated kilometers attended by conductors and the total kilometers (attended and unattended) of the entire network. Attendance rates can vary depending on product types, lines, route sections or time windows. For example, a transportation contract can request an attendance rate of 25% for regional trains, 50% for

regional expresses and from 7 p.m. until the end of the day 100% for both product types. The crew scheduling process results in a *shift schedule* including all duties that cover all required trips of the transport network.

Therefore, the railway crew scheduling problem with attendance rates (CSPAR) is to find a minimum cost shift schedule satisfying legal requirements, specifications from labor contracts and operating conditions. This schedule should cover a subset of all trips such that the attendance rates specified in the transportation contract are met.

1.3 Purpose and research questions

This work aims to develop a solution concept for optimized and automated railway crew scheduling, especially ensuring attendance rates for conductors in regional trains. Since there already exists a variety of publications concerning modeling approaches and solution methods related to railway crew scheduling, the first step is to identify and classify relevant literature. This is necessary to determine suitable mathematical formulations and solution approaches which can also be used or further modified for the special case of railway crew scheduling problems with attendance rates for conductors. By systematizing the reviewed articles according to model formulations, objectives, constraints and solution methods, research gaps can easily be identified and opportunities for further research can be revealed.

After an analysis of the given legal requirements, regulations from labor contracts, operating conditions and claims under transportation contracts, a first mathematical model has to be developed which represents the given problem with attendance rates for conductors. In order to first analyze the effect of the new constraints on attendance rates, further requirements necessary in practice can be omitted (e.g. personnel capacity at crew bases) and the planning horizon can be limited to one day.

After modeling the problem with further requirements, a suitable solution approach has to be established which, above all, guarantees the solvability of large real-world instances. The generated shift schedules have to meet legal, contractual and operational requirements and thereby minimize the resulting costs.

Since in practice a planning period of one day is neither operationally reasonable nor cost-efficient, the next goal is to extend the planning period to several days. This extension should affect both the model and the developed solution approach. This allows further restrictions concerning several days to be integrated, such as the uniform distribution of attended trips.

In research, it is important to establish comparability or an assessment of the quality of the model or solution method. For this reason, an arc-flow formulation of the crew

scheduling problem with attendance rates should be formulated to solve small-sized instances optimally and provide lower bounds for real-world instances. To accelerate and improve the arc-flow formulation solution, the application of valid inequalities will be validated.

The purpose of this work derived from the above mentioned objectives can be summarized into five research questions on railway crew scheduling with and without attendance rates for conductors:

- Q1** What is the current state of research for railway crew scheduling problems and which research gaps can be identified?
- Q2** How can railway crew scheduling problems with attendance rates for conductors be modeled?
- Q3** How can instances of railway crew scheduling problems with attendance rates be solved with regard to real-world requirements?
- Q4** How can the developed mathematical model and hybrid solution approach be extended to a multiple day period? What is the potential of an integrated approach in contrast to the sequential day-by-day approach?
- Q5** Can an arc-flow formulation of the railway crew scheduling problem with attendance rates be used to evaluate or even enhance the solution quality of the previous approach? Can valid inequalities improve the performance of the arc-flow formulation concerning computing times and lower bounds?

1.4 Structure of this work

As illustrated in Figure 1.3 this work consists of eight chapters that focus on problem specific aspects of railway crew scheduling, especially with attendance rates for conductors. Five of these eight chapters are main chapters, each of which representing published manuscripts by the author. The figure also depicts the bi-partition of the individual chapters of this work and the connections between them.

After emphasizing the importance of the topic as well as purpose and research design of this work in Chapter 1, Chapter 2 gives a brief introduction to the mathematical basics of large-scale optimization problems (e.g. column generation, Dantzig-Wolfe decomposition).

Figure 1.3: Structure of this thesis

Chapter 3 provides a comprehensive review on railway crew scheduling literature answering research question **Q1**.³ The basis of the review is the characterization of railway crew planning including strategic, tactical, operational and real-time planning steps and the differences between transportation modes. Therefore, 123 articles on railway crew scheduling published since 2000 are classified according to planning stage, transportation mode, crew type, model formulations, objectives, constraints and solution methods. The most frequently used model formulations (set covering/set partitioning problems, network flow problems), objectives (schedule efficiency, robustness, employee satisfaction) and solution methods (integer programming methods, heuristics, column generation, meta-heuristics) are presented in detail and various characteristics are discussed using suitable references. Finally, we conclude with some possible directions and opportunities for further research.

Chapter 4 presents a broad definition of operating conditions, legal requirements and regulations from labor as well as transportation contracts, which must be considered in the context of railway crew scheduling problems. The development from the standard set-covering model favored in the literature to the modified set-covering formulation, which also integrates attendance rates, is described in detail. Afterwards two solution approaches are compared using a small sample instance. The first method corresponds to the semi-manual procedure of the personnel planner, in which an optimal solution for attendance rates of 100% is generated. Subsequently, the minimum cost subset of duties covering the required attendance rates, e.g. 30%, is used. The second approach generates a cost-optimal solution of the proposed set covering formulation with attendance rates. Both approaches generate all feasible duties in advance and select the final optimal shift schedule using a mathematical solver, here the IBM ILOG CPLEX Optimization Studio. This provides an answer to the first part of research question **Q2**.⁴

Since a pre-generation of all potential duties is not efficient and not even possible for most real-world instances, research question **Q3** has to be answered. Chapter 5 presents a hybrid solution approach consisting of a column generation framework based on the previously defined model. The model is decomposed into a master problem and a pricing problem (PP). In the restricted master problem (RMP) the linear programming relaxation of the model is solved with respect to a small subset of all feasible duties using a mathematical solver (here Gurobi Optimizer). New cost-improving duties are added iteratively solving the pricing problem by a specialized genetic algorithm until no

³ This chapter corresponds to HEIL, J./HOFFMANN, K./BUSCHER, U. (2019): Railway crew scheduling: Models, methods and applications. In: *European Journal of Operational Research* Vol. 2019, Available online June 12, 2019.

⁴ This chapter corresponds to HOFFMANN, K. (2014): Schichtplanung von Zugbegleitpersonal unter Berücksichtigung von Prüfquoten. In: KUNDISCH, D./SUHL, L./BECKMANN, L. (Eds.): *Tagungsband MKWI 2014*. Paderborn University, pp.1458–1470.

more such duties are found. The characteristics (fitness function, replacement scheme, termination criterion) and the individual operators (selection, crossover, mutation) of the developed genetic algorithm are specifically adapted to the duty generation problem. Based on a real-world instance, a comparison of the hybrid approach and a simple two-phase approach is drawn with respect to resulting total costs and computation time.⁵

Since it is important and useful in practice to consider a longer planning period as basis for personnel planning (e.g. two weeks), both the developed mathematical model and the hybrid solution approach are extended to a multiple day period in Chapter 6.⁶ Business analytic methods are applied in order to offer an approach to transform real-world data to concrete operational decision support. The focus is on the analysis step using the developed modified set covering model with several essential restrictions integrated for the first time, e.g., capacity of crew bases, mandatory trips or a uniform distribution of the attended trips over the planning horizon. With the help of a case study of three real-world instances the artifact is evaluated. It is shown that the multiple day hybrid solution approach is able to solve the problem more effectively and efficiently compared to the sequential day-by-day approach used in practice. This successfully answers research question **Q4**.

The implementation of CSPAR as a specified set covering model represents a path-flow formulation of the problem, i.e. the decision variables represent paths of a network, in our case duties. This formulation is only an exact representation of the problem if all paths are known in advance. For problems of practical relevance, it is usually not possible or only possible with high computational effort to provide the set of all feasible duties. Even by using column generation techniques, in the best case only an optimal solution for the linear programming (LP) relaxation of CSPAR can be provided. For this reason, Chapter 7 presents an exact arc-flow formulation of CSPAR to solve small-sized instances optimally, improve solutions of real-world instances and provide good lower bounds for them (see research question **Q5**).⁷ In addition, various valid inequalities are defined, which offer the possibility to fasten the solution process and improve the bound of the LP relaxation of CSPAR. Their influence on computation times as well as bounds of the LP relaxation are estimated.

In Chapter 8, a summary of gained insights, assessment of benefits and open issues of

⁵ This chapter corresponds to HOFFMANN, K. (2017): A Hybrid Solution Approach for Railway Crew Scheduling Problems with Attendance Rates. In: DOERNER, K. et al. (Eds.): *Operations Research Proceedings 2015*. Springer International Publishing, pp. 243–250.

⁶ This chapter corresponds to HOFFMANN, K. et al. (2017): Solving Practical Railway Crew Scheduling Problems with Attendance Rates. In: *Business & Information Systems Engineering*, Vol. 59, pp. 147–159.

⁷ This chapter corresponds to HOFFMANN, K./BUSCHER, U. (2019): Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates. In: *Computers & Industrial Engineering*, Vol. 127, pp. 1143–1152.

the presented mathematical models and hybrid solution approaches are given, followed by a discussion of the research questions established in Section 1.3. Furthermore, interesting directions for future research are derived and clarified.

1.5 Research design

The disciplines of science can be distinguished in various ways. A common distinction of the branches of science is formal science (studying formal language disciplines concerned with formal systems), natural science (description, prediction, and understanding of natural phenomena) and social science (studying the society and the relationships among individuals within a society) (BUNGE (1985, p.1), JOHANNESSON/PERJONS/BIDER (2013, pp.2–3)). In each individual scientific discipline, in most cases a differentiation can be made between basic research and applied research. Whereas basic research is driven by a scientist’s curiosity and aims at acquire knowledge, applied research uses existing scientific theories to develop practical applications (ROLL-HANSEN (2009, pp.4–6)). For such an overarching topic, it is difficult to establish a unified and clearly delimited definition of the various branches of science.

However, this work is based on the classification of science according to AKEN (2004, p.224). He distinguishes the scientific disciplines in *formal sciences* (e.g. philosophy and mathematics), *explanatory sciences* (e.g. natural sciences and major sections of social sciences) and *design sciences* (e.g. engineering sciences and medical science). Formal sciences build systems of propositions aiming to be internally logically consistent. “True” propositions should be the result of explanatory sciences that describe, explain and possibly predict observable phenomena in their field. However, understanding a problem is just the first step to solving it. The necessary second step is to develop and test a solution. This kind of science can be summarized as design sciences. Its goal is to develop knowledge for the design and realization of artifacts as well as to analyze the performance of these artifacts with various rigorous methods (AKEN (2004, p.224), MANSON (2006, pp.160f.)).

The research of this thesis consists of the development of models and solutions for crew scheduling problems of conductors including attendance rates. It leads to a first prototypical decision support tool for personnel planners of railway operators. Since different artifacts are developed and evaluated, this research can be classified as design science. Going further into depth, an assignment of this work to operations research is obvious. Operations research deals with the development and application of quantitative models and methods for decision support and is characterized by the cooperation of applied mathematics, economics and computer science.

HEVNER et al. (2004, p. 77) describe design science in information system research as research that creates and evaluates artifacts intended to solve identified organizational problems. Thereby, artifacts in information technology are constructs (vocabulary and symbols), models (abstractions and representations), methods (algorithms and practices) and instantiations (implemented and prototype systems). According to MANSON (2006, p. 160), this kind of research definition and concept is also applicable to operations research.

Regardless of which scientific field a researcher belongs to, it is important to understand the theoretical assumptions and beliefs about the development of knowledge in their field (research philosophy). In most of the literature, positivism and interpretivism are mentioned as main streams of research (VAISHNAVI et al. (2019, pp. 8–10)), although some authors disagree with this distinction (WEBER (2004)). To understand the research philosophy of the design science approach, positivism, interpretivism and design-science research philosophy are compared according to the meta-theoretical assumptions of *ontology* (nature of reality or being), *epistemology* (what constitutes acceptable knowledge), *axiology* (role of values) and methodology in, for example, MANSON (2006, pp. 166–169) or VAISHNAVI et al. (2019, pp. 8–10). Below only a short differentiation of the three selected research philosophies is given.

Positivism Positivist research assumes that there exists one true reality that is separate and independent. This implies that the researcher and the observed phenomenon are two separate things and the observation is objective (MANSON (2006, pp. 166–169)). Knowledge is gained by scientific methods or by observable and measurable facts. Typical methods a positivist uses are deductive, for example highly structured and large samples or quantitative methods of analysis (SAUNDERS/LEWIS/THORNHILL (2016, p. 136)).

Interpretivism In contrast to positivism, interpretivism assumes that reality and the individual observing it cannot be separated (MANSON (2006, pp. 166–169)). All of a researcher's observations are based on his/her own perceptions which are inextricably connected to previous experiences (subjectivity). Therefore, there are multiple interpretations and realities. They construct knowledge by living in and experiencing the world, depending on social environment, culture and language (SAUNDERS/LEWIS/THORNHILL (2016, p. 136)). The understanding of a phenomenon depends on the researcher's interpretation. Qualitative methods such as case studies and ethnographic studies are common.

Design-science research philosophy Similar to positivism, the view in design-science research is that there is a single, stable underlying reality (MANSON (2006, pp. 166–169)). Knowledge is generated through an iterative process of construction and circumscription. Truth and understanding as well as manipulation and control of the environment are val-

ued in the design-science research community. While in the design phase the work is rather abductive, in the development and evaluation phase the methods are rather deductive. In the evaluation phase, for example, both quantitative and qualitative methods can be used to measure the effectiveness and impact of the developed artifact (MANSON (2006, pp. 166–169)).

The evaluation of each form of research by appropriate criteria is very important to demonstrate the quality of research to other researchers, editors, reviewers and readers. However, these criteria depend strongly on the research philosophy used. HEVNER et al. (2004) describe a conceptual framework and clear guidelines for understanding, executing and evaluating design-science research. Table 1.2 summarizes all seven guidelines of design-science research articulated by HEVNER et al. (2004, pp. 82–90). The following illustrates the application of the design-science research guidelines to this work.

Table 1.2: Design-science research guidelines by HEVNER et al. (2004, p. 83)

Guideline	Description
Design as an artifact	Design-science research must produce a viable artifact in the form of a construct, a model, a method or an instantiation.
Problem relevance	The objective of design-science research is to develop technology-based solutions to important and relevant business problems.
Design evaluation	The utility, quality and efficacy of a design artifact must be rigorously demonstrated via well-executed evaluation methods.
Research contributions	Effective design-science research must provide clear and verifiable contributions in the areas of the design artifact, design foundations and/or design methodologies.
Research rigor	Design-science research relies upon the application of rigorous methods in both the construction and evaluation of the design artifact.
Design as a search process	The search for an effective artifact requires utilizing available means to reach desired ends while satisfying laws in the problem environment.
Communication of research	Design-science research must be presented effectively both to technology-oriented as well as management-oriented audiences.

Design as an artifact This work designs several artifacts. First, two models for the crew scheduling problem with attendance rates are developed (model). Furthermore, the hybrid algorithm to solve one of these models (method) and the decision support system (instantiation) can be considered as artifacts.

Problem relevance Both the crew scheduling problem itself and crew scheduling in the railway sector have been intensively studied in the literature. Due to their size and complexity, these planning problems pose a great challenge to most railway companies. In Germany, there is an additional problem: due to competitive and cost pressure, the request for attendance rates is increasing. So far, we are not aware of any model, method or decision support tool that reflects attendance rates.

Design evaluation In order to evaluate the effectiveness of the individual artifacts, a variety of computer-based tests with different instances are performed. Both, the developed path-flow model and the hybrid solution algorithm are compared with the semi-manual planning approach applied in practice. Furthermore, the algorithm is tested with different settings (without/with uniform distribution, sequential/integrated) with regard to solution quality and calculation time. The developed arc-flow model is also evaluated on the basis of various tests. On the one hand the effect of different valid inequalities on the solution process is tested. On the other hand, small instances are solved optimally and for large instances heuristic solutions are improved.

Research contributions An essential contribution to research is the inclusion of attendance rates in the two mathematical models (path-flow/arc-flow) and the developed hybrid solution approach. For the railway companies' management, the prototypical developed decision support tool is of significant use.

Research rigor This research bases its design on previous research, especially the commonly use of set covering problems for modeling crew scheduling problems as well as the implementation of column generation techniques and genetic algorithms. Furthermore, testing the developed models and algorithms with different settings on various but practical test instances is a common methodology.

Design as a search process All developed artifacts proposed in this work are designed by first analyzing operating conditions as well as legal and contractual requirements. At the same time, the organization of regional rail passenger transport in Germany and the planning process of the individual participants are studied. The second step in the search process is reviewing the relevant literature. Keeping the goal of cost minimization in mind, the capability of the various crew scheduling approaches is compared. Based on the appropriate set covering approach, initially, a simple generate-and-select approach is used. The development of the hybrid algorithm, which links column generation and genetic algorithms, is done first for a standard day, second for a multiple day period. In order to evaluate the quality of the solutions of the developed approach, a modeling as arc-flow problem is finally performed. Additionally, the former approach is implemented in a prototypical decision support tool.

Communication of research This work, through its nature and processing, speaks more to a research audience than to people at management level. As this research topic is derived from a practice project, parallel to the elaboration of the scientific side of the topic, communication with the project partners was ongoing and results were presented.

Figure 1.4: Research onion adapted from SAUNDERS/LEWIS/THORNHILL (2016)

Summarizing, the research design of this work is classified on the basis of the research onion according to SAUNDERS/LEWIS/THORNHILL (2016, p. 124). The research onion illustrated in Figure 1.4 consists of six layers: philosophy, approach to theory development, methodological choice, strategy(ies), time horizon and techniques and procedures (from outside to inside). In the outer layer of the onion, concerning the research philosophy, we have added the design science paradigm. Accordingly, this work can be associated with design science philosophy, which in most cases is both abductive and deductive in theory development. The design process uses a variety of quantitative methods (multi quantitative), such as mathematical modeling and optimization techniques. As research strategies, a comprehensive literature review (survey) and an evaluation of the research results in computer-aided tests at different test instances are applied. The latter can be classified in a broader sense under the terms “experiment” and “case study”. The determination of the time horizon is typically useful for empirical studies. This paper presents the research results of several years of cooperation with a project partner. Both

the data and the requirements framework were adjusted and refined in the course of the collaboration. Accordingly, the time horizon is rather longitudinal, although, according to SAUNDERS/LEWIS/THORNHILL (2016, pp. 200f.), this term has a different meaning. The innermost part of the research onion deals with data collection and data analysis. The data used in this work were provided by the project partner and elaborated and expanded in close cooperation.

2 Large-scale optimization techniques

2.1 Column generation

Column generation is a technique to solve large linear programs involving a medium number of constraints, but a large number of variables (i.e. columns of the constraint matrix). Most variables are non-basic, i.e. they take the value zero in the optimal solution. Thus, only a small subset of variables needs to be considered when solving the problem. Instead of generating all variables, column generation starts with a small initial subset of variables. Iteratively, only those variables are generated and added that have the potential to improve the current objective function value. This corresponds to finding variables with negative reduced cost. The following illustrations are based on DESROSIERS/LÜBBECKE (2005, pp. 8–10).

Let us consider the following linear optimization problem as *master problem (MP)*:

$$\min \sum_{j \in N} c_j x_j \quad (2.1)$$

$$\text{s.t. } \sum_{j \in N} a_{ij} x_j \geq b_i \quad \forall i \in M \quad (2.2)$$

$$x_j \geq 0 \quad \forall j \in N, \quad (2.3)$$

where N is the index set of the variables (columns), M the index set of the constraints and $a_{ij}, b_i, c_j, x_j \in \mathbb{R}$. Let $N' \subseteq N$ be a reasonable small subset of all variables. Thus,

$$\min \sum_{j \in N'} c_j x_j \quad (2.4)$$

$$\text{s.t. } \sum_{j \in N'} a_{ij} x_j \geq b_i \quad \forall i \in M \quad (2.5)$$

$$x_j \geq 0 \quad \forall j \in N', \quad (2.6)$$

is called *restricted master problem (RMP)*. Obviously, an optimal solution of the RMP is a feasible solution for the MP. A so called *subproblem* has to be solved to check whether the solution is also optimal for the MP. This means that we have to test whether an improving variable (column) $j \in N \setminus N'$ with negative reduced cost exists. Let π be the

dual multipliers assigned to the constraints (2.5) of the RMP, then

$$\bar{c}_s = \min \left\{ c_j - \sum_{i \in M} \pi_i a_{ij} \mid j \in N \right\} \quad (2.7)$$

is the corresponding subproblem (also called *pricing problem*). Note that an explicit enumeration of all (remaining) columns should be avoided. If the columns a^j are implicitly given as elements of the set $\mathcal{A} \neq \emptyset$ and the cost coefficients c_j can be implicitly computed from a^j , then the subproblem can be formulated as

$$\bar{c}^* = \min \{ c(a) - \pi^T a \mid a \in \mathcal{A} \}. \quad (2.8)$$

If $\bar{c}^* \geq 0$, the RMP solution is also optimal for the MP. However, if at least one variable with negative reduced cost exists, the index of the variable $x_s = \arg \min \{ c(a) - \pi^T a \mid a \in \mathcal{A} \}$ with the least reduced cost is added to the index set N' , i.e. $N' = N' \cup \{s\}$. The iterative process of column generation algorithm terminates if no more variables with negative reduced cost are found. Algorithm 2.1 summarizes the procedure.

Algorithm 2.1 Column generation

```

1: Select feasible index set  $N'$ 
2: while true do
3:   Solve the RMP (2.4)-(2.6) to obtain a primal solution  $x$  and dual solution  $\pi$ 
4:   Select  $s \in N \setminus N'$  with  $x_s = \arg \min \{ c(a) - \pi^T a \mid a \in \mathcal{A} \}$ 
5:   if  $\bar{c}_s < 0$  then
6:      $N' = N' \cup \{s\}$ 
7:   else
8:     return  $x$ 
9:   end if
10: end while

```

At this point, we briefly want to interpret the reduced cost. Considering the dual problem corresponding to (2.1)-(2.3) with the dual variables π :

$$\max \sum_{i \in M} b_i \pi_i \quad (2.9)$$

$$\text{s.t. } \sum_{i \in M} a_{ij} \pi_i \leq c_j \quad \forall j \in N \quad (2.10)$$

$$\pi \geq 0. \quad (2.11)$$

It is evident that the reduced cost are the slack variables of the dual constraints (2.10). Accordingly, if an index j exists with $\bar{c}_j < 0$, then the associated dual constraint is violated and the associated solution is dual infeasible. For more information, especially

on the weak and strong duality theorem and complementary slackness, see DANTZIG/THAPA (2003, pp. 43–66).

The structure of the subproblem, that generates new columns, can greatly vary depending on the underlying optimization problem. The columns often have a special structure that can be exploited in the search for new columns. For example, the subproblem for the bin-packing problem is a comparably simplistic knapsack problem.

Column generation approaches are widely used in various research areas (e.g. packing problems or crew scheduling problems). As a result, there are numerous variations of the column generation algorithm as well as acceleration and stabilization techniques. Obviously, a reduction of iterations can be achieved if not only the variable with the smallest reduced cost is added to the RMP, but a set of columns with large negative reduced costs (e.g., MARTIN (1999, pp. 369–392)). This strategy is known as “multiple pricing”. The definition of termination criteria can also speed up the solution process. To avoid the “tailing off” effect, the iterative process is aborted as soon as the improvement of the objective function value falls below a predefined threshold. (e.g., VANDERBECK/WOLSEY (1996)). For more information we refer to DESAULNIERS/DESROSIERS/SOLOMON (2002), DESROSIERS/LÜBBECKE (2005) and LÜBBECKE/DESROSIERS (2005).

If the master problem contains the integrality condition (e.g., $x_j \in \mathbb{Z}_+$, $\forall j \in N$), the column generation approach can be integrated into a branch-and-bound procedure. This is called a branch-and-price method (see, e.g., BARNHART et al. (1998), VANDERBECK/WOLSEY (1996) or VANDERBECK (2000)).

2.2 Dantzig-Wolfe decomposition for linear programs

The idea of decomposition methods is to extract a set of conditions (variables) from the problem and observe them on a higher level. This results in a master problem and a subproblem, whereby the latter can be solved more efficiently. Decomposition methods work alternately on the master problem and the subproblem and iteratively exchange information to optimally solve the initial problem. As examples the Dantzig-Wolfe decomposition (DANTZIG/WOLFE (1960)) and the Benders’ decomposition (BENDERS (1962)) can be mentioned. The former eliminates a part of the constraints, the latter deletes some of the variables. Accordingly, Benders’ decomposition is the Dantzig-Wolfe decomposition applied to the dual problem. The following illustrations are based on DESROSIERS/LÜBBECKE (2005, pp. 8–10), JÜTTE (2012, pp. 14–19) and MARTIN (1999, pp. 369–392). For more information about Dantzig-Wolfe decomposition for integer programs we refer to DESROSIERS/LÜBBECKE (2005, pp. 8–10) and VANDERBECK (2000).

Consider a linear program with n variables and $m = m_1 + m_2$ constraints in the following form:

$$\min c^T x \quad (2.12)$$

$$\text{s.t. } Ax \geq b \quad (2.13)$$

$$Dx \geq d \quad (2.14)$$

$$x \geq 0, \quad (2.15)$$

where $x \in \mathbb{R}^n$, $b \in \mathbb{R}^{m_1}$, $d \in \mathbb{R}^{m_2}$, $A \in \mathbb{R}^{m_1 \times n}$ and $D \in \mathbb{R}^{m_2 \times n}$. Let $\mathcal{B}$ denote the convex polyhedron of the first subset of constraints (2.13) of the original linear program. Polyhedron $\mathcal{D}$ contains all non-negative real tuples that satisfy the second subset of the above constraints (2.14)-(2.15), i.e.

$$\mathcal{B} = \{x \in \mathbb{R}^n | Ax \geq b\} \neq \emptyset$$

$$\mathcal{D} = \{x \in \mathbb{R}^n | Dx \geq d, x \geq 0\} \neq \emptyset.$$

Each element $x \in \mathcal{D}$ can be written as a convex combination of extreme points $\{x^p\}_{p \in P}$ and a weighted combination of extreme rays $\{x^r\}_{r \in R}$ of $\mathcal{D}$ (Farkas-Minkowski-Weyl theorem, see SCHRIJVER (1998, p. 87)):

$$x = \sum_{p \in P} x^p \lambda_p + \sum_{r \in R} x^r \mu_r \quad (2.16)$$

$$\sum_{p \in P} \lambda_p = 1$$

$$\lambda_p, \mu_r \geq 0.$$

If $\mathcal{D}$ is bounded, a convex combination of the extreme points is sufficient. Substitution of (2.16) in (2.12) and (2.13) yields to the *Dantzig-Wolfe master problem*:

$$\min \sum_{p \in P} k_p \lambda_p + \sum_{r \in R} k_r \mu_r \quad (2.17)$$

$$\text{s.t. } \sum_{p \in P} a^p \lambda_p + \sum_{r \in R} a^r \mu_r \geq b \quad (2.18)$$

$$\sum_{p \in P} \lambda_p = 1 \quad (2.19)$$

$$\lambda_p \geq 0 \quad \forall p \in P \quad (2.20)$$

$$\mu_p \geq 0 \quad \forall r \in R, \quad (2.21)$$

where $k_p = c^T x^p$, $k_r = c^T x^r$, $a^p = Ax^p$ and $a^r = Ax^r$. Note that in the reformulated

problem, $\lambda_p, p \in P$, and $\mu_r, r \in R$, are the decision variables of the linear program. Constraints (2.18) are usually referred to as coupling constraints, (2.19) as convexity constraint.

By construction the Dantzig-Wolfe master problem (2.17)-(2.21) is equivalent to the original linear program (2.12)-(2.15). Due to the reformulation, the number of constraints can be reduced from $m_1 + m_2$ to $m_1 + 1$. In contrast, the number of variables has changed from n to $|P| + |R|$, whereby typically the number of extreme points of a polyhedron is much larger than the polyhedron's dimensions.

Here and in the following we assume that $\mathcal{D}$ is bounded, i.e. the Dantzig-Wolfe master problem takes the form

$$\min \sum_{p \in P} k_p \lambda_p \quad (2.22)$$

$$\text{s.t. } \sum_{p \in P} a^p \lambda_p \geq b \quad (2.23)$$

$$\sum_{p \in P} \lambda_p = 1 \quad (2.24)$$

$$\lambda_p \geq 0 \quad \forall p \in P. \quad (2.25)$$

Let π be the dual values corresponding to (2.23) and let π_0 the dual value corresponding to (2.24). Then, the reduced cost $\bar{c}_p$ of variable λ_p can be calculated as

$$\begin{aligned} \bar{c}_p &= k_p - \pi^T a^p - \pi_0 \\ &= c^T x^p - \pi^T A x^p - \pi_0 \\ &= (c - A^T \pi)^T x^p - \pi_0. \end{aligned}$$

In order to achieve the best possible improvement of the objective function, we are interested in the variable with the lowest reduced cost in each iteration:

$$\bar{c}_s = \min \left\{ (c - A^T \pi)^T x^p - \pi_0, p \in P \right\}. \quad (2.26)$$

If $\bar{c}_s \geq 0$, the Dantzig-Wolfe master problem is solved optimally. If $\bar{c}_s < 0$, the current objective function value of the master problem can be improved by adding variable $x_s = \arg \min \left\{ (c - A^T \pi)^T x^p - \pi_0, p \in P \right\}$ to the basis. As a reminder, P is the set of extreme points of polyhedron $\mathcal{D} = \{x \in \mathbb{R}^n | Dx \geq d, x \geq 0\}$ and typically very large. Accordingly, a calculation of the reduced cost for each extreme point would be very time consuming. From linear programming theory we know that the optimal solution occurs at an extreme point if the underlying polyhedron is bounded. Therefore, (2.26)

is equivalent to the following linear program (called *Dantzig-Wolfe subproblem*):

$$\min (c - A^T \pi)^T x - \pi_0 \quad (2.27)$$

$$\text{s.t. } Dx \geq d \quad (2.28)$$

$$x \geq 0. \quad (2.29)$$

Instead of explicitly calculating the reduced cost for all extreme points, solving the linear program implicitly identifies the variables that improve the objective function value. Thus, a simplification of the problem is achieved by enlarging the solution space.

Since we are interested in reducing the number of constraints in the master problem we would partition the constraint matrix in such way that D contains the majority of constraints. This strategy results in a very large number of variables, because typically the number of extreme points of a polyhedron is much larger than the polyhedron's dimensions. The column generation technique described in Section 2.1 can be used to efficiently solve this kind of problem. Starting with a (small) initial feasible solution of (2.22)-(2.25) the restricted Dantzig-Wolfe master problem is solved optimally. The obtained dual values π and π_0 are used to solve the Dantzig-Wolfe subproblem (2.27)-(2.29). If the optimal objective function value is negative, the variable solving the subproblem is added to the restricted Dantzig-Wolfe master problem. Iteratively, the dual variables are updated by solving the new restricted Dantzig-Wolfe master problem and new variables with negative reduced costs are added until no such variables are found.

3 Railway crew scheduling: models, methods and applications

Abstract

The railway crew scheduling problem consists of finding the most efficient duty combination for railway crews to cover all trains and related activities for a defined period of time. Crew scheduling problems in transportation originate in airline and bus industries. In the 1990s, researchers developed sophisticated algorithms which were capable of solving the larger and more complex problem instances of railway operators. Practical implementations and decision support tools received very satisfying feedback from the industry. Since then, numerous real-world problems have been studied requiring innovative algorithmic approaches to the NP-hard problem. In this paper, we review 123 articles on railway crew scheduling focusing on more recent publications since 2000. After depicting crew scheduling in railway including the differences between transportation modes, our goal is to classify the literature according to model formulations, objectives, constraints and solution methods. By systematizing the collected articles, we identify research opportunities including integrated approaches with other planning stages, real-time re-scheduling and a further investigation of the impact of robustness and employee satisfaction on the cost of railway crew schedules.

Reference

Published paper: HEIL, J./HOFFMANN, K./BUSCHER, U. (2019): Railway crew scheduling: Models, methods and applications. In: *European Journal of Operational Research* Vol. 2019, Available online June 12, 2019.

3.1 Introduction

A large number of articles on crew scheduling is highly application-oriented and thus often geared to the problem encountered in the industry under consideration. ERNST et al. (2004a), ERNST et al. (2004b) and VAN DEN BERGH et al. (2013) provide a comprehensive overview of personnel scheduling and rostering across all industries. A typical area of application is the transportation industry, especially airlines, railways and urban mass transit. The origins of the crew scheduling problem in transportation date back to the 1950s and 1960s (e.g., see ARABEYRE et al. (1969)). It gained greater momentum with the advances in computational power in the 1980s (see, e.g., CARRARESI/GALLO (1984) and WREN (1981)). In this period, mainly airline and urban mass transit, with a focus on bus transportation, benefited from the research activities. Recent reviews on crew scheduling in the context of airline and bus transportation can be found in DEVECI/DEMIREL (2018), GOPALAKRISHNAN/JOHNSON (2005), KASIRZADEH/SADDOUNE/SOUMIS (2017) and IBARRA-ROJAS et al. (2015) respectively.

In the 1990s, the railway industry came to the fore in crew scheduling research activities. Several research groups from different countries contributed to the progress (e.g., CAPRARA et al. (1997), DESROSIERS et al. (1995), DESROCHERS/SOUMIS (1989), MORGADO/MARTINS (1992), PARKER/WREN/KWAN (1995), WREN/KWAN/PARKER (1994)). The interest arose in particular as a result of the magnitude of potential cost savings achieved by Operation Research techniques and the available computational power to solve the comparably more complex crew scheduling problems for railway operators. The deregulation and privatization of railway transportation in Europe even increased the need for cost-efficient use of resources (see, e.g., CAPRARA et al. (1997)). Since cost for infrastructure cannot be influenced substantially, personnel costs become a critical factor next to rolling stock units and energy. Hence, railway companies' interest in using advanced optimization techniques for the complex crew scheduling task arose.

Different methods have emerged that can be applied in principle to crew scheduling problems. Detached from a specific application, BEASLEY/CAO (1996) define the basic crew scheduling problem as the assignment of crews to tasks with fixed start and finish times such that each crew does not exceed a limit on the total time it can spend working. In principle, crew scheduling problems in the transportation industry share a whole range of similarities. However, since each application has its own particular features and research challenges, crew scheduling papers usually focus on a specific application (see BARNHART et al. (2003)). With regards to the railway industry, CAPRARA et al. (2007), DESAULNIERS/HICKMAN (2007), HUISMAN et al. (2005) and NARAYANASWAMI/RANGARAJ (2011) contribute comprehensive overviews of models and methods along all steps of the planning process. Similarly, TEODOROVIĆ/JANIĆ (2017) provide a re-

cent overview for public transportation systems. But in contrast to the airline or bus transportation, to the best of our knowledge, there is still no comprehensive review of railway crew scheduling problems (RCSP), so that the aim of this paper is to provide a systematic overview of railway crew scheduling models, methods and applications as part of the operational planning process.

Figure 3.1: Number of publications on RCSP by year

To identify relevant articles, several databases including *IEEE explore*, *Google Scholar*, *ScienceDirect*, *Scopus* and *SpringerLink* were searched for the keywords “crew scheduling”, “driver scheduling”, “train” and “railway” or a combination of these. With the aim to complete our literature database, we examined the bibliographies of all relevant publications and added adequate references to our collection. In total, more than 400 journal articles, conference papers, book chapters or PhD theses were investigated. Special attention is paid to contributions that have been published since 2000. Figure 3.1 shows that a constant large number of articles has appeared during this period attracting a continuous high level of attention. Altogether, we have identified 136 articles to be relevant, thereof 123 publications are included in our classification and 13 articles represent methodical basis, related literature overviews or alike. Figure 3.2 indicates that on the basis of number of publications per journal *Annals of Operations Research*, *European Journal of Operational Research* and *Public Transport* are particularly important outlets for railway crew scheduling.

The remainder of this paper is organized as follows: In Section 3.2 we describe the role of crew planning at the different planning stages in railway operations. We also define the technical terms of crew scheduling and specify different characteristics for the various railway transportation modes. Section 3.3 provides an overview of railway crew scheduling literature since 2000. While Section 3.4 presents various model formulations and discusses objectives and constraints, Section 3.5 deals with the solution methods used in detail. In the final section we summarize our findings and give possible directions for future research.

Most research activities are motivated by real-world problems of railway operators and direct at developing new tools and applications to support the crew planners’ work. To

Figure 3.2: Number of publications on RCSP by journal or type

give practitioners an overview of existing systems, we outline selected decision support tools in Section 3.7 (online supplementary material of the published article).

3.2 Crew planning in railway operations

Decisions on railway crew members can be classified to different planning levels. This section outlines crew planning activities in the context of strategic/tactical planning, operational planning and disruption management. For a detailed overview of the planning process, models and solution methods in railway operations we recommend CAPRARA et al. (2007), DESAULNIERS/HICKMAN (2007) and HUISMAN et al. (2005). Moreover, we define the technical terms of crew scheduling (see Section 3.2.4) and describe the special characteristics of the different railway transportation modes (see Section 3.2.5).

3.2.1 Crew management in strategic and tactical planning

At strategic and tactical level with a time horizon longer than one year, crew planning deals with the long-term availability and capabilities of crew members as well as the location and the capacities of crew depots (*crew management*). For reliable long-term operations, it is crucial to anticipate the future need of different crew types (see Section 3.2.5) and to realize a balanced crew composition regarding age and skills. This includes decisions on hiring, training or moving crews from one depot to another (CAPRARA et al. (2007)). Besides, the choice of crew depot locations including opening or closing decisions play an important role at this stage (HUISMAN et al. (2005)).

3.2.2 Crew scheduling in operational planning

At operational level, crew planning is the task of building work schedules for crew members to operate a planned timetable. A generic operational planning process in railway

passenger transportation is illustrated in Figure 3.3. The process starts with the *line planning* problem, that determines lines, their origin/destination stations and stops. Types and frequencies of trains on each line are specified so that all travel demands are satisfied while maximizing the service or minimizing operating costs (CAPRARA et al. (2007), FUENTES/CADARSO/MARÍN (2015)). Afterwards, arrival and departure times of each train at each track section and station are fixed ensuring all relevant safety constraints (*train timetabling*). Once the timetable of each line is fixed, trains have to be assigned to platforms in the stations they visit, taking into account the maximum number of trains that can be simultaneously dispatched in a station (CAPRARA et al. (2007)). This planning step is called *train platforming*. The following *rolling stock scheduling* problem aims at assigning the rolling stock units (number and type) to scheduled trains with a pre-defined timetable and platforms in a conflict-free and resource-efficient way (CAPRARA et al. (2007)). Often, regular maintenance activities are integrated in this planning step. During the night and outside rush hour, most train units have to be parked on a shunting area near one of the stations or in depots. Therefore, the *train unit shunting* problem deals with parking train units outside the stations when they are not used or are in maintenance (CAPRARA et al. (2007)).

Figure 3.3: Operational planning process in passenger railway transportation

The following two planning tasks concern crew members and are usually divided into two steps: the *crew scheduling* and the *crew rostering* problem. The first forms anonymous duties covering all the trips for a defined period of time, e.g., a single work day. Each duty represents a sequence of tasks and has to satisfy a large set of constraints (see Section 3.4.3). Next, the duties are combined to weekly, in some cases monthly, sequences which are subsequently assigned to individual crew members (*crew rostering*). Feasible duty sequences typically follow defined days-off patterns to achieve a legal and sustainable mix of work and rest days. When assigning rosters to crew members, individual restrictions such as working time accounts, vacations, special track or rolling stock knowledge, language qualifications and a fair work distribution must be considered (HUISMAN et al. (2005)). Our review focuses on the first crew planning step, i.e. *crew scheduling*. Typically for freight railway transportation, because of its different operating model (see Section 3.2.5), trips are directly assigned to available crew members (*crew assignment*, see, e.g., KUZNETSOV et al. (2016) and VAIDYANATHAN/JHA/AHUJA (2007)). We also consider these studies since they integrate crew scheduling and crew rostering into one planning step.

Integrated planning with crew scheduling or crew rostering The vast majority of research done regarding the operational planning steps in railway operations considers them to be performed sequentially. Even though FRELING/HUISMAN/WAGELMANS (2003) show that under specific circumstances integrated approaches lead to higher cost efficiency, especially in personnel cost. In the last years, research on integrated planning came to the fore. Some of this work is done in the context of re-scheduling for disruption management which we will discuss in the following Section. MENG et al. (2018) and LU/HAN/ZHOU (2018) provide recent overviews of integrated optimization models in railway and urban transit operations, respectively. Since modeling complete railway system is a very complex task, to the best of our knowledge, each study on integrated operational railway planning existing to date investigates one specific link. In most cases they explore the integration of line planning and timetabling or timetabling and rolling stock scheduling (see CADARSO/MARÍN (2012), MENG et al. (2018)). SCHÖBEL (2017) provides an eigenmodel for a holistic integration of all these three planning steps, i.e. line planning, timetabling and vehicle routing (another term for rolling stock scheduling coming from bus industries), for generic transportation industry problems. The integration of crew scheduling with other planning tasks is primarily explored in the context of freight transportation (e.g., BACH/DOLLEVOET/HUISMAN (2016)) or with a focus on crew rostering (e.g., BORNDÖRFER et al. (2017), LIN/TSI (2019), see Section 3.3.1 and Table 3.2 for an overview). While integrated planning of rolling stock and crew scheduling is investigated extensively for urban transit systems, especially bus transportation (see, e.g., FRELING/HUISMAN/WAGELMANS (2003), HAASE/DESAULNIERS/DESROSIERS (2001), HUISMAN/FRELING/WAGELMANS (2005), KLIEWER/AMBERG/AMBERG (2012), SHEN/XIA (2009)), this is not the case for passenger transportation in railway yet. Hence, integrative approaches for railway operations which consider crew planning steps remain a field for future research.

3.2.3 Real-time crew re-scheduling in disruption management

In case of disruptions, i.e. unforeseen incidents due to accidents, bad weather, rolling stock breakdowns and others, railway schedules might become infeasible and therefore need to be modified as quickly as possible (CACCHIANI et al. (2014)). Disruption management aims at recovering the system's broken part in real-time and can be executed in different ways depending on the railway operator (SCHIPPER/GERRITS (2018)). CACCHIANI et al. (2014) provide an extensive review of studies in real-time railway re-scheduling. Due to its complexity, the re-scheduling problem is usually broken up into three consecutive phases: temporarily adjusting the timetable, modifying the rolling stock schedule and re-scheduling the crews. Among others, VEELANTURF et al. (2012),

VEELENTURF et al. (2016), LAI/LEUNG (2018) discuss *crew re-scheduling* in railway operations. Since comprehensive overviews of rail-time railway rescheduling are available (see e.g., CACCHIANI et al. (2014)), we do not cover related literature in our work. Though, the term *crew re-scheduling* is equally used for longer-term adjustments to the crew schedule, e.g., due to construction sites (see HUISMAN (2007)), or for short-term adjustments on the following day in case of expected snow or other extreme weather conditions (ultra-short term re-scheduling, see ABBINK/HUISMAN/KROON (2018)). These studies are considered in our review.

3.2.4 Technical terms of crew scheduling

The results of the rolling stock scheduling step (passenger transportation), which precedes crew scheduling, are *vehicle schedules* consisting of a group of vehicle blocks. In freight transportation, the steps of car blocking to locomotive assignment obtain schedules for connections of locomotives and car blocks. One *vehicle block* represents a set of vehicle tasks and journeys that have to be operated consecutively by one vehicle during a day (SHEN/CHEN (2014)). The type of *crew members* driving on trains varies depending on the type of railway transportation (see Section 3.2.5 for a description). Each crew member is assigned to a *home depot* (also: crew depot, crew base, home base), which is often located at terminals or stations with high frequency of train services (DERIGS/MALCHEREK/SCHÄFER (2010)). Typically, there are multiple depots in railway networks. A railway network contains special stations, called *relief points*, where crew members can be relieved. These stations have specific installations to enable waiting, resting or having a meal break (ELIZONDO et al. (2010)). Typically, relief points are located at terminal stations or important junctions for the railway traffic. If relief location and time are considered at the same time, researchers speak of *relief opportunity* (DE GROOT/HUISMAN (2008)). The aforementioned relief points are used in the crew scheduling process to subdivide train journeys into smaller units, called *trips*, following the terminology in rolling stock scheduling, or *pieces*. Trips are the smallest amount of work defined by a fixed starting and ending time at each location (HANAFI/KOZAN (2014)) and can be assigned to a crew member. Several researchers use the term *tasks* analogously or even use this term to include operational work like signing-on and -off. Inspired by airline crew scheduling, some authors use the term *legs*, representing trips (DERIGS/MALCHEREK/SCHÄFER (2010), BENGTSSON et al. (2007), PARK/RYU (2006)). *Deadheading* designates non-working trips to transport a crew member as passenger to another relief point by train, bus, taxi or other means of transportation (HAN/LI (2014)).

A sequence of tasks performed by a single crew member for a day's work forms a

duty or *shift*, containing sign-on, meal breaks, rest, deadheads, paperwork, handover activities and sign-off (HAN/LI (2014), FROGER/GUYON/PINSON (2015)). These duties represent anonymous work schedules, that start and end at the same crew depot (DERIGS/MALCHEREK/SCHÄFER (2010)). Each duty must satisfy a set of government rules, labor agreement rules and operational constraints (PENG/SHEN (2016)). These rules can differ from one country to another and from one company to another. A detailed description of legal and contractual requirements in Germany can be found in JÜTTE (2012) and HOFFMANN et al. (2017). For labor rules in the Netherlands see ABBINK et al. (2011), in Italy see CAPRARA/MONACI/TOTH (2001) and in France see FROGER/GUYON/PINSON (2015). We summarize the requirements relevant in practice in Section 3.4.3. Analogous to airline crew scheduling, some researchers refer to the concept of *pairings* to describe duties (BENGTSSON et al. (2007), DERIGS/MALCHEREK/SCHÄFER (2010), FROGER/GUYON/PINSON (2015), PARK/RYU (2006), DOS SANTOS/MATEUS (2009)). *Duty cycle* or *round-trip* are rarely used. Especially in the railway modes freight and long-distance, duties can consist of a home-to-away trip, a layover at the away station followed by an away-to-home trip (e.g., BALAKRISHNAN/KUO/SI (2016), FROGER/GUYON/PINSON (2015)).

A set of legal duties that cover altogether the required trips is called *crew/driver schedule* (SHEN et al. (2013)). In most articles it is assumed that each trip is covered (at least) once in a crew schedule (e.g., ABBINK et al. (2011), KWAN (2011)). In some approaches, only a subset of trip needs to be covered, for instance, in the form of attendance rates (e.g., HOFFMANN et al. (2017)) or of allowed uncovered trip (e.g., FROGER/GUYON/PINSON (2015), SNIJDERS/SALDANHA (2017)). The solution of the crew schedule problem is a valid schedule according to operational, legal and labor agreement aspects (see Section 3.4.3 for more details). Finally, a *roster* is a sequence of duties over a period of typically one week that satisfies certain rules such as a minimal number of days off and a good mix of work and rest days (DJELLAB/BIONNIER (2011)). These rosters are assigned to individual crew members considering their working time account, preferred vacation days, personal qualifications and a fair work distribution.

3.2.5 Special characteristics of transportation modes

Although personnel must be planned in each railway transportation mode, there are differences in the planning processes. A selection of relevant characteristics for freight and passenger railway transportation is summarized in Table 3.1. The latter is divided into long-distance, regional/suburban and urban transportation modes.

In passenger transportation, operational crew planning is based on a fixed timetable, i.e. fixed demand, and is therefore reviewed and adjusted on a (bi-) annual basis. Pas-

Table 3.1: Special characteristics of different railway transportation modes

Mode	Freight	Passenger		
		Long-distance	Regional/ suburban	Urban
Planning horizon	monthly to daily	(bi)annual	(bi)annual	(bi)annual
Type of demand	mix of fixed and flexible/ad hoc	fixed	fixed	fixed
Service frequency	mix of regular and irregular	regular, weekly up to hourly	regular, daily up to several times per hour	regular, based on time intervals (minutes)
Crew members	driver, conductor, brakeman	driver, conductors, on-board catering staff	driver, conductor	driver
Average trip length	long	long	medium	short
# of trips per duty	few (often outbound and return trip)	few, e.g., 2-4	20 or more not uncommon	20 or more not uncommon
# of possible duties	medium	medium	large	large
Hotel stay allowed	yes	yes	no	no
Maximal deadheading time	very long	very long	medium	short

senger transportation modes differ in their operated geographical distance and in the frequency of their services. Long-distance trains run on a monthly, weekly, daily or hourly basis depending on the country, the travel distance and the demand. Regional trains satisfy the travel demand of the daily life (e.g., commuting) and therefore run at least daily, rather hourly or even several times per hour. Urban railways serve the high travel demand in large cities and areas of dense population and, thus, typically operate on interval timetables (i.e. trains run at specific intervals, e.g. every 10 minutes). In contrast, freight transportation is to a significant extend last-minute business (JÜTTE/THONEMANN (2012b)). At a large European freight railway carrier, 80% of all trains are regular trains with about 20% of these being canceled or changed at short notice. The

remaining 20% are special trains which are scheduled only a few days before operation. Therefore, the operational planning horizon is usually monthly to daily, because a considerable proportion of trains is integrated in the timetable a few days before operation (changes or short-term demand). Accordingly, transportation services and the associated timetable can be either a combination of both regular and irregular or in some cases completely irregular (KUMAR et al. (2009)).

The type and number of driving personnel also varies, not only depending on the transportation mode but also on the country in which the service is operated. While subways require only one or even no train driver (also referred to as engineer (American English) or engine driver (British English)) to operate the train, regional trains are often manned by a driver and a conductor. The latter is responsible for safe and efficient operations and passenger service by, among others, controlling tickets, making announcements and securing departure (FUENTES/CADARSO/MARÍN (2015)). Recently, the demand for security guards to improve the safety of both passengers and personnel has been growing (SNIJDERS/SALDANHA (2017)). In long-distance services, crews consist of the driver, several conductors and the catering staff who operate the on-board restaurant or provide snacks at short notice. In freight transportation, the terms are similar, but the tasks are slightly different. The driver operates the train and the conductor is responsible for operational and safety activities (BALAKRISHNAN/KUO/SI (2016)). Some crew types and their terminology are specific per country: in the US freight transportation, for example, the driver is assisted by an assistant conductor (historically a brakeman to assist the braking of the train, LIU/HAGHANI/TOOBAIE (2010)). Other railway operation personnel has also been subject to scheduling studies, but are not part of this review (see POUR et al. (2017) and WANG/GRONALT/SUN (2017) for a study on maintenance crews and depot shunting driver, respectively).

The length of trips is also a major distinguishing feature of the individual transportation modes. On average, a freight or long-distance trip is longer than in suburban and urban transportation, both spatially and temporally. A gradation can also be observed between suburban and urban traffic (medium vs. short average trip length). As a result, the number of trips per duty varies greatly. In urban and suburban transportation 20 or more trips are not uncommon. In contrast, a long-distance duty contains only few trips, e.g., 2 to 4 trips (KOHL (2003)). The main operating hours in passenger transportation occur during day time with some operations during the night (e.g., night trains in long-distance or during the weekends in regional and sub-urban/urban transportation). The workdays follow the structure of weekdays, hence, duties are typically planned on an one-workday basis. In contrast, freight transportation is usually operated 24/7 with no working day boundaries. A duty typically consists of an outbound trip from the crew

member's home station to the away station, followed by a return trip from the away station to the home station (BALAKRISHNAN/KUO/SI (2016)). These characteristics also apply to some long-distance passenger transportation, especially in large countries with sparse railway networks. Therefore, a freight, and in some cases long-distance, duty can last two or more days accompanied by an overnight stay in a hotel. Accordingly, the number of possible duties in freight and long-distance transportation is rather medium (up to 100,000 per day, see KOHL (2003)), in suburban and urban transportation rather big (more than 1,000,000 per day possible, see HOFFMANN (2017)).

Operators aim at using the trains of their transportation network for deadheading activities for cost reasons. However, this is not always possible since a duty might not end at a home depot and there is no train run available to bring the crew back. Such cases require special crew transport, mainly taxis, which increases the cost for deadheading. In freight and long-distance transportation, deadheading time might be very long and therefore expensive. In this case, a layover in a hotel might be more cost-efficient. Since the range of regional and urban railway networks is relatively smaller, the time for deadheading is medium to short. In such cases, taxis are only used if there is no other possibility.

3.3 Overview of RCSP literature

In this section, we discuss the classification of the surveyed literature. The 123 selected articles can be categorized according to their planning stage, railway transportation mode, crew type, model formulation, objective function, solution method and associated country if real-world instances are considered. All publications of RCSP studied in this review are summarized in Table 3.2 with regard to the above-mentioned criteria.

3.3.1 Planning stage

Although only the planning step crew scheduling is focused in this review, there are articles that additionally consider preceding or following planning steps. Therefore, the selected articles are categorized according to the planning process illustrated in Section 3.2.2. In both railway passenger and freight transportation, the terms of passenger transportation are used. Accordingly, the individual articles can be assigned to the planning steps timetabling (TT), rolling stock scheduling (RSS), crew scheduling (CS) and crew rostering (CR). Additionally, there is the identifier DG for duty generation as some articles focus on the generation of duties as preparation for the actual crew scheduling step (e.g., CAPRARA/MONACI/TOTH (2001), GOUMOPOULOS/HOUSOS (2004), KONIORCZYK/TALAS/GEDEON (2015)). If planning stages are considered as an integrated

problem, the corresponding abbreviations are linked by an asterisk (*). 12 out of 21 articles on freight transportation consider crew scheduling and rostering as integrated. Often, these two steps are collectively referred to as crew assignment (e.g., KUMAR et al. (2009), VAIDYANATHAN / JHA / AHUJA (2007)). With respect to passenger transportation, only 8 articles discuss approaches or frameworks to integrate crew scheduling with the previous (RSS, 2 articles, e.g., CAPRARA (2015)) or following (CR, 7 articles, e.g., BORNDÖRFER et al. (2017)) planning step.

3.3.2 Mode

As described in Section 3.2, the publications can be differentiated by their mode of transportation - freight (F) or passenger. The latter is subdivided into long-distance (LD), regional/suburban (R) and urban (U). Most of the 123 articles relate to passenger railway transportation, thereof 17 explicitly discuss cases in urban transportation, 15 in long-distance, 9 in regional and 31 consider several modes. Crew scheduling in freight transportation is covered by 24 publications. For empty table entries either the transportation mode is not explicitly mentioned or the authors state that the model or solution approach can be applied generically to all transportation modes (e.g., BORNDÖRFER / GRÖTSCHER / LÖBEL (2001), BOSCHETTI / MINGOZZI / RICCIARDELLI (2004), CAPRARA (2015), DESAULNIERS (2007), GOUMOPOULOS / HOUSOS (2004)).

3.3.3 Crew type

As already mentioned in Section 3.2.4, different types of crew members can be distinguished. In some cases a distinction makes sense, because other legal or operational requirements may apply to the respective crew type (e.g., HOFFMANN et al. (2017)). Almost all researchers take the driver (D) as subject of their considerations. In many cases, conductors (C) are included or drivers and conductors are considered as permanent team (referred to as crew). DERIGS / MALCHEREK / SCHÄFER (2010), FRELING / LENTINK / ODIJK (2001), HOFFMANN (2017) and HOFFMANN et al. (2017) focus on conductors (C), although some of the mentioned methods can also be applied to drivers. SNIJDERS / SALDANHA (2017) and THORLACIUS / CLAUSEN (2008) consider only security guards (SG). If no reference to a crew type could be found in the publication, the corresponding cell of the table is empty. Other crew types such as on-board catering staff are not highlighted explicitly.

3.3.4 Model

RCSP are typically formulated as mixed integer problem. More than half of the researchers use a set covering problem formulation (SCP, 63 articles). The second most popular problem formulation is the related set partitioning problem (SPP, 25 articles). Both models represent a path-flow formulation of a multi-commodity flow problem on a time-space network. Only few researchers (12 articles) apply the arc-flow formulation of the multi-commodity flow problem, here referred to as network flow problem (NFP). Other problem formulations such as assignment problem, maximum covering problem or set packing problem are marked as “other” due to their rare application. A detailed discussion of the models and their applications in RCSP can be found in Section 3.4.1. Empty cells indicate articles which do not present a model.

3.3.5 Objective

In order to achieve an optimal crew schedule for a given problem, an appropriate evaluation criterion must be specified. In most cases, researchers use an objective function that estimates the efficiency of the crew schedule (Schedule eff.). Schedule efficiency can be measured with different parameters such as total cost (TC), total number of duties (ND), total idle time (IT) or a combination of these. Other parameters such as working hours (complement of idle time) or uncovered trips are summarized under “other” due to their rare use. Empty cells mark papers that do not define a model and, therefore, also no objective function. Articles that do not present a model but use a meta-heuristic approach and define a fitness function have an entry in the column “schedule efficiency”. In this case, the fitness function is specified instead of the objective function. Few articles not only consider pure monetary goal criteria but also the quality of the solution in terms of robustness (Rob. - 8 articles) and employee satisfaction (Satisf. - 6 articles) or at least aspects of them. Section 3.4.2 provides a detailed explanation of these different objectives.

3.3.6 Solution method

Since most articles about railway crew scheduling problems are highly application-oriented in terms of country specifics and the underlying problem structure, there is a variety of different approaches to obtain good solutions that satisfy certain constraints. Therefore, a useful differentiation criterion of RCSP is the solution method in use, which is discussed in more detail in Section 3.5. In Table 3.2 we distinguish between integer programming methods (IPM), heuristics (H), column generation (CG), meta-heuristics (MH) and simulation (S). Since RCSP are NP-hard optimization problems, IPM are only

applied to small or sparse problem instances (15 articles). Therefore, some researchers develop heuristics (26 articles). The vast majority of researchers uses column generation techniques (50 articles) or meta-heuristics (32 articles). Column generation techniques combine two approaches. Either the solution procedure of the relaxed problem (solved by column generation) and the resulting integer problem is consecutive, or column generation is integrated in a branch-and-bound scheme (branch-and-price, marked with $\circ$ in Table 3.2). Another three publications deal with crew planning in American and Canadian freight transportation using discrete event simulation (CHAHAR/CHENG/PRANOTO (2011), DALAL/JENSEN (2001), GUTTKUHN et al. (2003)) which is not a solution method itself and therefore not discussed in Section 3.5. We still list these articles here to show the complete range of methods used in crew scheduling applications. A detailed discussion on available crew scheduling applications can be found in the online appendix.

3.3.7 Country

If at least one real-world instance is considered and solved in the respective article, this column indicates the corresponding country code according to ISO 3166-1 ALPHA-2. 61 articles examine real-world instances from railway networks of Europe, 25 of Asia, 6 of North America, 3 of South America and 2 of Australia/New Zealand. If only small examples, randomly generated instances, benchmark instances or real-world instances without country information are used the corresponding cell in the table is marked with $\diamond$. Empty cells indicate articles that do not present test results related to train operations (e.g., bus) or not any test results at all.

Table 3.2: Overview of RCSP literature

Reference	Planning	Mode	Crew	Model	Objective			Solution method				Country
	stage		type		Schedule eff.	Rob.	Satisf.	IPM	H	CG	MH	S
ABBINK et al. (2005)	CS	LD,R	D,C	SCP	TC		•			•		
ABBINK / WOUT / HUISMAN (2007)	CS	LD,R	D,C	SCP	TC					•		NL
ABBINK et al. (2011)	CS	LD,R	D,C	SCP	TC		•			•		NL
ABBINK (2014)	CS,CR	LD,R	D,C	SCP	TC	•	•			•		NL
ABBINK / HUISMAN / KROON (2018)	CS,CR	LD,R	D,C	SCP	ND,TC					•		NL
ALBERS (2009)	CS	F	D	SCP	TC					◦		DE
ALEFRAGIS et al. (2000)	CS		D	SPP,SCP	TC				•			◊
ALFIERI / KROON / VAN DE VELDE (2007)	CS	LD,R	D	SCP	ND	•				◦		NL
AMAYA / URIBE (2018)	CS*CR	F	D	SPP	other					•		CL
BACH / DOLLEVOET / HUISMAN (2016)	TT*RSS*CS	F	D	SCP	TC					◦		DE,DK,SE
BALAKRISHNAN / KUO / SI (2016)	CS*CR	F	D,C	NFP	TC					•		US
BANIHASHEMI / HAGHANI (2001)	CS	U	D	NFP	TC					•		US
BENGTSSON et al. (2007)	CS	LD,R	D,C	SCP	TC						•	DE
BORNDÖRFER / GRÖTSCHER / LÖBEL (2001)	CS	U		SPP	TC						•	DE
BORNDÖRFER et al. (2017)	CS*CR		D	SPP	TC		•		•			DE,◊
BOSCHETTI / MINGOZZI / RICCIARDELLI (2004)	CS			SPP	TC			•				IT,◊
CABRERA / RUBIO (2009)	CS	R,U		SPP,SCP	TC						•	CL
CAPRARA / MONACI / TOTH (2001)	DG,CS*CR		D							•		IT
CAPRARA (2015)	TT,RSS,CS*CR			NFP,SPP						•	•	
CEDER / HASSOLD (2015)	CS		D	SCP	TC						•	NZ
CHAHAR / CHENG / PRANOTO (2011)	CS*CR	F										•
CHEN / SHEN (2013)	CS	R,U		SCP	ND,TC						•	CN
CHEN et al. (2013)	CS	U		SCP	TC					•		CN
CHEW et al. (2001)	CS	U	D	SPP,other	ND,TC			•			•	SG
CLAUSEN (2007)	TT,RSS,CS	U	D									
CLAUSEN / BAUDACH (2008)	CS	F		SPP	TC					•	•	◊
DALAL / JENSEN (2001)	CS*CR	F										•
DAUZÈRE-PÉRÈS et al. (2015)	RSS*CS		D	SPP	ND,TC					•		FR
DERIGS / MALCHEREK / SCHÄFER (2010)	CS	LD	C	SPP,SCP	TC						◦	DE
DESAULNIERS (2007)	CS			SPP	TC						◦	◊
DJELLAB / BIONNIER (2011)	CS,CR	F	D	SPP	ND,TC						•	FR

Reference	Planning	Mode	Crew	Model	Objective			Solution method					Country
	stage		type		Schedule eff.	Rob.	Satisf.	IPM	H	CG	MH	S	
DORNBERGER / FREY / SCHMID (2007)	CS,CR												◇
ELIZONDO et al. (2010)	CS	U	D		IT,ND						•		CL
ERNST et al. (2001)	CS*CR	LD	D	SPP	TC			•					AU
FENG / RUIHUA (2010)	CS	U	D	SPP	ND				•				◇
FISCHETTI et al. (2001)	RSS,CS		D	NFP	TC			•					IT,◇
FOLKMANN / JESPERSEN / NIELSEN (2007)	CS	U	D	SCP	ND,TC				•				DK
FORES / PROLL / WREN (2001)	CS	R,U	D	SCP	ND,TC					•			
FORES / PROLL / WREN (2002)	CS	R,U	D	SCP	ND,TC					•			
FRELING / LENTINK / ODIJK (2001)	CS	LD,R	C	SCP	TC					◦			NL
FRELING / LENTINK / WAGELMANS (2004)	CS*CR	LD,R	D,C	SPP	TC					◦			NL
FROGER / GUYON / PINSON (2015)	CS	LD,R	D	other	other				•				FR
FUENTES / CADARSO / MARÍN (2015)	CS	R,U	D,C	other	TC						•		ES
FUENTES / CADARSO / MARÍN (2019)	CS	R,U	D,C	NFP	TC						•		ES
GARCÍA et al. (2018)	CS			SCP	TC						•		◇
GOUMOPOULOS / HOUSOS (2004)	DG												DE
GRÖTSCHER / BORNDÖRFER / LÖBEL (2003)	CS	U		SPP	TC					•			DE
Guo / ZHOU / LI (2014)	CS	LD	D,C		TC						•		
GUTTKUHN et al. (2003)	CS*CR	F										•	
HAN / LI (2014)	CS	U	D	SCP	ND			•		•			TW
HANAFI / KOZAN (2014)	CS		D,C	SPP	IT,ND						•		◇
HOFFMANN (2017)	CS	R	C	SCP	TC					•			DE
HOFFMANN et al. (2017)	CS	R	C	SCP	TC					•			DE
HOFFMANN / BUSCHER (2019)	CS	R	C	NFP	TC			•					DE
HUANG / YANG / WANG (2011)	CS		D	NFP	IT,ND						•		TW
HUISMAN (2007)	CS	R		SCP	TC					•			NL
JANACEK / MARTON / KONIORCZYK (2016)	CS	F,R	D,C	SPP	IT,TC			•					HU,SK
JANACEK et al. (2017)	CS	F,R	D,C	SPP	IT,ND,TC					•			HU,SK
JÜTTE et al. (2011)	CS	F	D	SCP	TC	•				•			DE
JÜTTE / THONEMANN (2012a)	CS	F	D	SCP	TC					•			DE
JÜTTE / THONEMANN (2012b)	CS	F	D	SCP	TC					•			DE
JÜTTE (2012)	CS	F	D	SCP	TC					•			DE
JÜTTE / THONEMANN (2015)	CS	F	D	SCP	TC					•			DE
JÜTTE / MÜLLER / THONEMANN (2017)	CS	F	D	SCP	TC		•			•			DE
KHMELEVA et al. (2014)	CS*CR	F	D	SCP	TC						•		GB,◇

Reference	Planning	Mode	Crew	Model	Objective			Solution method					Country
	stage		type		Schedule eff.	Rob.	Satisf.	IPM	H	CG	MH	S	
KHMELEVA et al. (2018)	CS*CR	F	D	SCP	TC						•		GB
KHOSRAVI / TAMANNAEI / REISI-NAFCHI (2017)	CS,CR	LD		SCP	TC			•					IR
KHOSRAVI BIZHAEM / TAMANNAEI (2017)	CS,CR	LD		SCP	TC			•					IR,◊
KOHANI / JANACEK (2017)	CS	F,R	D,C	SPP	IT,TC					•			HU,SK
KOHL (2003)	CS	LD	D,C	SPP									DE
KOKUBO / FUKUYAMA (2017b)	CS			other	ND,other						•		
KOKUBO / KAWAGUCHI / FUKUYAMA (2017)	CS			other	ND,other						•		
KOKUBO / FUKUYAMA (2017a)	CS			other	ND,other						•		
KONIORCZYK / TALAS / GEDEON (2015)	DG	LD,R,U	D,C										HU
KROON / FISCHETTI (2000)	CS	LD,R	D,C	SCP	ND	•				•			NL
KROON / FISCHETTI (2001)	CS	LD,R	D,C	SCP	ND	•	•			•			NL
KROON et al. (2009)	TT,RSS,CS	LD,R	D,C	SCP	ND					•			NL
KUMAR et al. (2009)	CS*CR	F	D,C	NFP	TC	•		•	•				US
KUZNETSOV et al. (2016)	CS*CR	F	D	other	other				•		•		RU
KWAN / WREN / KWAN (2000)	CS	LD,R	D,C	SCP	ND						•		GB
KWAN / KWAN / WREN (2001)	CS	R	D,C	SCP	ND,TC						•		GB
KWAN (2004)	CS		D	SCP	TC,TD				•		•		
KWAN / KWAN (2007)	CS	R	D,C	SCP	ND,TC					•			GB
KWAN (2011)	CS	LD,R	D,C	SCP	ND,TC					•			GB
LAPLAGNE / KWAN / KWAN (2005)	CS	R	D	SCP	ND,TC	•			•				GB
LAPLAGNE (2008)	CS	R	D	SCP	ND,TC	•			•				GB
LEE / CHEN (2003)	CS,CR	LD,R	D	SCP	ND,TC					•	•		TW
LI / WU / LI (2012)	CS												
LI / KWAN (2003)	CS		D		ND,TC				•				GB
LI / KWAN (2005)	CS		D		ND,TC				•				GB
LI / NIE (2014)	CS,CR	LD		SPP	TC						•		CN
LIN / TSAI (2019)	CS*CR	L,R	D	other	other					•			TW
LIU / HAGHANI / TOOBAIE (2010)	CS*CR	LD	D,C	SPP	TC					•			US
MARTINS / MORGADO (2010)	CS	LD,R,U	D,C										NL,NO,FI,GB
MUROI / NISHI / INUIGUCHI (2010)	CS			SCP	TC					•			◊
NISHI / MUROI / INUIGUCHI (2011)	CS			SCP	TC					•			JP,◊
PARK / RYU (2006)	CS	U		other	other						•		◊
PENG / SHEN (2016)	CS	U		SCP	ND,TC				•				CN
PENG / SHEN (2018)	CS	U		SCP	ND,TC				•				CN

Reference	Planning stage	Mode	Crew type	Model	Objective			Solution method					Country
					Schedule eff.	Rob.	Satisf.	IPM	H	CG	MH	S	
PORTUGAL / LOURENÇO / PAIXÃO (2009)	CS		D	SCP	TC								PT
ŞAHİN / YÜCEOĞLU (2011)	CS	LD,R	D,C	NFP	other			•	•				TR
DOS SANTOS / MATEUS (2009)	CS			SPP	TC					◦			◊
SHEN / KWAN (2001)	CS		D		ND,TC						•		GB
SHEN (2001)	CS		D		ND,TC						•		GB
SHEN / KWAN (2002)	CS	U	D		ND,TC						•		GB
SHEN / CHEN / SU (2010)	CS	LD	D,C	SCP	TC			•					CN
SHEN et al. (2013)	CS			SCP	ND,TC						•		CN
SHEN / CHEN (2014)	CS		D,C	SCP	ND,TC					◦			CN
SHEN / LI / PENG (2017)	CS	U	D	SCP	TC				•				CN
SHI / ZHU / TIAN (2015)	CS	LD	D,C	SCP	IT						•		CN
SNIJTERS / SALDANHA (2017)	CS	R	SG	SCP	TC,other					•			NL
SONG et al. (2012)	CS	LD	D,C	other	IT						•		CN
SUYABATMAZ / ŞAHİN (2012)	CS	LD,R		SCP	ND					•			TR
SUYABATMAZ / ŞAHİN (2015)	CS	LD,R		NFP,SCP	ND			•		•			TR
THORLACIUS / CLAUSEN (2008)	CS	U	SG										
TIAN / SONG (2013)	CS	LD		SCP	TC						•		CN
VAIDYANATHAN / JHA / AHUJA (2007)	CS*CR	F	D,C	NFP	TC			•	•				US
VAIDYANATHAN / AHUJA (2015)	CS*CR	F	D,C	NFP	TC			•	•				US
WANG et al. (2008)	CS	LD		SCP	ND					◦			CN
YAGHINI / KARIMI / RAHBAR (2015)	CS	LD	D	SCP	TC						•		IR,◊
ZHAO / ZHEN (2007)	CS				ND						•		◊
ZHOU et al. (2016)	CS	U		SCP	TC						•		CN
ZHU et al. (2014)	CS	LD	D,C	SCP	TC						•		CN

Notes: TT-train timetabling; TP-train platforming; RSS-rolling stock rostering; DG-duty generation; CS-crew scheduling; CR-crew rostering; *-integrated approach; F-freight; LD-long distance; R-regional/suburban; U-urban; D-driver; C-conductor; SG-security guard; SCP-set covering problem; SPP-set partitioning problem; NFP-network flow problem; IT-idle time; ND-total number of duties; TC-total cost; ◦-branch-and-price; column “Country”: if real-world instances: country code of the respective country according to ISO 3166-1 ALPHA-2; if example: randomly generated instances, benchmark instances or real-world instances without country information: ◊.

3.4 Model formulations, objectives and constraints of RCSP

Research in RCSP is usually motivated by real-world cases with multiple objectives and numerous restrictions (see Table 3.2). In the interest of generating feasible and efficient crew schedules, a thorough understanding of the underlying problem instance and a convenient translation into a mathematical model is essential. In this section, we describe mathematical models used in RCSP literature and discuss three fundamental objectives: schedule efficiency, robustness and employee satisfaction. We close the section by giving an overview of the numerous and diverse constraints.

3.4.1 Model formulations

0/1-programming model formulations dominate RCSP literature. As Figure 3.4 shows, the set covering problem formulation (SCP) is by far the most popular model formulation among RCSP researchers: around 80% of the publications after 2000 use a variant of it. The set partitioning problem (SPP) is closely related to the SCP and the second most used mathematical model in this field. Both models (see Section 3.4.1) are path-flow formulations for RCSP, i.e. the decision variables represent feasible paths on a time-space network and therefore feasible duties. For specific cases, especially in freight transportation, some researchers describe RCSP as network flow problem (NFP), i.e. an arc-flow formulation where decision variables represent transitions between trips (see Section 3.4.1). In Section 3.4.1, we summarize other IP and LP model formulations which both are used seldom and only for individual cases.

Figure 3.4: Number of publications by model formulation for RCSP

Set covering/set partitioning problem

Historically and still today, the SCP/SPP model formulation can be characterized as the “standard model formulation” in RCSP literature (see Figure 3.4). In general, the railway crew scheduling problem is to cover each trip at least once with a feasible duty at minimal cost. The underlying idea in this mode is to generate all or at least a large

enough set of feasible duties of which a subset is selected to fulfill this target. This problem can be formulated as a generalized *set covering problem*. Let M denote the set of trips i and N the set of duties j . Furthermore, let c_j be the cost associated with duty j . The binary decision variable x_j correspond to selecting a feasible duty. The binary assignment matrix A defines the trips i covered by duty j , more precisely the coefficient a_{ij} is 1 or 0, if the duty j covers trip i or not, respectively. The SCP formulation is:

$$\min \sum_{j \in N} c_j x_j \quad (3.1)$$

$$s.t. \sum_{j \in N} a_{ij} x_j \geq 1 \quad \forall i \in M \quad (3.2)$$

$$x_j \in \{0, 1\} \quad \forall j \in N. \quad (3.3)$$

In general, the objective function (3.1) is to minimize the total cost of the schedule. Variants are discussed in Section 3.4.2. Constraints (3.2) ensure trip coverage by at least one of the duties of the final schedule. The covering constraints “ $\geq$ ” allow over-covering of trips, i.e. a crew works on the train while others are allowed to travel on the same trip without fulfilling working tasks. As a result, deadheading by train, i.e. crews travel back to their crew depot, can be directly generated from a SCP model formulation. Note that in fact, deadheading and non-working trips are often added or edited out manually in a following post-processing phase rather than generated by the solution approach. Modifications of the covering constraints can be found, for instance, in PORTUGAL/LOURENÇO/PAIXÃO (2009), who investigate model extensions which allow over- or undercover situations of trips for the original problem and for predefined sub-problems, respectively (e.g., at the beginning or end of a daily period). SHEN et al. (2013) allow temporary trip under-covering and a resulting infeasibility of the schedule by relaxing the covering constraints with penalties in the objective function. Similarly, SNIJDERS/SALDANHA (2017) introduce a slack variable for uncovered trips.

The *set partitioning problem* replaces the inequality “ $\geq$ ” of the covering constraints (3.2) “=” of the partitioning constraints (e.g., LIU/HAGHANI/TOOBAIE (2010)). Hence, the over-covering of trips, which is helpful, for instance, to easily model deadheading activities on trains, leads to infeasible solutions of the SPP. Some researchers suggest modifications to the SPP to maintain solution feasibility: LI/NIE (2014), for instance, add the corresponding traveling cost to the objective function. Other researchers (e.g., DAUZÈRE-PÉRÈS et al. (2015), ERNST et al. (2001)) allow over- or under-covering of trips by penalizing relaxed partitioning constraints or by adding slack variables. Still, SPP are by far more popular in airline crew scheduling problems where deadheading, if allowed, is much more expensive and undesirable.

The main advantage of these formulations is the simple constraint structure obtained by the 0-1-assignment matrix and the implicit fulfillment of all constraints at duty-level (see Section 3.4.3). Still, the problems are NP-hard with an exponential number of variables and require time-consuming, non-polynomial computation procedures (see FISCHETTI et al. (2001), HUISMAN et al. (2005)). Extensive work on improving the algorithms' performance has led to significant improvements of computational time (discussed in Section 3.5).

Network flow problem

In contrast to the duty-based (also referred to as *path-flow*) model formulation in the form of SCP or SPP, a group of researchers suggests the *arc-flow* formulation of a multi-commodity flow problem on a time-space network (*network flow problem, NFP*). Due to the great variety of instance-specific model formulations and modifications, we present a generic version (following e.g., HUANG / YANG / WANG (2011)): Let $\tilde{N}$ denote the set of nodes i associated with the train trips and D the set of drivers d . The binary decision variable x_{ij}^d represent the transition from trip i to trip j by driver d , where $x_{ij}^d = 1$ if arc (i, j) is used in the solution, $x_{ij}^d = 0$ otherwise. Let another binary decision variable $y_i^d = 1$ if node i is served by driver d , $y_i^d = 0$ otherwise. Furthermore, let c_{ij} be the cost associated with arc (i, j) .

The objective function is to minimize to total cost associated with the trip transitions

$$\min \sum_{d \in D} \sum_{i, j \in \tilde{N}} c_{ij} x_{ij}^d. \quad (3.4)$$

To ensure a feasible schedule, each node (trip) i must be served at least once

$$\sum_{d \in D} y_i^d \geq 1 \quad \forall i \in \tilde{N}. \quad (3.5)$$

Also, the flow out of the source node s equals the flow into the sink node t

$$\sum_{d \in D} \sum_{i \in \tilde{N} \setminus \{s\}} x_{si}^d = \sum_{d \in D} \sum_{i \in \tilde{N} \setminus \{t\}} x_{it}^d, \quad (3.6)$$

while both flows are limited to the number of available drivers

$$\sum_{d \in D} \sum_{i \in \tilde{N} \setminus \{s\}} x_{si}^d \leq |D|. \quad (3.7)$$

Finally, the flows at each node j are balanced

$$\sum_{d \in D} \sum_{i \in \tilde{N} \setminus \{j\}} x_{ij}^d = \sum_{d \in D} \sum_{m \in \tilde{N} \setminus \{j\}} x_{jm}^d \quad \forall j \in \tilde{N} \quad (3.8)$$

and the decision variables are integer

$$x_{ij}^d, y_i^d \in \{0, 1\} \quad \forall i, j \in \tilde{N}, \forall d \in D. \quad (3.9)$$

In RCSP literature, we found two slightly different variants of interpreting the underlying time-space network. In most cases, each trip is assigned to one node and the edges indicate whether two trips have a time-space connection or not. The objective is to minimize the total cost or transition times as shown in (3.4). A group of researchers (VAIDYANATHAN / JHA / AHUJA (2007) and KUMAR et al. (2009) among others) present a time-space network with specific details: each node corresponds to a crew event such as departure/arrival of trains or deadhead. This thorough representation of each duty activity and its associated cost results in a very large network. ŞAHİN / YÜCEOĞLU (2011) suggest another variant with the objective to minimize the total number of flows out of the sources, i.e. the number of required crews.

NFP allow for an accurate and explicit formulation of all real-world restrictions (see BALAKRISHNAN / KUO / SI (2016) for a detailed model) as well as selective problem adjustments, e.g., temporary modifications. This is especially handy for freight transportation, where orders are scheduled with very short lead time (VAIDYANATHAN / JHA / AHUJA (2007)). However, due to the usually heavily restricted RCSP (see Section 3.4.3), the problem size, in particular the number of constraints, is much larger than the size of corresponding SCP/SPP models (e.g., BANIHASHEMI / HAGHANI (2001)). Some researchers (e.g., SUYABATMAZ / ŞAHİN (2015)) compare the solution procedures of the two different model formulations, NFP and SCP/SPP. FISCHETTI et al. (2001) show that NFP only performs better in the case of loosely constrained instances of medium size.

Other model formulations

RCSP are subject to a great variety of operators' conditions and network structures. Therefore, some researchers develop other, case-dependent IP models. Aiming to avoid over-covered trips, FROGER / GUYON / PINSON (2015) and FUENTES / CADARSO / MARÍN (2015) propose *set packing problems*. These are similar to SCP/SPP formulations differing in the packing constraints, i.e. the trip covering constraints are restricted by " $\leq$ " instead of " $\geq$ " or " $=$ ". In other words, the packing constraints restrict the number

of duties to cover one trip to 1. Hence, the objective is to minimize the total number of duties while as many trips as possible are covered. Similarly, PARK/RYU (2006) suggest a *maximal covering problem* to minimize the number of uncovered trips by a fixed number of duties. Using a modified NFP, SONG et al. (2012) minimizes the rest time in all round-trips. The decision variables in the quadratic objective function correspond to whether a trip and its successor are selected in the respective duty. For a special case of night duties that consist of two trips only, CHEW et al. (2001) develop a *Bipartite Matching Model* to optimize two-trip-combinations. LIN/TSAI (2019) propose a mixed integer programming model for integrating the planning tasks of crew scheduling and crew rostering with the objective to minimize the number of drivers.

To the best of our knowledge, RCSP in passenger transportation exclusively apply 0-1 mathematical programming. The only non-integer model formulation is applied by KUZNETSOV et al. (2016). They propose a linear *assignment problem* to generate $\langle \text{train}, \text{crew} \rangle$ -pairings subject to maximal utility for a freight transportation problem with very long train trips.

3.4.2 Objectives

Besides feasibility of the final schedule, the most important objective of RCSP is schedule efficiency, that can be interpreted by different metrics such as total cost, total number of duties or crews or idle time. Section 3.4.2 discusses the differences, which often depend on the railway operator's individual requirements. Some researchers reflect on the objectives of robustness and/or employee satisfaction, which stand in contrast to schedule efficiency and require a trade-off decision by the operator (ABBINK/HUISMAN/KROON (2018)). The diverse ways of incorporating those objectives into RCSP models are described in Sections 3.4.2 and 3.4.2. We discuss objectives of RCSP from a general perspective, not only restricted to the mathematical formulation of the objective function itself. Thus, the following objectives can also be modeled as hard (explicitly modeled) or soft (penalties in the objective function) constraints.

Schedule efficiency

From an railway operator's perspective, in an optimal case, crews work exactly the monthly hours agreed by their working contract. In addition, they pursue highly productive duties, i.e. avoiding unused or exceeded contracted working hours and pushing the share of driving time to a maximum (see KHMELEVA et al. (2018)). Hence, the main driving force for the development of computer-aided railway crew scheduling systems has been schedule efficiency. In RCSP literature, improving schedule efficiency is modeled by different metrics such as to minimize total cost, to minimize the number of duties or

crews, to minimize idle times or a combination of the above.

Total cost The most popular objective function in RCSP literature is to minimize the cost of the total schedule (see Table 3.2). In general, the cost associated with one duty can be described by the following function

$$C_{\text{total}} = C_{\text{working time}} + C_{\text{idle time}} + C_{\text{paid break time}} + C_{\text{deadheading}} + C_{\text{layover}}. \quad (3.10)$$

The total duty cost usually consists of two parts: the cost to operate the trips and other direct costs. The first part is a function of the sum of working time, idle time and paid break time multiplied by the average personnel cost per hour. If applicable, other direct costs consist of expenses for deadheading (e.g., by taxi) and for layovers (e.g., hotels, (see KOHL (2003), KHMELEVA et al. (2018))). Hence, cost-efficient, i.e. highly productive, duties consist of a high share of working time, while idle times, deadheading trips and layovers are reduced to a minimum (see KHMELEVA et al. (2014)).

In RCSP literature, the design of the cost function depends on the actual problem instance. The most straightforward way is to assign a fixed cost part, e.g., to assign overhead cost or to manage the total number of duties and a variable cost part depending on the total duty time. A clear and simple version of a cost function can be found in LI / NIE (2014). Here, the total costs of one duty consist of the cost for working time plus the cost for traveling without working. Others outline a more detailed cost function, for instance similar to Equation (3.10) (e.g., VAIDYANATHAN / JHA / AHUJA (2007)).

Number of duties or crews Some researchers define the objective function as to minimize the number of duties to operate a predefined set of trips (e.g., MUROI / NISHI / INUIGUCHI (2010), NISHI / MUROI / INUIGUCHI (2011), ŞAHİN / YÜCEOĞLU (2011), SUYABATMAZ / ŞAHİN (2015)). In the UK, for instance, the total number of duties is of higher priority than the total working hours or cost per duty. Hence, a large research group develops models and objective functions around this objective (see KWAN / WREN / KWAN (2000), LAPLAGNE / KWAN / KWAN (2005), SHEN / CHEN (2014)). It should be noted that minimizing the number of duties might conflict with minimizing the total schedule cost. This is because a low number of duties in a schedule requires relatively long duties which represent not necessarily the most cost-efficient combinations of trips. As a result, researchers suggest a weighted multi-objective function (see KWAN / KWAN (2007), LAPLAGNE (2008), SHEN / KWAN (2002), PENG / SHEN (2016)) or a bi-objective SCP (LEE / CHEN (2003)), which allows the railway operator to prioritize according to his preferences.

Total idle time In some cases, researchers aim to generate highly productive duties by minimizing the total idle time, which is defined as non-working or transition times (see HANAFI/KOZAN (2014), SONG et al. (2012)). As minimizing idle times could lead to a higher number of duties and, therefore, the number of crews needed, ELIZONDO et al. (2010) and HUANG/YANG/WANG (2011) use multi-objective programming and add the objective to minimize the total number of duties and crews, respectively. Some researchers suggest to emphasize excessive idle times by adding penalties to the objective function (see JANACEK/MARTON/KONIORCZYK (2016), JANACEK et al. (2017)). SHI/ZHU/TIAN (2015) suggest chance constraint programming to minimize the connection time between trips.

Robustness

Robustness or the capability of a railway system to continue its operations despite disruptions includes the ability to absorb small disruptions (e.g., small train delays) and to recover from large disruptions (e.g., emergency accidents, train failures) (LUSBY/LARSEN/BULL (2018)). Robust operations are crucial to maintain a high service level for passengers and are therefore one main objective of operators (FRIEDRICH et al. (2018)). Aspects to achieve robustness have been investigated for each operational planning step (see LUSBY/LARSEN/BULL (2018) for an overview). However, since timetabling is the most critical planning step, it is by far the most discussed in the literature, both separately and integrated with other planning steps (see CACCHIANI/TOTH (2018) or LU/HAN/ZHOU (2018) for overviews). In the case of a disruption which is too large to be absorbed by the system, real-time modifications to the timetable with impact on all depending plans including the crew schedule become necessary (see Section 3.2.3). Since our focus is operational crew scheduling, we restrict the discussion to strategies to improve the delay-tolerance of crew schedules.

Train changes of a crew are critical to smooth, i.e. disruption-free, operations. As long as a crew stays on the same vehicle, its duty is not or only slightly affected by possible other disruptions. In order to reduce the number of train changes, ALFIERI/KROON/VAN DE VELDE (2007), FRELING/LENTINK/ODIJK (2001) and FRELING/HUISMAN/WAGELMANS (2003) apply penalties or define a maximum number of train changes. Additionally, they prohibit crew changes in-between a train run. Since a policy of no train changes is not executable, a common approach is to define a minimum connection time (KROON/FISCHETTI (2000), KROON/FISCHETTI (2001)) or add buffer times (JÜTTE et al. (2011)). LAPLAGNE/KWAN/KWAN (2005) and LAPLAGNE (2008) explore the concept of windows of relief opportunities to take advantage of the fact that train vehicles often stop for some time at a station before continuing and, thus, optimize

the timing of the driver's relief with respect to robustness. By applying a local search algorithm, they could improve the robustness measures of a schedule without increasing the schedule cost.

Other robustness considerations include the concept of train teams (driver and conductor) to cut the degrees of freedom for disruptions (KROON/FISCHETTI (2001)), increasing the crews' knowledge about the operated train and timetable (KROON/FISCHETTI (2001)) and marginally reducing the maximal work time per duty to ensure that a duty remains valid in spite of ongoing disruptions (JÜTTE et al. (2011)). Since crew assignment in freight transportation is done on a more regular basis, other measures can be taken: KUMAR et al. (2009) explicitly add train delays by constructing additional arcs in their time-space network.

To date, there is only little research assessing crew schedule robustness against disruptions and evaluating the trade-offs between robustness and cost-efficiency. FRIEDRICH et al. (2018) and AMBERG/AMBERG/KLIEWER (2019) provide comprehensive studies in related fields, namely train timetabling and bus vehicle with crew scheduling. To the best of our knowledge, only YAP/VAN OORT (2018) propose a framework to quantify the passengers and operator costs of disruptions as a function of different driver schedule schemes. They show that the cost benefits from more robust crew schedules outweigh the benefits from complex, but cost-efficient ones. Hence, the need for robust railway crew schedules and the impact on cost and other objectives could be investigated in more detail.

Employee satisfaction

A cost-efficient and/or robust schedule will not be implemented if it does not gain wide acceptance in the workforce. In Europe, for instance, crews and their interests are strongly represented by company-wide and local work councils. In some cases, new schedules or rosters even request the work councils' approval at each depot before implementation (JÜTTE/MÜLLER/THONEMANN (2017)). Even without a strong work council, railway operators should aim for sustainable and fair crew schedules. One reason to consider employees' needs in the schedules is security: in their recent study, RUDIN-BROWN/HARRIS/ROSBERG (2018) investigate accidents in the Canadian railways and identify crew schedules which do not reflect the employees' circadian rhythms and sleep requirements as one major issue. Even though employee satisfaction and schedule cost efficiency are conflicting objectives, JÜTTE/MÜLLER/THONEMANN (2017) and BORNDÖRFER et al. (2017) show that only small investments (up to 3%, see JÜTTE/MÜLLER/THONEMANN (2017)) of the total schedule cost could significantly increase the fairness and the popularity of the schedule. Still, there is only little research that assesses

the effects of specific measures to the employees' satisfaction and trade-offs between the conflicting objectives. Instead, there are only few fundamental concepts presented in the crew scheduling literature.

In most cases, legal rules and labor tariffs (see Section 3.4.3) set appropriate limits, e.g., to total working hours per duty or break times. However, not all duties enjoy the same popularity among crews for different reasons. For example, duties with comparably unfavorable working hours but equal pay are not very popular (JÜTTE/MÜLLER/THONEMANN (2017)). In the Netherlands, preferred duties (*sweet*) respond to a high variety in routes and train types, while *sour duties* are on lines with a lot of anticipated passenger aggression or on old rolling stock (see ABBINK et al. (2005), ABBINK et al. (2011)). ABBINK et al. (2011) propose to distinguish between A- (preferred) and B- (unpopular) trains. The number of unpopular duties is either limited, penalized or distributed across the different depots (e.g., KROON/FISCHETTI (2001), ABBINK et al. (2005), ABBINK et al. (2011), JÜTTE/MÜLLER/THONEMANN (2017)). Additionally, KROON/FISCHETTI (2001) formulate *repetition-in-duty* characteristics, so that each long duty varies in at least two of the three components line, train type or corridor of infrastructure.

Since a balanced mix of working and recovery time is fundamental on a longer term perspective, the subsequent planning step of assigning anonymous duties to crew members (crew rostering) has even more impact on the employees' satisfaction. A common approach is to penalize the operator's and crews' preferences to satisfy the majority of needs and create workload balance (FRELING/LENTINK/WAGELMANS (2004), ERNST et al. (2001)). Alternatively, BORNDÖRFER et al. (2017) propose integrating crew scheduling and crew rostering. This allows to model crew preferences, such as free weekends and avoiding erratic starting times of duties, explicitly. The resulting crew schedules increase employee satisfaction at almost zero costs.

3.4.3 Constraints

Railway crew scheduling is governed by a great variety of legal rules and regulations of public transport authorities (e.g., the Federal Railway Administration (FRA) in the US, see KUMAR et al. (2009)), complex labor union contracts (see ABBINK et al. (2005), JÜTTE/MÜLLER/THONEMANN (2017)), individual operating conditions and further rules defined by the operator. Researchers in RCSP, therefore, are obliged to build an extensive knowledge about the instance-specific rules and restrictions and to accurately translate them into a mathematical model. To manage the size of the solution space, it is common practice to relax constraints or differentiate between hard and soft rules, which are frequently modeled as constraints and penalties, respectively (see ABBINK et al.

(2005), BANIHASHEMI/HAGHANI (2001), KHMELEVA et al. (2018)).

For the sake of brevity, we refrain from surveying and categorizing all instance-specific forms of constraints in detail. For country and operator specific rules and restrictions, we refer the reader to publications of country cases, which can be seen in Table 3.2. Here, we give an overview of the most common constraints and highlight selected examples of special constraints or model extensions. In general, constraints apply to different levels of a schedule: to the duty itself, to a depot, to the total schedule or to specific types of crew members.

Duty-based constraints must be fulfilled to create a legal duty. This includes fundamental constraints such as a *geographical and chronological link between two consecutive trips* and the same start and end depot per duty (known as *duty symmetry*). In some cases, it appears useful to restrict the *number of trips per duty* to a maximum (see FROGER/GUYON/PINSON (2015), PARK/RYU (2006)) or to define a *maximal trip duration* (see SHEN/CHEN (2014)). The *minimal connection time* between train changes needs to reflect times for walking, handover tasks, etc. and has a major effect on the robustness of the schedule (see Section 3.4.2). *Deadheading* by train is often allowed in RCSP, even other transportation modes such as taxi can be used (e.g., see JANACEK/MARTON/KONIORCZYK (2016)). ABBINK et al. (2005) add penalties to the objective function in order to reduce the number of such positioning trips. In freight operations and special cases of long-distance passenger train services, the *away rest time during layovers* and the *home rest time between duties* have a lower and upper bound (see MUROI/NISHI/INUIGUCHI (2010), KUMAR et al. (2009)). Most restrictions on duty-level refer to time aspects in order to ensure sustainable working hours for crews. This includes a *maximal consecutive or total driving time* (or distance) and a *minimal and maximal total working time* (or duty duration). Besides driving time, the latter includes break times, idle times and all non-driving tasks, in particular additional sign-on/-off time or preparation/finishing tasks such as quality checks, paperwork and handover meetings (see FRELING/LENTINK/ODIJK (2001), ŞAHİN/YÜCEOĞLU (2011)). If the total working time does not equal the total paid time, a *minimal paid time per duty* can be required (see HOFFMANN et al. (2017)). Break rules belong to the most complex regulations. They usually depend on the duty duration. For instance, in the Netherlands, duties longer than 5:30 hours require a meal break of at least 30 minutes (see KROON/FISCHETTI (2000)). Hence, the *number and duration of breaks* must fulfill a certain minimum and they can also be restricted to a maximum at the same time. It is also common to define the *latest possible start time of a break*, usually after a certain time of duty duration (e.g., meal breaks must start at the latest after 5:30 hours). HAN/LI (2014) and ZHOU et al. (2016) allow breaks only at pre-defined time windows during the

day. It should be noted that breaks can only occur at defined relief points with meal break opportunity (see MUROI/NISHI/INUIGUCHI (2010)).

At depot-level and schedule-level, a subset or the total set of duties in the solution are subject to fulfill certain constraints. Commonly, railway networks exist of multiple depots from which crews might operate. Problems with a single depot are rather rare, they occur, for instance, when only one line is scheduled. The number of duties or crews assigned to each depot might be restricted (known as *depot capacity*). The *average working time*, *duty duration* or *paid time* can apply at depot-level (see KROON/FISCHETTI (2000)) or to the total schedule (see SHEN/CHEN (2014), HOFFMANN et al. (2017)). Similarly, specific duty types such as *night duties* or *part-time duties with special break time rules* might apply. Their *balancing across depots or weekdays* increases the problem's complexity (see e.g., SHEN/CHEN (2014)).

It is common practice to schedule each type of crew (driver, conductor, catering staff, security guard) separately because of variation in rules and restrictions (KWAN (2011)). *Line or traction knowledge* is very important for drivers; they usually need a qualification for operating a specific vehicle type (see ABBINK et al. (2005), DORNBERGER/FREY/SCHMID (2007), KHMELEVA et al. (2014), KUMAR et al. (2009), KWAN/KWAN/WREN (1999)). For conductors, HOFFMANN (2017) considers minimal attendance rates below 100% per line, day-time or other categories. SNIJDERS/SALDANHA (2017) address, among others, the one-or-nothing behavior of duties for security guards on trains, i.e. one trip of the train is covered or the train is not covered at all. KUMAR et al. (2009) and VAIDYANATHAN/JHA/AHUJA (2007) include the *assignment of crews in FIFO (first in - first out) order at a depot*. For safety reasons, SHEN/CHEN (2014) restrict the *time period on the same type of train* and ŞAHİN/YÜCEOĞLU (2011) add a *required double manning time*.

3.5 Solution methods

RCSP are very large because of not only the immense quantity of constraints and variables but also their complex structure and explosion in combination possibilities (see KOHL (2003)). Additionally, a large number of IP problems is known to be NP-hard and, therefore, their solution requires high computational effort. Figure 3.5 gives an overview of the absolute numbers of the different solution methods we found in the literature since 2000, categorized into integer programming methods (IPM), heuristics, column generation and meta-heuristics. The computational complexity led to extensive research in heuristics, column generation, and meta-heuristics. In contrast, integer programming methods are used in few cases only. Three articles in our collection focus on

the step of building an efficient initial set of duties. CAPRARA/MONACI/TOTH (2001) extensively investigate the efficiency of trip-combinations and combine different integer programming and heuristic procedures to generate duties. GOUMOPOULOS/HOUSOS (2004) reduce the search space using a rule modeling system and develop a duty generation module with an efficient legality check procedure. Lastly, KONIORCZYK/TALAS/GEDEON (2015) propose a backtracking algorithm to generate feasible duties.

Figure 3.5: Number of publications on RCSP by solution methods

3.5.1 Integer programming methods

The most straightforward way to solve SCP/SPP formulations close to optimality is a complete enumeration of all feasible duties (e.g., HAN/LI (2014), SHEN/CHEN/SU (2010)) and the subsequent solving of the problem instance by integer programming methods of a commercial solver (referred to as CEwIPM in Table 3.3). As a consequence of the high computational effort to solve these exact mathematical formulations, integer programming methods are only applied to problem instances of small or sparse railway networks with a relatively small number of feasible trip combinations (see Table 3.3). ERNST et al. (2001), KHOSRAVI/TAMANNAEI/REISI-NAFCHI (2017), KHOSRAVI BIZHAEM/TAMANNAEI (2017) and SHEN/CHEN/SU (2010) apply these methods to (bi-)weekly crew scheduling for long-distance passenger transportation in Australia, Iran and China, respectively. The largest problem instance combines up to 40,000 feasible duties. A slightly larger problem in terms of number of variables (57,000 feasible duties) is solved by HAN/LI (2014) for a daily schedule of one line for a subway operator in Taipei. JANACEK/MARTON/KONIORCZYK (2016) show that for small instances with up to 83 trips, the combination of complete enumeration and integer programming methods outperforms their column generation approach (see Section 3.5.3).

Some researchers simplify optimization models by removing difficult constraints and solving the relaxed problem by integer programming methods. The violated constraints are then re-added to the problem in iterative steps. VAIDYANATHAN/JHA/AHUJA (2007) apply this approach to a RCSP in US freight transportation. With successively adding violated constraints to the relaxed NFP, they generate a near-optimal bi-weekly schedule for 326 trips. As a result, only a few FIFO constraints remain violated (see also

KUMAR et al. (2009), VAIDYANATHAN/AHUJA (2015)). HOFFMANN/BUSCHER (2019) solve their NFP with a commercial solver and investigate the influence of different defined valid inequalities on computation times as well as on bounds of the linear relaxation. Small instances with up to 110 trips are solved to optimality.

In the early 2000s, FISCHETTI et al. (2001) developed exact branch-and-cut procedures that are able to solve at least the one-depot case with up to 500 trips. The multi-depot case could not be solved to optimality though. BOSCHETTI/MINGOZZI/RICCIARDELLI (2004) extend the method developed by MINGOZZI et al. (1999) to the multi-depot case. The underlying idea is to restrict the original problem to a smaller sub-problem which can be solved with an integer programming solver in reasonable time. The size of the sub-problem iteratively increases until optimality is proved by one of three lower bounds.

In some cases, the structure of the underlying real case allows a model formulation which can be solved with integer programming methods relatively fast. For instance, CHEW et al. (2001) deal with night duties which, per operator's definition, combine two trips only. The authors apply a Hungarian algorithm to the resulting Bipartite Matching Problem. SUYABATMAZ/ŞAHİN (2015) solve their problem of connecting trip-combinations to form a schedule with a commercial solver. ŞAHİN/YÜCEOĞLU (2011) use a commercial solver for their NFP to schedule crews of a Turkish railway operator in one region with days off requirements.

Table 3.3: Overview of integer programming methods in RCSP

Reference	Integer programming methods			Problem size # trips	Characteristics
	CEwIPM	Constraint relaxation	Other IPM		
BOSCHETTI / MINGOZZI / RICCIARDELLI (2004)			•	500	Three lower bounds
CHEW et al. (2001)			•	na	Hungarian algorithm for two-trips-duties
ERNST et al. (2001)	•			1,309	
FISCHETTI et al. (2001)			•	500	Branch-and-cut, one depot
HAN / LI (2014)	•			228	Constraint programming in 1st phase
HOFFMANN / BUSCHER (2019)			•	110	
JANACEK / MARTON / KONIORCZYK (2016)	•			83	
KHOSRAVI / TAMANNAEI / REISI-NAFCHI (2017)	•			1,602	
KHOSRAVI BIZHAEM / TAMANNAEI (2017)	•			1,602	
KUMAR et al. (2009)		•		326	
ŞAHİN / YÜCEOĞLU (2011)			•	na	
SHEN / CHEN / SU (2010)	•			67	
SUYABATMAZ / ŞAHİN (2015)	•		•	44	
VAIDYANATHAN / JHA / AHUJA (2007)		•		326	
VAIDYANATHAN / AHUJA (2015)		•		326	

Notes: CEwIPM-complete enumeration with integer programming methods; na-computational results provided, number of trips not available

3.5.2 Heuristics

Since especially for larger instances of RCSP optimal solutions are unlikely to be found in reasonable time, heuristics are subject to intensive research in this field. On the basis of certain problem-specific rules, these methods exploit the underlying problem structure to determine a good but not necessarily optimal solution. Owing to the great popularity of one heuristic method for RCSP, namely column generation, we outline this approach separately in Section 3.5.3.

Building on the combination of complete enumeration and integer programming methods discussed in Section 3.5.1, FOLKMANN/JESPERSEN/NIELSEN (2007) reduce the set of duties to a smaller number, that is generated according to defined rules, e.g., historical schedule information. The resulting SCP is solved by a commercial solver. A similar approach by CHEN et al. (2013) uses network information to relax relief opportunities generate a subset of feasible duties. However, these approaches reach their limit with regard to computational time with larger problem sizes. Using a similar solution method, CLAUSEN/BAUDACH (2008) show that already for instances with 500 trips their defined time limit of 12 hours is exceeded. Some researchers investigate heuristics to select duties from a pre-generated set. LI/KWAN (2003) and LI/KWAN (2005) apply a greedy heuristic to sequentially select duties. The evaluation of the duties in the remaining set relies on criteria obtained from a fuzzy genetic algorithm. SHEN/LI/PENG (2017) explore a flexible rule-based selection algorithm by using six different rules in combination with an estimation of distribution algorithm which belongs to the general class of genetic algorithms. PENG/SHEN (2016) apply a greedy algorithm to construct schedules based on parameters gained from an evolution procedure, called grey relational analysis. Aiming to achieve improved schedules in iterative steps, the parameters evolve over time using a genetic algorithm. Similarly, PENG/SHEN (2018) apply grey relational analysis to evaluate duties in a variable iterated greedy algorithm: each iteration includes duty destruction, duty construction and selection as well as local improvements. BANIHASHEMI/HAGHANI (2001) develop an iterative heuristic to generate a solution for a number of workdays. The solution of one workday is combined with the previous problem by adding soft and hard constraints as well as the new variables of the additional workday. Similarly, ŞAHİN/YÜCEOĞLU (2011) propose a sequential approach to schedule crews with day-off requirements. In the first step, the minimum flow problem with relaxed day-off requirements is solved by integer programming methods of a solver. Then, additional crews are added by solving an assignment problem with greedy heuristic. It should be noted that the alternative integrated approach, described in Section 3.5.1, outperforms this approach in terms of both solution quality and time. Additionally, ŞAHİN/YÜCEOĞLU (2011) explore the potential of planning multiple re-

gions by applying a neighborhood search algorithm to split and/or re-allocate duties to an adjacent region.

Lagrangian based heuristics which combine Lagrangian relaxation of constraints and sub-gradient optimization are among the most frequently used heuristics to solve larger instances of RCSP. CAPRARA (2015) provides a good overview of this method and discusses a powerful combination with a diving heuristic. The latter fixes variables to 1 based on the information obtained from the relaxed problem in iterative steps until a feasible solution is found. This diving heuristic can also be combined with linear relaxation. ALEFRAGIS et al. (2000) propose a Lagrangian based heuristic which considers one Lagrangian relaxed constraint at a time and updates the Lagrangian multiplier so that the solution is feasible for the considered constraint, the so-called constraint update. A heuristic procedure forces the constraint update towards a feasible solution. To accelerate computational time, they restrict the total set of duties to a smaller active set which excludes those variables with high likelihood of being non-critical to the final solution. FROGER/GUYON/PINSON (2015) suggest an effective method combining Lagrangian relaxation and sub-gradient optimization with a greedy heuristic and variable fixing technique to select duties and generate a good schedule.

Lagrangian relaxation is also very popular for problems that integrate crew scheduling with previous or successive railway planning steps. DAUZÈRE-PÉRÈS et al. (2015) suggest a Lagrangian based framework for an integrated problem of scheduling rolling stock (RSS) and crews (CS). After two sub-problems (RSS and CS) are generated by Lagrangian relaxation of the coupling constraints, they are solved separately in iterative steps with cost function updates until a rolling stock plan is determined. Based on this result, a feasible crew schedule is constructed. In a similar way, CAPRARA/MONACI/TOTH (2001) use Lagrangian relaxation to solve an integrated crew scheduling and crew rostering problem. The solution procedure uses the available decision support tools for each of the two relaxed sub-problems. In each iteration, the cost function is updated until a reasonable crew schedule is obtained upon which the roster is finally built. With the aim to increase employee satisfaction, BORNDÖRFER et al. (2017) apply Lagrangian relaxation and Benders decomposition to solve an integrated crew scheduling and crew rostering problem similarly as described above.

Local-search heuristics are applied to improve an existing schedule. As mentioned in Section 3.4.2, LAPLAGNE/KWAN/KWAN (2005) and LAPLAGNE (2008) explore the potential of windows of relief opportunities (WRO) in order to increase schedule robustness. They propose a two-stage multi-neighborhood local search algorithm with approximated WRO to a schedule obtained from a generate-and-select-procedure (also see KWAN (2004)). LAPLAGNE (2008) extends this approach to looping back into the

generate-and-select-procedure. In order to balance the weekly workload among crews, AMAYA/URIBE (2018) apply a local search algorithm to a feasible solution. This local search heuristic iterates over defined time windows in a weekly schedule and re-optimizes the variables in each window with respect to total workload balance. In the final step, they assign crews to the duties, taking into account conditions like current location and hours-of-rest requirements (crew rostering).

Since RCSP in freight transportation often are modeled as NFP, the solution methods differ from the passenger transportation cases described above. A research team around VAIDYANATHAN/AHUJA (2015) suggests quadratic cost perturbation to relax the difficult FIFO constraints of their freight crew scheduling problem (see Section 3.4.3). Constraint violations are accepted but might be pruned out by re-adding the violated constraints to the model. For solving a freight transportation case, BALAKRISHNAN/KUO/SI (2016) let crews travel across a time-space network and assign them to their next primary or secondary trip according to defined rules. Subsequently, several local improvement procedures, e.g., re-assignment of deadheading crews, resolving constraint violations and improving the total cost. FENG/RUIHUA (2010) use best fit greedy algorithm to construct duties by trip combination for a subway line with two terminals. Lastly, KUZNETSOV et al. (2016) apply the method of auction for their assignment problem in freight transportation and show its strong performance against other methods such as simulated annealing.

3.5.3 Column generation

Column generation is a powerful method to keep the problem size manageable. In our literature collection, problem instances with up to 30,000 trips (see JÜTTE/THONEMANN (2012a)) could be solved in reasonable time. Hence, we observe many variants to implement CG for RCSP (50 articles, see Table 3.4). DESROSIERS/LÜBBECKE (2005) and LÜBBECKE/DESROSIERS (2005) provide comprehensive overviews of CG and its many applications. In broad terms, the procedure starts with a small subset of feasible duties and iteratively adds new duties if they potentially improve the current best solution. For this purpose, RCSP is divided into two problems: the master problem (MP) to select duties and the pricing problem (PP, also known as sub-problem) to generate new duties. To achieve an integer solution, the CG procedure is either integrated in a branch-and-bound-scheme (called branch-and-price) or the integer solution is computed in a subsequent step building on the solution of the relaxed MP.

Master problem

As shown in Table 3.4, the majority of researchers (36 out of 50) apply linear relaxation to the MP. In most cases, the solution is obtained by LP methods of a commercial solver, such as CPLEX, XPRESS or Gurobi (e.g., FRELING / LENTINK / WAGELMANS (2004), HOFFMANN et al. (2017), JÜTTE / THONEMANN (2012a), SHEN / CHEN (2014)). BENGTTSSON et al. (2007) benchmark commercial solvers and their variety of LP methods with regard to the convergence of lower and upper bounds.

The other investigated way to simplify the MP is Lagrangian relaxation and subgradient optimization coupled with a pricing technique. Most of these solution approaches are based on a heuristic originally developed by CAPRARA / FISCHETTI / TOTH (1999).

Pricing problem

Based on the dual information obtained from the solution of the MP, the PP is solved. Commonly, the PP is modeled as shortest path problem with resource constraints (SP-PRC) and solved by dynamic programming (DP, e.g., JÜTTE (2012)). Here, the construction of the underlying time-space network is important to represent the network information as adequate as possible. In the considered literature, there exist two alternatives: either a task is represented by a node and arcs show all possible connections between these nodes (e.g., ABBINK et al. (2011) or ALBERS (2009)), or, vice-versa, an event is a node and a task is an arc connecting two nodes (e.g., CLAUSEN / BAUDACH (2008) or KROON / FISCHETTI (2001)). NISHI / MUROI / INUIGUCHI (2011) do not explicitly model all features of the network but add dual inequalities to the MP to ensure that specific trip-combinations cannot be selected by the PP. Within dynamic programming, two different strategies are commonly employed: label setting (e.g., DERIGS / MALCHEREK / SCHÄFER (2010), DESAULNIERS (2007), JANACEK et al. (2017) and KOHANI / JANACEK (2017)) or label pulling algorithms (e.g., ALBERS (2009), JÜTTE / THONEMANN (2015)). In ABBINK et al. (2011) and HUISMAN (2007), several variations of the shortest path are created and added to the MP. A similar procedure, namely k -shortest-path enumeration, is introduced by BENGTTSSON et al. (2007). BORNDÖRFER / GRÖTSCHER / LÖBEL (2001) present a depth-first search enumeration algorithm that uses Lagrangian distance labels as a backtracking criterion. FRELING / LENTINK / WAGELMANS (2004) combine different algorithms, namely a dynamic programming algorithm, a depth-first search algorithm and an all-pairs shortest path algorithm, to solve the PP.

LEE / CHEN (2003) apply a heuristic (H) based on decision rules and a genetic algorithm to generate new duties. A genetic algorithm (GA) to accelerate the solution time of the PP is also proposed by HOFFMANN (2017), HOFFMANN et al. (2017) and LIU / HAGHANI / TOOBAIE (2010). DOS SANTOS / MATEUS (2009) combine the two ap-

proaches, genetic algorithm and dynamic programming. They show significant improvements in the first steps with the genetic algorithm, while the latter proves optimality of the relaxed MP in the final iterations.

CLAUSEN/BAUDACH (2008), FORES/PROLL/WREN (2001) and FORES/PROLL/WREN (2002) select duties only from a previously generated duty pool using the information on reduced cost (DSP). HAN/LI (2014) generate new duties based on a constraint programming approach (CP). If no solution method for the PP is mentioned explicitly in the respective article, the corresponding cell in Table 3.4 is empty.

Integer problem

Since the solution of the relaxed MP is not necessarily integer, several techniques are proposed to generate the IP solution. 10 articles in our collection apply branch-and-price (B&P, e.g., DOS SANTOS/MATEUS (2009), WANG et al. (2008)). Usually, the search tree is explored by performing a depth-first search strategy (e.g., ALFIERI/KROON/VAN DE VELDE (2007), BACH/DOLLEVOET/HUISMAN (2016)). A frequently used branching rule applied and possibly modified in ALFIERI/KROON/VAN DE VELDE (2007), BACH/DOLLEVOET/HUISMAN (2016), DERIGS/MALCHEREK/SCHÄFER (2010) and DOS SANTOS/MATEUS (2009) is a strategy called “follow-on” introduced by RYAN/FOSTER (1981). CHEN/SHEN (2013) and SHEN/CHEN (2014) use a problem-specific relief opportunity based branching strategy and compare different variants of node selection strategies. Set-based branching rules are used by FORES/PROLL/WREN (2002). For instance, if the number of drivers released at a particular relief point is not integer, the duties that use this relief point are segregated from those that do not. Due to their bi-level objective function, DESAULNIERS (2007) introduces a lexicographic order of the solution vectors to explore the search tree. Other strategies, such as terminating the PP and early branching, are discussed in ALBERS (2009) and DERIGS/MALCHEREK/SCHÄFER (2010). To manage the computational time, the number of nodes to explore can be limited (e.g., SHEN/CHEN (2014)). Because of the aforementioned modifications, branch-and-price approaches are usually heuristics.

Some researchers propose to solve the IP in a subsequent step using a commercial solver after the relaxed MP is solved to near-optimality (e.g., CEDER/HASSOLD (2015), LIU/HAGHANI/TOOBAIE (2010) and SUYABATMAZ/ŞAHİN (2015), marked as IPM (integer programming method) in column “2nd step” in Table 3.4). Due to time limits (e.g., 2 hours in SUYABATMAZ/ŞAHİN (2012)) or other stopping criteria, the IP problems are solved to optimality for only a few instances. Other researchers explicitly use branch-and-bound methods (B&B) to obtain the IP solution. Analogously to branch-and-price, different branching strategies can be applied. KWAN/KWAN (2007) and KWAN (2011)

obtain the target number of duties from the relaxed solution that is used to make branching decisions. FORES/PROLL/WREN (2002) discuss different branching rules, such as relief opportunity branching, duty branching, depot branching and type branching.

Because of their computational efficiency, heuristics (H) are useful methods to generate integer solutions (NISHI/MUROI/INUIGUCHI (2011)). In RCSP, variable fixing (or variable rounding) integrated in the course of the CG procedure is extensively studied (e.g., BORNDÖRFER/GRÖTSCHER/LÖBEL (2001), JÜTTE/THONEMANN (2012a), MUROI/NISHI/INUIGUCHI (2010)). ALBERS (2009) present a specific scoring scheme to identify variables to be fixed. Likewise, most approaches based on Lagrangian relaxation and sub-gradient optimization use a column fixing strategy (e.g., ABBINK et al. (2011), CLAUSEN/BAUDACH (2008), HUISMAN (2007)). BENGTSSON et al. (2007) apply a dual-ascent heuristic which produces new integer solutions every two or three pricing calls. DJELLAB/BIONNIER (2011) investigate two methods: restricted integer programming and adaptive rounding heuristics. KROON/FISCHETTI (2000) and KROON/FISCHETTI (2001) select duties with an iterative greedy heuristic combined with a duty evaluation based on Lagrangian multipliers. They also apply variable fixing to very efficient duties. Large instances with up to 18,000 trips can be solved by this method in less than 24 hours (KROON et al. (2009)).

Initial set of duties

The efficiency of CG depends, among others, on the quality of the initial set of duties (see CAPRARA/MONACI/TOTH (2001) and JANACEK et al. (2017) for a detailed discussion). The variants of building this set ranges from trivial duties (one trip only, see ALBERS (2009) and DERIGS/MALCHEREK/SCHÄFER (2010)) to a depth-first search procedure (ALFIERI/KROON/VAN DE VELDE (2007)), column generation (ABBINK et al. (2011)) and constraint programming (CEDER/HASSOLD (2015) and HAN/LI (2014)). For their specific problem of re-scheduling for temporary maintenance or construction works, HUISMAN (2007) generate “look-alike” duties of the unfeasible duties by a complete enumeration.

Acceleration techniques and problem size management

Due to the slow convergence of CG and the increasing problem size at each iteration as well as the increasing size of practical problems, computational times can be very long, in some cases even more than 100 hours (e.g., LIU/HAGHANI/TOOBAIE (2010)). DESAULNIERS/DESROSIERS/SOLOMON (2002) provide a comprehensive overview of existing strategies and techniques. Also researchers in RCSP engage in great effort to investigate acceleration techniques and procedures to manage and/or reduce the problem size. Com-

mon approaches are column deletion in the early phase of CG (e.g., ABBINK/WOUT/HUISMAN (2007), KROON et al. (2009)) or dynamic and static graph reduction (e.g., FRELING/LENTINK/ODIJK (2001), DERIGS/MALCHEREK/SCHÄFER (2010), KWAN/KWAN (2007)) to reduce the size of the problem and control the search space.

In recent years, researchers in RCSP explored the decomposition of railway networks into smaller sub-problems extensively. Dimensions along which a problem can be decomposed include time periods (e.g., ABBINK/WOUT/HUISMAN (2007), JANACEK et al. (2017)), geographic information (mainly distance, e.g., ABBINK/WOUT/HUISMAN (2007), FORES/PROLL/WREN (2001)), railway network characteristics such as train types (e.g., ABBINK/WOUT/HUISMAN (2007), KONIORCZYK/TALAS/GEDEON (2015)) or information obtained from previous interim solutions (ABBINK/WOUT/HUISMAN (2007)). WANG et al. (2008) describe a genetic algorithm to assign trips to depots and solve the smaller instances independently. JÜTTE/THONEMANN (2012a), JÜTTE/THONEMANN (2012b) and JÜTTE/THONEMANN (2015) explore and compare different graph-partitioning strategies and propose a powerful divide-and-price algorithm to dynamically solve sub-problems of large instances in parallel. They report only small losses in solution quality.

Table 3.4: Overview of column generation approaches in RCSP

Reference	MP relaxation		PP solution	IP solution		Problem size # trips	Characteristics
	Linear	Lagrange		B&P	2nd step		
ABBINK et al. (2005)		•	DP		H		TURNI algorithm
ABBINK / WOUT / HUISMAN (2007)		•	DP		H	18,000	TURNI algorithm, partitioning methods
ABBINK et al. (2011)		•	DP		H	30,000	LUCIA algorithm
ABBINK (2014)		•	DP		H	30,000	TURNI and LUCIA algorithm, partitioning methods
ABBINK / HUISMAN / KROON (2018)		•	DP		H		General overview
ALBERS (2009)	•		DP		H	35,199	PP: label pulling
ALFIERI / KROON / VAN DE VELDE (2007)	•		DP	•		na	Branching strategy: follow-on
BACH / DOLLEVOET / HUISMAN (2016)	•		DP	•		1,214	Branching strategy: follow-on
BENGTTSSON et al. (2007)	•	•	DP		H	7,000	PP: k shortest path, rule modeling language
BORNDÖRFER / GRÖTSCHER / LÖBEL (2001)		•	DP		H	1,968	MP: Coordinate ascent algorithm; PP: Lagrangian distance labels
CAPRARA (2015)	•		DP				General overview
CEDER / HASSOLD (2015)	•				B&B		
CHEN / SHEN (2013)	•		DP	•		701	Branching strategy: relief opportunity, PP: multi label based dynamic programming method
CLAUSEN / BAUDACH (2008)		•	DSP				
DERIGS / MALCHEREK / SCHÄFER (2010)	•		DP	•		8,149	PP: label setting
DESAULNIERS (2007)	•		DP	•		1,200	MP: bi-level objective function, PP: label setting
DJELLAB / BIONNIER (2011)	•				H	na	
FORES / PROLL / WREN (2001)	•		DSP		B&B		MP: primal CG, dual steepest edge
FORES / PROLL / WREN (2002)	•		DSP		B&B		MP: primal CG, dual steepest edge
FRELING / LENTINK / ODIJK (2001)	•		DP	•		1,114	Dynamic network size, multiple variable fixing
FRELING / LENTINK / WAGELMANS (2004)	•		DP	•		1,114	Column management, temporary and fixed relaxation of the PP
GRÖTSCHER / BORNDÖRFER / LÖBEL (2003)		•	DP		H	1,968	MP: Coordinate ascent algorithm; PP: Lagrangian distance labels

Reference	MP relaxation		PP solution	IP solution		Problem size # trips	Characteristics
	Linear	Lagrange		B&P	2nd step		
HAN / LI (2014)	•		CP		IPM	228	Duty generation: constraint programming
HOFFMANN (2017)	•		GA		IPM	713	
HOFFMANN et al. (2017)	•		GA		IPM	9,836	
HUISMAN (2007)		•	DP		H		Look-alike duties in initial set of duties
JANACEK et al. (2017)	•		DP		IPM	84	Concept of frames to reduce search space; PP: label setting; compared to IPM
JÜTTE et al. (2011)	•		DP		H	36,173	Graph-partitioning, PP: label pulling
JÜTTE (2012)	•		DP		H	36,173	Graph-partitioning, PP: label pulling
JÜTTE / THONEMANN (2012b)	•		DP		H	16,225	Graph-partitioning, PP: label pulling
JÜTTE / THONEMANN (2012a)	•		DP		H	27,786	Graph-partitioning
JÜTTE / THONEMANN (2015)	•		DP		H	16,225	Graph-partitioning, PP: label pulling
JÜTTE / MÜLLER / THONEMANN (2017)	•		DP		H	3,911	Fairness and popularity of schedule
KOHANI / JANACEK (2017)	•		DP		IPM	84	PP: label setting
KROON / FISCHETTI (2000)		•	DP		H	1,200	TURNI algorithm
KROON / FISCHETTI (2001)		•	DP		H	9,500	TURNI algorithm
KROON et al. (2009)		•	DP		H	18,000	TURNI algorithm
KWAN (2011)	•		DSP		B&B	na	Domain knowledge to reduce problem size; TrainTRACS algorithm
KWAN / KWAN (2007)	•		DSP		B&B	2,073	Domain knowledge to reduce problem size; TrainTRACS algorithm
LEE / CHEN (2003)	•		H		H	na	Compared to genetic algorithm
LIN / TSAI (2019)	•		DP	•		305	Integrated crew scheduling and rostering
LIU / HAGHANI / TOOBAIE (2010)	•		GA		IPM	2,245	
MUROI / NISHI / INUIGUCHI (2010)	•		DP		H	276	Compared to IPM
NISHI / MUROI / INUIGUCHI (2011)	•		DP		H	1,389	
DOS SANTOS / MATEUS (2009)	•		GA, DP	•		101	PP: combination of GA and DP
SHEN / CHEN (2014)	•		DP	•		830	Branching strategy: relief opportunity, PP: multi label based dynamic programming method
SNIJDEERS / SALDANHA (2017)		•	DP		H	5,018	Improvement step to reduce constraint violations

Reference	MP relaxation		PP solution	IP solution		Problem size # trips	Characteristics
	Linear	Lagrange		B&P	2nd step		
SUYABATMAZ / ŞAHİN (2012)	•		DP		IPM	329	Column-and-row-generation
SUYABATMAZ / ŞAHİN (2015)	•		DP		IPM	44	Compared to IPM solution of corresponding NFP formulation
WANG et al. (2008)	•		DP	•		614	GA to reduce problem size

Notes: B&B-branch-and-bound; CP-constraint programming; DP-dynamic programming; DSP-duty set pricing; IPM-integer programming method (with stopping criteria); GA-genetic algorithm; H-heuristic; na-computational results provided, number of trips not available

3.5.4 Meta-heuristics

Meta-heuristics are problem-independent heuristic solution procedures, which have gained widespread success in solving a wide variety of difficult combinatorial optimization problems since the 1980s. Likewise among RCSP researchers, these methods arouse increasing interest: more than half of the articles using a meta-heuristic solution approach were published over the last five years, as shown in Table 3.5. The reason is that in contrast to exact methods, which solve a problem to optimality, meta-heuristics achieve sufficiently good solutions for the NP-hard RCSP, especially when computation capacity is limited (e.g., CHEW et al. (2001), KHMELEVA et al. (2014)). Meta-heuristics start with one (single-solution-based) or a number of (population-based) feasible crew schedules as initial solution. This solution is improved in iterative steps on a pre-defined search space using some form of stochastic optimization, e.g., random numbers, until a pre-defined stopping criterion is fulfilled. This family of approaches includes single-solution-based meta-heuristics, such as tabu search (TS), simulated annealing (SA) or simulated evolution algorithms (SE) and population-based procedures, for instance, genetic algorithms (GA), ant colony optimization (ACO) as well as their hybrids.

Table 3.5: Overview of meta-heuristics in RCSP

Reference	Meta-heuristic					Characteristics
	GA	ACO	TS	Other	Hybrid	
CABRERA / RUBIO (2009)			•		•	TS with mathematical programming
CHEW et al. (2001)			•			
ELIZONDO et al. (2010)				EA		EA compared to TS and Greedy algorithm
FUENTES / CADARSO / MARÍN (2015)				NS	•	Trip clustering; NS with mathematical programming
FUENTES / CADARSO / MARÍN (2019)				F&R		Trip clustering
GARCÍA et al. (2018)				CUS		Binary cuckoo search big data algorithm
GUO / ZHOU / LI (2014)				SE		Random initial population
HANAFI / KOZAN (2014)				SA		Initial schedule by constructive heuristic
HUANG / YANG / WANG (2011)		•				
KHMELEVA et al. (2014)	•					Indirect chromosome representation with decoding
KHMELEVA et al. (2018)	•					Fuzzy-logic controller
KOKUBO / FUKUYAMA (2017b)			•			2-opt, 3 operators
KOKUBO / KAWAGUCHI / FUKUYAMA (2017)			•			2-opt, 6 operators
KOKUBO / FUKUYAMA (2017a)			•			2-opt, 6 operators
KUZNETSOV et al. (2016)				SA		Compared to method of auction
KWAN / WREN / KWAN (2000)	•				•	GA to generate schedule based on LP solution
KWAN / KWAN / WREN (2001)	•					Initial population by Greedy algorithm; combinatorial traits
KWAN (2004)	•			•		Overview of methods
LEE / CHEN (2003)	•					
LI / NIE (2014)	•					
PARK / RYU (2006)	•				•	Greedy crossover operator
SHEN / KWAN (2001)			•			Multi-neighborhood, 2-opt
SHEN (2001)			•			Multi-neighborhood, 2-opt
SHEN / KWAN (2002)			•			Multi-neighborhood, 2-opt
SHEN et al. (2013)	•				•	Dynamic chromosome length, Greedy crossover operator
SHI / ZHU / TIAN (2015)		•				
SONG et al. (2012)		•				Serial-parallel grouping strategy
TIAN / SONG (2013)		•				Backtracking, bi-phenomena
YAGHINI / KARIMI / RAHBAR (2015)				NS		LP-based neighborhood structure
ZHAO / ZHEN (2007)				SE		Initial schedule by labeling method
ZHOU et al. (2016)		•				
ZHU et al. (2014)		•				Bi-phenomena

Notes: CUS-cuckoo search; EA-evolutionary algorithm; F&R- fix-and-relax; NS-neighborhood search; SA-simulated annealing; SE-simulated evolution

Research on applying GA to RCSP started in the mid 1990s (see KWAN/KWAN/WREN (2001)) and still GA is one of the most frequently used meta-heuristic in this field. In fact, eight publications use this powerful method (see Table 3.5). There are two main obstacles of GA in the context of RCSP: maintaining feasibility of the schedule and reducing trip over-coverage. As a result, all publications modify crossover and mutation operators: in most cases greedy variants of it are used. Additionally, some researchers (KHMELEVA et al. (2014), KHMELEVA et al. (2018), PARK/RYU (2006), SHEN et al. (2013)) introduce special chromosome representations. KWAN/WREN/KWAN (2000), KWAN/KWAN/WREN (2001), LEE/CHEN (2003) and LI/NIE (2014) propose chromosomes that represent all or a subset of all feasible duties and, therefore, the corresponding schedule. KWAN/WREN/KWAN (2000) preselect efficient duties for the GA by using solution information of the linear relaxed SCP and a subsequent repair mechanism to maintain feasibility. KWAN/KWAN/WREN (2001) additionally explore combinatorial traits to use extra information about a group of duties which effectively fit to the current schedule (see also KWAN (2004)). In contrast to the static chromosome representation described above, SHEN et al. (2013) apply an adaptive GA with dynamic chromosome length, representing one feasible schedule, for which a lower bound is provided by mathematical programming. To sustain diversity of the population and prevent premature convergence, PARK/RYU (2006) divide the chromosome into an expressed and unexpressed part of which only the first is evaluated by the fitness function. With an indirect chromosome representation and decoding procedure, KHMELEVA et al. (2014) propose an approach that does not require the generation of a large set of duties beforehand. Additionally, KHMELEVA et al. (2018) explore fuzzy-logic controllers for crossover and mutation operations in order to steer the balance between exploration and exploitation phases.

Tabu search is discussed extensively as an alternative solution method by SHEN/KWAN (2001), SHEN (2001) and SHEN/KWAN (2002). They explore the iterative improvement of an initial, not very good and sometimes unfeasible schedule with a multi-neighborhood search, in particular with four different move operations. Similarly, KOKUBO/FUKUYAMA (2017a) develop six different move operations for two selected duties and show that their TS algorithm becomes more powerful by applying six instead of three of these operations (see KOKUBO/FUKUYAMA (2017b) and KOKUBO/KAWAGUCHI/FUKUYAMA (2017)). Two research groups propose TS to solve problem instances for urban transportation: CABRERA/RUBIO (2009) propose a hybrid TS and integer programming algorithm and CHEW et al. (2001) apply multi-criterion TS approach.

Ant colony algorithms derive their fundamental idea from the observation of ant

colonies finding the shortest path from their nest to food by exchanging information via pheromones along their way (SONG et al. (2012)). In RCSP literature, this approach is almost exclusively applied by research on real cases in China, either in long-distance passenger transportation (SHI/ZHU/TIAN (2015), SONG et al. (2012), TIAN/SONG (2013), ZHU et al. (2014)) or in the urban rail context (ZHOU et al. (2016)). HUANG/YANG/WANG (2011) discuss a variant of ACO for the Taiwanese railway transportation.

In recent years, some researchers explored alternative meta-heuristics. FUENTES/CADARSO/MARÍN (2015) and YAGHINI/KARIMI/RAHBAR (2015) combine neighborhood search with mathematical programming. For larger instances, FUENTES/CADARSO/MARÍN (2015) additionally divide the set of trips into smaller, overlapping clusters. Building on a similar trip clustering strategy, FUENTES/CADARSO/MARÍN (2019) develop a fix-and-relax algorithm for their NFP formulation, aiming for providing a framework to integrate other planning tasks. ELIZONDO et al. (2010) propose an evolutionary algorithm to improve the initial solution by crossover operations with two sets, a set of elite duties and a random set. Simulated evolution algorithm is applied by GUO/ZHOU/LI (2014) and ZHAO/ZHEN (2007). The procedure starts with a randomly generated initial solution. Then, individual duties are eliminated based on their fitness evaluation and released trips are re-combined to new duties. For a multi-dimensional assignment problem of trains, crews and engines, KUZNETSOV et al. (2016) suggest a simulated annealing algorithm. Also HANAFI/KOZAN (2014) develop a hybrid approach with a constructive heuristic to generate the initial solution and a simulated annealing heuristic for improvement steps. GARCÍA et al. (2018) explore the use of unsupervised learning methods based on k-means clustering techniques in combination with a cuckoo search algorithm.

3.6 Conclusion and further research opportunities

In this paper, we gave a structured and comprehensive overview of RCSP literature published since 2000. It was shown that most papers (almost 80% of the literature considered) discuss the planning step of crew scheduling separately from other planning steps. In particular in passenger transportation only few articles present integrated approaches, i.e. planning crew schedules simultaneously with rolling stock units or crew rosters. Note that the cost structure of railway operations differs from, for instance, the bus industry. In the latter, personnel cost account for a relatively higher share of total cost which makes integrative approaches more attractive regarding the potential cost savings. As a result, integrating crew scheduling with other planning tasks has been studied by several research groups. In contrast, the cost effect of integrated planning of

crew scheduling in railways is not comprehensively studied and might build a possible larger research stream for future studies.

While cost reduction remains the main motivation for research in crew scheduling, robustness as a means to improve the customer service level and reduce regulatory penalties will play an increasingly important role in near future. New methods or concepts, e.g., based on historical schedule information, could be developed to achieve more robust crew schedules. However, crew schedules become more often subject to change for a defined period of time, e.g., due to large and frequent railway network maintenance projects. In extreme cases, the schedule of the same workday is different each week. This is true in particular for freight transportation with last minute customer orders but applies as well to passenger transportation. Hence, further research is needed to develop RCSP models and methods that are able to adapt to and plan with changed circumstances easily and quickly. This implies a thorough investigation of the impact on schedule cost and employee and customer satisfaction. Likewise, research on real-time (re-)scheduling could lead to higher customer satisfaction in a fast moving world with information available instantly.

As especially in the developed countries labor markets become more competitive, railway operators will aim to make their jobs more appealing. This includes, besides payment and company culture, a satisfying and sustainable work schedule. We showed that crew rostering plays an important role by assigning duties to crews. However, specific aspects that affect duty popularity and fairness are determined by the schedule. As employee satisfaction seems not thoroughly investigated in RCSP, research could support operators to investigate different policies for crew scheduling and their effect on employee satisfaction, also as integrated step with crew rostering.

We presented the potential of heuristics, column generation, and meta-heuristics to achieve high quality solutions in reasonable time. Also, acceleration techniques and problem size management strategies were investigated in the past. However, given the complexity and size of RCSP, research to solve even very large-scale instances close to optimality in a reasonable time could continue in the following years. The increasing competition in the private railway sector and public pressure on state-owned companies demand close to optimal solutions. Also, with faster solution methods operators can conveniently test and verify different input parameters. Also, the information obtained could provide recommendations to change the operating model and to improve railway transportation with respect to satisfying the needs of customers, operators and employees equally. Additionally, with the advances of algorithms that are able to recognize patterns in large data sets, e.g., machine learning techniques, new insights to crew scheduling could be found in historical data.

Since almost all publications in the observed literature are motivated by real industry cases, further research can be expected to meet the railway industry needs. New questions in crew scheduling could be posed by the digitization of operations. Hence, new business models and processes require new capabilities and affect the conditions of RCSP. While the first is a matter of training, the latter requires researchers and operators to deeply understand advancing operating models and adjust crew scheduling models and methods accordingly.

In larger cities, for instance, requests for security guards become more frequent especially during night times. The demand for such crew types consists of a pre-defined fixed schedule and a dynamic element (i.e. likelihood of need for security guards). To the best of our knowledge only two papers reflect on such type of crews (ticket inspectors THORLACIUS/CLAUSEN (2008) and security guards (SNIJDERS/SALDANHA (2017))). Also with the advances of driver-less vehicles, a shift from fixed crew members (e.g., drivers) to more flexible types of crew members (e.g., security guard, technician, ticket inspector) could emerge and pose new questions to RCSP research.

In summary, RCSP remains a topic of high interest and is worth to investigate further with more research activities.

3.7 Decision support tools and railway crew scheduling in practice

For many years, planners in railway companies have solved the extremely complex crew scheduling problem manually. In the late 1990s, for instance, long-term crew scheduling at the Dutch Railways NS involved 24 planners, who took about 6 months to produce duties for approximately 5000 train drivers and guards (MORGADO/MARTINS (1998)). Therefore, from the beginning of the 1990s, a number of research groups in different countries, mainly in Europe, has reported significant progress in developing decision support tools for crew scheduling in railway industry. Nearly all research in this field is motivated by real-world cases from railway operators (see Table 3.2) with the aim to provide a decision support tool for the collaborating industry partner. Hence, this section does not aim for a complete picture of all available tools but gives the reader a close view to the tools that are presented in detail in our literature collection.

In general, railway crew scheduling tools build on data and information input which include, for instance, the rolling stock schedule, network information such as relief and break opportunities, crew schedule restrictions and other operator specific information including manual scheduler experience. The tool output is then a close to complete crew schedule which might be adjusted manually at some local points. Each railway operator

has its own processes and input data. Consequently, there is no one-size-fits-all but a variety of customized solutions.

The transformation from manual scheduling to computer-aided scheduling is still an ongoing process in railway industry and we can highlight here some successful use cases. However, within the implementation process, a number of challenges and concerns with regards to IT system integration and employees' mindset change have to be overcome (e.g., ABBINK et al. (2005) and CLAUSEN (2007) for more details).

IMPACS, TRACS II, TrainTRACS The IMPACS (Integer Mathematical Programming for Automatic Crew Scheduling) system was developed by the University of Leeds in the late 1970's to produce bus driver schedules (KWAN (1999)). In 1990, IMPACS was adapted to provide train driver scheduling to open up another transportation market. Since 1994, intensive development effort was invested in rail operations and TRACS II (Techniques for Running Automatic Crew Schedules, Mark II) superseded IMPACS. TRACS II consists of a Generate-and-Select approach. First, a set of duties, which are valid according to labor agreement rules is generated and, second, the size of the generated duty set is reduce if possible. Third, a subset of duties is selected which covers all trips (FORES/PROLL (1998)). The application of column generation, a reduction heuristic and branch-and-bound enables to handle large problem instances. We refer the interested reader to KWAN et al. (1999) and FORES/PROLL/WREN (2002) for further information. With an iterative heuristic, called PowerSolver, to derive and solve smaller sub-problems and its dynamic integration into the TRACS II approach, KWAN/KWAN (2007) facilitate the solution of even larger and more complex problem instances (see also LAPLAGNE (2008)). In the 2000s, TRACS II was replaced by the TrainTRACS system (KWAN (2011)). The University of Leeds founded the company TRACSiS to commercialize TrainTRACS and to expand its influence on the UK rail market as well as on other parts of the world.

TRACS II and its predecessor IMPACS were applied to driver scheduling problems in the UK, Australia, Hong Kong, South Africa and Zimbabwe as well as in bus, tram and rail operations (FORES/PROLL/WREN (2002)). Since 2003, the first user of TrainTRACS was ScotRail and it gained wide acceptance by the UK operators such as Northern Rail, National Express and Virgin West Coast (KWAN (2011)).

HASTUS, Crew-Opt, GENCOL Since the 1970s, there has been a joint research project between the Transportation Research Center of the University of Montreal and the Montreal Urban Community Transit Corporation. They developed the HASTUS vehicle and operator scheduling package with support of the software company Giro Inc. (BLAIS/ROUSSEAU (1988)). The HASTUS system is composed of three main

software modules, namely HASTUS-Bus (vehicle scheduling), HASTUS-Macro (crew scheduling) and HASTUS-Micro (crew rostering). Similar to IMPACS/TRACS II, the software was originally developed to model and optimize the planning steps of a bus company. Later it was extended to the railway sector. Starting in the late 1980s, a new driver scheduling method called Crew-Opt was developed at the GERAD research center (Groupe d'Étude et de Recherche en Analyse des Décisions) in cooperation with Giro Inc. It was embedded within the HASTUS system (ROUSSEAU/DESROSIERS (1995)). The Crew-Opt module contains a column generation approach with a resource constrained shortest path method for generating new columns (duties). The GENCOL package as the core of the column generation code implements a branch-and-price approach (DESAULNIERS (2007)). Unlike TRACS II, HASTUS does not use column generation to select a new (but already generated) column but to generate a new column (SHEN (2001)).

HASTUS was implemented, for example, by the Belgian national railway SNCB, the passenger rail network in the Paris region SNCF Transilien and the regional and long-distance passenger rail operator Queensland Rail in Australia.

CREWS, ESCALAS, CREWS_NS, LUCIA, TUTIS In the late 1980s and 1990s, the software company SISCOG developed the crew scheduling prototype CREWS, that can be customized to several transportation companies. It is based on artificial intelligence and schedules both driving and other crews. CREWS is designed as a white-box system, i.e. the planner can interact with the system by suggesting alternatives or requesting decisions and can adapt the behavior of the system to changing circumstances. The software tool can be used in automatic, semiautomatic or manual mode (MORGADO/MARTINS (1998)).

There are several notable applications of the tool: it was adapted to requirements of the Portuguese Railways and the resulting system, called ESCALAS, was completed in 1991 (MORGADO/MARTINS (1992), MORGADO/MARTINS (1993)). Starting in 1993, SISCOG developed the system CREWS_NS for the Dutch Railways NS, that was used in the long-term scheduling of drivers and conductors. CREWS_NS was built on top of CREWS. The rail traffic supplier of the city-rail network in Copenhagen, DSB S-tog, used CREWS for short term scheduling and for maintaining all relevant information regarding each individual driver (CLAUSEN (2007)). Other CREWS-based systems were developed for the Norwegian State Railways, the Finnish Railways and the London Underground (MARTINS/MORGADO (2010)).

In 2007, SISCOG and the Dutch railway company NS started a research project resulting in the development of the algorithm LUCIA. Based on an algorithm for the crew rescheduling problem (HUISMAN (2007)), it combines Lagrangian heuristics, column gen-

eration and fixing techniques (ABBINK et al. (2011)). First, the algorithm was used as a stand-alone solution, then, it was fully integrated into the CREWS system. In recent years, this cooperation developed another solution algorithm. The resulting software prototype, named TUTIS, addresses the problem of scheduling work of security guards operating on trains and stations (SNIJDERS/SALDANHA (2017)).

TURNI The optimization software TURNI was developed in the early 2000s by Double-Click (Padova – Italy). It is based on a technique introduced by CAPRARA/FISCETTI/TOTH (1999) combining dynamic column generation, Lagrangian relaxation and heuristic search. For further information we refer to KROON/FISCETTI (2000), KROON/FISCETTI (2001), ABBINK et al. (2005) and ABBINK/WOUT/HUISMAN (2007). ABBINK (2014) presents a comparison of the solution algorithms in TURNI, TURNI with iterative partitioning and LUCIA (see CREWS).

KROON/FISCETTI (2000) describe that in 2000 TURNI replaced the system CREWS_NS at Dutch Railways NS. In the late 2000s, they switched back to the CREWS system (see LUCIA, MARTINS/MORGADO (2010)). Another user of the TURNI system is DSB S-tog, the rail traffic supplier of the city-rail network in Copenhagen, who uses it to construct their driver duties (CLAUSEN (2007)).

CARMEN The commercial crew planning system CARMEN was originally developed by CARMEN Systems (now Jeppesen, a subsidiary firm of Boeing) for airline crew scheduling and rostering (WEDELIN (1995), SANDERS/TAKKULA/WEDELIN (1999), ALEFRAGIS et al. (1998)). Around the year 2000, the application was also adapted to legal and operational requirements of rail transportation companies (ALEFRAGIS et al. (2000)). The system is based on a column generation approach, that combines resource constraints, k -shortest path enumeration and label merging techniques (BENGTS-SON et al. (2007)). Another important component of the CARMEN system is a rule and quality modeling language used to define legality, cost and other objectives (KOHL (2003)). The decision support system CARMEN is or was used by the German railway operator Deutsche Bahn, the Swedish State Railways, the freight operator Green Cargo as well as all major European airlines and several operators in North America and Asia (BENGTS-SON et al. (2007)).

Other decision support tools In the 1990s, the Italian railway company Ferrovie dello Stato SpA developed the crew planning system ALPI in collaboration with researchers from the University of Bologna (CAPRARA et al. (1999)). It includes the heuristic method proposed by CAPRARA/FISCETTI/TOTH (1999), which consists of subgradient optimization coupled with a pricing technique for saving computation time.

The duty scheduling system DS-OPT was developed by GRÖTSCHEL/BORNDÖRFER/LÖBEL (2003) (LBW Optimization GmbH) for planning drivers and conductors in railway and bus transportation companies. It is based on a set covering/partitioning model solved with column generation and branch-and-bound. Since 2000, IVU Traffic Technologies AG distributes the software product DS-OPT under the brand IVU.plan and IVU.rail. The latter is used by the German railway operator DB Regio, the Swiss freight operator SBB Cargo and the Italian railway operator Trenitalia among others. The software product RailOpt, developed by Qnamic, is a resource management and optimization tool for several planning steps of railway companies (DORNBERGER/FREY/SCHMID (2007)). The module RailOpt DSS supports crew scheduling and rostering among other planning activities. The decision support system on.Track was developed for analyzing consequences of timetable changes, modifications of break and working time regulations as well as changes in the cost structure on future crew needs (DERIGS/MALCHEREK/SCHÄFER (2010)). The optimization system is based on branch-and-price techniques. FROGER/GUYON/PINSON (2015) present an algorithm implemented in a software module, called PLAISANCE, for passenger train drivers at the French national railway company SNCF. It combines a subgradient method, a constructive heuristic and a fixation technique for selecting efficient duties. KONIORCZYK/TALAS/GEDEON (2015) describe the crew scheduling and rostering approach implemented in Railm@n, a system used by the Hungarian passenger railway transportation company MAV START. SINA, a decision support tool for railway crew scheduling problems with attendance rates, is presented by NEUFELD et al. (2018). The algorithm included in SINA and presented in HOFFMANN et al. (2017) uses column generation techniques, where the pricing problem is solved by a genetic algorithm.

4 Schichtplanung von Zugbegleitpersonal unter Berücksichtigung von Prüfquoten

Abstract

Steigender Kostendruck zwingt Verkehrsunternehmen zum effizienten Einsatz ihres Personals mit dem Ziel der Kostensenkung und Produktivitätserhöhung. Speziell im Schienenpersonennahverkehr sind Zugbegleiter und Triebfahrzeugführer von zentraler Bedeutung. Aufgrund der fortschreitenden Automatisierung der Fahrzeuge verschwinden zunehmend betriebliche Aufgaben von den Schichtplänen der Zugbegleiter. Infolgedessen geht in Deutschland der Trend weg von einer ständigen Begleitung aller Zugleistungen hin zu einer partiellen Abdeckung, deren Größe anhand der Prüfquote gemessen wird. Dieser Beitrag beschäftigt sich mit den Auswirkungen dieser neuen Entwicklungen und stellt ein neues Modell für die Schichtplanung von Zugbegleitern unter Berücksichtigung von Prüfquoten, rechtlichen und tariflichen Bestimmungen vor.

Referenz

Publizierter Konferenzbeitrag: HOFFMANN, K. (2014): Schichtplanung von Zugbegleitpersonal unter Berücksichtigung von Prüfquoten. In: KUNDISCH, D./SUHL, L./BECKMANN, L. (Eds.): *Tagungsband MKWI 2014*. Paderborn University.

4.1 Einleitung

Eisenbahnverkehrsunternehmen stehen vor einem komplexen System von Aufgaben. Einerseits wächst das Verkehrsaufkommen und damit die Anzahl der beförderten Personen in Deutschland stetig (siehe Abbildung 4.1), d. h. mit gleichbleibenden Ressourcen muss eine größere Leistung erbracht werden. Andererseits unterliegen Eisenbahnverkehrsunternehmen im Zuge der fortschreitenden Globalisierung der Märkte einem steigenden Konkurrenz- und Kostendruck. Durch den effizienten Einsatz von Ressourcen und eine verbesserte Produktqualität sollen Kunden und Besteller der Verkehrsleistungen überzeugt und Wettbewerber verdrängt werden. Zudem gewinnt heutzutage auch die soziale und ökologische Komponente immer mehr an Bedeutung. Es gilt Mitarbeiter zufriedenzustellen, einen attraktives Arbeitsumfeld zu bieten und Nachhaltigkeit zu verankern.

Bei intensiver Betrachtung der Kostenstruktur ist ersichtlich, dass neben den Materialkosten für Fahrzeuge, Energie und die Nutzung von Infrastruktur die Personalkosten einen bedeutenden Teil der gesamten Aufwendungen ausmachen. Während Erste kaum beeinflussbar sind, können Personalkosten durch einen effizienten Einsatz des Personals erheblich gesenkt werden. Dabei spielt vor allem das Fahrpersonal, wie Triebfahrzeugführer und Zugbegleiter, eine zentrale Rolle. Zudem erfahren Zugbegleiter, die vor allem für die Fahrkartenkontrolle zuständig sind, gerade eine weitere Entwicklung. Durch den steigenden Kostendruck und die zunehmende Automatisierung der Fahrzeuge verschwinden betriebliche Aufgaben von ihren Schichtplänen und von einer dauerhaften Besetzung der Züge mit Zugbegleitern wird abgesehen. Eine Prüfquote legt nun fest, welcher Anteil an Zügen oder Streckenkilometern mit Zugbegleitern besetzt werden muss.

Abbildung 4.1: Verkehrsaufkommen in Deutschland (Quelle: DEUTSCHES INSTITUT FÜR WIRTSCHAFTSFORSCHUNG DIW BERLIN (2013))

Das Problem der Schichtplanung von Zugbegleitern unter Einhaltung verschiedener betrieblicher und rechtlicher Rahmenbedingungen und Berücksichtigung von Prüfquoten ist in der Literatur weitgehend unbekannt. Aus diesem Grund beschäftigt sich diese Arbeit mit der neuen Problemstellung und definiert und analysiert ein Modell für das modifizierte Schichtplanungsproblem. Konkrete Lösungsverfahren werden nicht betrachtet. Zunächst erläutert Abschnitt 4.2 die Planungsprozesse im Schienenpersonennahverkehr, woraufhin in Abschnitt 4.3 das Schichtplanungsproblem definiert und betriebliche und rechtliche Restriktionen diskutiert werden. Nach der Vorstellung des in der Literatur verwendeten Set-Covering-Modells in Abschnitt 4.4 folgt in Abschnitt 4.5 zunächst die Erläuterung der aktuellen Vorgehensweise bei der Schichtplanung der Zugbegleiter mit Prüfquoten. Das Aufzeigen der Nachteile dieser Vorgehensweise mündet in der Definition des neuen Modells und dessen Anwendung an einem kleinen Beispiel in Abschnitt 4.6. Den Abschluss bilden eine Zusammenfassung der Ergebnisse und ein Ausblick auf weitere Forschungsfragen.

4.2 Planungsprozesse im Schienenpersonennahverkehr

Anfang des Jahres 1996 wurde mithilfe des Gesetzes zur Regionalisierung des öffentlichen Personennahverkehrs (RegG) die Verantwortung für den öffentlichen Personennahverkehr (ÖPNV) vom Bund auf die Länder übertragen. Die weitere Aufteilung und Organisation ist in den Nahverkehrsgesetzen der einzelnen Bundesländer geregelt. Speziell im Schienenpersonennahverkehr (SPNV) agieren Bundesländer teilweise selbst über Tochterunternehmen als Besteller der Verkehrsleistungen (z. B. Bayern und Thüringen); in anderen Bundesländern übernehmen eigens gegründete Zweckverbände diese Aufgaben. Derzeit organisieren und finanzieren den SPNV in Deutschland 27 Aufgabenträger, die in der Bundesarbeitsgemeinschaft Schienenpersonennahverkehr zusammengefasst sind.

Der Planungsprozess im Schienenpersonennahverkehr (vgl. Abbildung 4.2) gliedert sich dabei in zwei Phasen – die Planung des Aufgabenträgers (Besteller) und des Leistungserbringers (Betreiber). Der Aufgabenträger beginnt mit der Analyse der erwarteten Reisendenströme und der Bedarfsermittlung des Nahverkehrsangebots bezüglich Bedienhäufigkeit und Kapazität. Die anschließende Linienplanung legt fest, welche Strecken des Schienennetzes zu Linien oder Linienbündeln zusammengefasst werden. Dabei finden unter anderem die Umsteigehäufigkeit der Reisenden, der Fahrzeugbedarf und Reisezeiten Beachtung. Ergebnis dieser beiden Prozesse ist ein grober Fahrplan, der in der nachfolgenden Fahrplanung spezifiziert wird. Die bisher beschriebene Planungsphase hat einen Vorlauf von mehreren Jahren vor der eigentlichen Leistungserbringung und bildet die Grundlage für die Ausschreibung oder Direktvergabe der SPNV Leistungen.

Dabei enthält der Auftrag unter anderem Informationen in Bezug auf:

- den festen Fahrplan, die Bedienhäufigkeit der Linien/Linienbündel
- das Rollmaterial, das Sitzplatzangebot,
- die Aufgaben der Zugbegleiter,
- die Häufigkeit der Fahrkartenkontrolle.

Die potentiellen Leistungserbringer, wie beispielsweise das Eisenbahnverkehrsunternehmen DB Regio AG, bewerben sich mit einem Angebot für die ausgeschriebenen SPNV Leistungen. Dabei erfolgt zunächst eine Grobplanung der Leistungen (benötigtes Rollmaterial und Personal), um die Kosten abzuschätzen. Nach einer gewonnenen Ausschreibung beginnt eine differenzierte Planung.

Abbildung 4.2: Planungsprozess im Schienenpersonennahverkehr

Die Phasen der Planung des Leistungserbringers können nach dem Detaillierungsgrad unterschieden werden. Zunächst erfolgen die Umlauf-, Ortsdienst- und Schichtplanung mit anonymisierten Fahrzeugen bzw. Personen. Dabei werden im Rahmen der Umlaufplanung Fahrgastfahrten, Leerfahrten, Rangier- und Bereitstellungsfahrten so verknüpft, dass zur Erbringung dieser Leistung so wenige Fahrzeuge wie möglich eingesetzt werden müssen. Unmittelbar im Anschluss oder sogar parallel zur Umlaufplanung findet die Planung der Ortsdienste, wie z. B. Innen- und Außenreinigung oder Fahrzeuginstandhaltung, statt. In einem weiteren Schritt werden die Umläufe konkreten physischen Fahrzeugen

zugeordnet, wobei das Fahrzeug den gestellten Anforderungen der Fahrlagen beispielsweise in Bezug auf die Baureihe oder die Restlaufzeit bis zur nächsten Instandhaltung genügen muss. Die folgende Fahrzeugdisposition integriert alle kurzfristigen Änderungen, die durch Umleitung eines Fahrzeuges oder Fahrzeugtausch aufgrund eines Defektes auftreten können.

Auf der Grundlage der Umlauf- und Ortsdienstpläne wird die Planung der am Produktionsprozess beteiligten Mitarbeiter angestoßen. Die Schichtplanung erstellt aus der vorgegebenen Leistungsmasse Schichten, die den gesetzlichen, tariflichen und betrieblichen Rahmenbedingungen genügen und dabei das vorhandene Personal effizient einsetzen. Analog zur Fahrzeugeinsatzplanung werden in der Personaleinsatzplanung die bereits erstellten Schichten konkreten Mitarbeitern zugeordnet. Hierbei findet z. B. die Strecken- und Baureihenkenntnis oder der aktuelle Stand des Jahresarbeitszeitkontos Beachtung. In diesem Stadium erfolgt die Vorlage der Schichtpläne beim Betriebsrat, dessen Zustimmung notwendig ist. Kurzfristige Änderungen, verursacht durch Krankmeldungen oder Betriebsstörungen, werden in der Personaldisposition in die Schichtpläne eingearbeitet.

4.3 Problembeschreibung

Diese Arbeit legt den Fokus auf die Schichtplanung von Zugbegleitern (siehe Markierung in Abbildung 4.2), die für die Fahrkartenkontrolle, Information der Reisenden am und im Zug (z. B. Fahrplan- und Tarifauskünfte, Information über Störungen), Überwachung von Ordnung und Sicherheit im Zug und betriebliche Aufgaben (z. B. Zugkontrollgang) zuständig sind. Eine Schicht besteht dabei aus einer Aneinanderreihung von Blöcken, die einen Arbeitstag einer anonymen Person gestalten. Zu diesen Schichtblöcken gehören unter anderem

- Einsicht der Arbeitsunterlagen,
- Fußwege,
- Begleitung eines Zuges,
- Vorbereitungs- und Abschlussdienste,
- Pausen (laut Arbeitszeitgesetz) und Tätigkeitsunterbrechungen,
- Gastfahrten (u. a. in anderen Zügen, Bussen, Straßenbahnen, Taxis).

Bisher war es im SPNV üblich, dass jeder Zug mit mindestens einem Zugbegleiter besetzt wird. In den letzten Jahren entwickelte sich aufgrund des hohen Kostendrucks und

dem zunehmenden Wegfall betrieblicher Aufgaben die Tendenz zu einer partiellen Abdeckung aller Züge. Lediglich ein Teil der Züge oder Streckenkilometer, angegeben durch eine Prüfquote, muss laut Verkehrsvertrag begleitet werden. Diese Prüfquoten können sich unter Umständen nach der Produktart, Linien(bündeln), Zugnummern, Streckenabschnitten oder Zeitfenstern unterscheiden. So ist beispielsweise eine Quote von 25 % für Regionalbahnzüge und eine Quote von 75 % für Regionalexpresszüge denkbar. Die Abrechnung der geleisteten Züge bzw. Streckenkilometer erfolgt am Ende einer festgelegten Periode. Eine nachgewiesene Untererfüllung (und evtl. sogar Übererfüllung) der Prüfquote wird dabei häufig durch den Aufgabenträger pönalisiert.

Neben den Quotenrestriktionen können noch weitere Forderungen auftreten. So legen einige Aufgabenträger Wert darauf, dass keine Regelmäßigkeiten in der Besetzung der Zugbegleiter zu erkennen sind. Das heißt für Züge oder Streckenabschnitte, die geprüft werden, ist eine gleichmäßige Verteilung auf einen gewissen Zeitraum wünschenswert. Da wir uns in dieser Arbeit auf ein Modell für die Schichtplanung von Zugbegleitern eines Standardtages beschränken, haben solche Anforderungen keine Auswirkung.

4.3.1 Klassifikation

Aufgrund der neuen Anforderung, nur einen gewissen Teil der Züge zu begleiten, ist eine Abweichung von der bisherigen Vorgehensweise erforderlich. Es beweist sich als zweckmäßig, eine Zugfahrt nicht mehr als Ganzes zu betrachten, sondern an geeigneten Stellen zu brechen. Diese Vorgehensweise nutzt das Optimierungspotential aus und ermöglicht dem Zugbegleiter, nur einen Teil der Zugfahrt zu begleiten. Dabei repräsentiert ein Trip einen Teil einer Zugfahrt von einem Brechpunkt zum nächsten, wobei Brechpunkte alle Stationen entlang der entsprechenden Linie oder aus betrieblichen bzw. arbeitsrechtlichen Gründen nur eine Auswahl davon sein können.

Die so definierten Trips des Verkehrsnetzes werden anhand der im Verkehrsvertrag vorgeschriebenen Quoten klassifiziert. Die Stufen der Abfrage zur Klassifikation, wie im linken Teil des Bildes 3 dargestellt, werden von oben nach unten durchlaufen. Zuerst erfolgt eine Überprüfung, ob die Quote anhand der Produktart unterschieden wird. Ist dies der Fall, wird eine entsprechende Anzahl an Klassen festgelegt. Mit den weiteren Abfragen nach Linien oder Linienbündeln, Zugnummern, Streckenabschnitten und Zeitfenstern wird analog verfahren. Sollte bei einer Stufe keine korrespondierende Forderung im Verkehrsvertrag sein, so erfolgt keine Klassenneubildung.

In einem fiktiven Beispiel (siehe Abbildung 4.3) wird für alle Regionalexpress-Linien (RE) eine Begleitung aller Züge gefordert, wohingegen für Regionalbahn-Züge (RB) eine Quote von 25 % in der Zeit von 6 bis 19 Uhr und eine Quote von 75 % sonst gefordert ist.

Abbildung 4.3: Klassifikation der Trips in Quotenklassen

4.3.2 Betriebliche und rechtliche Rahmenbedingungen

Grundsätzlich basiert die Schichtplanung auf der abgeschlossenen Umlaufplanung, da in dieser Informationen über den zu einer Zugfahrt gehörenden Fahrzeugtyp, Bahnsteige und die damit verbundenen Vorbereitungs- und Abschlussdienste enthalten sind. Weitere grundlegende Forderungen lauten:

- Eine Schicht endet an der gleichen Einsatzstelle, an der sie beginnt.
- Zwei aufeinanderfolgende Trips einer Schicht (unter Umständen mit weiteren Aufgaben zwischen diesen Trips) müssen kompatibel sein, d. h. der vorangehende Trip endet an der Station, an der der folgende Trip beginnt.
- Zwischen zwei aufeinanderfolgenden Trips, die nicht im gleichen Umlauf enthalten sind (Wechsel des Fahrzeuges), legt der Zugbegleiter einen Fußweg zurück.

Unter Umständen sind zu Beginn und Ende einer Zugfahrt oder bei Personalwechsel an einem Unterwegsbahnhof Vorbereitungs- und Abschlussdienste notwendig. Die Art und Dauer der Dienste hängt dabei möglicherweise von den aufeinanderfolgenden Trips ab und richtet sich damit nach der jeweiligen Kombination. Ferner kann die Berücksichtigung unterschiedlich langer Fußwege notwendig sein, abhängig von den Abständen der korrespondierenden Bahnsteige.

Neben den betrieblichen Rahmenbedingungen treten weitere Restriktionen auf, die sowohl auf dem Arbeitszeitgesetz (ArbZG) als auch auf Tarifverträgen basieren. Dafür müssen zunächst die Begriffe Schichtlänge und Arbeitszeit voneinander abgegrenzt werden. Die Schichtlänge reflektiert die gesamte Zeit von Beginn bis Ende der Schicht,

währenddessen die Arbeitszeit der Schichtlänge abzüglich der Tätigkeitsunterbrechungen, wie beispielsweise Gastfahrten und Pausen, entspricht. Mögliche rechtliche und tarifliche Forderungen sind in Tabelle 4.1 aufgelistet. Dabei gilt es zu beachten, dass sich genannte konkrete Zeitwerte auf das Arbeitszeitgesetz stützen, wohingegen fehlende Zeitwerte meist durch Tarifverträge oder Betriebsräte festgelegt sind.

Tabelle 4.1: Mögliche rechtliche und tarifliche Restriktionen der Schichtplanung

Bezug	Restriktion
Schichtlänge	Maximale Schichtlänge (evtl. variierend nach Wochentag) Minimal bezahlte Schichtlänge Durchschnittliche Schichtlänge
Arbeitszeit	Maximale Arbeitszeit (evtl. variierend nach Wochentag)
Pausen	Arbeitszeit bis 6 h erfordert keine Pause Arbeitszeit über 6 h bis 9 h erfordert Pause von 30 min Arbeitszeit über 9 h erfordert Pause von 45 min Schichtlänge über 12 h erfordert zusammenhängende Pause von 2 h Minimale Pausenlänge: 15 min Nach 6 h pausenloser Arbeit muss Pause erfolgen Zu Beginn und am Ende jeder Schicht sind Pausen zu vermeiden/verboten Pausen dürfen nur an Stationen mit Pausenraum und WC stattfinden Tätigkeitsunterbrechungen mit kleiner Dauer gelten als Arbeitszeit

Von Seiten des Eisenbahnverkehrsunternehmens, das die Verkehrsleistung erbringt, sind außerdem aufgrund unterschiedlicher Lohnkosten mehr Tag- als Nachtschichten und mehr Werktag- als Wochenendschichten wünschenswert. Diese Tatsache erfährt im hier vorgestellten Modell allerdings keine Berücksichtigung, da sich dieses auf die Schichtplanung eines Standardtages bezieht.

4.4 Modellierung als Set-Covering-Problem

Die in der Literatur vorherrschende Modellierungsmethode für Schichtplanungsprobleme ist das Set-Covering- bzw. Set-Partitioning-Problem. CAPRARA et al. (1999) nutzen ein solches Modell für die Formulierung des Schichtplanungsproblem der italienischen Eisenbahngesellschaft Ferrovie dello Stato, das anschließend mit einem Lagrange-Ansatz gelöst wird. Für das niederländische Eisenbahnverkehrsunternehmen NS Reizigers schildern KROON/FISCHETTI (2001) und ABBINK/WOUT/HUISMAN (2007) weitere Modelle und Lösungsalgorithmen für die Schichtplanung. Eine detaillierte Beschreibung

der Lösung großer Schichtplanungsprobleme im deutschen Personen- und Güterverkehr erfolgt in JÜTTE et al. (2011) und JÜTTE (2012). Für alternative Modellierungs- und Lösungsmöglichkeiten sei auf STEINZEN et al. (2010) und VAIDYANATHAN / JHA / AHUJA (2007) verwiesen. Erstere modellieren sowohl die Umlauf- als auch Schichtplanung als Flussproblem in einem Time-Space-Netzwerk, Letztere nutzen ein Mehrgüterflussproblem als Modellierungs- und Lösungsansatz.

Ausgangspunkt für das Modell sind alle zulässigen Schichten, die den betrieblichen und rechtlichen Rahmenbedingungen genügen (siehe Abschnitt 4.3.2). Die Menge dieser zulässigen Schichten sei mit N bezeichnet. Weiterhin benötigen wir für das Ziel der Kostenminimierung diverse Kostenfaktoren. Diese lassen sich in fixe und variable Kosten aufteilen. Während die fixen Kosten die Kosten für eine weitere Schicht beinhalten, bilden die variablen Kosten einer Schicht die Kosten einer Arbeitsminute, Kosten für Nacharbeit und Gastfahrten oder eventuell benötigte Strafkosten (z. B. für zu kurze oder zu lange Schichten) ab. Zur Bewahrung der Übersichtlichkeit werden hier lediglich die ersten beiden Kostenfaktoren berücksichtigt. Seien nun c_{fix} die Fixkosten einer Schicht, c_{var} die Kosten je Arbeitsminute und t_j die Arbeitsminuten der Schicht $j \in N$.

Jede Schicht $j \in N$ repräsentieren wir durch einen binären Vektor, der angibt, welche Trips $i \in M$ in der jeweiligen Schicht enthalten sind. Diese Vektoren werden zu einer Adjazenzmatrix $A \in \{0, 1\}^{|M| \times |N|}$ zusammengefasst und es gilt $a_{ij} = 1$, falls Trip i in der Schicht j enthalten ist, $a_{ij} = 0$ anderenfalls. Zur Formulierung eines Modells für die Auswahl der kostenminimalen Schichten definieren wir eine binäre Entscheidungsvariable x_j , die angibt, ob Schicht j der Lösung angehört ($x_j = 1$) oder nicht.

Das Problem der Minimierung der Gesamtkosten bei Abdeckung aller Trips kann wie folgt als Set-Covering-Modell formuliert werden:

$$\sum_{j \in N} (c_{\text{fix}} + c_{\text{var}} t_j) x_j \longrightarrow \min \quad (4.1)$$

$$\text{bei} \quad \sum_{j \in N} a_{ij} x_j \geq 1 \quad \forall i \in M \quad (4.2)$$

$$x_j \in \{0, 1\} \quad \forall j \in N. \quad (4.3)$$

Dieses Modell enthält $|N|$ Variablen und $|M|$ Restriktionen, wobei die Anzahl der Trips $|M|$ wesentlich kleiner ist als die Anzahl der möglichen Schichten $|N|$. Der zentralen Forderung des bisherigen Ansatzes, dass jeder Trip in mindestens einer Schicht enthalten sein muss, wird durch die Restriktionen (4.2) nachgekommen. Wenngleich dieses Modell nicht mehr für die Schichtplanung der Zugbegleiter mit Berücksichtigung von Prüfquoten genutzt werden kann, ist eine Anwendung für Triebfahrzeugführer oder komplette Netze mit einer Quote von 100 % weiterhin sinnvoll.

4.5 Modellierung der Schichtplanung der Zugbegleiter mit Prüfquoten

Aufgrund des Mangels geeigneter Modelle wird bislang auf das herkömmliche Set-Covering-Modell zurückgegriffen und die Lösung im Nachgang angepasst. Zunächst erfolgt eine Partition des Verkehrsnetzes anhand der Prüfquoten, d. h. alle Trips mit der gleichen Quote werden gruppiert. Für jede einzelne Quotenklassen erzeugt das Modell (4.1)-(4.3) eine Menge kostenoptimaler Schichten, die allerdings alle Züge bzw. Streckenkilometer der gruppierten Trips abdecken. Anschließend findet eine manuelle Auswahl der Schichten statt, die eine Abdeckung der durch die Prüfquote geforderten Züge bzw. Streckenkilometer sichern und gleichzeitig die geringsten Kosten aufweisen.

Diese Vorgehensweise ermöglicht keine Kostenoptimierung über das gesamte zu verplanende Netz, da sinnvolle Schichten, bestehend aus Trips mehrerer Quotenklassen, nicht betrachtet werden. Außerdem können für eine Quote unter 100 % andere Schichten kostengünstiger sein als die durch das Lösen des Set-Covering-Modells generierten Schichten.

Um den neuen Forderungen nach einer anteiligen Begleitung der Züge durch Zugbegleiter gerecht zu werden und gleichzeitig eine kostenoptimale Lösung für das gesamte Verkehrsnetz zu erzeugen, ist eine Anpassung des Modells (4.1)-(4.3) erforderlich. Im Weiteren erfolgt die Berechnung des zu begleitenden Anteils auf Grundlage der Streckenkilometer. Quotenrestriktionen, die auf der Anzahl der Züge basieren, sind analog modellierbar.

Wie in Abschnitt 4.3.1 beschrieben kann es mehrere Klassen mit verschiedenen Quoten geben. Sei nun G die Menge der Quotenklassen und s^g die kumulierten Streckenkilometer aller Trips der Klasse $g \in G$. Aufgrund der neuen Forderung, dass lediglich ein gewisser Anteil an Streckenkilometern mit Zugbegleitern besetzt werden muss, spielen auch die Streckenkilometer jedes einzelnen Trips eine wesentliche Rolle. Dazu bezeichnet d_i^g die Streckenkilometer des Trips i in der Klasse g .

Zur Formulierung eines ganzzahligen Modells führen wir zwei binäre Entscheidungsvariablen x_j und y_i ein. Dabei gibt x_j analog zum herkömmlichen Modell an, ob die Schicht j in der Lösung enthalten ist ($x_j = 1$) oder nicht.

Das ganzzahlige lineare Modell für das Schichtplanungsproblem von Zugbegleitpersonal unter Berücksichtigung von Prüfquoten lautet:

$$\sum_{j \in N} (c_{\text{fix}} + c_{\text{var}} t_j) x_j \longrightarrow \min \quad (4.4)$$

$$\text{bei} \quad \sum_{i \in M} d_i^g y_i \geq q^g s^g \quad \forall g \in G \quad (4.5)$$

$$\sum_{j \in N} a_{ij} x_j \geq y_i \quad \forall i \in M \quad (4.6)$$

$$y_i \geq x_j a_{ij} \quad \forall i \in M, j \in N \quad (4.7)$$

$$x_j \in \{0, 1\} \quad \forall j \in N. \quad (4.8)$$

$$y_j \in \{0, 1\} \quad \forall i \in M. \quad (4.9)$$

Dabei erzwingen die Bedingungen (4.5) die Einhaltung der Quoten in der jeweiligen Klasse, denn die aufsummierten Streckenkilometer der Trips, die in der Lösung enthalten sind, muss den benötigten Quotenanteil erreichen oder übersteigen.

Die Restriktionen (4.6) fordern für jeden Trip, der in der Lösung enthalten ist ($y_i = 1$), dass mindestens eine Schicht j in der Lösung existiert ($x_j = 1$), die diesen Trip enthält. Wenn alle Schichten j , die Trip i enthalten ($a_{ij} = 1$), nicht in der Lösung sind ($x_j = 0$), wird andererseits in (4.6) erzwungen, dass Trip i nicht in der Lösung sein darf ($y_i = 0$).

Ist hingegen Trip i nicht in der Lösung enthalten ($y_i = 0$), dann sichern die Bedingungen (4.7), dass alle Schichten j , die Trip i enthalten ($a_{ij} = 1$), nicht zur Lösung gehören ($x_j = 0$). Außerdem wird für alle Trips i , die durch Schichten der Lösung ($x_j = 1$) abgedeckt sind ($a_{ij} = 1$), das Enthaltensein in der Lösung gefordert ($y_i = 1$). Für das Modell (4.4)-(4.9) lässt sich die Entscheidungsvariable y_i wie folgt interpretieren. Gilt $y_i = 1$, dann ist der Trip i in der Lösung enthalten, anderenfalls nicht. Da diese Restriktionen (4.7) keine Auswirkungen auf die Entscheidungsvariablen x_j und damit die Zielfunktion haben, können sie ohne Genauigkeitsverlust vernachlässigt werden. Bei dieser Variante darf die Entscheidungsvariable y_i allerdings nicht mehr wie oben beschrieben interpretiert werden.

Dieses neue Modell (4.4)-(4.9) für die Schichtplanung von Zugbegleitern mit verschiedenen Prüfquoten enthält $|N| + |M|$ Variablen und $|G| + |M|$ ($+|M||N|$) Restriktionen – je nach Verwendung der Nebenbedingungen (4.7). Es kann leicht auf den Fall mit einer ständigen Begleitung (100 % Quote) übertragen werden. Setze dazu $|G| = 1$, $\sum_{i \in M} d_i = s$, $q = 1$ und $y_i = 1 \forall i \in M$. Die Restriktionen (4.5) und (4.7) sind für jedes $x_j \in \{0, 1\}$ erfüllt und können demnach gestrichen werden. Das Resultat ist ein Modell analog zu (4.1)-(4.3).

4.6 Beispiel

Gegeben sei ein Netz mit drei Stationen A, B und C. Zwischen den Stationen A und C verkehrt auf direkter Strecke ein Regionalexpress (RE), der die Distanz von 140 km in 70 Minuten zurücklegt. Des Weiteren gibt es eine Regionalbahnlinie (RB) zwischen den beiden Stationen, die über die Station B führt und dort 10 Minuten Aufenthalt

hat. Zudem verkehren auf den Teilstrecken A-B und B-C zwei Regionalbahnlinien als Ergänzungsangebot. Dabei beträgt die Distanz zwischen A und B 60 km, die in 30 Minuten zurückgelegt werden kann, zwischen B und C 90 km, für die 60 Minuten im Fahrplan veranschlagt werden (siehe Abbildung 4.4).

Abbildung 4.4: Beispielnetz mit Strecken- und Zeitdistanzen

Die genauen Fahrplandaten sind der Tabelle 4.2 zu entnehmen. Es gilt zu beachten, dass diese Tabelle bereits die einzelnen Trips enthält, d. h. die Zugfahrten der Regionalbahnlinie zwischen den Stationen A und C ist in Trips zwischen A-B und B-C aufgebrochen.

Tabelle 4.2: Beispielfahrplan mit Regionalexpress- und Regionalbahnlinien

	Nummer	Abfahrtsort	Ankunftsart	Abfahrtszeit	Ankunftszeit	Distanz (km)	Klasse
RE A-C	1	A	C	6:00	7:10	140	RE
	2	C	A	7:20	8:30	140	RE
	3	A	C	10:00	11:10	140	RE
	4	C	A	11:20	12:30	140	RE
	5	A	C	14:00	15:10	140	RE
	6	C	A	15:20	16:30	140	RE
RB A-B	7	A	B	8:40	9:10	60	RB
	8	B	A	9:20	9:50	60	RB
	9	A	B	12:40	13:10	60	RB
	10	B	A	13:20	13:50	60	RB
	11	A	B	16:40	17:10	60	RB
	12	B	A	17:20	17:50	60	RB
RB A-C	13	A	B	9:20	9:50	60	RB
	14	B	C	10:00	11:00	90	RB
	15	C	B	11:20	12:20	90	RB
	16	B	A	12:30	13:00	60	RB
	17	A	B	13:20	13:50	60	RB
	18	B	C	14:00	15:00	90	RB
	19	C	B	15:20	16:20	90	RB
	20	B	A	16:30	17:00	60	RB
RB B-C	21	C	B	11:20	12:20	90	RB
	22	B	C	14:10	15:10	90	RB
	23	C	B	15:20	16:20	90	RB
	24	B	C	18:10	19:10	90	RB

Laut Verkehrsvertrag ist die Regionalexpresslinie mit 100 % zu prüfen, d. h. jeder Zug wird mit einem Zugbegleiter besetzt. Für alle Regionalbahnlinien ist eine Prüfquote von 50 % festgelegt. Ferner ist eine Wendezeit von 5 Minuten zwischen allen in einer Schicht enthaltenen Trips vorgeschrieben, die maximale Schichtlänge beträgt 11 Stunden und Schichten unter 5 Stunden werden wie eine 5-Stunden-Schicht bezahlt. Zur Wahrung der Übersichtlichkeit erweist es sich nicht als sinnvoll weitere Vorbereitungs- und Abschlussdienste, Fußwege oder Arbeitszeit- und Pausenregelungen zu beachten.

Beide Modelle für die Schichtplanung von Zugbegleitern, mit Besetzung aller Trips (4.1)-(4.3) bzw. mit Prüfquoten (4.4)-(4.9), wurden mit CPLEX 12.5 implementiert. Dabei wurden die Kostenparameter wie folgt fixiert: $c_{\text{var}} = 50$ für eine Schichtminute und $c_{\text{fix}} = 2000$.

Wie bereits erwähnt, erfolgt in der bisherigen Vorgehensweise eine Aufspaltung des Netzes nach den verschiedenen Prüfquoten (hier nach Produktart). Nachfolgend werden für alle Teilnetze mithilfe des Modells (4.1)-(4.3) optimale Schichtpläne erstellt. Liegt bei einem Teilnetz eine geringere Prüfquote vor, so werden die Schichten ausgewählt, die kostenminimal die geforderten Streckenkilometer abdecken.

Die erste Gruppe der Regionalexpress-Züge enthält 6 Trips, die sich zu 16 möglichen Schichten kombinieren lassen. Die Lösung des Modells (4.1)-(4.3) mit der Adjazenzmatrix der Schichten

$$A = \begin{pmatrix} 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 0 & 1 & 0 & 1 \\ 0 & 0 & 0 & 1 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & 1 \\ 0 & 1 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & 1 & 1 & 1 \\ 0 & 0 & 1 & 0 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 1 & 1 & 0 & 1 & 1 \end{pmatrix}$$

und dem Vektor der Arbeitszeiten

$$t = (300 \quad 390 \quad 630 \quad 300 \quad 470 \quad 300 \quad 390 \quad 300 \quad 300 \quad 390 \quad 630 \quad 630 \quad 630 \quad 470 \quad 390 \quad 630)$$

liefert Schicht 16 (siehe Abbildung 4.5) mit Kosten von 33500. Dabei repräsentiert der horizontale Verlauf die Zeitschiene, die Zahlen in den grauen Blöcke die Zugnummer und die Buchstaben unter den Blöcken die jeweiligen Stationen. Die dargestellte Schicht gehört ebenfalls zur Lösung des Gesamtnetzes, da im Verkehrsvertrag für diese Regionalexpresslinie eine Prüfquote von 100 % vorgegeben ist.

Die 18 Trips der zweiten Gruppe der Regionalbahn-Züge ermöglichen 282 Schichten. Unter der Maßgabe, dass jeder Trip mit einem Zugbegleiter besetzt sein muss, ergeben sich die in Abbildung 4.6 dargestellten Schichten.

Die erste Schicht verursacht Kosten von 25500 und deckt dabei eine Strecke von 300 km ab, die zweite Schicht enthält Trips mit einer Strecke von 420 km bei Kosten von 27000 und die dritte Schicht deckt 600 km ab bei Kosten von 27500. Da für eine Lösung des

Abbildung 4.7: Schichtplan für Beispielfall unter Zuhilfenahme des neuen Modells

4.7 Zusammenfassung und Ausblick

Das Problem der Schichtplanung für Zugbegleiter ist sehr komplex, dennoch gibt es in der Literatur verschiedene Modellierungs- und Lösungsansätze. Unter der Annahme, dass nicht alle Züge eines Verkehrsnetzes mit einem Zugbegleiter besetzt werden, ist die Nutzung dieser Modelle und Lösungsverfahren nicht möglich oder stark eingeschränkt. Aus diesem Grund stellt das in diesem Beitrag vorgestellte Modell, das kostenoptimale Schichten bei Einhaltung der Prüfquoten erzeugt, eine zeitgemäße Weiterentwicklung dar. Die Anwendung des Modells beschränkt sich dabei nicht nur auf Zugbegleiter im Schienenverkehr. Ähnliche Problemstellungen treten bei Prüfrupps für Straßenbahnen oder Bussen auf.

Dieses Modell bildet bisher lediglich das Schichtplanungsproblem eines Standardtages ab. Die Forderung nach einer gleichmäßigen Verteilung der geprüften Fahrten erhebt den Anspruch auf eine Erweiterung des Planungshorizontes bei der Modellierung. Dabei gilt es zu beachten, dass ein Fahrplan innerhalb einer Standardwoche nicht zyklisch ist und für unterschiedliche Tage verschiedene Züge verplant werden müssen. Weiterhin setzt das Modell als Eingangsdaten zulässige Schichten voraus. Das Verfahren der vollständigen Enumeration erweist sich insbesondere bei großen praxisnahen Problemen als ineffizient oder nicht realisierbar. Daher stellt die effiziente Generierung zulässiger Schichten ein notwendiges Forschungsgebiet dar. Eine Möglichkeit, iterativ neue Schichten anhand der Lösung des Modells zu erstellen, ist die Methode der Column Generation wie sie in BARNHART et al. (1998) für ganzzahlige Probleme im Allgemeinen, GAMACHE et al. (1999) für Personalplanungsprobleme im Flugverkehr und HUISMAN (2007) im Eisenbahnverkehr vorgestellt wird. Die Übertragung dieser Technik auf das hier definierte Modell ist zu prüfen. Außerdem erreicht ein Solver wie beispielsweise CPLEX bei großen praxisnahen Problemen seine Grenzen. Aus diesem Grund sollte eine Überprüfung alternativer Lösungsmethoden (für das herkömmliche Set-Covering-Modell in CAPRARA / FISCHETTI / TOTH (1999) und BENGTSSON et al. (2007) zu finden) in den Fokus rücken.

5 A hybrid solution approach for railway crew scheduling problems with attendance rates

Abstract

This paper presents a model for railway crew scheduling problems dealing with attendance rates for conductors. Afterwards we discuss a hybrid solution approach for these kind of problems. This approach consists of a column generation framework using genetic algorithm to solve the pricing problem. Based on a real-world instance, we compare our hybrid solution approach with the enumeration approach with respect to resulting total costs and computation time.

Reference

Published paper: HOFFMANN, K. (2017): A Hybrid Solution Approach for Railway Crew Scheduling Problems with Attendance Rates. In: DOERNER, K. et al. (Eds.): *Operations Research Proceedings 2015*. Springer International Publishing.

5.1 Introduction

Apart from energy costs (fuel, electricity), crew costs are the largest cost factor in rail passenger transport. Therefore, the efficient assignment of crews is becoming increasingly more important. Previous crew scheduling models and solution approaches mostly deal with covering all trips of the given train timetable. The diminishing importance of operational tasks and increasing cost pressure, however, force responsible authorities in Germany to reduce the deployment of conductors. Therefore, transportation contracts defining all frame conditions for different transportation networks determine one or more percentage rates of trains or kilometres that have to be attended by conductors.

In regional rail transport, crew members are train drivers (operator of a train) and conductors (tasks: ticket collection and other customer services). We focus on the latter, as variable attendance rates cannot be applied to train drivers, obviously. Nevertheless, train drivers could be included with attendance rates of 100 %.

There is a wide range of models and algorithms concerning transport crew scheduling and rostering, respectively. For a recent review on passenger railway optimization, see CAPRARA et al. (2007). Due to the size of crew scheduling problems (up to several millions of possible duties), metaheuristics are increasingly gaining in importance. SHEN/KWAN (2001) introduce a tabu search algorithm for bus and train drivers. HANAFI/KOZAN (2014) present a mathematical model for railway crew scheduling solved by simulated annealing. Genetic algorithms can be applied in two different ways: After generating feasible duties, genetic algorithms are used to find the optimal shift schedule. On the other hand, the pricing problem (generation of new duties) can be solved with genetic algorithms DOS SANTOS/MATEUS (2009); LIU/HAGHANI/TOOBAIE (2010).

To the best of our knowledge, there are no appropriate models or algorithms dealing with attendance rates. Therefore, we define a new model with attendance rates in Section 5.2. Section 5.3 presents the hybrid solution approach, containing a column generation framework with a genetic algorithm to solve the pricing problem. Section 5.4 reports the results of our computational experiments.

5.2 Crew scheduling problem with attendance rates

In public transport, especially railway traffic, there are several requirements that have to be satisfied. For operational and legal requirements of the German railways see JÜTTE et al. (2011). Additionally, the transportation contract regulates attendance rates, possibly distinguished between product types, lines, train numbers, track sections, and time windows. Moreover, responsible authorities determine penalization if real attendance rates are too low. The railway crew scheduling problem with attendance rates

is to find a minimum cost shift schedule satisfying operating conditions and legal requirements. The schedule should cover a subset of all trips such that the different attendance rates specified in the transportation contract are met.

The most common model for crew scheduling problems is the set covering problem, which is known to be NP-hard. To modify this set covering model for our purposes, we need a set M of all trips assigned to the considered transportation network and a set N of all feasible duties. Each duty $j \in N$ is represented by one column in matrix $A \in \{0, 1\}^{|M| \times |N|}$ with $a_{ij} = 1$ if duty $j \in N$ covers trip $i \in M$, 0 otherwise. Parameter c_j displays the costs of duty $j \in N$. Let x_j be the binary decision variables such that $x_j = 1$, if duty j is part of the solution schedule, 0 otherwise. Let $G \subset (0, 1]$ be a set of all attendance rates defined in the transportation contract. Let d_{ig} be the distance of trip $i \in M$ with attendance rate $g \in G$ and y_i the decision variable at which $y_i = 1$ if trip $i \in M$ is covered in the solution schedule. The railway crew scheduling problem with attendance rates for a single day (CSPAR) is

$$\min \sum_{j \in N} c_j x_j \quad (5.1)$$

$$\text{s.t. } \sum_{i \in M} d_{ig} y_i \geq g \sum_{i \in M} d_{ig} \quad \forall g \in G \quad (5.2)$$

$$\sum_{j \in N} a_{ij} x_j \geq y_i \quad \forall i \in M \quad (5.3)$$

$$y_i \geq a_{ij} x_j \quad \forall i \in M, j \in N \quad (5.4)$$

$$x_j \in \{0, 1\} \quad \forall j \in N \quad (5.5)$$

$$y_i \in \{0, 1\} \quad \forall i \in M. \quad (5.6)$$

The objective function (5.1) minimizes the total costs over all chosen duties. Constraints (5.2) guarantee that the accumulated distance of the covered trips in the solution schedule is greater than or equal to the requested percentage of the total distance assigned to the special attendance rate. Constraints (5.3) and (5.4) are linking constraints for the x_j and y_i variables.

We can relax constraints (5.4) without changing the value of the objective function. However, variables y_i can no longer be interpreted as existence of trip i in the solution schedule. In practice, we have some additional constraints, e.g. the average working time of the shift schedule or the personnel capacity of each crew base. This model can easily be transferred to multiple days which is, due to the increasing complexity of sets, variables, and indices, not part of the paper.

5.3 Hybrid solution approach

A simple solution approach for the CSPAR consists of two phases: First, generate all possible duties N , e.g. with depth-first search, than solve model (5.1)-(5.6) with suitable algorithms or optimisation solver. For practical application, where several million feasible duties are possible, this approach is too time consuming and the memory usage is high.

To get shift schedules for few days or weeks within reasonable time, we have to speed up the solution process. To achieve this goal, column generation is an useful instrument. The problem (5.1)-(5.6) is decomposed into master and pricing problem. In the restricted master problem (RMP) the linear programming relaxation of (5.1)-(5.6) is solved to optimality with respect to a small subset of duties. To generate new duties that lower the objective value dual values are used. Let $\pi_i, i \in M$, be the dual values of constraints (5.3) then $\bar{c}_j = c_j - \sum_{i \in M} \pi_i a_{ij}$ specifies the reduced costs of duty j . To lower the objective value add duties with negative values (5.3) to the restricted master problem. The question is how to generate feasible duties with negative reduced costs (pricing problem, PP). The most common approach uses the shortest path problem with resource constraints to solve the pricing problem DESROCHERS et al. (1992). To reduce the problem size and accelerate the pricing problem, we apply a genetic algorithm for the generation of new duties.

Genetic algorithms adopt techniques derived from natural evolution to search for solutions of optimisation problems. For further information we refer to MICHALEWICZ (1996). The individuals of the population represent the duties. We implement a trip based representation, where the trips are sorted by increasing departure time. The basic operators and properties are discussed below.

Initial schedule (overall) Since we have to start with a feasible schedule to generate dual values, the initial schedule has to suffice (5.2)-(5.6). In order to determine such set of duties, we use a block generation approach with depth-first search. For each trip starting at a crew base, duty blocks with given minimum and maximum duration and maximum transition time are formed. The resulting highly productive blocks are randomly matched to feasible duties with required breaks.

Fitness function The fitness function equates the objective function of the pricing problem, i.e. the reduced costs.

Initial population (pricing problem) In each iteration of the column generation approach, the set of all duties is available for the pricing problem, whether from the initial schedule or generated in earlier iterations. We select the best `popSize` individuals of the

initial population starting the genetic algorithm procedure in each column generation iteration.

Crossover We implement a special kind of one-point crossover. This operator is applied in four stages: First, select an individual of the current population randomly. Then, choose a different individual starting at the same crew base. After random choice of a cut point of the first parent, we search for a proper cut point of the second parent. On the one hand, the stations at the cut points must match. On the other hand, arrival and departure times have to be compatible. All trips located right of the cut points swap places.

Mutation The mutation operator replaces the randomly chosen genome (trip) with a suitable one. The new trip has to fit into the resulting gap with respect to departure and arrival time/station. The operator is configured in such way that either the resulting duties are always feasible or the mutation will not be executed.

Selection for replacement The population of the next generation contains all generated duties without duplicates and the best old ones not included in the former set.

Figure 5.1: Hybrid solution approach

Figure 5.1 summarizes the introduced hybrid solution approach. Compared to LIU/HAGHANI/TOOBAIE (2010), the operators are highly adapted to the crew scheduling

problem, so that just a few generated duties are infeasible concerning the break times. The whole framework exclusively deals with feasible duties. DOS SANTOS/MATEUS (2009) solve the pricing problem in an exact way if the genetic algorithm fails to generate new duties. For instances with up to 1,500 trips per day and a planning period up to 14 days, this approach is too time consuming, especially considering the fact that these duties reduce the value of the linear relaxation, not necessarily of the integer problem. Furthermore, some practical requirements can hardly or not be modelled mathematically. For this reasons, we decided to use a completely metaheuristic pricing step.

5.4 Computational results

All computational tests were performed on a real-world test instance with 713 trips, 18 relief points, 10 crew bases and 5 break rooms. Further requirements are: maximum duty time (640 min), maximum working time (600 min), minimum paid time (300 min), and average paid time ($\in [418, 512]$ min). The attendance rates are predefined to 30 % of the total distance in the transportation network during the day and 90 % from 7pm. Observed cost factors are fixed costs of 2,000 per duty and 50 per working minute. This values are prescribed by our project partners and influence the duration of the duties in relation to the number. We use a Intel(R) Xenon(R) CPU E5-2630 v2 @ 2.6 GHz server with 12 cores and 384 GB RAM and Gurobi 6.0.

Table 5.1: Computational results of the two-phase approach

Parameter set	# Duties	Time Generator (s)	Time Solver (s)	Total time (s)	Costs
set1	121,892	50	31	81	407,150
set2	3,821,534	796	578	1,374	397,850
set3	2,807,746	16,224	322	16,546	396,400
set4	7,512,654	45,532	1,351	46,883	394,450

The results of the two-phase approach (depth-first search, solve model with the Gurobi Optimizer) are summarized in Table 5.1. Parameter sets **set1**, **set2**, **set3**, **set4** define various values of the maximum transition time, productivity of the duties, and minimum duration of connected trips. Both phases run parallel with 24 threads. Considering the limited memory capacity of our system, we receive the best solution within 13 hours, whereby 7.5 million duties are generated in the first phase.

For the computational tests of the hybrid solution approach we perform 30 runs per parameter configuration to measure the random component. The crossover rate is fixed at 0.9, the mutation rate at 0.1, and the initial schedule contains 52,900-53,000 duties. The Gurobi Optimizer runs parallel on 24 threads, the pricing problem on one thread.

The values stated in Table 5.2 are mean values, and all real numbers are rounded up to the next integer number.

Table 5.2: Computational results of the hybrid approach (selection)

pop Size	gen Size	Iter	# Duties	Time (s)				Costs			
				PP	LP	IP	Total	Mean	SD	Min	Max
500	50	60	2,099	104	14	231	384	406,061	4,222	394,501	412,200
500	100	50	2,568	142	15	298	489	403,464	5,536	394,100	412,200
1,000	10	105	1,228	138	25	163	362	406,992	4,813	395,250	412,201
1,000	30	83	2,206	198	19	153	403	401,459	5,792	391,950	412,200
1,000	50	61	2,863	212	15	178	440	399,824	5,374	391,450	408,650
1,000	75	50	3,341	245	13	113	406	401,959	4,673	392,150	412,200
1,000	100	42	4,076	265	13	212	524	400,139	5,460	392,250	412,200
2,000	10	119	1,314	276	27	286	623	406,517	3,977	399,850	412,550
2,000	30	84	2,303	473	20	74	601	396,694	5,102	390,650	408,150
2,000	50	60	3,688	557	16	162	769	398,299	5,213	391,200	410,650
2,000	75	55	5,135	755	15	55	859	396,965	4,327	390,900	406,450
2,000	100	45	6,107	828	14	71	948	396,604	4,546	390,800	405,100
4,000	50	70	4,659	2,072	18	34	2,158	394,672	3,902	390,050	403,600
4,000	100	49	9,768	2,922	16	51	3,023	393,889	3,955	389,350	404,200

As shown in the table, an increasing generations size (**genSize**) results in a decreasing number of Iterations (Iter) and an increasing number of duties generated in the pricing problem (# Duties). This implies a rising computation time of the pricing problem (PP). Increasing the population size (**popSize**), the pricing problem lasts longer, too. Furthermore, the mean (Mean), standard deviation (SD) and minimum/maximum value (Min/Max) of the costs are lowered. DOS SANTOS/MATEUS (2009) recommend that the population size has to be equal to three times the number of trips. The proportion of the computation time the Gurobi Optimizer uses for solving the RMP (LP) is insignificant, whereas the time for the integer solution (IP) is fluctuating.

5.5 Conclusions and further research

In this paper we presented a new model for crew scheduling problems with special focus on variable attendance rates for conductors. Although this work is still at an early stage, the introduced solution approach composed of column generation and genetic algorithm delivers good results within reasonable time. In comparison with the simple two-phase approach we obtain better solutions in less time in many cases.

The results show that, in many cases, the time for solving the integer problem with the Gurobi Optimizer exceeds the time for the column generation process. Therefore,

we have to check heuristic solutions for the integer problem to reduce the computing time, such as variable fixing. Furthermore, various methods for generating the initial schedule have to be tested. In the pricing problem, we could modify the way of selection or diversify the crossover and mutation operator. In implementation, multi-threading has to be applied to the pricing procedure. Moreover, computational tests for instances covering multiple days have to be analysed with respect to computing time and memory usage.

6 Solving practical railway crew scheduling problems with attendance rates

Abstract

Arising from a practical problem in German rail passenger transport, a prototype for a multi-period railway crew scheduling problem with attendance rates (MCSPAR) for conductors is developed and evaluated in this paper. The consideration of attendance rates is of increasing importance in regional transport networks and requires decision support. For this purpose business analytics is applied in order to offer an approach to transform real-world data to concrete operational decision support (action). The focus here is on the analysis step using a new set covering model with several essential restrictions integrated for the first time. A hybrid column generation solution approach is applied, which solves the pricing problem by a genetic algorithm. The artifact is evaluated with the help of a case study for three real-world transport networks. It is shown that the hybrid solution approach is able to solve the problem more effectively and efficiently compared to conventional approaches from practice.

Reference

Published paper: HOFFMANN, K. et al. (2017): Solving Practical Railway Crew Scheduling Problems with Attendance Rates. In: *Business & Information Systems Engineering*, Vol. 59.

6.1 Introduction

Since the rail reform in 1996 railway companies in Germany are in competition with each other and face various challenges. In order to cope with increasing transport volumes under constant resources they are forced to deliver services efficiently. At the same time, railway companies endeavor to offer an attractive work environment and to fulfill sustainability requirements like energy savings and noise-reduction. To provide their transport services, they have to take part in tender processes for transport services. For being successful, railway companies have to submit cost-efficient offers. Often costs for rolling stock units, energy and infrastructure cannot be influenced substantially by the company. This means that personnel costs become the critical factor. Especially an intelligent and automated planning of crew schedules offers the chance to create a competitive advantage in tender processes.

The classical planning process in regional passenger rail transport is performed by two different actors in Germany. The general structure of this planning process is illustrated in Figure 6.1. Federal states are responsible for the organization and implementation of regional passenger rail transport. In some cases federal states are represented by subsidiary demand transport services whereas in most cases this role is delegated to transport associations, being the first actor. These specify offered services and are responsible for the line planning, that aims to find lines and corresponding frequencies in a transport network such that all travel demand can be satisfied (BORNDÖRFER/GRÖTSCHEL/PFETSCH (2007)). Moreover, for a given set of lines and frequencies arrival and departure times at each track section and station are determined (timetabling) ensuring all relevant safety constraints (KASPI/RAVIV (2013)).

Railway companies are the second actor and take care of the usage of crews and rolling stock units. The key task in rolling stock scheduling is to determine arrival and departure times of a group of unspecified trains at each station in a conflict-free way and to utilize railway resources as efficiently as possible. Furthermore, regular maintenance activities have to be integrated (CAPRARA et al. (2007)). The principal focus of this paper is on crew scheduling, which will be described in more detail later. The following processes refine the planning. While the rolling stock circulation problem determines the concrete type and number of rolling stock units per scheduled train, crew rostering assigns duties to individuals and duties are sequenced together to form a roster (CAPRARA et al. (2007)). Short-term changes due to e.g. operational interruptions and sickness notifications are managed within the vehicle and crew disposition.

Crew scheduling is of particular relevance for railway companies, because efficient schedules can reduce personnel costs significantly. In regional rail transport, crew members are train drivers (operator of a train) and conductors (tasks: ticket control and other

Figure 6.1: Planning process

customer services), from which the latter will be the center of interest in the following. An increasing cost pressure forces transport associations in Germany to minimize the deployment of conductors. While in the past at least one conductor was required for all trips, today a large number of new transportation contracts allow a certain number of unattended trips in order to keep costs low. Depending on product types, lines, track sections or time windows a so-called attendance rate is defined. It is calculated as the ratio between cumulated attended kilometers and all cumulated kilometers (attended and unattended). For example, a transportation contract may specify for a local train an attendance rate of 30 percent until 9 p.m. and thereafter a rate of 90 percent. It has to be emphasized, that for railway companies, who are responsible for the crew scheduling, these attendance rates are predefined by the transport associations and cannot be changed.

Typically, in advance of crew scheduling the rolling stock scheduling is done, so that scheduled train runs are given and split into a number of unique trips. Since a change of trains is not viable at every stop, usually a limited number of stations, referred to as relief points, is defined at which a changeover is possible. A unique trip always runs between two relief points and is characterized by a departure time, a departure station, an arrival time as well as an arrival station. Each unique trip can be valid on several days of the week so that it may result in several trips that have to be planned in the planning horizon. It is normally serviced by a certain type of conductor. Combining single trips leads to a duty, for which several requirements have to be met, such as compatibility of

subsequent trips concerning time and place or legal requirements regarding working time. The crew scheduling finally constructs a set of duties covering relevant trips (KASPI/RAVIV (2013)).

If we look at the crew scheduling process in practice, we observe no automated decision support to handle the various attendance rates. The reason for this is that attendance rates cannot be modeled in the applied systems so far. Thus, the aim of this paper is to improve and automate the crew scheduling process for railway companies. Hence, this article proposes a new, extended multi-period railway crew scheduling model with variable attendance rates (MCSPAR) for the tactical planning, i. e. that a standardized weekly or fortnightly schedule is determined, which is rolled out for a planning horizon of several weeks up to 3 months. Particularly for the crew scheduling problem with attendance rates a multi-period model is promising since not all trips have to be scheduled every day and, hence, finding the best day for covering each trip can lead to an additional cost reduction. The proposed model minimizes total costs over all duties and extends single-day-related approaches by covering now a period of several days. Thereby, a number of operating conditions as well as social, labor and bargaining law regulations are regarded.

The paper is organized as follows. Section 6.2 provides a brief overview of related literature. Afterwards, Section 6.3 describes the analytics-based design of this study and defines the considered problem. Moreover, a set covering model for the railway crew scheduling problem with attendance rates is formulated. Section 6.4 presents the hybrid solution approach, containing a column generation framework with a genetic algorithm to solve the pricing problem. Section 6.5 reports the evaluation of the gained artifact in the form of computational results for a case study. Conclusions are provided in Section 6.6.

6.2 Related work

Recently, VAN DEN BERGH et al. (2013) stated that personnel scheduling has an important economic impact because labor costs represent one major direct cost component for many companies. Hence, an optimized personnel scheduling could be very beneficial. We focus on the Crew Scheduling Problem (CSP), that has been studied for a long time and is still an area of active research. Its origins lie in the airline industry. Already in 1969 ARABEYRE et al. (1969) gave an overview of the airline crew scheduling problem (for more recent reviews see BARNHART et al. (2003) as well as GOPALAKRISHNAN/JOHNSON (2005)). Another area of application is urban mass transit (DESROCHERS/SOUMIS (1989); HAASE/DESAULNIERS/DESROSIERS (2001); MICHAELIS/SCHÖBEL (2009); STEINZEN/SUHL/KLIEWER (2009)). However, in this paper we con-

centrate on railway crew scheduling. Thereby, the term crew member can cover drivers, conductors and mechanics. Both options, assigning all personnel and assigning only one type of personnel to trains can be found in literature. Although there are special requirements for each type, the process of crew scheduling is basically the same for all crew members. However, the consideration of attendance rates is relevant for conductors only, since driverless trains are not allowed until today. To the best of our knowledge the aspect of finding an optimal attendance rate for a transport network has not been discussed in literature so far. Nevertheless, recently similar questions concerning toll enforcement have been solved using game theoretic approaches (see e.g. BORNDÖRFER et al. (2016)). However, in the considered crew scheduling problem attendance rates are predefined and cannot be changed.

SUYABATMAZ/ŞAHİN (2015) state that two mainstream formulation approaches are predominant in the field of crew planning problems. The first approach applies network flow formulations (VAIDYANATHAN/JHA/AHUJA (2007); ŞAHİN/YÜCEOĞLU (2011)) but is comparatively seldom used. The second, most commonly used method utilizes set covering or set partitioning type formulations. On this basis, column generation based methods turn out to be able to solve real-world problems of practical size with reasonable computational effort (see e.g. CAPRARA et al. (1997); CAPRARA et al. (2007); ERNST et al. (2001); SHEN/CHEN (2014)). Hereby, an initial feasible schedule, using a subset of duties covering all tasks, marks the beginning of the column generation approach. Subsequently, feasible candidate duties (columns) are generated (duty generation problem) taking into account dual prices of the master problem. With these new duties the problem is resolved and this iterative solution finding process stops until the optimal or a good solution is found. For details on the methodology of the column generation technique see e.g. BARNHART et al. (1998) and LÜBBECKE/DESROSIERS (2005). Recently, decomposition techniques were applied to the crew scheduling problem as well, leading to very promising results (JÜTTE/THONEMANN (2012a); JÜTTE/THONEMANN (2015)).

Since the CSP belongs to the class of NP-hard problems (see KWAN (2011)), it is not surprising that metaheuristics are regarded as potentially suitable candidates for the solution of the CSP, because they have shown very good performance with respect to finding (near-)optimal solutions in large solution spaces. In the past tabu search as well as genetic algorithms were proposed for crew scheduling. For an overview of various applications of metaheuristics in the area of crew scheduling see SHEN et al. (2013). Recently, YAGHINI/KARIMI/RAHBAR (2015) applied matheuristics that combine metaheuristics and mathematic programming techniques to the train driver crew scheduling problem.

In this paper, we also intend to take advantage of metaheuristics. Since a large number of operating conditions as well as social, labor, and bargaining law regulations are being observed, a set covering approach is chosen. To solve the problem we apply a hybrid column generation method in which a genetic algorithm serves to generate new duties (columns) with reduced costs. The studies that are particularly relevant to ours are HOFFMANN (2014) and HOFFMANN (2017) due to the integration of attendance rates. These first approaches are extended to a multi-period crew scheduling setting that allows a distribution of scheduled trips over the planning horizon instead of fulfilling attendance rates for each single day. The application of the proposed solving method to real-world railway crew scheduling problems with attendance rates shows its suitability and usefulness.

6.3 The crew scheduling problem with attendance rates

6.3.1 Analytics-based design

Our objective is to provide decision support for a railway company that aims to solve multi-period railway crew scheduling problems with attendance rates (MCSPAR) for conductors. Thereby, we follow the process-oriented view of business analytics, that consists of transforming data into actions through analysis and insights in the context of organizational decision making and problem solving (LIBERATORE/LUO (2010)).

For a comprehensive overview of various definitions of business analytics the reader is referred to HOLSAPPLE/LEE-POST/PAKATH (2014). Data, Analysis, Insight and Action represent the four stages of the process-oriented approach. As in the majority of cases, the process of extracting relevant data from various data sources and the subsequent rearrangement in order to make data ready for further analysis was very time-consuming. Nevertheless, the analysis stage can indeed be described as the engine and therefore as the most important component of our analytic process (see again LIBERATORE/LUO (2010)). The analysis stage comprises a problem description and formulation as well as the solution approach, offering the decision maker a clear recommendation for the deployment of conductors. The gained results and insights enable the decision maker to apply them directly to real-world instances. To evaluate the results three specific transport networks were considered and solved with the newly developed method.

6.3.2 Problem description and practical requirements

The analysis stage starts with the description of the crew scheduling problem in public transport, especially railway transport, that is characterized by numerous restrictions that have to be satisfied. First of all, operating conditions regulate the structure of duties. Duties have to start and end at the same crew base and two consecutive trips in a duty have to satisfy some compatibility constraints: between the arrival of a trip at a station and the departure of the following trip there has to be enough time for required walks between two platforms as well as train-related services. In general, the final arrival station of a duty has to equal the departure station of the first trip of a duty. Furthermore, the number of conductors (and thereby duties) starting at each crew base can be limited.

Legal requirements and regulations from labor contracts form the second group of conditions. According to German law three types of working time have to be distinguished: First, the *duty time* is the whole time from beginning to end of a duty, starting with signing up and ending with signing off at a crew base. Second, the *protected working time* specifies the duty time less all breaks, idle times and deadhead times. Finally, the *paid time* corresponds to the duty time without break times. Table 6.1 presents a selection of common requirements. On the one hand, the maximum duty time as well as the maximum protected working time is regulated by law, while, on the other hand, a minimum paid time of a duty can be demanded. In order to ensure that conductors can fulfill their weekly working time generally within five workdays, the average paid time or average working time of all duties has to be restricted between certain upper and lower bounds. Besides, rest periods within each duty have to follow various regulations. The required break time is dependent on the protected working time of a duty and can differ between two hours for duties with more than 12 hours duty time and none for duties with less than 6 hours protected working time. Breaks might be split into several parts, however, should not be placed in the beginning or at the end of a duty. In general, breaks can only be planned at stations where an appropriate infrastructure is available, such as break rooms or sanitary installations. Apart from legal requirements, individual regulations may exist within each company.

The last group of requirements are claims under the transportation contract of the specific transport network. Among others, such as the frequency of trips and the type of vehicles, this contract regulates attendance rates, that can be dependent on product types, lines, train numbers, track sections or time windows. Usually, attendance rates range between 0% (i. e. no conductor is necessary) and 100%, which means that trips always have to be accompanied by a conductor. Attendance rates are defined as the percentage of kilometers of all trips with a common rate that have to be covered by

Table 6.1: Legal and contractual requirements concerning duties

duty time	<ul style="list-style-type: none"> • maximum duty time
paid time	<ul style="list-style-type: none"> • minimum paid time of a duty • average paid time of all duties
protected working time	<ul style="list-style-type: none"> • maximum protected working time • average protected working time of a crew schedule
break times	<ul style="list-style-type: none"> • protected working time up to 6 h: no break • protected working time more than 6 h and up to 9 h: total break time 30 min • protected working time more than 9 h: total break time 45 min • duty time more than 12 h: one non-interrupted break of 120 min • minimum non-interrupted break time: 15 min • maximum working time without break: 6 h • no breaks at beginning and end of the duty (e.g. 2 h duty time) • breaks are only allowed at stations with break rooms • small idle times up to 5 min are counted as working time

conductors. If these attendance rates are not satisfied the railway company is penalized. Despite an attendance rate of $q < 100\%$ for certain trips, in some cases for these trips still a conductor can be mandatory. This may be caused by technical requirements of the employed vehicles, but can be a requirement of the transportation contract, too. Furthermore, a uniform distribution of the attended trips over the planning period can be claimed in order to avoid a predictable or imbalanced appearance of conductors on trains. Usually, a definition of a uniform distribution is used stating that each trip has to be conducted at least once within a period of two weeks. Hence, the planning horizon for the crew scheduling problem is usually set to 14 days. The goal is to find a schedule satisfying all operating conditions and legal requirements at minimal costs. This schedule should cover a subset of all trips such that different attendance rates, specified in the transportation contract, are met.

6.3.3 Problem formulation

Before the optimization can be started, the problem described previously has to be formulated mathematically, which represents the second step within the analysis stage. Often, the crew scheduling problem is modeled as set covering problem. Based on the basic set covering model and its extension integrating attendance rates for a single day (HOFFMANN (2017)), a mixed integer linear programming model is presented, that allows the integration of all requirements mentioned above and covers a planning horizon of

Table 6.2: Sets, decision variables and parameters used

N	set of all duties j
N_k	subset of N with all duties j on day k
M	set of all trips i
M_k	subset of M with all trips i valid on day k
K	set of all days k of the planning horizon
G	set of all attendance rates g
O	set of mandatory trips i on day k as pair (i, k)
E	set of all crew bases e
c_j	costs of duty j
d_{ig}	distance of unique trip i that has to be attended with rate g
q_g	attendance rate g
a_{ij}	assignment parameter, 1 if duty j covers trip i , 0 otherwise
t_j	paid time of duty j
$t^{\min}$	minimum average paid time of all duties
$t^{\max}$	maximum average paid time of all duties
b_{je}	assignment parameter, 1 if duty j starts at crew base e , 0 otherwise
C_e	maximum number of duties starting at crew base e
x_j	binary variable, 1 if duty j is in solution, 0 otherwise
y_{ik}	binary variable, 1 if trip i on day k is in solution, 0 otherwise

several days $k \in K$. All relevant sets, parameters and decision variables are presented in Table 6.2. Each trip $i \in M$ can exist on a single day only or on several days of the planning horizon. Let M be a set of all trips in the considered transport network and N a set of feasible duties. N_k defines a subset of N , containing all duties on a certain day k of the planning horizon with $N = \bigcup_{k \in K} N_k$. Likewise, M_k represents a subset of M , with $M = \bigcup_{k \in K} M_k$. Each duty $j \in N$ is represented by one column in matrix $A \in \{0, 1\}^{|M| \times |N|}$ with $a_{ij} = 1$ if duty $j \in N$ covers trip $i \in M$, 0 otherwise. Parameter c_j displays the costs of duty $j \in N$, that can consist of fixed costs per duty, costs per minute of paid time or penalty costs e.g. for night shifts. Let x_j be a binary decision variable such that $x_j = 1$, if duty j is part of the solution schedule, 0 otherwise. A second type of decision variables y_{ik} is 1 if trip $i \in M$ is attended on day k in the solution schedule. With G representing a set of all attendance rates $q_g \in [0, 1]$ defined in the transportation contract, let d_{ig} be the distance of trip $i \in M$ with attendance rate $g \in G$. Note that the index g is necessary since one trip may consist of several segments with differing attendance rates. As the distance of a trip i is equal on each day, index k can be omitted.

To model additional constraints like the average working time and capacity of crew bases, the paid time t_j of duty $j \in N$ as well as the minimum and maximum average paid time $t^{\min}$ and $t^{\max}$ are required. Furthermore, let E be the set of crew bases and

b_{je} the assignment parameter with $b_{je} = 1$ if duty $j \in N$ is assigned to crew base $e \in E$, 0 otherwise. Each crew base $e \in E$ may have a limited daily number of duties C_e (i. e. conductors) that can start at this base. The set O contains a pair of trip $i \in M$ and day $k \in K$, if i is mandatory on k regardless of the attendance rate.

$$\text{MCSPAR: } \min \sum_{j \in N} c_j x_j \quad (6.1)$$

$$\text{s.t. } \sum_{k \in K} \sum_{i \in M_k} d_{ig} y_{ik} \geq q_g \sum_{k \in K} \sum_{i \in M_k} d_{ig} \quad \forall g \in G \quad (6.2)$$

$$\sum_{j \in N_k} a_{ij} x_j \geq y_{ik} \quad \forall k \in K, i \in M_k \quad (6.3)$$

$$y_{ik} \geq a_{ij} x_j \quad \forall k \in K, j \in N_k, i \in M_k, \quad (6.4)$$

$$\sum_{j \in N} t_j x_j \geq t^{\min} \sum_{j \in N} x_j \quad (6.5)$$

$$\sum_{j \in N} t_j x_j \leq t^{\max} \sum_{j \in N} x_j \quad (6.6)$$

$$\sum_{k \in K: i \in M_k} y_{ik} \geq 1 \quad \forall i \in M \quad (6.7)$$

$$y_{ik} = 1 \quad \forall (i, k) \in O \quad (6.8)$$

$$\sum_{j \in N_k} b_{je} x_j \leq C_e \quad \forall e \in E, k \in K \quad (6.9)$$

$$x_j \in \{0, 1\} \quad \forall j \in N \quad (6.10)$$

$$y_{ik} \in \{0, 1\} \quad \forall k \in K, i \in M_k. \quad (6.11)$$

The objective function (6.1) minimizes the total costs over all duties. Constraints (6.2) guarantee that the accumulated distance of the covered trips in the solution schedule is greater or equal than the requested percentage of the total distance assigned to the special attendance rate. Constraints (6.3) and (6.4) are linking constraints for the x_j and y_{ik} variables. On the one hand, there has to be a duty $j \in N_k$ in the solution schedule that covers trip i ($a_{ikj} = 1$) if trip i on day k is in the solution (Constraints (6.3)). Because of the inequality deadheads are possible. On the other hand, each trip i that is covered by a duty j (i. e. each trip with $a_{ikj} = 1$) has to be part of the solution if this duty is part of the solution schedule (Constraints (6.4)). Constraints (6.5) and (6.6) ensure that the average paid time in the final schedule is between the minimum and maximum average paid working time. A uniform distribution of covered trips, i. e. that all trips are covered at least once in the planning horizon, is modeled by Constraints (6.7), while Constraints (6.8) guarantee that all mandatory trips are in the final schedule. In Constraints (6.9) the number of duties starting at crew base $e \in E$ is limited to the crew bases' capacity

C_e on each day.

The proposed MCSPAR can be simplified without changing its generality by omitting the second set of linking Constraints (6.4). Since the objective function is not dependent on the variables y_{ik} and Constraints (6.3) ensure that each variable y_{ik} is set 1 if the corresponding trip is necessary for fulfilling the attendance rate, this does not change the objective value and the optimal solution. However, if a required attendance rate g is exceeded by the solution schedule, variables y_{ik} can no longer be interpreted as existence of trip i on day k in the solution schedule. In using this simplification the solution process of this model can be sped up significantly. Hence, Restrictions (6.4) are not considered in the following. Since the MCSPAR is an extension of the set covering problem, the MCSPAR is NP-hard as well.

6.4 Solution approaches for the MCSPAR

6.4.1 A multi-period column generation algorithm

In our case real decision support can be provided only, if the crew scheduling problem is solved for real-world instances. Therefore, the development of efficient solution algorithms is a crucial step within the analysis stage. One trivial solution approach for solving MCSPAR to optimality is composed of two sequential steps: first, the set N of all feasible duties is generated and, afterwards, the set-covering formulation presented above is solved using N . However, this is not viable for practical problem sizes since the cardinality of N easily reaches several billions. Hence, finding all duties and solving MCSPAR afterwards is enormously demanding with respect to memory usage and computation time.

Therefore, a different solution procedure is necessary to obtain duty schedules for a planning horizon of up to two weeks in a fast and efficient manner. As mentioned in Section 6.2, column generation is a well known and widely used method to solve crew scheduling problems and, thus, is considered as a useful instrument. For this purpose, MCSPAR is decomposed into two iteratively connected problems. The first part is the restricted master problem (RMP) as linear relaxation of MCSPAR with just a small subset N' of all feasible duties. Please note, that the upper bound on variables x_j , which could either lead to basic variables with negative reduced costs or extra constraints depending on the modeling approach, can be omitted during solving the RMP. This follows directly from the direction of optimization. Secondly, a pricing problem (PP) is needed to generate new feasible duties which could improve the current solution. Since we are dealing with multiple but independent days (all duties contain trips of one day solely), we have a single PP for each day k . To cope with that property, a cyclic

generation strategy introduced in MOURGAYA/VANDERBECK (2007) for a multi-period vehicle routing problem is adapted. The resulting general solution procedure as well as the interaction between RMP and PP are shown in Figure 6.2 and will be explained in greater detail hereinafter.

Figure 6.2: Flowchart of proposed multi-period column generation algorithm

Starting point of the column generation algorithm is a *feasible initial schedule* N_0 . In order to produce such a set of duties, a block generation approach with depth-first search is applied. The generator builds duty blocks with given minimum and maximum duration as well as maximum transition time for each trip starting at a crew base. Moreover, the size of N_0 can be adjusted by a limit on the number of subsequent trips and symmetry of blocks can be demanded. To reduce computation time, the maximum duration of a block is limited to values below the minimum average working time. Hence, the block generator yields highly productive but short blocks, which do not guarantee feasibility of N_0 with respect to Constraints (6.5). Thus, a supplementary preprocessing procedure is necessary. There, a sufficient amount of random blocks with the same crew base is matched to create feasible duties with required breaks at junctures.

After initialization of the schedule, the RMP is solved to optimality for the first time. Subsequently, the dual values of Constraints (6.3), (6.5), (6.6) and (6.9) are used in the PP to obtain new duties with negative reduced costs for the first day (see Section 6.4.2). If such duties can be found, they are added to the RMP. As unique trips can occur on various days, it is expedient in terms of computational efficiency to check whether some of the generated duties are feasible and have negative reduced costs on other days and if so, add them as well. In case that no new duties are generated, the counter for days without new duties i is increased by one. Afterwards, the current day k is updated according to $k = (k + 1) \bmod |K|$. Here, the modulo operation is required in order to return to the first day of the planning horizon after the last day is reached. The procedure is repeated until no more duties with negative reduced costs are generated during one iteration of the entire planning horizon, i. e., $i = |K|$. Finally, the relaxation of the decision variables is omitted and the resulting integer programming model is solved.

6.4.2 Solving the pricing problem

Finding new columns (duties) with negative reduced costs, i. e., solving the pricing problem, is a crucial and challenging part in every column generation algorithm. As mentioned previously, we have $|K|$ different PP. Let $\pi_{ik}, i \in M_k$, be the dual value of Constraints (6.3), ρ_1 and ρ_2 of (6.5) resp. (6.6) and $\sigma_e, e \in E$, of (6.9) then

$$\bar{c}_j = c_j - \sum_{i \in M} a_{ij} \pi_{ik} - (t_j - t^{\min}) \cdot \rho_1 - (t^{\max} - t_j) \cdot \rho_2 + \sum_{e \in E} b_{je} \sigma_e \quad (6.12)$$

specifies the reduced costs of duty $j \in N_k$. In addition to negative reduced costs, a new duty has to fulfill the legal and contractual requirements described in Section 6.3.2. This makes the PP an optimization problem itself with (6.12) as the objective function to minimize and the requirements as constraints.

According to IRNICH/DESAULNIERS (2005), subproblems arising in crew scheduling or vehicle routing applications commonly correspond to a shortest path problem with resource constraints (SPPRC) or one of its variants. However, this approach is not viable for the present subproblem due to a lack of good dominance criteria to eliminate labels. The same challenge has been observed by ALBERS (2009) for a similar subproblem in crew scheduling for freight train drivers. Even though ALBERS (2009) was able to solve the subproblem as SPPRC, it has to be noted that trips in freight railway crew scheduling are quite long and hence, feasible duties consist of only four to six trips on average. In contrast, duties of conductors can comprise easily 15 to 20 trips. Therefore, the propagation of all labels generated would be too demanding in terms of memory and time. This leads to the usage of a heuristic solution approach, which can yield

various duties at once for large problem sizes in fast computation times. Moreover, newly arising practical requirements are easy to integrate. For these reasons, we apply a genetic algorithm to generate new duties.

Algorithm 6.1 Genetic algorithm

```

1: evaluate all duties with reduced costs (6.12)
2: for  $i \leftarrow 1$ ,  $i \leq \text{generSize}$  do
3:   select best popSize individuals out of duty pool
4:   create individuals of next generation by crossover and mutation
5:   for all  $j \in$  new duties do
6:     calculate reduced costs  $\bar{c}_j$  with (6.12)
7:     if  $\bar{c}_j < 0$  then
8:       add duty  $j$  to duty pool
9:     end if
10:  end for
11:   $i++$ 
12: end for

```

Genetic algorithms are optimization methods based on the concept of natural evolution and are used in a vast number of different research areas. We refer to HAUPT/HAUPT (2004) for further information on this topic. The general procedure of our genetic algorithm is shown in Algorithm 6.1. In our implementation the duties are represented by *individuals*. Each individual consists of a string of trips sorted by increasing departure time. Therefore, the value of a gene can range from 0 to $|M|$. The *fitness* of an individual equals the reduced costs of a duty presented in (6.12). Every iteration of the subproblem begins with the set of all duties available at this point - regardless whether these are part of the initial schedule or have been created in previous iterations. The best **popSize** individuals of this set are picked to populate the *initial population* and to start the genetic algorithm. In the next step, new duties are generated by a *one-point crossover*. Since new duties have to be feasible concerning time, space and symmetry, a special four-stage crossover operator is implemented. First, an individual is selected randomly from the current population. To fulfill the symmetry aspect, another duty starting and ending at the same crew base is chosen from the remaining individuals subsequently. In the third stage, the cut point of the first parent is randomly set and, finally, a suitable cut point for the second parent has to be determined. Possible cut points are examined in random order concerning, on the one hand, matching stations and, on the other hand, compatibility of arrival and departure times. The latter includes required walks or different types of train-related services if a change of trains is executed. In case of a positive result of this check, all trips located right of the cut points swap places. Still, it is not guaranteed that a proper cut point is found. If a crossover is not possible, missing offspring are substituted by their parents. An example of the described

crossover procedure is depicted in Fig. 6.3. Parent 1 is chosen randomly out of all duties. Afterwards, parent 2 is selected from the subset of all duties starting and ending at relief point A to ensure symmetry. Subsequently, cut point 1 at station C is randomly determined. Next, in parent 2 a trip departing at C after the arrival of the trip from D to C in duty one is sought. Since there is only one feasible trip, cut point 2 can be easily set. After that, all trips starting after cut point 1 in parent 1 swap places with all trips starting after cut point 2 in parent 2, generating offspring 1 and 2. Note that offspring 2 could be infeasible if trip C to B in duty one would depart earlier than trip B to C in duty two would arrive. In this case, offspring 2 would be substituted by parent 2. After the crossover a *mutation operator* is used to slightly modify resulting duties by replacing a random trip by another spatial and temporal suitable one. Since it can often difficult to find similar trips, the mutation operator is most successful at exchanging the first or last trip. Eventually, the next generation is composed of all generated duties without duplicates and the best old individuals not included in the former set. New generations are created until the maximum number of generations per iteration of the subproblem `generSize` is reached.

Figure 6.3: One-point crossover

Since we apply a purely heuristical solution approach to the subproblem, we cannot obtain a valid lower bound for MCSPAR. However, we are able to provide good solutions within reasonable time.

6.5 Artifact evaluation

6.5.1 Considered transport networks and experimental design

The method described in Section 6.4, was implemented as a prototype using a three-tier architecture in order to offer a number of different crew-scheduling planners the chance to benefit from the decision support. According to HEVNER et al. (2004) the developed artifact should be exercised within appropriate environments. Following this recommendation a case study was conducted for three real-world transport networks in order to test the applicability and effectiveness of the MCSAPR model and solution approach. The results offer insights as distinct recommendations for deploying conductors are given. The results can be transformed directly into action.

With between 2.8 and 5.6 million train kilometers per year the considered instances represent networks of regular size for regional transport. However, dependent on the number of trips as well as their structure the resulting MCSPAR show considerable differences: while Network I is more branched, Network II and Network III contain circular subnets, which lead to a large number of possible duties and, hence, are more difficult to solve. Relevant data and the general structures of the networks are depicted in Figure 6.4.

The given attendance rates vary depending on the considered network: In Network I the attendance rate is predefined with 30% during the day. For trips after 7 p.m. until close of operations an attendance rate of 90% has to be realized. This is the case for about 13.2% of all trips. For all trips a uniform distribution over the planning horizon is demanded, that means within 14 days all unique trips $i \in M$ have to be attended at least on one day $k \in K$. Network II also has an attendance rate of 25% during the day. For trips after 7 p.m., however, all trips have to be covered by a conductor, which equals an attendance rate of 100% (13.8% of all trips). Again, a uniform distribution over the planning horizon is demanded. In Network III only a certain route, containing 21.7% of all trips, has to be covered with an attendance rate of 100%. All other trips have an attendance rate of 25%. However, for about 10% of trips with a rate of 25% a conductor is mandatory because of a stipulation in the transportation contract.

According to valid requirements for all networks the maximum duty time (640 min), maximum working time (600 min), minimum paid time (300 min) and average paid time ($\in [418, 512]$ min) are given. The objective function is predetermined by fixed costs of 2,000 per duty and costs of 50 per minute of paid time.

The MCSPAR can be considered as a design alternative (see SIMON (1996)), that should be evaluated against the CSPAR model proposed by HOFFMANN (2017), solving each day individually with the column generation approach. In total four solutions

Figure 6.4: Structure and size of the considered regional transport networks

for each of the considered networks were taken into account: First, the CSPAR model was used. All generated daily schedules were merged to a joint schedule for the whole planning horizon. The respective objective values as well as computation times were summed up in order to evaluate this schedule. As in this approach the uniform distribution cannot be integrated, this restriction was omitted in the first place. Second, the algorithm presented in Section 6.4 solving the MCSPAR was applied. Again, the uniform distribution was not regarded. A comparison of these two solutions allows an evaluation of the multi-period approach.

In addition, the given transport network was solved integrating the uniform distribution into the MCSPAR, denoted as $\text{MCSPAR}_{\text{uni}}$. Finally, the gained schedule was compared to a conventional approach. Since the requirement of a uniform distribution as well as attendance rates themselves cannot be modeled easily by existing planning approaches, a conventional strategy in practice is to split all trips of a transport network into subsets according to the attendance rates. All trips with a certain attendance rate are planned separately for the considered planning horizon as regular crew scheduling problem with a rate of 100%. For all subsets g of trips with rates $q_g < 100\%$ the resulting schedule is split into $\frac{1}{q_g}$ sub-schedules, which are spread over $\frac{1}{q_g}$ weeks. This guarantees that, on the one hand, all trips are covered at least once within the planning horizon and, on the other hand, that each attendance rate q_g is gained. This means that, for example, all trips with an attendance rate of 25% are scheduled with an attendance rate of 100%. Afterwards, one fourth of these duties is assigned to each week of the planning horizon. The final schedule is obtained by combining the gained schedules with different rates. Of course, this approach does not lead to the best duties possible, since suitable trips

with differing attendance rates cannot be planned together in one duty. Nevertheless, it serves as a reference solution for $\text{MCSPAR}_{\text{uni}}$.

Due to the complexity and size of the MCSPAR with a planning horizon of 14 days, the computation time for column generation was limited to 6 hours. After this timespan the current iteration was completed by still considering all remaining days. The final solution of the integer programming model is terminated after 3 hours at the latest. Hence, the maximum total computation time for the proposed algorithm is about 9 hours (32,400 seconds). Since the generated schedule is designated for tactical planning, these computation times are reasonable for application in practice. Each algorithm was run ten times due to the random influence of genetic algorithms. The hybrid solution approach was coded in C# programming language, using Gurobi 6.5 interface to model and solve LP and ILP models. All tests were run on a Intel(R) Xenon(R) CPU E5-4627 with 3.3 GHz clock speed and 768 GB RAM. The maximum of parallel threads used by Gurobi was limited to 4 while the genetic algorithm was run on a single core only.

6.5.2 Evaluation and comparison of algorithms

The results of the tested solution approaches are displayed in Table 6.3. For all ten test runs the minimum, maximum, median and average objective function values as well as computation times t_{CPU} are presented. Δ_{Obj} shows the percentage deviation of the solution gained by the MCSPAR approach without a uniform distribution compared to the respective CSPAR solution. It can be seen that the MCSPAR approach leads to an average improvement of between 2.14% for Network III and 4.72% for Network II compared to the optimization on a daily basis. This shows the advantageousness of an integrated planning of the whole planning horizon. The reason for this is that attendance rates do not have to be fulfilled on every single day but can be compensated by covering additional trips on other days. Regardless the considered solution approach between 5-6% (Network I) and about 11% (Network III) of the objective value is caused by fixed costs per duty and the major share is induced by costs per minute of paid time. This is reasonable since the costs for paid time correspond directly to the actual personnel expenses. Thus, the gained improvement leads to significant cost reduction for the railway company.

Beside these improvements of solution quality, the MCSPAR allows an integration of the uniform distribution. It can be seen that this additional requirement results in an average objective function value of 5,298,200 compared to 4,829,305 (Network I) without a uniform distribution, 3,101,345 compared to 2,759,750 (Network II) and 4,172,920 compared to 3,696,255 (Network III), which equals an increase of about 9.8%, 12.4% and 12.9% respectively. The reason for this is that trips, that can be covered by unfavorable

Table 6.3: Computational results for Transport Networks I and II

Transport Network I							
	CSPAR		MCSPAR			MCSPAR _{uni}	
	Obj.	t_{CPU}	Obj.	Δ_{Obj}	t_{CPU}	Obj.	t_{CPU}
Min.	4,926,200	826	4,800,850	-2.54%	15,154	5,273,450	32,469
Max.	4,965,900	1,266	4,851,100	-2.31%	20,237	5,317,000	32,691
Median	4,944,850	897	4,830,625	-2.31%	17,302	5,297,375	32,515
Ave.	4,944,530	955	4,829,305	-2.33%	17,764	5,298,200	32,539

Transport Network II							
	CSPAR		MCSPAR			MCSPAR _{uni}	
	Obj.	t_{CPU}	Obj.	Δ_{Obj}	t_{CPU}	Obj.	t_{CPU}
Min.	2,880,300	1,268	2,748,750	-4.57%	22,623	3,059,000	25,779
Max.	2,941,000	2,648	2,776,150	-5.61%	32,778	3,151,000	32,846
Median	2,885,200	1,456	2,758,900	-4.38%	32,601	3,105,000	30,627
Ave.	2,896,590	1,568	2,759,750	-4.72%	31,626	3,101,345	30,385

Transport Network III							
	CSPAR		MCSPAR			MCSPAR _{uni}	
	Obj.	t_{CPU}	Obj.	Δ_{Obj}	t_{CPU}	Obj.	t_{CPU}
Min.	3,744,500	1,684	3,671,400	-1.95%	21,944	4,132,950	32,556
Max.	3,827,900	2,708	3,716,050	-2.92%	32,572	4,236,700	33,280
Median	3,771,450	1,939	3,696,925	-1.98%	23,908	4,177,050	32,634
Ave.	3,777,000	2,079	3,696,255	-2.14%	26,091	4,172,920	32,728

Note: computation time t_{CPU} in seconds.

duties only, still have to be attended at least once, even if the attendance rate is smaller than 100%. Adding the constraints leads to a more complex problem that is difficult to solve. By termination of the algorithms the gap between the lower bound and the best solution found by Gurobi was always below 0.25% for all three networks solving MCSPAR. For MCSPAR_{uni} the gap averaged at 1.39% with a maximum gap of 3.38% (Network II).

In order to evaluate the quality of this solution, it can be compared to the conventional approach integrating a uniform distribution by scheduling all trips separately according to their attendance rate. For the studied transport networks this planning strategy led to an objective value of 8,170,890 (Network I), 4,795,500 (Network II) and 4,940,625 (Network III), i. e. that the integrated approach of the MCSPAR_{uni} averages at decreases of 35.2%, 35.3% and 15.5%. This substantial improvement is caused by two effects: First, an integrated planning of trips with different attendance rates enables the exploitation of synergy effects between these, so that mixed duties can be much more efficient compared

to those in separated schedules. Second, the conventional approach plans trips with a rate of 25% (or 30% and 90% respectively) as if they had a rate of 100%. This means that each trip has to be covered on every day, even if this is possible in unfavorable duties only. In contrast, the $\text{MSCPAR}_{\text{uni}}$ allows to schedule these trip on one day only, which is sufficient for the condition of a uniform distribution. Even though both approaches result in an equal fulfillment of attendance rates, the $\text{MCSPAR}_{\text{uni}}$ is able to identify more efficient duties. This emphasizes the great benefit of the MCSPAR, particularly if a uniform distribution is stipulated. Moreover, with between 0.7% and 2.9% the spread of the maximum and minimum objective value is very low for all tested algorithms, which means that the proposed solution approaches are very robust.

However, this improvement is gained at the cost of a major increase of computational effort. While the daily solution of the CSPAR sums up to total computation times of 897 s (median Network I), 1,456 s (median Network II) and 1,939 s (median Network III), the solution of the MCSPAR requires at least 15,154 s (Network I). The distribution of computation time among the different stages of the algorithm is similar for all solved instances and is exemplified for Network III in Table 6.4. It can be seen that for the CSPAR the major share of time is required for the column generation stage. The integer programming model on a daily basis remains rather simple to solve. For each run of the MCSPAR and $\text{MCSPAR}_{\text{uni}}$ column generation even demanded the entire time limit. Only if a uniform distribution of trips is integrated, the time limit for the integer solution is reached. This proves the increase of complexity of the model by this additional requirement. Nevertheless, in the light of significant cost reductions and the planning level of tactical planning these computation times are acceptable in practice.

Table 6.4: Analysis of average computation times for Network III

Ave. t_{CPU} [sec.]	Time limit	CSPAR	MCSPAR	$\text{MCSPAR}_{\text{uni}}$
Column generation	21,600	1,999	21,760*	21,797*
Integer solution	10,800	80	4,331	10,931*
Total	32,400	2,079	26,091	32,728*

* Values exceed time limit due to completion of current iteration.

6.6 Conclusions and further research

In this paper, the process-oriented version of business analytics was applied to solve the multi-period model for crew scheduling problems with variable attendance rates. Beside the consideration of attendance rates, that are of increasing importance in German regional transport networks, for the first time several real-world requirements have been

integrated, such as a uniform distribution of trips over the planning horizon and mandatory trips. The proposed hybrid column generation algorithm was proven to be adequate for solving practical problems in regional rail transport by a case study. Within reasonable computation times for the tactical planning, schedules for conductors generated by conventional solution approach could be improved significantly, resulting in considerable reductions of personnel costs.

Nevertheless, this work still leaves interesting directions for future research. The presented algorithm may be improved by several adjustments. First, alternative methods for generating the initial solution should be tested. Second, during the column generation procedure unfavorable duties, that are not part of the solution for several iterations, may be removed from the restricted master problem in order to increase efficiency of the algorithm. Furthermore, testing variations of the genetic algorithm, with e.g. differing crossover or mutation operators as well as other termination conditions, may improve the algorithms performance. Finally, scalability of the MCSPAR approach should be tested for more large instances.

7 Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates

Abstract

Crew scheduling in regional rail transport consists of generating crew duties for train operators and conductors. We focus on the latter, because in the last few years we can observe the development that just a certain percentage of trains has to be attended. The goal is to minimize crew costs while satisfying operating conditions and legal requirements. Due to the size of real-world instances these problems are typically solved with column generation techniques based on path flow models. In contrast, we present an arc flow model for the railway crew scheduling problem with attendance rates to solve small-sized instances optimally, improve solutions of real-world instances and provide good lower bounds for them. Valid inequalities offer the possibility to fasten the solution process and improve the bound of the linear relaxation of the integer problem. We define various valid inequalities and perform computational tests to estimate the influence of different valid inequalities on computation times and bounds of the linear relaxation.

Reference

Published paper: HOFFMANN, K./BUSCHER, U. (2019): Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates. In: *Computers & Industrial Engineering*, Vol. 127.

7.1 Introduction

DB Regio AG, subsidiary of Deutsche Bahn (the biggest German railway operator), operates passenger trains on short and medium distances in Germany. Besides purchased services, like the use of infrastructure, cleaning, security and winter services (2,946m EUR), personnel costs (988m EUR) represent the largest cost factor, followed by maintenance costs (796m EUR) and energy costs (483m EUR) (see annual report DB REGIO AG (2016b)). Often purchased costs cannot be influenced by the company, so that the reduction of personnel costs can help to increase the corporate success. Furthermore, planners often cope with the task of crew scheduling manually, without support of automated planning tools. An intelligent and automated planning system offers the chance to prevent overload and staff shortage.

In Germany, the responsibility for regional passenger rail transport lies with the federal states. In some cases federal states delegate this task to subsidiary transport associations. The general structure of the planning process is illustrated in Figure 7.1. On the basis of predicted travel demand responsible planners design lines, group them to different transportation networks and specify the frequencies of trains that run on different lines (see CAPRARA et al. (2007)). Thereafter, the timetabling process starts defining departure and arrival times at each track section and station.

Figure 7.1: Planning process

All these requirements are summarized in public tender lots for which railway companies can submit an offer. For being successful, this offer has to be cost-efficient. Winning the tender, railway companies start their own planning procedure (dark coloring in Figure 7.1). First, the required type and capacity of the rolling stock units is determined. The main task is assigning unspecified trains to the train journeys defined in the timetable in a conflict-free way considering resource efficiency. Closely related to the previous step is the maintenance planning, where services like refueling, cleaning and vehicle repair are included. The final planning stage is the crew scheduling problem focused in this paper and described in detail later. All planning steps performed by the railway company will be refined during the planning process. After rolling stock scheduling, vehicle rotations are assigned to specific trains fulfilling operational and contractual requirements (rolling stock circulation). Operational planning includes short-term changes, for example relating to construction sites, bad weather or vehicle breakdown (vehicle disposition). The crew scheduling process can be refined in an equivalent way.

While crew rostering describes the assignment of duties to individuals, crew disposition manages unpredictable or short-term changes like sickness notifications or operational interruptions.

In regional rail transport, crew members are train drivers (operator of the train) and conductors (accompanying the train to control tickets and provide other customer services). This paper focuses on the latter, but the model can be transferred to train drivers with some modifications and attendance rates of 100%. The goal of the crew scheduling process is to build duties and shift schedules that cover all or, in our case, a part of the train journeys given in the timetable. Train journeys are characterized by fixed departure times, arrival times, departure stations as well as arrival stations and additional information, e.g. characteristics (tunnels). Along these train journeys there are some stations where conductors may change trains, so called relief points. Thus, train journeys are split into a sequence of unique trips, defined as a segment between two consecutive relief points which must be serviced by the same conductor. Combining unique trips leads to a duty containing signing on and off, walks, deadheads, operational tasks and breaks. Such duties have to fulfill operational and legal requirements, described in more detail later. The crew scheduling process results in a shift schedule, containing all duties that cover all required trips of the considered transportation network.

For solving real-world instances with up to 1,000 unique trips per day and finding low cost shift schedules satisfying all underlying requirements we need heuristic or meta-heuristic solution approaches. In contrast, the intention of this paper is an exact model of the railway crew scheduling problem with attendance rates. We can use it to solve small-sized instances optimally, provide good lower bounds for real-world instances and improve heuristic solutions of large instances. The exact model is solved by the mathematical programming solver Gurobi. Other approaches use dynamic optimization, but this is not applicable to our model because there are no good dominance criteria for eliminating paths.

The paper is organized as follows: A brief overview of related literature is provided in Section 7.2. Section 7.3 describes the considered problem with a selection of practical requirements. Main focus of this paper is the arc flow formulation of the problem defined in Section 7.4. Moreover, the graph construction step is described in detail. Afterwards, a selection of problem specific valid inequalities is presented in Section 7.5. Section 7.6 reports the influence of valid inequalities on computation times and bounds of the linear relaxation by the means of instances of different size. Finally, Section 7.7 summarizes the results and provides directions for future research.

7.2 Related work

Column generation (CG) is the most commonly used technique to solve crew scheduling problems. The problem modeled as path flow formulation is split into the restricted master problem (RMP) and the pricing problem (PP). The former represents the original problem only with a small set of duties. The latter generates new duties (columns) reducing the objective value of the RMP. Often, the duty generation is based on a structured network used in the arc flow formulation. Therefore, we discuss a choice of literature on CG in different transport sectors.

Already in 1969, ARABEYRE et al. (1969) gave an survey of the airline crew scheduling problem. More recent reviews are BARNHART et al. (2003) and GOPALAKRISHNAN/JOHNSON (2005). The airline crew scheduling problem is often based on a flight graph, where nodes represent flight legs and arcs are possible connections between these flight legs. VANCE et al. (1997) present a branch-and-price algorithm modeling the pricing problem (PP) as shortest-path problem in the flight graph and solve it with a labeling algorithm. OZDEMIR/MOHAN (2001) solve the flow problem with a genetic algorithm. Among other solution approaches AYDEMIR-KARADAG/DENGIZ/BOLAT (2013) present a CG approach modeling the RMP as set covering problem and solving the PP as shortest-path problem on the flight graph.

Another area of application is urban mass transit like bus driver scheduling. DESROCHERS/SOUMIS (1989) use CG and model the PP as shortest-path problem with resource constraints, which is solved by a dynamic programming algorithm. A hybrid CG approach using a genetic algorithm and a greedy randomized adaptive search procedure (GRASP) to solve the PP is presented by DOS SANTOS/MATEUS (2007) and DOS SANTOS/MATEUS (2009). They combine the heuristic solution with an exact integer programming approach that models the PP as a shortest-path problem with resource constraints to guarantee optimality. The different solution methods are applied to instances of the OR-library and real data from a bus crew scheduling problem.

Research in the field of railway crew scheduling is based on developments in airline crew scheduling. Often, the sequence of train journeys or trips is modeled in a graph. An algorithm formerly used by Deutsche Bahn is presented in BENGTTSSON et al. (2007). They develop a CG approach with k -shortest-path enumeration solving the PP. Here, the network consists of blocks (partial pairings), not single trips. NISHI/MUROI/INUIGUCHI (2011) use dual inequalities to improve convergence of CG and reduce the number of replications. Scheduling of train drivers in rail freight transport is discussed in JÜTTE (2012) and JÜTTE/THONEMANN (2015). They use a resource-constrained shortest-path algorithm and combine it with a label-pulling process. For solving large-scale problems a graph partitioning strategy is introduced. HOFFMANN et al. (2017) present a hybrid

column generation approach for conductor scheduling with attendance rates which solves the pricing problem by means of a genetic algorithm.

STEINZEN et al. (2010) try to integrate the vehicle and crew scheduling problem with multiple depots. The model is based on a time-space-network solved by CG with Lagrangian relaxation (branch-and-price). The PP is modeled as resource-constrained shortest-path problem. An integrated airline scheduling problem is studied in CACCHIANI/SALAZAR-GONZÁLEZ (2017). There fleet assignment, aircraft routing and crew pairing are formulated as both path-path and arc-path model. They present two exact solution approaches solving the linear programming relaxation by column generation (lower bound), generating an upper bound by a heuristic solution and, finally, computing the optimal solution making use of these bounds.

Crew scheduling for conductors is similar to the vehicle routing problem (VRP). Conductors are equivalent to the vehicles visiting customers in a certain order; the unique trips can be interpreted as customers. If each unique trip has to be attended by a conductor (attendance rate of 100%) the crew scheduling problems corresponds to the VRP with additional constraints related to operating and legal requirements. For lower attendance rates the VRP has to be modified. LAPORTE/NOBERT (1987) and LAPORTE (1992) present a survey of exact and approximate algorithms for the VRP. For further details see GOLDEN/RAGHAVAN/WASIL (2008) and TOTH/VIGO (2014). Vehicle routing problems with multiple depots are main focus of the survey of MONTROYA-TORRES et al. (2015). KALLEHAUGE et al. (2005) present a model for vehicle routing problems with time windows. The model is solved by branch-and-price methods and acceleration strategies. For multiple depots GUEDES/BORENSTEIN (2015) introduce a heuristic framework, combining time-space-network, column generation and state space reduction.

We also want to mention some literature on shortest-path problems with resource constraints, because the solution procedure is one possibility to solve the PP. BEASLEY/CHRISTOFIDES (1989) discuss the Lagrangean relaxation of the integer programming formulation and use a tree search procedure. A survey of exact solution approaches is presented in PUGLIESE/GUERRIERO (2013).

7.3 Problem description and practical requirements

In order to plan crews in rail passenger transport in Germany, railway companies have to fulfill a various range of requirements. First of all, operating conditions organize the structure of duties. Duties have to be symmetric, i.e. they have to start and end at the same crew base. Two consecutive trips contained in the same duty have to be

compatible, i.e. the first trip has to arrive at the same station as the second trip departs and there has to be enough time between arrival and departure for required walks between platforms as well as train-related services. Moreover, the capacity of crew bases (number of conductors starting their duty there) can be limited.

The second group of conditions are legal requirements and regulations from labor contracts. The German Working Hours Act defines three types of working time. The duty time corresponds to the whole time from the beginning (signing on at the crew base) to the end of a duty (signing off). By contrast, the protected working time equates the duty time less unproductive time, such as breaks, idle and deadhead times. Finally, the paid time specifies the duty time without breaks prescribed by law. Table 7.1 shows a collection of common requirements for planning conductors in Germany. See HOFFMANN et al. (2017) and JÜTTE (2012) for further details.

Table 7.1: Legal and contractual requirements

Duty time	<ul style="list-style-type: none"> • maximum duty time
Paid time	<ul style="list-style-type: none"> • minimum paid time of a duty • average paid time of all duties
Protected working time	<ul style="list-style-type: none"> • maximum protected working time • average protected working time of a crew schedule
Break times	<ul style="list-style-type: none"> • protected working time up to 6 h: no break • protected working time more than 6 h and up to 9 h: total break time 30 min • protected working time more than 9 h: total break time 45 min • duty time more than 12 h: one non-interrupted break of 120 min • minimum non-interrupted break time: 15 min • maximum working time without break: 6 h • no breaks at beginning and end of the duty (e.g. 2 h duty time) • breaks are only allowed at stations with break rooms • small idle times up to 5 min are counted as working time

Finally, there are many claims under the transportation contract. Besides the type or equipment of vehicles, the frequency of trips and more, this contract specifies the attendance rates. They are defined as percentage rates of trains or kilometers that have to be attended by conductors, based on the whole transportation network. Attendance rates can differ depending on product types, lines, train numbers, track sections or time windows and usually range between 0% and 100%, which means that each trip has to

be accompanied by a conductor.

The goal is to find a minimum cost shift schedule satisfying operating conditions and legal requirements. The schedule should cover a subset of all trips such that the different attendance rates specified in the transportation contract are met.

7.4 Arc flow formulation

The railway crew scheduling problem with variable attendance rates is defined by a set of conductors C and a directed graph G . Let $G = (V, A)$ be a graph with a set V of nodes and a set A of arcs. For each crew base $e \in E$ we define one source and one sink node. Furthermore, let M be the set of all unique trips. Each unique trip $\tau \in M$ receives one departure and one arrival node, so that $|V| = 2 \cdot (|E| + |M|)$. Set A consists of all trip arcs, all possible connections of two unique trips (waiting arcs), source and sink arcs as well as one sink-source-arc (return) for each crew base. The waiting arc between trips τ_1 and τ_2 is built only if trip τ_1 arrives at the same station as trip τ_2 departs and there is enough time between arrival and departure for walks or other operational tasks. Source arcs represent the connection between the source (crew base) and all trips starting at the respective crew base. In the same way we define sink arcs as connection between all trips ending at a crew base with the respective sink. Let $F \subset A$ denote all trip arcs (unique trips) and $R \subset A$ all sink-source arcs. For each arc $(i, j) \in A$ we determine the amount of various resources used by this arc, e.g. duty time t_{ij} , protected working time s_{ij} and possible break time b_{ij} . Depending on the type of arc, the resources t_{ij} , s_{ij} and b_{ij} are defined in a different way, as you can find in Table 7.2.

A fictional example graph with 8 trips can be found in Figure 7.2. There are three stations A, B, and C, of which A and C are crew bases. Below the graph, a timeline from 6 a.m. to 2 p.m. is given. The types of arcs are represented by different line styles (solid: trip arcs, dashed: source arcs, dotted: sink arcs, gray: waiting arcs, double arrow: sink-source arcs). For the sake of clarity, resource parameters and variables are omitted and separately presented for one arc in Figure 7.3.

By modeling the graph in this way we meet some of the requirements. We can guarantee the compatibility of two consecutive trips in the duty (with regard to time and location). Due to the sink-source arcs we ensure the symmetry of the duties (each duty starts and ends at the same crew base). The minimum non-interrupted break time of 15 minutes and the necessity that breaks are only allowed at stations with break rooms is modeled by the resource b_{ij} of the waiting arcs. All other conditions have to be implemented in the model.

Table 7.2: Definition of resources t_{ij} , s_{ij} , b_{ij} depending on the type of arc

Trip arc	<ul style="list-style-type: none"> • t_{ij}: difference between departure time of trip (i, j) and arrival time of trip (i, j) • s_{ij}: difference between departure time of trip (i, j) and arrival time of trip (i, j) • b_{ij}: 0
Source arc	<ul style="list-style-type: none"> • t_{ij}: time for signing on (examine working documents and walks) at crew base i • s_{ij}: time for signing on (examine working documents and walks) at crew base i • b_{ij}: 0
Sink arc	<ul style="list-style-type: none"> • t_{ij}: time for signing off (walks) at crew base j • s_{ij}: time for signing off (walks) at crew base j • b_{ij}: 0
Waiting arc between trip τ_1 and τ_2	<ul style="list-style-type: none"> • t_{ij}: transition time: difference between departure time of τ_2 (at node j) and arrival time of τ_1 (at node i) • s_{ij}: time for train-related services and walks between trip τ_1 and τ_2 (if the remaining time is less than 5 minutes $s_{ij} = t_{ij}$) • b_{ij}: 0, 15, 30 or 45 minutes (depends on remaining time gap and possibility of a break at the station)
Sink-source arc	<ul style="list-style-type: none"> • t_{ij}: 0 • s_{ij}: 0 • b_{ij}: 0

In order to satisfy the attendance rates we have to define the set $D \subset [0, 1]$ of all different attendance rates and the distance d_{ijg} of trip arc (i, j) with rate $g \in D$. It is even possible to have different rates for the same trip. In this case the total distance of the trip has to equal $\sum_{g \in D} d_{ijg}$. We have to define the maximum number C_q of duties starting at crew base q , because at each crew base only a certain number of conductors is available. In order to limit the duty and working time for each duty, we introduce $t^{\max}$, the maximum duty time, and $s^{\max}$, the maximum protected working time. In some cases, the average paid time of all duties is requested to remain in a specific interval $[\bar{t}^{\min}, \bar{t}^{\max}]$ to get feasible crew rosters. c^{fix} and c^{var} are the fixed costs per duty and variable costs per minute, respectively.

Finally, we have to define the decision variables. The first block of variables belongs to arc set A . Let x_{ijc} be a binary decision variable such that $x_{ijc} = 1$ if conductor c uses arc (i, j) , 0 otherwise. Very closed related, $y_{ij} = 1$ if trip arc (i, j) is in the solution (i.e. is used by any conductor). If conductor c takes a break between node i and j , the binary decision variable w_{ijc} takes the value 1, otherwise 0. Decision variables associated with

Figure 7.2: Example graph with trip, source, sink, waiting and sink-source arcs

Figure 7.3: Arc with resource parameters and variables

the resources mentioned above form the second block. The integer variable ta_{ic} defines the accumulated duty time, sa_{ic} the accumulated working time without break times and ba_{ic} the accumulated break time at node i for conductor c . Last but not least, let $u_c = 1$ if the protected working time of conductor c is greater than 360 minutes (the required accumulated break time at the sink node is 30 minutes), 0 otherwise. Similarly, $v_c = 1$ if the protected working time of c is larger than 540 minutes (45 minutes accumulated break time is required in sink node). All relevant sets, parameters and decision variables are summarized in Table 7.3.

Table 7.3: Sets and parameters

Sets	
V	nodes
Q	sources
S	sinks
A	arcs
F	trip arcs
R	sink-source arcs
C	set of conductors
D	set of attendance rates
Parameters	
d_{ijg}	distance of trip arc (i, j) with rate g
t_{ij}	duty time of arc (i, j)
s_{ij}	protected working time of arc (i, j)
b_{ij}	possible break time of arc (i, j)
C_q	maximum number of duties starting at crew base q
$t^{\max}$	maximum duty time
$s^{\max}$	maximum protected working time
$\bar{t}^{\min}$	minimum average paid time of all duties
$\bar{t}^{\max}$	maximum average paid time of all duties
c^{fix}	fixed costs per duty
c^{var}	variable costs per minute
Decision variables	
x_{ijc}	$= \begin{cases} 1, & \text{if conductor } c \text{ uses arc } (i, j), \\ 0, & \text{otherwise} \end{cases}$
y_{ij}	$= \begin{cases} 1, & \text{if trip arc } (i, j) \text{ is in solution,} \\ 0, & \text{otherwise} \end{cases}$
w_{ijc}	$= \begin{cases} 1, & \text{if conductor } c \text{ takes a break between node } i \text{ and } j, \\ 0, & \text{otherwise} \end{cases}$
ta_{ic}	accumulated duty time at node i for conductor c
sa_{ic}	accumulated protected working time without break times at node i for conductor c
ba_{ic}	accumulated break time at node i for conductor c
u_c	$= \begin{cases} 1, & \text{if protected working time of conductor } c \text{ is } > 360, \\ 0, & \text{otherwise} \end{cases}$
v_c	$= \begin{cases} 1, & \text{if protected working time of conductor } c \text{ is } > 540, \\ 0, & \text{otherwise} \end{cases}$

With this, the arc flow formulation of the railway crew scheduling problem with attendance rates for a single day is

$$c^{\text{var}} \cdot \sum_{c \in C} \left(\sum_{(i,j) \in A} t_{ij} x_{ijc} - (30u_c + 15v_c) \right) + c^{\text{fix}} \cdot \sum_{c \in C} \sum_{q \in Q} \sum_{j \in V} x_{qjc} \longrightarrow \min \quad (7.1)$$

$$\sum_{(i,j) \in F} d_{ijg} y_{ij} \geq g \sum_{(i,j) \in F} d_{ijg} \quad \forall g \in D \quad (7.2)$$

$$\sum_{c \in C} x_{ijc} \geq y_{ij} \quad \forall (i,j) \in F \quad (7.3)$$

$$y_{ij} \geq x_{ijc} \quad \forall (i,j) \in F, c \in C \quad (7.4)$$

$$\sum_{c \in C} \left(\sum_{(i,j) \in A} t_{ij} x_{ijc} - (30u_c + 15v_c) \right) \geq \bar{t}^{\min} \sum_{c \in C} \sum_{q \in Q} \sum_{j \in V} x_{qjc} \quad (7.5)$$

$$\sum_{c \in C} \left(\sum_{(i,j) \in A} t_{ij} x_{ijc} - (30u_c + 15v_c) \right) \leq \bar{t}^{\max} \sum_{c \in C} \sum_{q \in Q} \sum_{j \in V} x_{qjc} \quad (7.6)$$

$$\sum_{k \in V: (k,i) \in A} x_{kic} - \sum_{j \in V: (i,j) \in A} x_{ijc} = 0 \quad \forall i \in V, c \in C \quad (7.7)$$

$$ta_{jc} - ta_{ic} - t_{ij} \geq -2 \cdot t^{\max} \cdot (1 - x_{ijc}) \quad \forall (i,j) \in A \setminus R, c \in C \quad (7.8)$$

$$ta_{jc} - ta_{ic} - t_{ij} \leq t^{\max} \cdot (1 - x_{ijc}) \quad \forall (i,j) \in A \setminus R, c \in C \quad (7.9)$$

$$ta_{qc} = 0 \quad \forall q \in Q, c \in C \quad (7.10)$$

$$\sum_{(i,j) \in A} t_{ij} x_{ijc} \leq t^{\max} \quad \forall c \in C \quad (7.11)$$

$$\sum_{(i,j) \in A} s_{ij} x_{ijc} \leq s^{\max} \quad \forall c \in C \quad (7.12)$$

$$ba_{jc} - ba_{ic} - b_{ij} w_{ijc} \geq -2 \cdot 45 \cdot (1 - x_{ijc}) \quad \forall (i,j) \in A \setminus R, c \in C \quad (7.13)$$

$$ba_{jc} - ba_{ic} - b_{ij} w_{ijc} \leq 45 \cdot (1 - x_{ijc}) \quad \forall (i,j) \in A \setminus R, c \in C \quad (7.14)$$

$$ba_{qc} = 0 \quad \forall q \in Q, c \in C \quad (7.15)$$

$$w_{ijc} \leq b_{ij} \quad \forall (i,j) \in A, c \in C \quad (7.16)$$

$$w_{ijc} \leq x_{ijc} \quad \forall (i,j) \in A, c \in C \quad (7.17)$$

$$\sum_{(i,j) \in A} s_{ij} x_{ijc} - 361u_c \geq 0 \quad \forall c \in C \quad (7.18)$$

$$\sum_{(i,j) \in A} s_{ij} x_{ijc} - (s^{\max} - 360)u_c \leq 360 \quad \forall c \in C \quad (7.19)$$

$$ba_{sc} - 30u_c + 30(1 - \sum_{i \in V} x_{isc}) \geq 0 \quad \forall s \in S, c \in C \quad (7.20)$$

$$\sum_{(i,j) \in A} s_{ij} x_{ijc} - 541v_c \geq 0 \quad \forall c \in C \quad (7.21)$$

$$\sum_{(i,j) \in A} s_{ij} x_{ijc} - (s^{\max} - 540)v_c \leq 540 \quad \forall c \in C \quad (7.22)$$

$$ba_{sc} - 45v_c + 45(1 - \sum_{i \in V} x_{isc}) \geq 0 \quad \forall s \in S, c \in C \quad (7.23)$$

$$ta_{ic} - 121w_{ijc} + 121(1 - x_{ijc}) \geq 0 \quad \forall (i,j) \in A, c \in C \quad (7.24)$$

$$ta_{sc} - ta_{jc} - 121w_{ijc} + 121(1 - x_{ijc}) \geq 0 \quad \forall (i,j) \in A, s \in S, c \in C \quad (7.25)$$

$$sa_{jc} - sa_{ic} - s_{ij} \geq (-360 - s^{\max}) \cdot (1 - x_{ijc} + w_{ijc}) \quad \forall (i,j) \in A \setminus R, c \in C \quad (7.26)$$

$$sa_{jc} - sa_{ic} - s_{ij} \leq 360 \cdot (1 - x_{ijc} + w_{ijc}) \quad \forall (i, j) \in A \setminus R, c \in C \quad (7.27)$$

$$sa_{jc} \leq 360 \cdot (2 - x_{ijc} - w_{ijc}) \quad \forall (i, j) \in A, c \in C \quad (7.28)$$

$$sa_{ic} \leq 360 \quad \forall i \in V, c \in C \quad (7.29)$$

$$\sum_{c \in C} x_{iqc} \leq C_q \quad \forall q \in Q, (i, q) \in R \quad (7.30)$$

$$x_{ijc} \in \{0, 1\} \quad \forall (i, j) \in A, c \in C \quad (7.31)$$

$$w_{ijc} \in \{0, 1\} \quad \forall (i, j) \in A, c \in C \quad (7.32)$$

$$y_{ij} \in \{0, 1\} \quad \forall (i, j) \in F \quad (7.33)$$

$$ta_{ic} \in \mathbb{N} \quad \forall i \in V, c \in C \quad (7.34)$$

$$ba_{ic} \in \mathbb{N} \quad \forall i \in V, c \in C \quad (7.35)$$

$$sa_{ic} \in \mathbb{N} \quad \forall i \in V, c \in C \quad (7.36)$$

$$u_c \in \{0, 1\} \quad \forall c \in C \quad (7.37)$$

$$v_c \in \{0, 1\} \quad \forall c \in C. \quad (7.38)$$

The objective function (7.1) minimizes the total costs of all duties with the paid time of the duty equaling the duty time minus the required break time. Constraints (7.2) guarantee that the accumulated distance of the covered trips in the solution schedule is greater than or equal to the requested percentage of the total distance assigned to the special attendance rate. Constraints (7.3) and (7.4) are linking constraints for variables x_{ijc} and y_{ij} . On the one hand, there has to be at least one conductor using arc (i, j) if trip $(i, j) \in F$ is part of the solution schedule. On the other hand, trip (i, j) must not be in the solution if there is no conductor traveling from i to j . Furthermore, trip $(i, j) \in F$ has to be in the solution if there is a conductor c using trip arc (i, j) . However, if trip (i, j) is not part of the solution schedule, each conductor must not use trip arc (i, j) . Constraints (7.5) and (7.6) ensure that the average paid time in the solution schedule is between the minimum and maximum average paid time. The flow conservation constraints for each conductor are modeled by (7.7). These are also valid for all sources and sinks, as the crew base capacity is controlled by the flow on sink-source arcs (see (7.30)). Constraints (7.8)-(7.11) represent the resource “accumulated duty time”. If arc (i, j) is used by conductor c the resource extension function corresponds to $ta_{ic} + t_{ij} = ta_{jc}$. This function is modeled by two big- M -constraints with $M = t^{\max}$. Furthermore, for each conductor and source node the duty time has to start from 0 and the maximum duty time must not be exceeded. The latter also applies to the protected working time (7.12). Constraints (7.13)-(7.15) model the resource “accumulated break time”. The resource extension function $ba_{ic} + b_{ij}w_{ijc} = ba_{jc}$ has to be valid if conductor c uses arc (i, j) . The resource is set to 0 for each conductor in all source nodes. Constraints

(7.16) guarantee that no conductor can take a break between i and j if arc (i, j) offers no possibility to take a break ($b_{ij} = 0$). Constraints (7.17) ensure that conductor c can take breaks only on arcs (i, j) he uses. Legal requirements on break times are implemented by constraints (7.18)-(7.29). The first block (7.18)-(7.23) determines the duration of breaks depending on the protected working time of conductor c (see Table 7.1). The accumulated break time at the sink node ba_{sc} has to be equal to or greater than 30 minutes if the protected working time of conductor c exceeds 6 hours, but, at the same time, is not larger than 9 hours. If the protected working time of conductor c exceeds 9 hours, the accumulated break time of conductor c at the sink node has to be equal to or greater than 45 minutes. Constraints (7.24) and (7.25) guarantee that breaks in the first and last two hours are excluded. The last block (7.26)-(7.29) refers to the resource “accumulated working time without break”, that must not exceed 6 hours. On the one hand, the resource extension function $sa_{ic} + s_{ij} = sa_{jc}$ has to be valid if conductor c uses arc (i, j) and takes no break ($w_{ijc} = 0$). On the other hand, resource sa_{jc} is set to 0 if conductor c uses arc (i, j) and takes a break there. In constraints (7.30) the number of duties starting at crew base $q \in Q$ is limited to the capacity C_q of the crew base.

7.5 Valid inequalities

Valid inequalities (also: cutting planes or cuts) are inequalities that are valid for all feasible solutions of the (mixed) integer problem. Solutions of the linear relaxation violating the integrality constraints for some integer and binary variables do often not fulfill these valid inequalities. Accordingly, valid inequalities can strengthen the linear formulation and, therefore, improve the bounds yielded from the relaxation. This behavior can help to fasten the solution process of the integer problem, i.e. to prune Branch-and-Bound nodes and support integer-feasibility of a node’s linear relaxation.

Valid inequalities presented in this paper are divided into four groups. After starting with model specific valid inequalities in 7.5.1, we present two kinds of symmetry breaking constraints in 7.5.2. Finally, we define constraints assigning parallel trips to different conductors (7.5.3 and 7.5.4).

7.5.1 Model specific valid inequalities

Valid inequalities concerning resources used in the model (duty time, protected working time, break time) are

$$t^{\max} \sum_{i \in V} x_{ijc} \geq ta_{jc} \quad \forall j \in V \setminus S, \forall c \in C \quad (7.39)$$

$$45 \sum_{i \in V} x_{ijc} \geq ba_{jc} \quad \forall j \in V \setminus S, \forall c \in C \quad (7.40)$$

$$360 \sum_{i \in V} x_{ijc} \geq sa_{jc} \quad \forall j \in V \setminus S, \forall c \in C \quad (7.41)$$

$$u_c \geq v_c \quad \forall c \in C \quad (7.42)$$

$$\sum_{(i,j) \in R} x_{ijc} \geq u_c \quad \forall c \in C \quad (7.43)$$

$$\sum_{(i,j) \in R} x_{ijc} \geq v_c \quad \forall c \in C \quad (7.44)$$

$$\sum_{(i,j) \in A} b_{ij} w_{ijc} \geq 30u_c \quad \forall c \in C \quad (7.45)$$

$$\sum_{(i,j) \in A} b_{ij} w_{ijc} \geq 45v_c \quad \forall c \in C. \quad (7.46)$$

Constraints (7.39)-(7.41) ensure that the resources of c in node j (duty time ta_{jc} , break time ba_{jc} and working time without break sa_{jc}) are set to 0 if conductor c does not use any arc entering node j . In constraints (7.42) the relation between u_c and v_c is described. On the one hand, if the protected working time of conductor c is not larger than 360 minutes ($u_c = 0$), it cannot be larger than 540 minutes ($v_c = 0$). On the other hand, the protected working time of conductor c is larger than 360 minutes ($u_c = 1$) if it is larger than 540 minutes ($v_c = 1$). Constraints (7.43) and (7.44) guarantee that there is no break if conductor c is not employed. If conductor c takes no regular breaks in his duty ($w_{ijc} = 0 \quad \forall (i,j) \in A$), then the protected working time has to be less than or equal to 360 minutes ($u_c = 0$). Otherwise, the sum of the breaks has to be greater than or equal to 30 minutes if the protected working time of conductor c is larger than 360 minutes ($u_c = 1$), see constraints (7.45). Constraints (7.46) are equivalent.

7.5.2 Symmetry breaking constraints

In combinatorial optimization computation time often is wasted in finding new solutions which are symmetric to already visited solutions. Symmetry breaking constraints can reduce the search space and, therefore, the solution time. See COELHO/LAPORTE (2014) and ADULYASAK/CORDEAU/JANS (2014) for application of symmetry breaking in vehicle routing problems. To avoid symmetry in our arc flow model we can demand that conductor 1 is employed before conductor 2 and so on:

$$\sum_{(i,j) \in R} x_{ijc} \geq \sum_{(i,j) \in R} x_{ij(c+1)} \quad \forall c \in \{1, \dots, |C| - 1\} \quad (7.47)$$

and duty times are sorted in decreasing order

$$\sum_{(i,j) \in A} t_{ij} x_{ijc} \geq \sum_{(i,j) \in A} t_{ij} x_{ij(c+1)} \quad \forall c \in \{1, \dots, |C| - 1\}. \quad (7.48)$$

7.5.3 Parallel arcs

Due to the structure of the problem any conductor can attend only one train (unique trip) at the same time. Thus, trains operated parallel at any time in the transportation network have to be attended by different conductors. To model this restriction, we extract all sets $P_1, \dots, P_N$ of trip arcs running parallel. Let arc 1 and 2 be some arcs with start time t^{start} and end time t^{end} . These arcs are parallel if

$$\begin{aligned} t_1^{\text{start}} \leq t_2^{\text{start}} \quad \text{and} \quad t_2^{\text{start}} < t_1^{\text{end}} \quad \text{or} \\ t_2^{\text{start}} \leq t_1^{\text{start}} \quad \text{and} \quad t_1^{\text{start}} < t_2^{\text{end}}. \end{aligned}$$

Now, we can demand that the arcs of such a set P_n cannot be used by the same conductor, i.e.

$$\sum_{(i,j) \in P_n} x_{ijc} \leq 1, \quad \forall c \in C, n \in \{1, \dots, N\}. \quad (7.49)$$

7.5.4 Fixed arcs

Following up on this considerations, there is a possibility to fix arcs to a specific conductor if the transportation network contains parallel trips with an attendance rate of 100%. We build all sets $P_1, \dots, P_L$ of parallel trip arcs with attendance rate $g = 100\%$ and let $\bar{P}$ be the set of $P_1, \dots, P_L$ with maximum cardinality. Now, we can assign each trip arc to a different conductor, i.e.

$$x_{ijc} = 1, \quad \forall (i, j) \in \bar{P}, c \text{ index of } (i, j) \text{ in } \bar{P}. \quad (7.50)$$

Equations (7.50) enforce, that the first arc in $\bar{P}$ is assigned to conductor $c = 1$, the second arc to conductor $c = 2$ and so on. Note that one unique trip with attendance rate of 100% is assigned to the first conductor if there are no parallel arcs (i.e. $|\bar{P}| = 1$). Furthermore, if equations (7.50) and inequalities (7.48) are added to the model simultaneously, the decreasing order of duty times can no longer be guaranteed for the fixed assignment of trip and conductor. For example, trip 1 is assigned to conductor 1. We have no influence on whether this conductor has the largest duty time or not. Therefore, symmetry breaking constraints (7.48) can only be applied for conductors $c \in \{|\bar{P}| + 1, \dots, |C|\}$ not assigned to any trip.

7.6 Computational results

After defining the arc flow model for railway crew scheduling problems with attendance rates and a choice of valid inequalities, we provide some computational results in this section to show the influence of adding or omitting valid inequalities on computation times and bounds of the linear relaxation. As shown in Table 7.4, valid inequalities are aggregated in distinct sets S1, ..., S7.

Table 7.4: Sets of valid inequalities

Set	Valid inequalities
S1	(7.39)-(7.41)
S2	(7.42)-(7.44)
S3	(7.45), (7.46)
S4	(7.47)
S5	(7.48)
S6	(7.49)
S7	(7.50)

Following practical requirements we define the parameters as follows: The maximum duty time $t^{\max} = 640$, the maximum working time $s^{\max} = 600$ and the range of the average paid time $[\bar{t}^{\min}, \bar{t}^{\max}] = [418, 512]$. The objective function is predetermined by costs of 50 per minute paid time (c^{var}) and fixed costs (c^{fix}) of 2000. For all runs we omit constraints concerning the capacity of crew bases, because limitation of the number of conductors is not required in the considered transportation networks.

All instances used for the following tests represent real-world instances for a standard day or subsets thereof. Table 7.5 summarizes the names of the instances, the number of trips, crew bases (CB) and relief points (RP) as well as the set of attendance rates. To get a good estimation of the number of conductors $|C|$ for medium- and large-sized instances, we use the hybrid solution approach proposed in HOFFMANN et al. (2017) and add a safety margin, because minimum costs can be achieved with a larger number of conductors. In general, models based on a flow problem with resource constraints are often solved by dynamic optimization, e.g. labeling algorithms. These approaches are not viable for the present model (7.1)-(7.38) due to a lack of good dominance criteria to eliminate labels (see ALBERS (2009)). Basically, only two paths containing the same set of trips can be compared. And even in this case, it is not always possible to decide whether one path dominates the other. This is due to the fact that a legal break can be included later on in the whole duty that reduces costs even though the duty time is longer.

Table 7.5: Instances

Instance	Trips	CB	RP	Attendance rates
CSPAR01a	45	2	7	$D = \{0.5, 1\}$
CSPAR02a	52	2	4	$D = \{0.25, 1\}$
CSPAR03a	60	5	6	$D = \{0.25, 0.75\}$
CSPAR04a	64	5	7	$D = \{0.3, 0.9\}$
CSPAR01b	92	2	7	$D = \{0.5, 1\}$
CSPAR03b	103	5	6	$D = \{0.25, 0.75\}$
CSPAR02b	104	2	4	$D = \{0.25, 1\}$
CSPAR04b	110	5	7	$D = \{0.3, 0.9\}$
CSPAR05	243	7	12	$D = \{0.3, 0.9\}$
CSPAR06	246	3	6	$D = \{0.25, 1\}$
CSPAR07	471	9	16	$D = \{0.3, 0.9\}$
CSPAR08	482	3	11	$D = \{0.25, 1\}$
CSPAR09	584	3	13	$D = \{0.25, 1\}$
CSPAR10	713	10	18	$D = \{0.3, 0.9\}$

The graph construction step was coded in C# programming language, using the Gurobi 7.5 interface to model and solve arc flow models. All tests were run on a Intel(R) Xenon(R) CPU E5-2630 v2 with 2.6GHz clock speed and 384 GB RAM. The maximum of parallel threads used by Gurobi was limited to 8.

7.6.1 Small-sized instances

To show the influence of the valid inequalities presented in this paper on computation times and bounds derived from the linear relaxation (LP bound), we tested all $2^7 = 128$ possible combinations of sets of valid inequalities defined in Table 7.4. For each combination we use 10 different random number seeds for optimization to get distinct solution paths with different computation times, because the seed is used for tie breaking in the preprocessing and solution process of the solver. Table 7.6 summarizes a selection of settings, properties and results. Depending on the size of the instances we set an upper bound for the transition time (Trans., in minutes) between two consecutive trips to reduce the number of arcs (more precisely, reduce the number of waiting arcs) of the underlying graph. The maximum number of conductors $|C|$ is set to 4 for all small-sized instances. The number of nodes $|V|$, number of arcs $|A|$ of the graph, maximum number of parallel arcs $|\overline{P}|$ and the optimal solution value (Obj.) found by the model are also presented in Table 7.6.

Figure 7.4 displays the results of all tested runs as box plots. For instances CSPAR03a, CSPAR04a, CSPAR03b and CSPAR04b we skip set S7, because there are no trips with

Figure 7.4: Mean computation times depending on selected sets of inequalities

Table 7.6: Small-sized instances

Instance	Trans.	$ C $	$ V $	$ A $	$ \overline{P} $	Obj.
CSPAR01a	∞	4	94	212	1	46,050
CSPAR02a	∞	4	108	422	2	46,500
CSPAR03a	∞	4	130	435	-	45,800
CSPAR04a	∞	4	138	458	-	45,800
CSPAR01b	120	4	188	350	2	68,700
CSPAR03b	120	4	216	514	-	52,700
CSPAR02b	120	4	212	532	3	69,200
CSPAR04b	120	4	230	542	-	68,700

an attendance rate of 100%. The dashed line shows the computation time for solving the original problem without valid inequalities. The box plot consists of boxes and whiskers, whereby the bottom and top of the boxes represent the first and third quartiles, the line inside the box the second quartile (median). The upper whisker extends from the top of the box to the largest value no further than 1.5 times the distance between the first and third quartiles. The lower whisker is defined analogously. Outlying points represent data beyond the end of the whiskers.

We will describe the plot in the upper left corner (CSPAR01a) a little bit more in detail. For instance CSPAR01a we perform $2^7 \cdot 10 = 1280$ runs, because there are 128 combinations of sets of valid inequalities and we run each combination 10 times with different random number seeds to reduce the influence of coincidence. The measured computation times of all 10 runs are averaged so that each combination delivers one mean computation time value. Computation times of all 64 combinations where set S1 is added to the basic arc flow model (regardless of the state of all other sets) form the light gray filled box above “S1” (right box plot). The dark gray filled box is represented by computation times of all 64 combination omitting set S1 (left box plot).

Figure 7.4 clearly demonstrates that valid inequalities rather increase computation times for small problem sizes (e.g. CSPAR02a, CSPAR03a and CSPAR04a) in contrast to larger instances, for which computations times rather are improved. We can derive that some sets of valid inequalities have a positive influence on the computation time, others not. Sets S4 and S7 seem to affect the computation time in a positive way, whereas set S1 can be omitted for fast solutions. In the case of S7 all quartiles for all instances are better if S7 is added to the basic model. Set S4 performs in a similar way. Almost all quartiles are better if S4 is activated. In contrast, omitting set S1 delivers better quartiles except for instance CSPAR01a. The activation of S6 appears to have a slight positive impact on computation times for instances with attendance rate less than

100% (CSPAR04a, CSPAR04b). For instances with trips that have to be attended by a conductor (100%), set S7 has the biggest influence on computation times (CSPAR01a, CSPAR02a, CSPAR01b, CSPAR02b).

An extract from the test results delivering good computation times is presented in Table 7.7. We use various criteria for filtering the best combinations. First, we delete all combinations where the computation times for two or more instances exceed the computation time for the basic arc flow model. Second, we sort all remaining combinations by increasing total computation time as well as decreasing accumulated percentage deviation from the computation time of the basic arc flow model. The intersection of the first 10 positions of both rankings are the 5 combinations presented in Table 7.7. Combinations of S1, ..., S7 are binary coded, e.g. 0000001 means only S7 is added to the arc flow model. All values represent mean computation times for 10 runs with different random number seeds. Best mean values of all combinations are highlighted in bold. There are only three bold numbers, because these combinations provide near-best values over all instances. All other best mean values are presented in Table 7.8 (columns “Best mean”) and are highlighted in bold in Table 7.11 in the supplementary material.

Table 7.7: Computation times for small-sized instances (extract)

Instances	0000000	0001001	0001011	0011001	0011011	0111011
CSPAR01a	35.27	12.18	11.98	15.85	17.57	16.14
CSPAR02a	30.28	19.51	13.71	28.90	19.36	13.84
CSPAR03a	55.68	43.47	62.46	56.35	53.36	38.42
CSPAR04a	67.90	76.41	49.46	59.24	81.50	62.68
CSPAR01b	308.53	50.67	53.12	65.27	59.05	84.58
CSPAR03b	271.99	166.06	159.03	203.73	181.50	141.35
CSPAR02b	146.09	27.72	33.74	25.92	29.43	33.53
CSPAR04b	3,059.05	778.39	428.08	713.74	634.57	671.68

Table 7.8 summarizes best computation times for all small-sized instances. Column “0000000” shows the mean of computation times for the basic arc flow model without any valid inequality. We compare the best of all computation times (Best overall) as well as the best of all means (Best mean) with the basic arc flow model. All best cases are represented by the binary coding of valid inequality sets S1, ..., S7 (VI), the computation time (t) and the improvement of the computation time compared to the basic arc flow model (Δt). As you can see, computation time can be improved by 31 – 86.01% on average. In some cases the computation time can be reduced by up to 94.79%. Here again, combinations with set S1 omitted and set S7 activated are the best for most instances.

Table 7.8: Best computation times for small-sized instances

Instances	0000000	Best overall			Best mean		
		VI	t	Δt	VI	t	Δt
CSPAR01a	35.27	1111101	6.20	-82.42%	1011101	8.22	-76.69%
CSPAR02a	30.28	0100101	7.70	-74.57%	0001011	13.71	-54.72%
CSPAR03a	55.68	0000001	25.89	-53.50%	0111011	38.42	-31.00%
CSPAR04a	67.90	0000011	16.17	-76.19%	0110011	35.78	-47.30%
CSPAR01b	308.53	0100111	19.41	-93.71%	0101001	50.22	-83.72%
CSPAR03b	271.99	0110111	53.47	-80.34%	0001111	123.49	-54.60%
CSPAR02b	146.09	0010111	16.06	-89.01%	0100001	23.14	-84.16%
CSPAR04b	3,059.05	0011011	159.32	-94.79%	0001011	428.08	-86.01%

7.6.2 Bounds for real-world instances

All small-sized instances (CSPAR01a-CSPAR04b) are solved optimally within reasonable time by using the arc flow model. Instances CSPAR05-CSPAR10 are medium- or large-sized and, therefore, non solvable within appropriate times without further treatment. For that reason, we analyze the solution of the linear relaxation below. Besides the influence on computation times, valid inequalities can strengthen the linear relaxation of any (mixed-)integer problem. In case of minimizing the objective function there is the possibility to get a better (higher) lower bound.

We test all combinations providing good computation times for the small-sized instances presented in 7.6.1 (0001001, 0001011, 0011001, 0011011, 0111011, 1001001, 1011001 and 1011011). Table 7.9 shows an extract of the results for all medium- and large-sized instances used in this paper. We only present combinations where the value of the linear relaxation changes significantly for at least one instance. Columns “0000000” represent the value of the linear relaxation (LP) derived from the arc flow formulation without any valid inequality and the corresponding computation time (t). In contrast, all following columns show the percentage improvement of the LP value (ΔLP) and the corresponding time (t). For all tested combinations we can improve the value of the linear relaxation by up to 3.02% (basis model: 116,228.34, basic model with valid inequalities represented by 0111011: 119,734.97). In this case, computation time increases from 5.58 to 18.96 seconds (increase of 239.78%). Combination 0001011 decreases computation times by up to 40% for the majority of instances, but provides no better LP value. We can conclude that there is trade-off between better bounds and increasing computation times. Worse computation times for lower bounds do not give any indication of slowing the further solution process, in fact rather the opposite.

Table 7.9: Deviation of the linear relaxation value and computation times without and with valid inequalities

	0000000		0001011		0011011		0111011	
	LP	t	Δ LP	t	Δ LP	t	Δ LP	t
CSPAR05	117,182.81	29.52	0.00%	31.96	0.55%	44.72	1.27%	50.21
CSPAR06	116,228.34	5.58	1.36%	11.85	2.99%	23.79	3.02%	18.96
CSPAR07	263,204.84	4,290.19	0.00%	2,568.13	1.02%	2,435.83	1.03%	4,023.75
CSPAR08	183,200.00	89.38	0.00%	75.48	0.00%	451.23	0.00%	125.55
CSPAR09	183,200.00	139.55	0.00%	93.09	0.00%	698.63	0.00%	194.14
CSPAR10	343,079.10	38,243.87	0.00%	28,768.03	0.30%	48,937.06	0.86%	44,921.52

7.6.3 Improve heuristic solution

Besides the solution of the linear relaxation, we evaluate the warm starting solution procedure for all medium- or large-sized instances. Therefore, we start the optimization process with an initial solution to cut off nodes with higher objective values.

Table 7.10: Best objective values, best bounds and gaps at the beginning and after 24 h

	Start			After 24 h		
	LP	Obj.	Gap	LP	Obj.	Gap
CSPAR05	118,668.47	132,400	10.37%	126,173.67	132,350	4.67%
CSPAR06	119,734.97	129,550	7.58%	127,470.35	128,950	0.37%
CSPAR07	265,915.16	297,700	10.68%	269,730.37	297,700	9.40%
CSPAR08	183,200.00	196,350	6.70%	192,351.19	196,000	1.94%
CSPAR09	183,200.00	203,750	10.09%	194,390.70	200,900	3.24%
CSPAR10	346,014.30	376,500	8.10%	346,014.30	376,500	8.10%

For the tests presented in Table 7.10 we use sets S2, S3, S4, S6 and S7 (binary coding: 0111011) added to the basic arc flow model, because this combination provides good solution times for small-sized instances and best bounds for medium- and large-sized instances. In contrast to the small-sized instances, we start the optimization process for the medium- and large-sized instances with an initial solution received from the hybrid solution approach proposed in HOFFMANN et al. (2017). Starting with an initial duty pool, this approach produces new duties by a column generation procedure solving the pricing problem with a specialized genetic algorithm. Computing times for the initial solution vary between 2 minutes (CSPAR05) and 79 minutes (CSPAR10) and are neglected for the following tests. The left side shows the bound of the linear relaxation at the root node (LP), the objective value of the initial solution (Obj.) and the resulting gap. The right side presents the best bound (LP), the best objective value (Obj.) and the resulting gap after 24 hours computation time. The differences between best objective

values and lower bounds could be reduced by up to 7.21% (CSPAR06). In 4 of 6 cases better solutions are found, whereby the objective value of CSPAR06 is proved to be optimal after 24 hours and 47 minutes. It is noticeable that the improvement of the lower bounds (in percent) is greater than the improvement of the objective values. This suggests that the hybrid solution approach used to provide an initial solution performs already very well. Furthermore, all instances without trips having an attendance rate of 100% (CSPAR05, CSPAR07, CSPAR10) produce greater gaps after 24 hours than instances with 100%-trips. For instance CSPAR10 no improvement is achieved within 24 hours. In summary, the differences between best objective values and lower bounds could be reduced significantly within 24 hours.

7.7 Conclusion

This paper presents an arc flow formulation for the railway crew scheduling problem with attendance rates dealing with various practical requirements like specific requirements related to times and breaks defined by the Working Hours Act or labor contracts and limited crew base capacities. We define several valid inequalities to reduce the search space and to get better lower bounds which can fasten the solution process.

The results indicate that small-sized instances can be solved optimally by the arc flow model within appropriate time. A reasonable selection of valid inequalities can reduce computational times by up to 94.79%. With an appropriate choice of valid inequalities the value of the linear relaxation at the root node can be increased by up to 3.02%. Better bounds at the root node can, however, correlate with worse computation times for the root relaxation. This behavior does not indicate a slow running further solution process, in fact rather the opposite. For real-world instances this model helps to verify the quality of heuristic solutions by providing good lower bounds. We show that the gap between best objective values and lower bounds can be reduced by up to 7.21%.

With regard to real-world instances and practical scenarios, a planning horizon of several days to two weeks is more appropriate. The distribution of duties over the weekdays, an even distribution of the attended trips over the planning horizon and many other restrictions can only be applied over several days. It makes no sense to extend the arc flow model to multiple days, therefore, future research should deal with the integration of the model in superior solution approaches, e.g. HOFFMANN et al. (2017). If any heuristic or metaheuristic algorithm terminates with a potentially suboptimal solution, we can solve the exact model for each day separately or for the whole planning period. The heuristic solution can be used as initial solution for the model (similar to our procedure in chapter 6.3). If the model is solvable, we get the optimal integer solution.

Furthermore, it is possible to integrate the model into a column generation approach. If the algorithm cannot find new duties with negative reduced costs in the pricing problem, we can integrate parts of the model, more precisely all (in)equalities dealing with one conductor, in the pricing problem to get new duties with negative reduced costs or to prove that there is no such additional duty. In this case, we get the optimal solution of the linear relaxation and, most commonly, a near-optimal integer solution. Finally, additional valid inequalities should be tested on their influence on computation times and bounds of the linear relaxation.

Supplementary material

Table 7.11: Mean computation times for all small-sized instances

Nb.	Valid inequ.	CSPAR								Total sum	Perc. dev.
		01a	02a	03a	04a	01b	02b	03b	04b		
0	0 0 0 0 0 0 0	35.27	30.28	55.68	67.90	308.53	146.09	271.99	3,059.05	3,974.80	0.00
1	0 0 0 0 0 0 1	14.63	15.53	55.68	67.90	62.41	31.08	271.99	3,059.05	3,578.27	265.72
2	0 0 0 0 0 1 0	36.41	25.46	47.94	40.36	377.12	185.00	250.17	2,267.82	3,230.29	52.18
3	0 0 0 0 0 1 1	14.34	13.76	47.94	40.36	60.97	28.12	250.17	2,267.82	2,723.48	363.26
4	0 0 0 0 1 0 0	39.47	52.94	113.39	101.97	217.06	146.73	202.05	909.07	1,782.68	-115.37
5	0 0 0 0 1 0 1	11.15	18.93	113.39	101.97	60.42	31.06	202.05	909.07	1,448.03	207.22
6	0 0 0 0 1 1 0	39.89	33.95	135.13	98.13	238.92	188.43	162.43	1,654.77	2,551.65	-132.69
7	0 0 0 0 1 1 1	11.45	18.27	135.13	98.13	55.35	28.23	162.43	1,654.77	2,163.75	168.91
8	0 0 0 1 0 0 0	16.98	25.69	43.47	76.41	152.66	128.07	166.06	778.39	1,387.74	252.77
9	0 0 0 1 0 0 1	12.18	19.51	43.47	76.41	50.67	27.72	166.06	778.39	1,174.41	388.53
10	0 0 0 1 0 1 0	16.51	24.06	62.46	49.46	702.87	154.60	159.03	428.08	1,597.08	82.62
11	0 0 0 1 0 1 1	11.98	13.71	62.46	49.46	53.12	33.74	159.03	428.08	811.58	422.98
12	0 0 0 1 1 0 0	15.96	35.59	112.18	122.61	203.32	127.99	151.73	1,272.49	2,041.85	4.30
13	0 0 0 1 1 0 1	11.02	18.26	112.18	122.61	59.21	27.84	151.73	1,272.49	1,775.33	190.77
14	0 0 0 1 1 1 0	15.60	32.04	109.65	119.16	119.30	154.24	123.49	1,568.26	2,241.73	36.65
15	0 0 0 1 1 1 1	11.82	14.73	109.65	119.16	52.30	34.05	123.49	1,568.26	2,033.45	208.52
16	0 0 1 0 0 0 0	63.45	33.15	49.40	57.84	501.46	162.15	367.84	2,739.99	3,975.28	-161.63
17	0 0 1 0 0 0 1	14.52	20.10	49.40	57.84	82.47	31.46	367.84	2,739.99	3,363.61	245.48
18	0 0 1 0 0 1 0	70.12	33.03	48.91	41.13	616.66	299.27	416.59	2,041.00	3,566.71	-280.93
19	0 0 1 0 0 1 1	19.32	15.70	48.91	41.13	103.26	54.59	416.59	2,041.00	2,740.49	254.25
20	0 0 1 0 1 0 0	65.41	48.71	102.21	77.92	371.60	162.45	216.65	1,532.17	2,577.12	-206.04
21	0 0 1 0 1 0 1	11.80	27.83	102.21	77.92	91.09	31.14	216.65	1,532.17	2,090.81	195.74
22	0 0 1 0 1 1 0	62.95	59.62	112.56	86.17	565.20	298.58	191.37	1,436.04	2,812.48	-409.30
23	0 0 1 0 1 1 1	10.25	34.67	112.56	86.17	117.29	54.98	191.37	1,436.04	2,043.32	134.44
24	0 0 1 1 0 0 0	21.22	57.14	56.35	59.24	127.75	169.73	203.73	713.74	1,408.90	106.86
25	0 0 1 1 0 0 1	15.85	28.90	56.35	59.24	65.27	25.92	203.73	713.74	1,168.99	334.06
26	0 0 1 1 0 1 0	20.18	51.67	53.36	81.50	326.62	182.35	181.50	634.57	1,531.74	38.15
27	0 0 1 1 0 1 1	17.57	19.36	53.36	81.50	59.05	29.43	181.50	634.57	1,076.34	343.63
28	0 0 1 1 1 0 0	17.76	38.69	100.69	99.46	173.20	169.88	191.46	2,335.75	3,126.90	-24.64
29	0 0 1 1 1 0 1	10.11	20.23	100.69	99.46	50.51	26.01	191.46	2,335.75	2,834.22	196.26
30	0 0 1 1 1 1 0	20.55	29.73	138.01	72.31	418.64	182.31	225.61	1,466.18	2,553.35	-102.18
31	0 0 1 1 1 1 1	12.33	19.06	138.01	72.31	61.34	29.23	225.61	1,466.18	2,024.08	176.94
32	0 1 0 0 0 0 0	40.27	42.42	56.55	55.37	241.16	183.69	353.14	2,817.79	3,790.38	-63.21
33	0 1 0 0 0 0 1	20.37	22.84	56.55	55.37	82.28	23.14	353.14	2,817.79	3,431.48	219.23

Nb.	Valid inequ.	CSPAR								Total sum	Perc. dev.
		01a	02a	03a	04a	01b	02b	03b	04b		
34	0 1 0 0 0 1 0	41.43	46.43	49.79	55.59	334.94	204.98	302.57	3,036.66	4,072.39	-101.46
35	0 1 0 0 0 1 1	20.58	23.84	49.79	55.59	95.18	39.39	302.57	3,036.66	3,623.61	223.29
36	0 1 0 0 1 0 0	42.46	42.66	96.87	109.35	307.21	181.89	124.35	1,086.85	1,991.65	-101.62
37	0 1 0 0 1 0 1	13.95	38.56	96.87	109.35	71.36	23.38	124.35	1,086.85	1,564.67	177.69
38	0 1 0 0 1 1 0	40.11	81.68	109.32	78.43	234.22	204.14	230.63	4,550.81	5,529.34	-344.54
39	0 1 0 0 1 1 1	8.82	35.11	109.32	78.43	64.92	40.21	230.63	4,550.81	5,118.25	65.07
40	0 1 0 1 0 0 0	18.58	45.37	41.17	55.29	886.07	160.36	148.35	1,171.06	2,526.25	-47.65
41	0 1 0 1 0 0 1	14.09	38.51	41.17	55.29	50.22	33.37	148.35	1,171.06	1,552.06	345.56
42	0 1 0 1 0 1 0	16.22	51.26	55.41	49.76	95.12	160.77	191.02	1,061.11	1,680.68	166.11
43	0 1 0 1 0 1 1	14.46	34.58	55.41	49.76	52.41	32.43	191.02	1,061.11	1,491.19	327.89
44	0 1 0 1 1 0 0	22.65	36.36	125.29	116.16	241.26	163.08	175.70	971.78	1,852.29	-66.58
45	0 1 0 1 1 0 1	10.45	28.26	125.29	116.16	66.46	34.12	175.70	971.78	1,528.21	139.69
46	0 1 0 1 1 1 0	22.53	41.38	91.82	105.18	275.31	161.37	181.36	817.38	1,696.32	-13.42
47	0 1 0 1 1 1 1	10.68	17.56	91.82	105.18	79.01	33.57	181.36	817.38	1,336.56	249.93
48	0 1 1 0 0 0 0	117.78	38.88	52.37	50.82	470.81	162.98	445.12	2,654.15	3,992.91	-345.84
49	0 1 1 0 0 0 1	52.11	24.34	52.37	50.82	98.58	34.55	445.12	2,654.15	3,412.04	96.96
50	0 1 1 0 0 1 0	117.40	46.65	51.47	35.78	616.60	289.63	327.32	2,475.02	3,959.88	-431.44
51	0 1 1 0 0 1 1	52.41	19.01	51.47	35.78	93.06	40.22	327.32	2,475.02	3,094.30	184.51
52	0 1 1 0 1 0 0	36.54	56.93	114.89	66.30	383.98	163.45	166.15	2,077.89	3,066.12	-160.94
53	0 1 1 0 1 0 1	27.04	15.89	114.89	66.30	97.85	33.90	166.15	2,077.89	2,599.92	182.92
54	0 1 1 0 1 1 0	36.82	57.52	134.21	152.88	443.35	291.27	135.15	1,939.62	3,190.81	-416.72
55	0 1 1 0 1 1 1	27.30	21.97	134.21	152.88	89.97	40.61	135.15	1,939.62	2,541.70	13.78
56	0 1 1 1 0 0 0	21.47	38.50	69.62	74.00	134.10	198.59	162.78	1,225.48	1,924.54	98.64
57	0 1 1 1 0 0 1	15.83	26.01	69.62	74.00	80.01	28.14	162.78	1,225.48	1,681.87	290.09
58	0 1 1 1 0 1 0	19.83	37.11	38.42	62.68	357.09	179.27	141.35	671.68	1,507.42	147.54
59	0 1 1 1 0 1 1	16.14	13.84	38.42	62.68	84.58	33.53	141.35	671.68	1,062.22	422.92
60	0 1 1 1 1 0 0	31.15	42.29	107.23	65.03	147.17	199.06	140.78	1,019.10	1,751.80	14.65
61	0 1 1 1 1 0 1	8.90	33.20	107.23	65.03	67.97	27.89	140.78	1,019.10	1,470.10	250.59
62	0 1 1 1 1 1 0	30.24	42.86	158.29	116.92	293.93	179.67	128.02	977.30	1,927.22	-181.03
63	0 1 1 1 1 1 1	8.95	25.04	158.29	116.92	82.70	32.87	128.02	977.30	1,530.08	107.13
64	1 0 0 0 0 0 0	54.30	101.08	164.52	111.67	884.03	662.25	851.74	7,213.29	10,042.88	-1,436.50
65	1 0 0 0 0 0 1	25.98	21.58	164.52	111.67	150.30	69.29	851.74	7,213.29	8,608.37	-449.97
66	1 0 0 0 0 1 0	54.16	48.89	184.20	104.17	862.63	1,040.08	739.06	7,457.20	10,490.39	-1,506.29
67	1 0 0 0 0 1 1	25.76	19.77	184.20	104.17	128.07	76.06	739.06	7,457.20	8,734.30	-431.65
68	1 0 0 0 1 0 0	32.79	62.83	127.07	138.62	750.33	661.48	499.87	4,898.54	7,171.54	-972.75
69	1 0 0 0 1 0 1	12.70	31.72	127.07	138.62	169.70	69.35	499.87	4,898.54	5,947.56	-219.50
70	1 0 0 0 1 1 0	32.51	103.55	189.31	96.81	977.10	1,042.87	492.80	3,444.02	6,378.96	-1,441.02
71	1 0 0 0 1 1 1	12.42	34.98	189.31	96.81	105.32	76.51	492.80	3,444.02	4,452.16	-213.58
72	1 0 0 1 0 0 0	22.67	41.55	69.90	59.11	778.50	169.51	450.79	1,303.21	2,895.24	-190.77
73	1 0 0 1 0 0 1	13.20	13.91	69.90	59.11	103.23	66.81	450.79	1,303.21	2,080.17	216.49
74	1 0 0 1 0 1 0	22.18	48.60	80.11	79.51	208.90	327.17	270.80	1,290.01	2,327.28	-117.74
75	1 0 0 1 0 1 1	13.44	23.02	80.11	79.51	97.99	84.46	270.80	1,290.01	1,939.35	193.57
76	1 0 0 1 1 0 0	18.32	35.89	103.02	165.61	154.08	169.03	340.83	4,376.20	5,362.98	-233.41
77	1 0 0 1 1 0 1	12.34	27.25	103.02	165.61	122.14	66.12	340.83	4,376.20	5,213.51	-107.12
78	1 0 0 1 1 1 0	18.93	50.69	148.30	148.36	198.01	327.98	180.01	2,566.92	3,639.19	-344.69
79	1 0 0 1 1 1 1	12.19	33.60	148.30	148.36	106.35	85.68	180.01	2,566.92	3,281.41	-73.59
80	1 0 1 0 0 0 0	55.39	86.71	198.45	110.89	995.65	622.10	790.64	5,454.09	8,313.92	-1,380.64
81	1 0 1 0 0 0 1	14.52	24.93	198.45	110.89	144.08	68.09	790.64	5,454.09	6,805.69	-405.52
82	1 0 1 0 0 1 0	55.78	60.18	148.88	71.42	754.30	729.35	799.93	4,627.21	7,247.06	-1,118.58
83	1 0 1 0 0 1 1	15.33	19.88	148.88	71.42	129.54	50.78	799.93	4,627.21	5,862.97	-203.78
84	1 0 1 0 1 0 0	28.62	49.60	193.92	153.14	502.17	627.51	490.18	3,938.12	5,983.25	-920.01
85	1 0 1 0 1 0 1	8.66	38.20	193.92	153.14	138.42	67.78	490.18	3,938.12	5,028.43	-324.76
86	1 0 1 0 1 1 0	27.76	93.65	187.11	124.26	586.75	728.30	318.30	2,750.41	4,816.55	-1,002.70
87	1 0 1 0 1 1 1	8.74	22.85	187.11	124.26	118.93	50.17	318.30	2,750.41	3,580.78	-99.14

Nb.	Valid inequ.	CSPAR								Total sum	Perc. dev.
		01a	02a	03a	04a	01b	02b	03b	04b		
88	1 0 1 1 0 0 0	14.20	30.48	62.47	36.61	236.48	212.96	331.59	1,156.06	2,080.85	110.85
89	1 0 1 1 0 0 1	8.83	27.79	62.47	36.61	106.92	65.24	331.59	1,156.06	1,795.51	278.06
90	1 0 1 1 0 1 0	14.72	37.96	76.59	65.10	163.04	288.48	308.79	1,080.48	2,035.17	0.28
91	1 0 1 1 0 1 1	8.83	24.71	76.59	65.10	97.53	55.82	308.79	1,080.48	1,717.85	241.26
92	1 0 1 1 1 0 0	16.23	41.97	161.81	171.12	238.06	217.85	260.77	4,223.91	5,331.71	-387.48
93	1 0 1 1 1 0 1	8.22	27.19	161.81	171.12	115.90	67.19	260.77	4,223.91	5,036.10	-173.23
94	1 0 1 1 1 1 0	16.36	31.97	168.16	123.95	189.73	288.10	289.75	3,548.08	4,656.11	-317.77
95	1 0 1 1 1 1 1	8.84	22.16	168.16	123.95	105.54	56.72	289.75	3,548.08	4,323.20	-78.35
96	1 1 0 0 0 0 0	61.65	57.84	143.03	161.65	325.99	647.98	856.23	9,426.29	11,680.66	-1,232.92
97	1 1 0 0 0 0 1	22.96	23.04	143.03	161.65	166.34	67.99	856.23	9,426.29	10,867.52	-559.53
98	1 1 0 0 0 1 0	62.71	63.65	135.91	107.71	569.27	924.84	1,056.28	6,314.83	9,235.22	-1403.13
99	1 1 0 0 0 1 1	22.83	15.08	135.91	107.71	162.26	55.45	1,056.28	6,314.83	7,870.36	-402.60
100	1 1 0 0 1 0 0	36.98	67.61	142.17	109.51	371.80	645.39	471.02	2,538.29	4,382.77	-763.19
101	1 1 0 0 1 0 1	15.08	24.91	142.17	109.51	203.49	68.11	471.02	2,538.29	3,572.58	-110.38
102	1 1 0 0 1 1 0	36.44	71.80	160.79	173.07	653.95	923.59	358.10	2,968.22	5,345.97	-1,156.97
103	1 1 0 0 1 1 1	15.05	40.22	160.79	173.07	149.62	55.75	358.10	2,968.22	3,920.84	-234.52
104	1 1 0 1 0 0 0	19.34	33.76	49.90	82.83	456.22	192.75	367.91	1,855.65	3,058.35	-53.65
105	1 1 0 1 0 0 1	12.91	20.63	49.90	82.83	132.55	60.52	367.91	1,855.65	2,582.91	203.33
106	1 1 0 1 0 1 0	20.13	42.07	55.56	46.29	192.92	214.03	290.12	1,839.10	2,700.22	60.22
107	1 1 0 1 0 1 1	13.26	26.66	55.56	46.29	130.47	50.67	290.12	1,839.10	2,452.14	262.63
108	1 1 0 1 1 0 0	25.72	36.57	160.66	169.79	380.00	193.06	359.57	3,036.98	4,362.34	-419.09
109	1 1 0 1 1 0 1	13.55	25.91	160.66	169.79	145.20	60.38	359.57	3,036.98	3,972.03	-182.45
110	1 1 0 1 1 1 0	25.75	50.32	157.23	171.58	508.78	214.46	299.43	2,350.54	3,778.10	-472.92
111	1 1 0 1 1 1 1	13.05	24.54	157.23	171.58	144.19	50.82	299.43	2,350.54	3,211.38	-121.58
112	1 1 1 0 0 0 0	72.96	51.90	166.30	138.87	1,362.62	553.73	912.44	5,957.55	9,216.38	-1,432.39
113	1 1 1 0 0 0 1	19.70	20.35	166.30	138.87	161.03	67.02	912.44	5,957.55	7,443.27	-454.56
114	1 1 1 0 0 1 0	73.55	81.88	148.80	90.56	1,639.06	697.55	746.80	6,165.46	9,643.67	-1,564.41
115	1 1 1 0 0 1 1	19.36	18.46	148.80	90.56	151.97	52.43	746.80	6,165.46	7,393.84	-277.74
116	1 1 1 0 1 0 0	19.32	68.15	144.98	132.86	872.57	552.31	359.34	2,902.67	5,052.20	-823.75
117	1 1 1 0 1 0 1	10.18	32.28	144.98	132.86	154.60	66.86	359.34	2,902.67	3,803.77	-114.41
118	1 1 1 0 1 1 0	19.82	61.47	173.26	108.31	1,433.01	693.30	357.13	3,044.62	5,890.93	-1,099.76
119	1 1 1 0 1 1 1	10.05	38.32	173.26	108.31	153.57	52.62	357.13	3,044.62	3,937.89	-142.38
120	1 1 1 1 0 0 0	13.42	41.96	51.85	58.34	249.39	187.07	215.58	1,625.30	2,442.91	103.07
121	1 1 1 1 0 0 1	8.92	13.92	51.85	58.34	118.69	66.25	215.58	1,625.30	2,158.85	333.47
122	1 1 1 1 0 1 0	13.08	36.04	73.29	54.16	214.62	246.89	255.03	2,250.11	3,143.22	26.62
123	1 1 1 1 0 1 1	8.74	22.73	73.29	54.16	120.11	57.68	255.03	2,250.11	2,841.86	243.00
124	1 1 1 1 1 0 0	30.62	21.12	153.07	151.19	179.32	186.97	233.57	2,419.28	3,375.14	-205.20
125	1 1 1 1 1 0 1	10.61	17.32	153.07	151.19	124.57	66.38	233.57	2,419.28	3,176.00	-35.65
126	1 1 1 1 1 1 0	29.47	46.83	177.80	90.37	285.23	248.26	296.63	1,531.89	2,706.49	-312.17
127	1 1 1 1 1 1 1	10.13	24.45	177.80	90.37	129.99	57.77	296.63	1,531.89	2,319.03	-2.71

8 Conclusion

8.1 Summary

Well-considered and efficient crew planning is becoming more and more important, as cost pressure on companies increases and the role of personnel becomes more crucial due to the shortage of skilled workers. These developments can also be observed in the railway sector. Therefore this work dealt with an efficient and automated crew scheduling of conductors especially considering attendance rates. In contrast to the permanent accompaniment of trains, these stipulate that only a certain proportion of trains or train kilometers must be accompanied by a conductor. Similar problems arise in crew planning of security staff and mobile ticket control teams in long-distance and regional transportation. The aim was to create anonymous duties from individual trips in order to minimize costs for the whole shift schedule and meet attendance rates. In addition, operational, legal, tariff-based and contractual requirements had to be observed.

In this work, the research questions formulated in Section 1.3 were answered successfully. The first research question **Q1**¹ asks for the current state of research in the field of railway crew scheduling. The comprehensive literature review of 123 articles in Chapter 3 showed that slightly more than 80% of the literature considers the planning step of crew scheduling separately. Only few articles tackle integrated approaches, for example crew scheduling simultaneously with crew rostering (18 articles). When dividing the reviewed publications into different transport modes, most of the articles can be assigned to rail passenger transport, of which 17 discuss cases in urban transportation, 15 in long-distance, 9 in regional and 31 consider several modes. Only about one fifth study models or solution approaches for crew scheduling in rail freight transport. Another insight was that railway crew scheduling problems are typically formulated as mixed integer problems. More than half of the researchers apply set covering formulations of the problem, less than a quarter uses set partitioning formulations. Only 12 of 123 articles model the problem as arc flow in a multi-commodity flow network. In most cases, the objective function of these models is the efficiency of the shift schedule, measured by various parameters, such as total cost, total number of duties or total idle time. The

¹ What is the current state of research for railway crew scheduling problems and which research gaps can be identified?

reviewed articles also indicate a tendency towards solution algorithms. A large majority of researchers uses column generation techniques (50 articles) or meta-heuristics (32 articles). Since most research activities are motivated by real-world problems of railway operators and aim at developing new applications to support the crew planners' work, the appendix of the review gave an overview of existing decision support systems.

This structured and extensive review enabled the identification of various research gaps. At this point we present only the research gap motivating this work. All further ones are discussed in detail at the end of this chapter. The categorization of 123 articles indicated that almost all researchers take the train driver as subject of their considerations. In many cases, conductors are included or drivers and conductors build a permanent team (crew). Besides articles of this work only two other articles focus on crew scheduling models and solution approaches solely for conductors, but without considering attendance rates that are becoming more and more important in Germany.²

In order to answer research question **Q2**³, we analyzed planning processes in regional rail passenger transport, outlined operational, legal as well as tariff-based requirements and studied the subject of attendance rates in detail. From the literature research resulted that it is promising to model crew scheduling problems as set covering formulations. Accordingly, we integrated the new constraints of attendance rates into a set covering formulation in Chapter 4. Therefore, a set of additional variables had to be introduced to model the attendance rate restrictions. However, the set covering constraints had to be modified because they now act as linking constraints between the old set covering variables and the new ones. First computer-aided tests on the basis of a small sample instance showed that a solution that includes attendance rates from scratch outperforms the semi-manual planning approach applied in practice. A cost reduction of more than 40% was achieved.

The solution method developed in Chapter 4, which consists of a duty-generation phase and a duty-selection phase, was not applicable for large real-world instances, since a pre-generation of all duties is not efficient or even not possible. Therefore, we developed a hybrid solution approach using column generation techniques in Chapter 5 to answer research question **Q3**⁴. The railway crew scheduling model was decomposed into a master and a pricing problem. In the restricted master problem the linear programming relaxation of the model was solved to optimality by Gurobi Optimizer with respect to a small set of duties. Starting with an initial schedule duties obtained in the pricing problem were added iteratively to the restricted master problem to improve its objective

² The literature review in Chapter 3 already contains the articles of Chapter 5-7.

³ How can railway crew scheduling problems with attendance rates for conductors be modeled?

⁴ How can instances of railway crew scheduling problems with attendance rates be solved with regard to real-world requirements?

function value (total cost). Thereby, the initial schedule was generated using depth-first search in a block generator. For the solution of the pricing problem we evolved a specialized genetic algorithm. The individual components of the genetic algorithm, such as initial schedule generation, fitness function, crossover, mutation or selection for replacement, were adapted extensively to the duty generation. If no cost-improving duty could be generated, Gurobi Optimizer was used to obtain an integer solution to the initial problem.

The developed hybrid algorithm was tested on a real-world instance of medium size with various input parameters for the genetic algorithm. A simple two-phase approach, which uses a depth-first search to generate feasible duties and selects the optimal solution using Gurobi Optimizer, served as a comparison for computing time and solution quality. In many cases the hybrid solution approach obtained better results in less time in comparison with the simple two-phase approach.

After both a suitable model and a solution approach for a standard day have been developed, research question **Q4**⁵ asks for an extension of the planning period to several days. By introducing additional sets and variables, Chapter 6 showed that we could easily transfer the model to a multiple day period. In this context, further restrictions were implemented, such as upper and lower bounds for the average paid time, capacity of crew bases or mandatory trips. By considering several days, it was now possible to model another condition relevant in practice: a uniform distribution of the attended trips over the planning period to avoid a predictable or imbalanced appearance of conductors on trains. The adaptation of the hybrid solution algorithm to a planning period of several days was much more difficult. Since we were dealing with multiple but independent days (all duties contain trips of one day solely), there was one pricing problem for each day of the planning period. Starting with an initial schedule for the whole planning period the developed algorithm solved the restricted master problem using Gurobi Optimizer. Afterwards, the specialized genetic algorithm generated new duties for day 1 of the planning period (pricing problem). Cost-improving duties were added to the restricted master problem. As trips can occur on various days, it was expedient in terms of computational efficiency to check whether some of the generated duties are feasible and cost-improving on other days. If so, these were also added to the restricted master problem. This procedure was performed subsequently for each day of the planning period. Reaching the last day, the algorithm returned to the first day. Iteration ended if no new cost-improving duty was found for any day in the planning period. Again, we used Gurobi Optimizer to generate an integer solution to the initial problem.

⁵ How can the developed mathematical model and hybrid solution approach be extended to a multiple day period? What is the potential of an integrated approach in contrast to the sequential day-by-day approach?

The computational experiments were based on three real-world instances representing networks of regular size for regional transport. Different sets of attendance rates were required for the selected instances, e.g. daytime and line-dependent attendance rates or mandatory trips. For all instances, four different solution approaches were compared with regard to objective function and computing time. First, the model of a standard day presented in Chapter 5 was used. All generated daily schedules were merged to a joint schedule for the whole planning horizon and objective values as well as computation times were summed up. The developed multiple day approach, initially without and then with uniform distribution of the trips, represented the second and third solution approach. Finally, the gained schedule was compared to the semi-manual planning approach applied in practice taking into account the uniform distribution.

Excluding the uniform distribution of the attended trips, the integrated approach resulted in an average improvement of between 2.14% and 4.72% compared to the sequential day-by-day approach. The integrated approach is beneficial, because the attendance rates do not have to be met for each individual day, but can be compensated by accompanying additional trips on other days. The comparison of the test results with uniform distribution was even more significant. The developed multi-period hybrid solution approach achieved average cost reductions of between 15.5% and 35.3% compared to the semi-manual planning approach.

In contrast to the previous path-based approach, research question **Q5**⁶ asks for an arc-flow formulation of the problem. This question was answered positively in Chapter 7. The specification of a directed graph with nodes characterized by the departure or arrival of a trip and arcs representing valid connections of these nodes allowed the definition of a suitable model. In addition, the resources duty time, protected working time and possible break time were introduced, whose consumption varies depending on the arc type.

Tests have shown that this model solved by Gurobi Optimizer only provides optimal solutions in reasonable time for small instances. Furthermore, it could be used to provide lower bounds and to improve heuristic solutions for large real-world problems. To strengthen the linear formulation and, therefore, improve the bounds yielded from the relaxation valid inequalities were proposed. Computational tests have shown that the applied valid inequalities can fasten the solution process for the integer problem, i.e. prune Branch-and-Bound nodes and support integer-feasibility of a node's linear relaxation. The valid inequalities defined in this work were divided into four groups: model specific valid inequalities, symmetry breaking constraints, constraints affecting parallel

⁶ Can an arc-flow formulation of the railway crew scheduling problem with attendance rates be used to evaluate or even enhance the solution quality of the previous approach? Can valid inequalities improve the performance of the arc-flow formulation concerning computing times and lower bounds?

arcs and fixed arcs. For small-sized instances a reasonable selection of valid inequalities reduced computing time by up to 94.8%. On average, a reduction of 31% to 86% was achieved depending on the test instance. Further tests with medium- and large-sized instances showed that the values of the linear relaxations, i.e. lower bounds, could be improved by up to 3% and the gap between best objective values and lower bounds could be reduced by up to 7.2%.

Based on the test results presented in Chapter 4-6, it is obvious that the complex hybrid solution algorithm developed with the help of operations research techniques enables practical, (near-)optimal solutions. The developed approach forms the basis of a decision support tool called SINA, used in practice by DB Regio AG. To the best of our knowledge, there was no software solution that provided crew scheduling solutions considering attendance rates until the start of our developments. The hybrid solution approach, which was refined by our research group based on the approach developed in this work, and its application was selected as one of the six finalists of the EURO Excellence in Practice Award 2019 that acknowledges outstanding accomplishments in the practice of operations research.

8.2 Future research

Even though many questions from the field of railway crew scheduling with attendance rates have been answered successfully in this work, interesting directions are arising for future research areas. Due to increasing computing capacities in terms of memory and speed, further emerging requirements from practice can be integrated into existing models. It has to be assessed whether an integration really creates added value for research and practice. For the developed hybrid algorithm of column generation techniques and genetic algorithm the functionality of the individual modules should be scrutinized. For example, alternative methods should be tested for the generation of initial schedules in order to obtain the best possible feasible duties. During column generation, it should be checked whether deleting unfavorable duties (that are not part of the solution for several iterations) from the restricted master problem increases the efficiency of the algorithm. Diversification of crossover and mutation operators, as well as the way of selection or other termination criteria are possible. Furthermore, there are different acceleration strategies. On the one hand, heuristic approaches, such as variable fixing, can fasten the solution of the integer problem. On the other hand, it should be checked whether the pricing problems of the individual days can be performed in parallel in the case of multiple-day problems.

Combining both models, path-flow and arc-flow formulation, can move large instances

(large transport network, long planning period) closer to the optimal solution. On the one hand, a possibly suboptimal solution from the developed hybrid algorithm can be used as initial solution for the arc-flow model. In this case, we obtain an optimal integer solution if the model is solvable. On the other hand, the model can be integrated into the column generation approach. If the algorithm cannot find new cost-improving duties in the pricing problem, a subset of the model constraints can prove that there is no such additional duty or generate new ones. Hence, we get the optimal solution of the linear relaxation and, most commonly, a near-optimal integer solution. In this work the arc-flow model was solved using Gurobi Optimizer. In literature similar problems such as resource-constrained shortest path problems are often solved using dynamic optimization. A transfer of the solution mechanisms seems difficult because there are no good dominance criteria for eliminating paths. Future research should focus on a solution detached from commercial solvers.

At strategic and tactical level of railway crew scheduling current developments must be observed and incorporated. The integrated scheduling of several planning steps, such as rolling stock scheduling, crew scheduling and crew rostering, should be further advanced. Due to smaller problem sizes and a different cost structure, i.e. personnel costs account for a larger share of the total costs, bus transportation offers considerably more integrated planning approaches. In order to achieve cost savings, vehicles and personnel are often planned simultaneously in one planning step. In future studies, it will be necessary to check whether integrated planning in the railway sector is reasonable and possible in terms of problem size and computing capacity and whether it is suitable to transfer approaches from bus transport. Success factors such as robustness or employee and customer satisfaction should be further disseminated in mathematical models or solution algorithms. Robustness refers to the ability of a shift schedule to react to disruptions with as few changes as possible. To increase employee satisfaction, railway companies can offer their employees to choose their preferred trips, working hours, days off and possibly even crew members.

Despite the complexity of railway crew scheduling problems, research will continue in the following years to solve very large instances in reasonable time. The increasing competition in the private railway sector and the public pressure on state-owned companies require (near-)optimal and robust solutions. Furthermore, tests of different input parameters and their verification are possible with faster solution methods. The information gained from the tests could also be used to recommend changes to the operating model and improvements to railway transportation to satisfy the needs of customers, operators and staff. Moreover, algorithms capable of recognizing patterns in large data sets, e.g., machine learning techniques, could be used to obtain new insights into crew scheduling

from historical personnel planning data.

The railway sector, like many other transport sectors, is constantly changing, influenced by politics, people's attitudes (e.g. environmental movement) and other factors. The size and characteristics of transport networks are changing, in the same way as operational and tariff-based requirements. Since most publications on crew scheduling are motivated by real industrial cases, research must also adapt to the needs of the railway industry. The topic of digitization in rail transport is also progressing more and more. Depending on the degree of implementation, this can mean, for example, a selection of preferred duties by app (employee) or travel without ticket control in long-distance traffic (customer). Accordingly, there is a need for further research in the development of new operating models, applications and interfaces that will enable these goals to be achieved.

A Declarations of authorship

Fakultät Wirtschaftswissenschaften Lehrstuhl für BWL, insb. Industrielles Management, Prof. Dr. Udo Buscher

Declaration of authorship of a publication

Title Railway crew scheduling: Models, methods and applications
Invited review submitted to *European Journal of Operational Research*;
current status: Available online 12 June 2019

The aforementioned publication is written in collaboration by the following authors:

Author 1: Julia Heil (JH)
Author 2: Kirsten Hoffmann (KH)
Author 3: Udo Buscher (UB)

The individual contribution of each participating author is stated in the table hereinafter. Underlined initials, if any, indicate authors with a major share in the respective field.

Establishing of research topic	JH, KH, UB
Literature review	JH, KH
Conducting of research	JH, KH
Appraisal and interpretation of results	JH, KH
Publication strategy	UB
Writing of manuscript	JH, KH
Pre-review and lectorship	JH, KH, UB

By their signature, the authors declare their agreement with the above statement.

 Author 1

 Author 2

Dresden, 18 November 2019

 Author 3

Postadresse (Briefe)
TU Dresden, 01062 Dresden

Postadresse (Pakete u.ä.)
TU Dresden
Helmholtzstraße 10
01069 Dresden

Besucheradresse:
Helmholtzstr. 10
Hülse-Bau
Zimmer N 503

Zufahrt
Seiteneingang,
gezeichnete Park-
fläche im Innenhof

DRESDEN
concept
Exzellenz aus
Wissenschaft
und Kultur

Kein Zugang für elektronisch signierte sowie verschlüsselte elektronische Dokumente.

Internet
<http://tu-dresden.de>

**TECHNISCHE
UNIVERSITÄT
DRESDEN**

Fakultät Wirtschaftswissenschaften Lehrstuhl für BWL, insb. Industrielles Management, Prof. Dr. Udo Buscher

Declaration of authorship of a publication

Title	Solving practical railway crew scheduling problems with attendance rates
In	<i>Business & Information Systems Engineering</i> 59 (2017), no. 3, pp. 147-159

The aforementioned publication is written in collaboration by the following authors:

Author 1: Kirsten Hoffmann (KH)
 Author 2: Udo Buscher (UB)
 Author 3: Janis S. Neufeld (JN)
 Author 4: Felix Tamke (FT)

The individual contribution of each participating author is stated in the table hereinafter. Underlined initials, if any, indicate authors with a major share in the respective field.

Establishing of research topic	KH
Literature review	UB
Conducting of research	<u>KH</u> , FT
Appraisal and interpretation of results	JN, FT
Publication strategy	UB
Writing of manuscript	KH, UB, JN, FT
Pre-review and lectorship	KH

By their signature, the authors declare their agreement with the above statement.

Dresden, 14 November 2019

Author 1	Author 2	Author 3	Author 4

Postadresse (Briefe)
TU Dresden, 01062 Dresden

Postadresse (Pakete u.ä.)
TU Dresden
Helmholtzstraße 10
01069 Dresden

Besucheradresse:
Helmholtzstr. 10
Hülse-Bau
Zimmer N 503

Zufahrt
Seiteneingang,
gekennzeichnete Park-
fläche im Innenhof

**DRESDEN
concept**
Exzellenz aus
Wissenschaft
und Kultur

Kein Zugang für elektronisch signierte sowie verschlüsselte elektronische Dokumente.

Internet
<http://tu-dresden.de>

**TECHNISCHE
UNIVERSITÄT
DRESDEN**

Fakultät Wirtschaftswissenschaften Lehrstuhl für BWL, insb. Industrielles Management, Prof. Dr. Udo Buscher

Declaration of authorship of a publication

Title	Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates
In	<i>Computers & Industrial Engineering</i> 127 (2019), pp. 1143-1152

The aforementioned publication is written in collaboration by the following authors:

Author 1: Kirsten Hoffmann (KH)

Author 2: Udo Buscher (UB)

The individual contribution of each participating author is stated in the table hereinafter. Underlined initials, if any, indicate authors with a major share in the respective field.

Establishing of research topic	KH
Literature review	KH
Conducting of research	KH
Appraisal and interpretation of results	KH
Publication strategy	KH
Writing of manuscript	KH
Pre-review and lectorship	KH, UB

By their signature, the authors declare their agreement with the above statement.

Dresden, 14 November 2019

Author 1

Author 2

Postadresse (Briefe)
TU Dresden, 01062 Dresden

Postadresse (Pakete u.ä.)
TU Dresden
Helmholtzstraße 10
01069 Dresden

Besucheradresse:
Helmholtzstr. 10
Hülse-Bau
Zimmer N 503

Zufahrt
Seiteneingang,
gekennzeichnete Park-
fläche im Innenhof

**DRESDEN
concept**
Exzellenz aus
Wissenschaft
und Kultur

Kein Zugang für elektronisch signierte sowie verschlüsselte elektronische Dokumente.

Internet
<http://tu-dresden.de>

Bibliography

- ABBINK, E. J. W. (2014): Crew Management in Passenger Rail Transport. Ph. D thesis, Erasmus University Rotterdam.
- ABBINK, E. J. W. ET AL. (2011): Solving large scale crew scheduling problems in practice. In: *Public Transport*, Vol. 3, No. 2, pp.149–164.
- ABBINK, E. J. W. ET AL. (2005): Reinventing Crew Scheduling at Netherlands Railways. In: *Interfaces*, Vol. 35, No. 5, pp.393–401.
- ABBINK, E. J. W. / HUISMAN, D. / KROON, L. (2018): Railway Crew Management. In: BORNDÖRFER, R. ET AL. (EDS.): *Handbook of Optimization in the Railway Industry*. Springer International Publishing, pp.243–264.
- ABBINK, E. J. W. / WOUT, J. V. / HUISMAN, D. (2007): Solving Large Scale Crew Scheduling Problems by using Iterative Partitioning. In: LIEBCHEN, C. / AHUJA, R. K. / MESA, J. A. (EDS.): *ATMOS 2007*. Leibniz Centre for Informatics, pp.96–106.
- ADULYASAK, Y. / CORDEAU, J. / JANS, R. (2014): Formulations and Branch-and-Cut Algorithms for Multivehicle Production and Inventory Routing Problems. In: *INFORMS Journal on Computing*, Vol. 26, No. 1, pp.103–120.
- AKEN, J. E. v. (2004): Management Research Based on the Paradigm of the Design Sciences: The Quest for Field-Tested and Grounded Technological Rules. In: *Journal of Management Studies*, Vol. 41, No. 2, pp.219–246.
- ALBERS, M. (2009): Freight railway crew scheduling: models, methods, and applications. Logos Verlag Berlin.
- ALEFRAGIS, P. ET AL. (2000): Parallel Integer Optimization for Crew Scheduling. In: *Annals of Operations Research*, Vol. 99, No. 1-4, pp.141–166.
- ALEFRAGIS, P. ET AL. (1998): Parallel crew scheduling in PAROS. In: PRITCHARD, D. / REEVE, J. (EDS.): *Parallel Processing: 4th International Euro-Par Conference*. Springer Berlin Heidelberg, pp.1104–1113.

- ALFIERI, A. / KROON, L. / VELDE, S. VAN DE (2007): Personnel scheduling in a complex logistic system: a railway application case. In: *Journal of Intelligent Manufacturing*, Vol. 18, No. 2, pp. 223–232.
- AMAYA, J. / URIBE, P. (2018): A model and computational tool for crew scheduling in train transportation of mine materials by using a local search strategy. In: *TOP*, Vol. 26, No. 3, pp. 383–402.
- AMBERG, B. / AMBERG, B. / KIEWER, N. (2019): Robust Efficiency in Urban Public Transportation: Minimizing Delay Propagation in Cost-Efficient Bus and Driver Schedules. In: *Transportation Science*, Vol. 53, No. 1, pp. 89–112.
- ARABEYRE, J. P. ET AL. (1969): The Airline Crew Scheduling Problem: A Survey. In: *Transportation Science*, Vol. 3, No. 2, pp. 140–163.
- AYDEMIR-KARADAG, A. / DENGIZ, B. / BOLAT, A. (2013): Crew pairing optimization based on hybrid approaches. In: *Computers & Industrial Engineering*, Vol. 65, No. 1, pp. 87–96.
- BACH, L. / DOLLEVOET, T. / HUISMAN, D. (2016): Integrating Timetabling and Crew Scheduling at a Freight Railway Operator. In: *Transportation Science*, Vol. 50, No. 3, pp. 878–891.
- BALAKRISHNAN, A. / KUO, A. / SI, X. (2016): Real-Time decision support for crew assignment in double-ended districts for U.S. freight railways. In: *Transportation Science*, Vol. 50, No. 4, pp. 1337–1359.
- BANIHASHEMI, M. / HAGHANI, A. (2001): A New Model for the Mass Transit Crew Scheduling Problem. In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 1–15.
- BARNHART, C. ET AL. (2003): Airline Crew Scheduling. In: HALL, R. W. (ED.): *Handbook of Transportation Science*. Springer US, pp. 517–560.
- BARNHART, C. ET AL. (1998): Branch-and-Price: Column Generation for Solving Huge Integer Programs. In: *Operations Research*, Vol. 46, No. 3, pp. 316–329.
- BEASLEY, J. E. / CAO, B. (1996): A tree search algorithm for the crew scheduling problem. In: *European Journal of Operational Research*, Vol. 94, No. 3, pp. 517–526.
- BEASLEY, J. E. / CHRISTOFIDES, N. (1989): An algorithm for the resource constrained shortest path problem. In: *Networks*, Vol. 19, No. 4, pp. 379–394.

- BENDERS, J. F. (1962): Partitioning procedures for solving mixed-variables programming problems. In: *Numerische Mathematik*, Vol. 4, No. 1, pp. 238–252.
- BENGTSOON, L. ET AL. (2007): Railway Crew Pairing Optimization. In: GERAETS, F. ET AL. (EDS.): *Algorithmic Methods for Railway Optimization*. Springer Berlin Heidelberg, pp. 126–144.
- BERGH, J. VAN DEN ET AL. (2013): Personnel scheduling: a literature review. In: *European Journal of Operational Research*, Vol. 226, No. 3, pp. 367–385.
- BLAIS, J.-Y. / ROUSSEAU, J.-M. (1988): Overview of HASTUS Current and Future Versions. In: DADUNA, J. R. / WREN, A. (EDS.): *Computer-Aided Transit Scheduling: 4th International Workshop on Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 175–187.
- BORNDÖRFER, R. / GRÖTSCHER, M. / LÖBEL, A. (2001): Scheduling Duties by Adaptive Column Generation. Konrad-Zuse-Zentrum für Informationstechnik Berlin – Technical report.
- BORNDÖRFER, R. / GRÖTSCHER, M. / PFETSCH, M. E. (2007): A column-generation approach to line planning in public transport. In: *Transportation Science*, Vol. 41, No. 1, pp. 123–132.
- BORNDÖRFER, R. ET AL. (2016): Optimal duty rostering for toll enforcement inspectors. In: *Annals of Operations Research*, Vol. 252, No. 2, pp. 383–406.
- BORNDÖRFER, R. ET AL. (2017): Integration of duty scheduling and rostering to increase driver satisfaction. In: *Public Transport*, Vol. 9, No. 1, pp. 177–191.
- BOSCHETTI, M. A. / MINGOZZI, A. / RICCIARDELLI, S. (2004): An exact algorithm for the simplified Multiple Depot Crew Scheduling Problem. In: *Annals of Operations Research*, Vol. 127, No. 1-4, pp. 177–201.
- BUNDESNETZAGENTUR (2019): Jahresbericht 2018. $\langle$ URL: https://www.bundesnetzagentur.de/SharedDocs/Downloads/DE/Allgemeines/Bundesnetzagentur/Publikationen/Berichte/2019/JB2018.pdf?__blob=publicationFile&v=5 $\rangle$ – visited on October 10, 2019.
- BUNGE, M. (1985): Treatise on Basic Philosophy, Part II Life Science, Social Science and Technology. Volume 7, Treatise on Basic Philosophy. Springer Netherlands.
- CABRERA, G. G. / RUBIO, J. M. L. (2009): Hybrid algorithm of tabu search and integer programming for the railway crew scheduling problem. In: *2nd Asia-Pacific*

- Conference on Computational Intelligence and Industrial Applications*. Volume 2, IEEE, pp. 413–416.
- CACCHIANI, V. ET AL. (2014): An overview of recovery models and algorithms for real-time railway rescheduling. In: *Transportation Research Part B: Methodological*, Vol. 63, pp. 15–37.
- CACCHIANI, V. / SALAZAR-GONZÁLEZ, J.-J. (2017): Optimal Solutions to a Real-World Integrated Airline Scheduling Problem. In: *Transportation Science*, Vol. 51, No. 1, pp. 250–268.
- CACCHIANI, V. / TOTH, P. (2018): Robust Train Timetabling. In: BORNDÖRFER, R. ET AL. (EDS.): *Handbook of Optimization in the Railway Industry*. Springer International Publishing, pp. 93–115.
- CADARSO, L. / MARÍN, Á. (2012): Integration of timetable planning and rolling stock in rapid transit networks. In: *Annals of Operations Research*, Vol. 199, No. 1, pp. 113–135.
- CAPRARA, A. (2015): Timetabling and assignment problems in railway planning and integer multicommodity flow. In: *Networks*, Vol. 66, No. 1, pp. 1–10.
- CAPRARA, A. ET AL. (1999): Solution of Large-Scale Railway Crew Planning Problems: the Italian Experience. In: WILSON, N. H. M. (ED.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp. 1–18.
- CAPRARA, A. / FISCHETTI, M. / TOTH, P. (1999): A Heuristic Method for the Set Covering Problem. In: *Operations Research*, Vol. 47, pp. 730–743.
- CAPRARA, A. ET AL. (1997): Algorithms for railway crew management. In: *Mathematical Programming*, Vol. 79, pp. 125–141.
- CAPRARA, A. ET AL. (2007): Passenger Railway Optimization. In: BARNHART, C. / LAPORTE, G. (EDS.): *Transportation*. Elsevier, Handbooks in Operations Research and Management Science, pp. 129–187.
- CAPRARA, A. / MONACI, M. / TOTH, P. (2001): A Global Method for Crew Planning in Railway Applications. In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 17–36.
- CARRARESI, P. / GALLO, G. (1984): Network models for vehicle and crew scheduling. In: *European Journal of Operational Research*, Vol. 16, No. 2, pp. 139–151.

- CEDER, A. / HASSOLD, S. (2015): Applied analysis for improving rail-network operations. In: *Journal of Rail Transport Planning & Management*, Vol. 5, No. 2, pp. 50–63.
- CHAHAR, K. / CHENG, C. / PRANOTO, Y. (2011): Strategic crew planning tool in railroad: a discrete event simulation. In: JAIN, S. ET AL. (EDS.): *Winter Simulation Conference*. IEEE, pp. 3688–3698.
- CHEN, S. / SHEN, Y. (2013): An improved column generation algorithm for crew scheduling problems. In: *Journal of Information & Computational Science*, Vol. 10, No. 1, pp. 175–183.
- CHEN, S. ET AL. (2013): A Crew Scheduling with Chinese Meal Break Rules. In: *Journal of Transportation Systems Engineering and Information Technology*, Vol. 13, No. 2, pp. 90–95.
- CHEW, K. ET AL. (2001): An Optimization Based Approach to the Train Operator Scheduling Problem at Singapore MRT. In: *Annals of Operations Research*, Vol. 108, No. 1, pp. 111–122.
- CLAUSEN, J. (2007): Applied Railway Optimization in Production Planning at DSB S-togtasks, tools and challenges. In: LIEBCHEN, C. / AHUJA, R. K. / MESA, J. A. (EDS.): *ATMOS 2007*. Leibniz Centre for Informatics, pp. 15–29.
- CLAUSEN, U. / BAUDACH, J. (2008): Crew Scheduling as one Part of Optimal Resource Allocation in Railway Freight Transportation. In: *DSOR-Beiträge zur Wirtschaftsinformatik 5*. Leibniz Center for Economics, pp. 89–103.
- COELHO, L. C. / LAPORTE, G. (2014): Improved solutions for inventory-routing problems through valid inequalities and input ordering. In: *International Journal of Production Economics*, Vol. 155, No. C, pp. 391–397.
- DALAL, M. A. / JENSEN, L. P. (2001): Simulation modeling at Union Pacific Railroad. In: PETERS, B. A. ET AL. (EDS.): *Winter Simulation Conference*. IEEE, pp. 1048–1055.
- DANTZIG, G. B. / THAPA, M. N. (2003): *Linear Programming 2: Theory and Extensions*. Springer, New York, NY.
- DANTZIG, G. B. / WOLFE, P. (1960): Decomposition Principle for Linear Programs. In: *Operations Research*, Vol. 8, No. 1, pp. 101–111.

- DAUZÈRE-PÉRÈS, S. ET AL. (2015): A Lagrangian heuristic framework for a real-life integrated planning problem of railway transportation resources. In: *Transportation Research Part B: Methodological*, Vol. 74, No. Supplement C, pp.138–150.
- DB REGIO AG (2012): Geschäftsbericht 2012. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2012/Berichte/2012_gb_dbregio_de-data.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2012/Berichte/2012_gb_dbregio_de-data.pdf) – visited on September 23, 2019.
- DB REGIO AG (2013): Geschäftsbericht 2013. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2013/Berichte/2013_gb_dbregio_de-data.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2013/Berichte/2013_gb_dbregio_de-data.pdf) – visited on September 23, 2019.
- DB REGIO AG (2014): Geschäftsbericht 2014. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2014/Berichte/2014_gb_dbregio_de.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2014/Berichte/2014_gb_dbregio_de.pdf) – visited on September 23, 2019.
- DB REGIO AG (2015): Geschäftsbericht 2015. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2015/Berichte/Geschaeftsbericht_2015_-_DB_Regio_AG.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2015/Berichte/Geschaeftsbericht_2015_-_DB_Regio_AG.pdf) – visited on September 23, 2019.
- DB REGIO AG (2016a): Geschäftsbericht 2016. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2016/Berichte/Geschaeftsbericht_2016_-_DB_Regio_AG.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2016/Berichte/Geschaeftsbericht_2016_-_DB_Regio_AG.pdf) – visited on September 23, 2019.
- DB REGIO AG (2016b): Geschäftsbericht 2016. [⟨URL: https://www.dbregio.de/db_regio/view/mdb/db_regio/unternehmen/mdb_250629_2016_gb_dbregio.pdf⟩](https://www.dbregio.de/db_regio/view/mdb/db_regio/unternehmen/mdb_250629_2016_gb_dbregio.pdf) – visited on September 23, 2019.
- DB REGIO AG (2017): Geschäftsbericht 2017. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2017/Berichte/Geschaeftsbericht_2017_-_DB_Regio_AG.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2017/Berichte/Geschaeftsbericht_2017_-_DB_Regio_AG.pdf) – visited on September 23, 2019.
- DB REGIO AG (2018): Geschäftsbericht 2018. [⟨URL: https://ir.deutschebahn.com/fileadmin/Deutsch/2018/Berichte/DB18_Regio_web_02.pdf⟩](https://ir.deutschebahn.com/fileadmin/Deutsch/2018/Berichte/DB18_Regio_web_02.pdf) – visited on September 23, 2019.
- DE GROOT, S. / HUISMAN, D. (2008): Vehicle and crew scheduling: Solving large real-world instances with an integrated approach. In: *Lecture Notes in Economics and Mathematical Systems*, Vol. 600, pp.43–56.
- DERIGS, U. / MALCHEREK, D. / SCHÄFER, S. (2010): Supporting strategic crew management at passenger railways – model, method and system. In: *Public Transport*, Vol. 2, No. 4, pp.307–334.

- DESAULNIERS, G. (2007): Managing large fixed costs in vehicle routing and crew scheduling problems solved by column generation. In: *Computers & Operations Research*, Vol. 34, No. 4, pp.1221–1239.
- DESAULNIERS, G. / DESROSIERS, J. / SOLOMON, M. (2002): Accelerating Strategies in Column Generation Methods for Vehicle Routing and Crew Scheduling Problems. In: RIBEIRO, C. C. / HANSEN, P. (EDS.): *Essays and Surveys in Metaheuristics*. Springer US, pp.309–324.
- DESAULNIERS, G. / HICKMAN, M. D. (2007): Public Transit. In: BARNHART, C. / LAPORTE, G. (EDS.): *Transportation*. Elsevier, pp.69–127.
- DESROCHERS, M. ET AL. (1992): CREW-OPT: Subproblem Modeling in a Column Generation Approach to Urban Crew Scheduling. In: DESROCHERS, M. / ROUSSEAU, J.-M. (EDS.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp.395–406.
- DESROCHERS, M. / SOUMIS, F. (1989): A column generation approach to the urban transit crew scheduling problem. In: *Transportation Science*, Vol. 23, No. 1, pp.1–13.
- DESROSIERS, J. ET AL. (1995): Time constrained routing and scheduling. In: BALL, M. ET AL. (EDS.): *Network Routing*. Elsevier, pp.35–139.
- DESROSIERS, J. / LÜBBECKE, M. E. (2005): A primer in column generation. In: DESAULNIERS, G. / DESROSIERS, J. / SOLOMON, M. M. (EDS.): *Column Generation*. Springer US, pp.1–32.
- DEUTSCHES INSTITUT FÜR WIRTSCHAFTSFORSCHUNG DIW BERLIN (2013): Verkehr in Zahlen 2012/2013. Volume 41, DVV Media Group GmbH, Hamburg: Bundesministerium für Verkehr, Bau und Stadtentwicklung.
- DEVECI, M. / DEMIREL, N. Ç. (2018): A survey of the literature on airline crew scheduling. In: *Engineering Applications of Artificial Intelligence*, Vol. 74, pp.54–69.
- DJELLAB, H. / BIONNIER, J. (2011): CARACO: a solution for crew planning problems, the French freight experience. In: *9th World Congress on Railway Research, Challenge C: Increasing Freight capacity and services*. SNCF, pp.1–8.
- DORNBERGER, R. / FREY, L. / SCHMID, C. (2007): Use of a genetic algorithm in a distributed resource management software. In: *IEEE Congress on Evolutionary Computation*. IEEE, pp.2428–2434.

- ELIZONDO, R. ET AL. (2010): An evolutionary and constructive approach to a crew scheduling problem in underground passenger transport. In: *Journal of Heuristics*, Vol. 16, No. 4, pp. 575–591.
- ERNST, A. T. ET AL. (2001): An Integrated Optimization Model for Train Crew Management. In: *Annals of Operations Research*, Vol. 108, No. 1, pp. 211–224.
- ERNST, A. ET AL. (2004a): An Annotated Bibliography of Personnel Scheduling and Rostering. In: *Annals of Operations Research*, Vol. 127, No. 1, pp. 21–144.
- ERNST, A. ET AL. (2004b): Staff scheduling and rostering: A review of applications, methods and models. In: *European Journal of Operational Research*, Vol. 153, No. 1, pp. 3–27.
- FENG, Z. / RUIHUA, X. (2010): Study on model and algorithm for urban rail transit crew scheduling system. In: *International Conference on Computer Design and Applications*. IEEE, pp. 213–216.
- FISCHETTI, M. ET AL. (2001): A Polyhedral Approach to Simplified Crew Scheduling and Vehicle Scheduling Problems. In: *Management Science*, Vol. 47, No. 6, pp. 833–850.
- FOLKMANN, M. / JESPERSEN, J. / NIELSEN, M. N. (2007): Estimates on Rolling Stock and Crew in DSB S-tog Based on Timetables. In: GERAETS, F. ET AL. (EDS.): *Algorithmic Methods for Railway Optimization*. Springer Berlin Heidelberg, pp. 91–107.
- FORES, S. / PROLL, L. (1998): Driver scheduling by integer linear programming: the TRACS II approach. In: BORNE, P. / KSOURI, M. / EL KAMEL, A. (EDS.): *Computational Engineering in Systems Applications. Symposium on Industrial and Manufacturing Systems*. CESA, pp. 213–218.
- FORES, S. / PROLL, L. / WREN, A. (2002): TRACS II: a hybrid IP/heuristic driver scheduling system for public transport. In: *Journal of the Operational Research Society*, Vol. 53, No. 10, pp. 1093–1100.
- FORES, S. / PROLL, L. / WREN, A. (2001): Experiences with a Flexible Driver Scheduler. In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 137–152.
- FRELING, R. / LENTINK, R. M. / WAGELMANS, A. P. M. (2004): A decision support system for crew planning in passenger transportation using a flexible branch-and-price algorithm. In: *Annals of Operations Research*, Vol. 127, No. 1-4, pp. 203–222.

- FRELING, R. / HUISMAN, D. / WAGELMANS, A. P. M. (2003): Models and Algorithms for Integration of Vehicle and Crew Scheduling. In: *Journal of Scheduling*, Vol. 6, No. 1, pp. 63–85.
- FRELING, R. / LENTINK, R. M. / ODIJK, M. A. (2001): Scheduling Train Crews: a Case Study for the Dutch Railways. In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 153–165.
- FRIEDRICH, M. ET AL. (2018): Robustness as a Third Dimension for Evaluating Public Transport Plans. In: BORNDÖRFER, R. / STORANDT, S. (EDS.): *ATMOS 2018*. Leibniz Centre for Informatics, pp. 1–17.
- FROGER, A. / GUYON, O. / PINSON, E. (2015): A set packing approach for scheduling passenger train drivers: the French experience. In: *RailTokyo2015*. Chiba Institute of Technology, Narashino, Japan, pp. 1–15.
- FUENTES, M. / CADARSO, L. / MARÍN, Á. (2015): A New Approach to Crew Scheduling in Rapid Transit Networks. In: *Transportation Research Procedia*, Vol. 10, pp. 554–563.
- FUENTES, M. / CADARSO, L. / MARÍN, Á. (2019): A hybrid model for crew scheduling in rail rapid transit networks. In: *Transportation Research Part B: Methodological*, Vol. 125, pp. 248–265.
- GAMACHE, M. ET AL. (1999): A Column Generation Approach for Large-Scale Aircrew Rostering Problems. In: *Operations Research*, Vol. 47, No. 2, pp. 247–263.
- GARCÍA, J. ET AL. (2018): A Binary Cuckoo Search Big Data Algorithm applied to Large-Scale Crew Scheduling Problems. In: *Complexity*, Vol. 2018, Available online July 30, 2018.
- GOLDEN, B. / RAGHAVAN, S. / WASIL, E. (2008): The Vehicle Routing Problem: Latest Advances and New Challenges. Springer US, Operations Research/Computer Science Interfaces Series.
- GOPALAKRISHNAN, B. / JOHNSON, E. L. (2005): Airline Crew Scheduling: State-of-the-Art. In: *Annals of Operations Research*, Vol. 140, No. 1, pp. 305–337.
- GOUMOPOULOS, C. / HOUSOS, E. (2004): Efficient trip generation with a rule modeling system for crew scheduling problems. In: *The Journal of Systems and Software*, Vol. 69, No. 1-2, pp. 43–56.

- GRÖTSCHEL, M. / BORNDÖRFER, R. / LÖBEL, A. (2003): Duty Scheduling in Public Transit. In: JÄGER, W. / KREBS, H.-J. (EDS.): *Mathematics – Key Technology for the Future: Joint Projects between Universities and Industry*. Springer Berlin Heidelberg, pp. 653–674.
- GUEDES, P. C. / BORENSTEIN, D. (2015): Column generation based heuristic framework for the multiple-depot vehicle type scheduling problem. In: *Computers & Industrial Engineering*, Vol. 90, No. Supplement C, pp. 361–370.
- GUO, B. / ZHOU, L. / LI, D. (2014): Study of crew scheduling system for high-speed railway. In: *Applied Mechanics and Materials*, Vol. 667, pp. 72–75.
- GUTTKUHN, R. ET AL. (2003): A discrete event simulation for the crew assignment process in North American freight railroads. In: CHICK, S. ET AL. (EDS.): *Winter Simulation Conference*. Volume 2, IEEE, pp. 1686–1692.
- HAASE, K. / DESAULNIERS, G. / DESROSIERS, J. (2001): Simultaneous Vehicle and Crew Scheduling in Urban Mass Transit Systems. In: *Transportation Science*, Vol. 35, No. 3, pp. 286–303.
- HAN, A. F. / LI, E. C. (2014): A constraint programming-based approach to the crew scheduling problem of the Taipei mass rapid transit system. In: *Annals of Operations Research*, Vol. 223, No. 1, pp. 173–193.
- HANAFI, R. / KOZAN, E. (2014): A Hybrid Constructive Heuristic and Simulated Annealing for Railway Crew Scheduling. In: *Computers & Industrial Engineering*, Vol. 70, pp. 11–19.
- HAUPT, R. L. / HAUPT, S. E. (2004): Practical genetic algorithms. John Wiley & Sons.
- HEIL, J. / HOFFMANN, K. / BUSCHER, U. (2019): Railway crew scheduling: Models, methods and applications. In: *European Journal of Operational Research* Vol. 2019, Available online June 12, 2019.
- HEVNER, A. R. ET AL. (2004): Design science in information systems research. In: *MIS quarterly*, Vol. 28, No. 1, pp. 75–105.
- HOFFMANN, K. (2014): Schichtplanung von Zugbegleitpersonal unter Berücksichtigung von Prüfquoten. In: KUNDISCH, D. / SUHL, L. / BECKMANN, L. (EDS.): *Tagungsband MKWI 2014*. Paderborn University, pp. 1458–1470.

- HOFFMANN, K. (2017): A Hybrid Solution Approach for Railway Crew Scheduling Problems with Attendance Rates. In: DOERNER, K. ET AL. (EDS.): *Operations Research Proceedings 2015*. Springer International Publishing, pp. 243–250.
- HOFFMANN, K. / BUSCHER, U. (2019): Valid inequalities for the arc flow formulation of the railway crew scheduling problem with attendance rates. In: *Computers & Industrial Engineering*, Vol. 127, pp. 1143–1152.
- HOFFMANN, K. ET AL. (2017): Solving Practical Railway Crew Scheduling Problems with Attendance Rates. In: *Business & Information Systems Engineering*, Vol. 59, pp. 147–159.
- HOLSAPPLE, C. / LEE-POST, A. / PAKATH, R. (2014): A unified foundation for business analytics. In: *Decision Support Systems*, Vol. 64, pp. 130–141.
- HUANG, S.-H. / YANG, T.-H. / WANG, R.-T. (2011): Ant colony optimization for railway driver crew scheduling: from modeling to implementation. In: *Journal of the Chinese Institute of Industrial Engineers*, Vol. 28, No. 6, pp. 437–449.
- HUISMAN, D. (2007): A column generation approach for the rail crew re-scheduling problem. In: *European Journal of Operational Research*, Vol. 180, No. 1, pp. 163–173.
- HUISMAN, D. / FRELING, R. / WAGELMANS, A. P. M. (2005): Multiple-Depot Integrated Vehicle and Crew Scheduling. In: *Transportation Science*, Vol. 39, No. 4, pp. 491–502.
- HUISMAN, D. ET AL. (2005): Operations Research in passenger railway transportation. In: *Statistica Neerlandica*, Vol. 59, No. 4, pp. 467–497.
- IBARRA-ROJAS, O. ET AL. (2015): Planning, operation, and control of bus transport systems: A literature review. In: *Transportation Research Part B: Methodological*, Vol. 77, pp. 38–75.
- IRNICH, S. / DESAULNIERS, G. (2005): Shortest path problems with resource constraints. In: DESAULNIERS, G. / DESROSIERS, J. / SOLOMON, M. M. (EDS.): *Column generation*. Springer, pp. 33–65.
- JANACEK, J. / MARTON, P. / KONIORCZYK, M. (2016): The column generation and train crew scheduling. In: *CommunicationsScientific Letters of the University of Zilina*, Vol. 18, No. 1, pp. 21–27.

- JANACEK, J. ET AL. (2017): Optimization of periodic crew schedules with application of column generation method. In: *Transportation Research Part C: Emerging Technologies*, Vol. 83, pp. 165–178.
- JOHANNESSON, P. / PERJONS, E. / BIDER, I. (2013): What are the siblings of design science research? In: *Electronic Proceedings ADWI Workshop - 2013*. AIS Special interest group on Pragmatist IS research (SIG Prag), Netherlands research School for Information and Knowledge Systems (SIKS) Stockholm University, Department of Computer and Systems Sciences.
- JÜTTE, S. ET AL. (2011): Optimizing railway crew scheduling at DB Schenker. In: *Interfaces*, Vol. 41, No. 2, pp. 109–122.
- JÜTTE, S. / MÜLLER, D. / THONEMANN, U. W. (2017): Optimizing railway crew schedules with fairness preferences. In: *Journal of Scheduling*, Vol. 20, No. 1, pp. 43–55.
- JÜTTE, S. / THONEMANN, U. W. (2015): A graph partitioning strategy for solving large-scale crew scheduling problems. In: *OR Spectrum*, Vol. 37, No. 1, pp. 137–170.
- JÜTTE, S. (2012): Large-scale crew scheduling-models, methods, and applications in the railway industry. Kölner Wissenschaftsverlag Köln.
- JÜTTE, S. / THONEMANN, U. W. (2012a): Decomposition Strategies for Solving Large-Scale Crew Scheduling Problems. Department of Supply Chain Management and Management Science, University of Cologne – Technical report.
- JÜTTE, S. / THONEMANN, U. W. (2012b): Divide-and-price: A decomposition algorithm for solving large railway crew scheduling problems. In: *European Journal of Operational Research*, Vol. 219, No. 2, pp. 214–223.
- KALLEHAUGE, B. ET AL. (2005): Vehicle Routing Problem with Time Windows. In: DESAULNIERS, G. / DESROSIERS, J. / SOLOMON, M. M. (EDS.): *Column Generation*. Boston, MA: Springer US, pp. 67–98.
- KASIRZADEH, A. / SADDOUNE, M. / SOUMIS, F. (2017): Airline crew scheduling: models, algorithms, and data sets. In: *EURO Journal on Transportation and Logistics*, Vol. 6, No. 2, pp. 111–137.
- KASPI, M. / RAVIV, T. (2013): Service-oriented line planning and timetabling for passenger trains. In: *Transportation Science*, Vol. 47, No. 3, pp. 295–311.

- KHMELEVA, E. ET AL. (2014): Rail-Freight Crew Scheduling with a Genetic Algorithm. In: BRAMER, M. / PETRIDIS, M. (EDS.): *Research and Development in Intelligent Systems XXXI*. Springer International Publishing, pp. 211–223.
- KHMELEVA, E. ET AL. (2018): Fuzzy-Logic Controlled Genetic Algorithm for the Rail-Freight Crew-Scheduling Problem. In: *KI - Künstliche Intelligenz*, Vol. 32, pp. 61–75.
- KHOSRAVI, A. / TAMANNAEI, M. / REISI-NAFCHI, M. (2017): A Comprehensive Approach for Railway Crew Scheduling Problem (Case Study: Iranian Railway Network). In: *International Journal of Transportation Engineering*, Vol. 4, No. 3, pp. 197–210.
- KHOSRAVI BIZHAEM, A. / TAMANNAEI, M. (2017): Two Mathematical Models for Railway Crew Scheduling Problem. In: *International Journal of Railway Research*, Vol. 4, No. 2, pp. 11–22.
- KLIEWER, N. / AMBERG, B. / AMBERG, B. (2012): Multiple depot vehicle and crew scheduling with time windows for scheduled trips. In: *Public Transport*, Vol. 3, No. 3, pp. 213–244.
- KOHANI, M. / JANACEK, J. (2017): Acceleration strategies of the column generation method for the crew scheduling problem. In: *International Conference on Service Operations and Logistics, and Informatics*. IEEE, pp. 54–57.
- KOHL, N. (2003): Solving the World's Largest Crew Scheduling Problem. In: *ORbit Extra, Newsletter Danish Operations Research Society*, Vol. 4, pp. 8–12.
- KOKUBO, T. / FUKUYAMA, Y. (2017a): Generation methods of neighborhood schedules for practical train crew scheduling problems using tabu search. In: *10th International Workshop on Computational Intelligence and Applications*. IEEE, pp. 39–44.
- KOKUBO, T. / FUKUYAMA, Y. (2017b): Train crew scheduling using tabu search. In: *56th Annual Conference of the Society of Instrument and Control Engineers of Japan*. SICE, pp. 63–66.
- KOKUBO, T. / KAWAGUCHI, S. / FUKUYAMA, Y. (2017): Practical train crew scheduling using improved tabu search. In: *Symposium Series on Computational Intelligence*. IEEE, pp. 1–7.

- KONIORCZYK, M. / TALAS, B. / GEDEON, F. (2015): Preconditioning in the backtracking duty generation of passenger rail crew scheduling: A case study. In: *CommunicationsScientific Letters of the University of Zilina*, Vol. 17, No. 2, pp.23–29.
- KROON, L. / FISCHETTI, M. (2000): Scheduling Train Drivers and Guards: the Dutch "Noord-Oost" case. In: *33rd Annual Hawaii International Conference on System Sciences*. Volume 2, IEEE, pp.1–10.
- KROON, L. / FISCHETTI, M. (2001): Crew Scheduling for Netherlands Railways "destination: customer". In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp.181–201.
- KROON, L. ET AL. (2009): The New Dutch Timetable: the OR Revolution. In: *Interfaces*, Vol. 39, No. 1, pp.6–17.
- KUMAR, A. ET AL. (2009): Railroad crew scheduling. In: FLOUDAS, C. A. / PARDALOS, P. M. (EDS.): *Encyclopedia of Optimization*. Springer US, pp.3227–3236.
- KUZNETSOV, N. A. ET AL. (2016): Design and comparison of freight scheduling algorithms for intelligent control systems. In: *Procedia Computer Science*, Vol. 98, No. Supplement C, pp.56–63.
- KWAN, A. S. K. ET AL. (1999): Producing Train Driver Schedules Under Differing Operating Strategies. In: WILSON, N. H. M. (ED.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp.129–154.
- KWAN, A. S. K. / KWAN, R. S. K. / WREN, A. (1999): Driver Scheduling Using Genetic Algorithms with Embedded Combinatorial Traits. In: WILSON, N. H. M. (ED.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp.81–102.
- KWAN, A. S. K. (1999): Train driver scheduling. Ph.D thesis, University of Leeds.
- KWAN, R. S. K. (2004): Bus and train driver scheduling. In: LEUNG, J. Y.-T. (ED.): *Handbook of Scheduling: Algorithms, Models, and Performance Analysis*. CRC Press, 51, pp.1–20.
- KWAN, R. S. K. (2011): Case studies of successful train crew scheduling optimisation. In: *Journal of Scheduling*, Vol. 14, No. 5, pp.423–434.
- KWAN, R. S. K. / KWAN, A. S. K. (2007): Effective search space control for large and/or complex driver scheduling problems. In: *Annals of Operations Research*, Vol. 155, No. 1, pp.417–435.

- KWAN, R. S. K. / KWAN, A. S. K. / WREN, A. (2001): Evolutionary Driver Scheduling with Relief Chains. In: *Evolutionary Computation*, Vol. 9, No. 4, pp. 445–460.
- KWAN, R. S. K. / WREN, A. / KWAN, A. S. K. (2000): Hybrid Genetic Algorithms for Scheduling Bus and Train Drivers. In: *Congress on Evolutionary Computation*. Volume 1, IEEE, pp. 285–292.
- LAI, D. S. W. / LEUNG, J. M. Y. (2018): Real-time rescheduling and disruption management for public transit. In: *Transportmetrica B: Transport Dynamics*, Vol. 6, No. 1, pp. 17–33.
- LAPLAGNE, I. / KWAN, R. S. K. / KWAN, A. S. K. (2005): A Hybridised Integer Programming and Local Search Method for Robust Train Driver Schedules Planning. In: BURKE, E. / TRICK, M. (EDS.): *Practice and Theory of Automated Timetabling V: 5th International Conference*. Springer Berlin Heidelberg, pp. 71–85.
- LAPLAGNE, I. E. (2008): Train driver scheduling with windows of relief opportunities. Ph. D thesis, University of Leeds.
- LAPORTE, G. (1992): The vehicle routing problem: An overview of exact and approximate algorithms. In: *European Journal of Operational Research*, Vol. 59, No. 3, pp. 345 – 358.
- LAPORTE, G. / NOBERT, Y. (1987): Exact Algorithms for the Vehicle Routing Problem. In: *North-Holland Mathematics Studies*, Vol. 132, pp. 147–184.
- LEE, C.-K. / CHEN, C.-H. (2003): Scheduling of train drivers for Taiwan railway administration. In: *Journal of the Eastern Asia Society for Transportation Studies*, Vol. 5, pp. 292–306.
- LI, C. / WU, J. / LI, C. (2012): Research on the Equilibrium of Train Crew Scheduling Plan of Motor Train Set. In: *Applied Mechanics and Materials*, Vol. 209-211, pp. 827–832.
- LI, J. / KWAN, R. S. (2005): A Self-Adjusting Algorithm for Driver Scheduling. In: *Journal of Heuristics*, Vol. 11, No. 4, pp. 351–367.
- LI, J. / KWAN, R. S. (2003): A fuzzy genetic algorithm for driver scheduling. In: *European Journal of Operational Research*, Vol. 147, No. 2, pp. 334–344.
- LI, J. / NIE, L. (2014): Crew Planning Optimization Model of High-Speed Railway. In: *Advanced Materials Research*, Vol. 869-870, pp. 298–304.

- LIBERATORE, M. J. / LUO, W. (2010): The analytics movement: Implications for operations research. In: *Interfaces*, Vol. 40, No. 4, pp. 313–324.
- LIN, D. / TSAI, M. (2019): Integrated Crew Scheduling and Roster Problem for Trainmasters of Passenger Railway Transportation. In: *IEEE Access*, Vol. 7, pp. 27362–27375.
- LIU, M. / HAGHANI, A. / TOOBAIE, S. (2010): Genetic Algorithm-Based Column Generation Approach to Passenger Rail Crew Scheduling. In: *Transportation Research Record: Journal of the Transportation Research Board*, Vol. 2159, pp. 36–43.
- LU, K. / HAN, B. / ZHOU, X. (2018): Smart Urban Transit Systems: From Integrated Framework to Interdisciplinary Perspective. In: *Urban Rail Transit*, Vol. 4, No. 2, pp. 49–67.
- LÜBBECKE, M. E. / DESROSIERS, J. (2005): Selected Topics in Column Generation. In: *Operations Research*, Vol. 53, No. 6, pp. 1007–1023.
- LUSBY, R. M. / LARSEN, J. / BULL, S. (2018): A survey on robustness in railway planning. In: *European Journal of Operational Research*, Vol. 266, pp. 1–15.
- MANSON, N. J. (2006): Is operations research really research? In: *ORiON*, Vol. 2, No. 2, pp. 155–180.
- MARTIN, R. K. (1999): Large Scale Linear and Integer Optimization: A Unified Approach. Klumer Academic Publishers.
- MARTINS, J. / MORGADO, E. (2010): Case studies in planning crew members. In: NING, B. / BREBBIA, C. (EDS.): *Computers in Railways XII*. WIT Press, pp. 371–381.
- MENG, L. ET AL. (2018): Special issue on Integrated optimization models and algorithms in rail planning and control. In: *Transportation Research Part C: Emerging Technologies*, Vol. 88, pp. 87–90.
- MICHAELIS, M. / SCHÖBEL, A. (2009): Integrating line planning, timetabling, and vehicle scheduling: a customer-oriented heuristic. In: *Public Transport*, Vol. 1, No. 3, pp. 211–232.
- MICHALEWICZ, Z. (1996): Genetic algorithms + data structures = evolution programs. Springer.
- MINGOZZI, A. ET AL. (1999): A set partitioning approach to the crew scheduling problem. In: *Operations Research*, Vol. 47, No. 6, pp. 873–888.

- MONTOYA-TORRES, J. R. ET AL. (2015): A literature review on the vehicle routing problem with multiple depots. In: *Computers & Industrial Engineering*, Vol. 79, No. Supplement C, pp. 115–129.
- MORGADO, E. M. / MARTINS, J. P. (1998): CREWS-NS Scheduling train crews in The Netherlands. In: *AI Magazine*, Vol. 19, No. 1, pp. 25–37.
- MORGADO, E. M. / MARTINS, J. P. (1992): Scheduling and Managing Crew in the Portuguese Railways. In: *Expert Systems with Applications*, Vol. 5, No. 3-4, pp. 301–321.
- MORGADO, E. M. / MARTINS, J. P. (1993): An AI-based approach to crew scheduling. In: *9th Conference on Artificial Intelligence for Applications*. IEEE, pp. 71–77.
- MOURGAYA, M. / VANDERBECK, F. (2007): Column generation based heuristic for tactical planning in multi-period vehicle routing. In: *European Journal of Operational Research*, Vol. 183, No. 3, pp. 1028–1041.
- MUROI, Y. / NISHI, T. / INUIGUCHI, M. (2010): Improvement of Column Generation Method for Railway Crew Scheduling Problems. In: *IEEJ Transactions on Electronics, Information and Systems*, Vol. 130, pp. 275–283.
- NARAYANASWAMI, S. / RANGARAJ, N. (2011): Scheduling and Rescheduling of Railway Operations: A Review and Expository Analysis. In: *Technology Operation Management*, Vol. 2, No. 2, pp. 102–122.
- NEUFELD, J. S. ET AL. (2018): Effiziente Schichtplanerstellung für Zugbegleiter im Nahverkehr unter Berücksichtigung von Quoten. In: *Eisenbahntechnische Rundschau*, Vol. 67, No. 4, pp. 37–41.
- NISHI, T. / MUROI, Y. / INUIGUCHI, M. (2011): Column generation with dual inequalities for railway crew scheduling problems. In: *Public Transport*, Vol. 3, No. 1, pp. 25–42.
- OZDEMIR, H. / MOHAN, C. K. (2001): Flight graph based genetic algorithm for crew scheduling in airlines. In: *Information Sciences*, Vol. 133, No. 3–4, pp. 165–173, Evolutionary Algorithms.
- PARK, T. / RYU, K. R. (2006): Crew pairing optimization by a genetic algorithm with unexpressed genes. In: *Journal of Intelligent Manufacturing*, Vol. 17, No. 4, pp. 375–383.

- PARKER, M. E. / WREN, A. / KWAN, R. S. K. (1995): Modelling the Scheduling of Train Drivers. In: DADUNA, J. R. / BRANCO, I. / PAIXÃO, J. M. P. (EDS.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp. 359–370.
- PENG, K. / SHEN, Y. (2016): An Evolutionary Algorithm Based on Grey Relational Analysis for Crew Scheduling. In: *Journal of Grey System*, Vol. 28, No. 3, pp. 75–88.
- PENG, K. / SHEN, Y. (2018): A variable iterated greedy algorithm based on grey relational analysis for crew scheduling. In: *Scientia Iranica*, Vol. 25, No. 2, pp. 831–840.
- PORTUGAL, R. / LOURENÇO, H. R. / PAIXÃO, J. P. (2009): Driver scheduling problem modelling. In: *Public Transport*, Vol. 1, No. 2, pp. 103–120.
- POUR, S. M. ET AL. (2017): A hybrid Constraint Programming/Mixed Integer Programming framework for the preventive signaling maintenance crew scheduling problem. In: *European Journal of Operational Research*, Vol. 269, No. 1, pp. 341–352.
- PUGLIESE, L. D. P. / GUERRIERO, F. (2013): A survey of resource constrained shortest path problems: Exact solution approaches. In: *Networks*, Vol. 62, No. 3, pp. 183–200.
- REINHARDT, W. (2018): Öffentlicher Personennahverkehr: Technik - rechts- und betriebswirtschaftliche Grundlagen. Springer Vieweg.
- ROLL-HANSEN, N. (2009): Why the distinction between basic (theoretical) and applied (practical) research is important in the politics of science. Centre for the Philosophy of Natural and Social Science, Contingency and Dissent in Science – Technical report.
- ROUSSEAU, J.-M. / DESROSIERS, J. (1995): Results Obtained with Crew-Opt: a Column Generation Method for Transit Crew Scheduling. In: DADUNA, J. R. / BRANCO, I. / PAIXÃO, J. M. P. (EDS.): *Computer-Aided Transit Scheduling*. Springer Berlin Heidelberg, pp. 349–358.
- RUDIN-BROWN, C. M. / HARRIS, S. / ROSBERG, A. (2018): How shift scheduling practices contribute to fatigue amongst freight rail operating employees: Findings from Canadian accident investigations. In: *Accident Analysis & Prevention*, Vol. 126, pp. 64–69.

- RYAN, D. M. / FOSTER, B. A. (1981): An integer programming approach to scheduling. In: WREN, A. (ED.): *Computer Scheduling of Public Transport: Urban Passenger Vehicle and Crew Scheduling*. North-Holland Publishing Company, pp. 269–280.
- ŞAHİN, G. / YÜCEOĞLU, B. (2011): Tactical crew planning in railways. In: *Transportation Research Part E: Logistics and Transportation Review*, Vol. 47, No. 6, pp. 1221–1243.
- SANDERS, P. / TAKKULA, T. / WEDELIN, D. (1999): High performance integer optimization for crew scheduling. In: SLOOT, P. ET AL. (EDS.): *7th International Conference on High-Performance Computing and Networking*. Springer International Publishing, pp. 1–12.
- SANTOS, A. G. DOS / MATEUS, G. R. (2009): General hybrid column generation algorithm for crew scheduling problems using genetic algorithm. In: *Congress on Evolutionary Computation*. IEEE, pp. 1799–1806.
- SANTOS, A. G. DOS / MATEUS, G. R. (2007): Hybrid approach to solve a crew scheduling problem: an exact column generation algorithm improved by metaheuristics. In: *7th International Conference on Hybrid Intelligent Systems 2007 (HIS 2007)*. IEEE, pp. 107–112.
- SAUNDERS, M. / LEWIS, P. / THORNHILL, A. (2016): Research methods for business students. Harlow: Pearson.
- SCHIPPER, D. / GERRITS, L. (2018): Differences and similarities in European railway disruption management practices. In: *Journal of Rail Transport Planning & Management*, Vol. 8, No. 1, pp. 42–55.
- SCHÖBEL, A. (2017): An eigenmodel for iterative line planning, timetabling and vehicle scheduling in public transportation. In: *Transportation Research Part C: Emerging Technologies*, Vol. 74, pp. 348–365.
- SCHRIJVER, A. (1998): Theory of Linear and Integer Programming. West Sussex, England: John Wiley & Sons, Ltd.
- SCHWEDES, O. (2018): Verkehrspolitik: Eine interdisziplinäre Einführung. Springer VS.
- SHEN, Y. (2001): Tabu search for bus and train driver scheduling with time windows. Ph.D thesis, University of Leeds.

- SHEN, Y. / CHEN, S. (2014): A column generation algorithm for crew scheduling with multiple additional constraints. In: *Pacific Journal of Optimization*, Vol. 10, No. 1, pp. 113–136.
- SHEN, Y. / CHEN, S. / SU, X. (2010): Rail Crew Scheduling Based on a Pooling Mode for High Speed Passenger Lines. In: *International Conference on Logistics Engineering and Intelligent Transportation Systems*. IEEE, pp. 1–4.
- SHEN, Y. / KWAN, R. S. K. (2001): Tabu Search for Driver Scheduling. In: VOSS, S. / DADUNA, J. R. (EDS.): *Computer-Aided Scheduling of Public Transport*. Springer Berlin Heidelberg, pp. 121–135.
- SHEN, Y. / KWAN, R. S. K. (2002): Tabu search for time windowed public transport driver scheduling. Central China Normal University – Technical report.
- SHEN, Y. / LI, J. / PENG, K. (2017): An estimation of distribution algorithm for public transport driver scheduling. In: *International Journal of Operational Research*, Vol. 28, No. 2, pp. 245–262.
- SHEN, Y. ET AL. (2013): Evolutionary crew scheduling with adaptive chromosomes. In: *Transportation Research Part B: Methodological*, Vol. 56, No. Supplement C, pp. 174–185.
- SHEN, Y. / XIA, J. (2009): Integrated bus transit scheduling for the Beijing bus group based on a unified mode of operation. In: *International Transactions in Operational Research*, Vol. 16, No. 2, pp. 227–242.
- SHI, G. / ZHU, C. / TIAN, Z. (2015): Solving Crew Scheduling Problem for High Speed Railway Based on Chance Constrained Programming. In: *Journal of Information & Computational Science*, Vol. 12, No. 7, pp. 2655–2664.
- SIMON, H. A. (1996): The sciences of the artificial. MIT press.
- SNIJDERS, H. / SALDANHA, R. L. (2017): Decision support for scheduling security crews at Netherlands Railways. In: *Public Transport*, Vol. 9, No. 1-2, pp. 193–215.
- SONG, X. ET AL. (2012): Study on crew scheduling model for the passenger dedicated line. In: *International Journal of Pattern Recognition and Artificial Intelligence*, Vol. 26, No. 3, pp. 1–17.
- STATISTISCHES BUNDESAMT (DESTATIS) (2019): Verkehr - Personenverkehr mit Bussen und Bahnen. (URL: <https://www.destatis.de/DE/Themen/Branchen-Unternehmen/Transport-Verkehr/>)

- [Personenverkehr/Publikationen/Downloads-Personenverkehr/personenverkehr-busse-bahnen-vierteljahr-2080310193214.pdf?__blob=publicationFile](#) – visited on September 23, 2019.
- STEINZEN, I. ET AL. (2010): A time-space network approach for the integrated vehicle- and crew-scheduling problem with multiple depots. In: *Transportation Science*, Vol. 44, No. 3, pp. 367–382.
- STEINZEN, I. / SUHL, L. / KLIEWER, N. (2009): Branching strategies to improve regularity of crew schedules in ex-urban public transit. In: *OR Spectrum*, Vol. 31, No. 4, pp. 727–743.
- SUYABATMAZ, A. Ç. / ŞAHİN, G. (2012): A Column-and-Row Generation Algorithm for a Crew Planning Problem in Railways. In: KLATTE, D. / LÜTHI, H.-J. / SCHMEDDERS, K. (EDS.): *Operations Research Proceedings 2011*. Springer Berlin Heidelberg, pp. 335–340.
- SUYABATMAZ, A. Ç. / ŞAHİN, G. (2015): Railway crew capacity planning problem with connectivity of schedules. In: *Transportation Research Part E: Logistics and Transportation Review*, Vol. 84, No. Supplement C, pp. 88–100.
- TEODOROVIĆ, D. / JANIĆ, M. (2017): Public Transportation Systems. In: TEODOROVIĆ, D. / JANIĆ, M. (EDS.): *Transportation Engineering*. Butterworth-Heinemann, pp. 387–493.
- THORLACIUS, P. / CLAUSEN, J. (2008): Scheduling of inspectors for ticket spot checking in urban rail transportation. Trafikdage på Aalborg Universitet – Technical report.
- TIAN, Z. / SONG, Q. (2013): Modeling and Algorithms of the Crew Scheduling Problem on High-speed Railway Lines. In: *Procedia Social and Behavioral Sciences*, Vol. 96, No. Supplement C, pp. 1443–1452.
- TOTH, P. / VIGO, D. (EDS.) (2014): *Vehicle Routing: Problems, Methods, and Applications*, Second Edition. Philadelphia, PA, USA: Society for Industrial and Applied Mathematics.
- VAIDYANATHAN, B. / JHA, K. C. / AHUJA, R. K. (2007): Multicommodity network flow approach to the railroad crew-scheduling problem. In: *IBM Journal of Research and Development*, Vol. 51, No. 3.4, pp. 325–344.

- VAIDYANATHAN, B. / AHUJA, R. K. (2015): Crew Scheduling Problem. In: PATTY, B. W. (ED.): *Handbook of Operations Research Applications at Railroads*. Springer US, pp. 163–175.
- VAISHNAVI, V. ET AL. (2019): Design Science Research in Information Systems. Association for information systems – Technical report (URL: <http://www.desrist.org/design-research-in-information-systems/>) – visited on November 27, 2019.
- VANCE, P. H. ET AL. (1997): A Heuristic Branch-and-Price Approach for the Airline Crew Pairing Problem. Auburn University, Georgia Institute of Technology, Massachusetts Institute of Technology, United Airlines – Technical report.
- VANDERBECK, F. (2000): On Dantzig-Wolfe Decomposition in Integer Programming and ways to Perform Branching in a Branch-and-Price Algorithm. In: *Operations Research*, Vol. 48, No. 1, pp. 111–128.
- VANDERBECK, F. / WOLSEY, L. A. (1996): An exact algorithm for IP column generation. In: *Operations Research Letters*, Vol. 19, No. 4, pp. 151–159.
- VEELEN TURF, L. P. ET AL. (2012): Railway crew rescheduling with retiming. In: *Transportation Research Part C: Emerging Technologies*, Vol. 20, No. 1, pp. 95–110.
- VEELEN TURF, L. P. ET AL. (2016): A Quasi-Robust Optimization Approach for Crew Rescheduling. In: *Transportation Science*, Vol. 50, No. 1, pp. 204–215.
- WANG, J. / GRONALT, M. / SUN, Y. (2017): A two-stage approach to the depot shunting driver assignment problem with workload balance considerations. In: *PLOS ONE*, Vol. 12, No. 7, pp. 1–23.
- WANG, Y. ET AL. (2008): A Column Generation-Based Approach for Railway Crew Scheduling Problem. In: MAO, B. ET AL. (EDS.): *Traffic and Transportation Studies*. American Society of Civil Engineers, pp. 697–708.
- WEBER, R. A. G. (2004): The Rhetoric of Positivism Versus Interpretivism: A Personal View. In: *MIS Quarterly: Management Information Systems*, Vol. 28, No. 1, pp. iii–xii.
- WEDELIN, D. (1995): An algorithm for large scale 0–1 integer programming with application to airline crew scheduling. In: *Annals of Operations Research*, Vol. 57, No. 1, pp. 283–301.

- WREN, A. (1981): General review of the use of computers in scheduling buses and their crews. In: WREN, A. (ED.): *Computer Scheduling of Public Transport: Urban Passenger Vehicle and Crew Scheduling*. North-Holland Publishing, pp.3–16.
- WREN, A. / KWAN, R. S. K. / PARKER, M. E. (1994): Scheduling of rail driver duties. In: *Transactions on the Built Environment*. Volume 7, WIT Press.
- YAGHINI, M. / KARIMI, M. / RAHBAR, M. (2015): A set covering approach for multi-depot train driver scheduling. In: *Journal of Combinatorial Optimization*, Vol. 29, No. 3, pp.636–654.
- YAP, M. / OORT, N. VAN (2018): Driver schedule efficiency vs. public transport robustness: A framework to quantify this trade-off based on passive data. Department of Transport and Planning, Delft University of Technology – Technical report.
- ZHAO, P. / ZHEN, J. (2007): A meta-heuristics algorithm for train-set crew scheduling. In: PENG, Q. ET AL. (EDS.): *International Conference on Transportation Engineering*. School of Traffic and Transportation, Beijing JiaoTong University, Beijing, China; Transportation and Economics Research Institute, China Academy of Railway Sciences, Beijing, China, pp.2877–2882.
- ZHOU, W. ET AL. (2016): Crew scheduling considering both crew duty time difference and cost on urban rail system. In: *Promet - Traffic & Transportation*, Vol. 28, No. 5, pp.449–460.
- ZHU, C. ET AL. (2014): Research on Optimization of Crew Scheduling for High Speed Railway. In: *Journal of Information & Computational Science*, Vol. 11, No. 16, pp.5735–5742.