Technischen Universität Dresden

Fakultät Maschinenwesen

Hydrodynamic forces on a sphere translating steadily in a wall-bounded linear shear flow

Dissertation

zur Erlangung des akademischen Grades

Doktor-Ingenieur (Dr.-Ing.)

von

M. Sc. Pengyu Shi

Gutachter:

1. Prof. Dr.-Ing. habil. Uwe Hampel

2. Prof. Dr. Dominique Legendre

Tag der Einreichung:

26.05.2020

Tag der Verteidigung:

16.02.2021

Acknowledgements

The research presented in this thesis was carried out during my Ph.D study at the Institute of Fluid Dynamics of Helmholtz-Zentrum Dresden-Rossendorf (HZDR). The funding was provided by the Chinese Scholarship Council (CSC).

I would first like to express my gratitude to Dr. Roland Rzehak for his supervision during the past four years. The lively discussions encouraged me to fully understand the problems and provide proof for my statements. I am also thankful for his effort in proofreading the thesis. I would also like to thank Dr. Dirk Lucas and Prof. Uwe Hampel for accepting me as a “joint” Ph.D student of HZDR and TU Dresden, and overseeing my work. Their continuing guidance has helped me greatly in the writing of this thesis. I am also very grateful to Prof. Dominique Legendre of the Institut de Mécanique des Fluides de Toulouse (IMFT) for accepting to be the second examiner.

My sincere thanks also go to Prof. Jacques Magnaudet of IMFT for the many motivating and stimulating discussions during the past two years and the opportunity to run numerical simulations using the numerical code JADIM. Without his support, in a multitude of ways, completion of this work would have not been possible. For the simulations, I would also like to thank many members in Jacques’ group, especially Annaig Pedrono for her intensive help and support with the code adaptations, Prof. Dominique Legendre for his help with the grid generation technique, and Dr. Laurent Lacaze for keeping the computer “Sophie” running at most times.

I would like to thank many of my friends, especially Dr. Tian Ma, Dr. Yixiang Liao, Dr. Liu Liu, Hongmei Lyu, and Dr. Wei Ding. It is my great pleasure to work with them at HZDR and share some free time with them in Dresden. Many thanks also to my colleagues from HZDR, especially Dr. Sascha Heitkam for his enlightening suggestion on the content of the thesis, Richard Meller, Hendrik Heßenkemper, and Anna Sommer for the valuable discussions on multiphase flow problems, Dr. Susann Haensch for her kind help on my language barrier.

I am also very grateful to Prof. Ping Zhou, Prof. Hongjie Yan, Prof. Zhuo Chen, and Dr. Tian Zhou who convinced me during our many discussions in Central South University that I should pursue my doctoral degree and who made it possible for me to obtain a scholarship from CSC to support my Ph.D work.

Finally, I wish to express my deepest gratitude to my parents, who raised me, supported me, and love me. To them I dedicate my thesis.

Abstract

Determining the hydrodynamic force acting on bubbles and particles moving parallel to a wall in a shear flow is a problem of fundamental importance, as this configuration is involved in a variety of technical and natural systems. The presence of the wall tends to increase the drag force, and more importantly causes a transverse lift force acting on the body. This transverse force may be directed either towards the wall or away from it, depending on the detailed flow conditions. The lift force, although often much smaller in magnitude than the drag force, plays a crucial role in the accumulation of bubbles and particles either close to or away from the wall. This thesis focuses on extending the current capability in predicting drag and lift forces on spherical bubbles and particles translating in a linear shear flow, primarily in the vicinity of a wall, and obtaining quantitative insight into the interaction mechanisms at work in the context of finite sphere Reynolds number. The investigations are performed through direct numerical simulation (DNS) using an accurate finite volume method.

The first part of the thesis summarizes all expressions for the drag and lift forces available in the literature. Cases of unbounded and wall-bounded flows are considered. Likewise, conditions where the sphere translates in a fluid at rest and in a linear shear flow are investigated. Furthermore, situations where the wall lies in the inner region and in the outer region of the flow disturbance produced by the sphere are distinguished. The focus is on spheres at Reynolds numbers up to $O(10^2)$ which are relevant for dispersed two-phase flows in chemical and minerals engineering. A comprehensive review of existing results from analytical, experimental, and direct numerical simulation studies is given. The available correlations are critically assessed by comparison to data from these studies. Based on the comparison, recommendations are given which correlations to use including some new proposals, and gaps in the data are identified.

The second part aims to fill the gaps mentioned above by means of DNS. Specifically, the three-dimensional flow around a non-rotating sphere translating steadily in a wall-bounded linear shear flow is investigated by solving the full Navier-Stokes equations. The investigation is concerned with the drag and lift forces experienced by the sphere over a wide range of Reynolds number ($0.1 \leq Re \leq O(10^2)$, Re being based on the sphere diameter and relative velocity with respect to the ambient fluid), wall distance ($1.5 \leq L_R \leq 8$, L_R being the distance from the sphere center to the wall normalized by the sphere radius), and relative shear rate ($-0.5 \leq Sr \leq 0.5$, Sr being the ratio between the velocity difference across the sphere and the relative velocity). Based on the above range of parameters, situations where the sphere is repelled from or attracted to the wall are both covered. The flow structure and the vorticity field are analyzed to obtain quantitative insight into the interaction mechanisms at work. The drag and lift forces are computed as well. Their variations agree well with analytical predictions available in the potential flow limit and in the limit of low-but-finite Reynolds number. Numerical results and analytical expressions are combined to provide accurate semi-empirical expressions for the drag and lift forces at arbitrary Reynolds number and separation distance.

Present numerical results help to rationalize and quantify the various mechanisms at work and the ways they interact. From a practical point of view, they also result in several closure models for the drag correction and transverse force, which are necessary inputs in the point-particle based Eulerian-Lagrangian simulations or in Eulerian-Eulerian simulations based on the interpenetrating continua concept.

Contents

1	INTRODUCTION	1
1.1	Background	1
1.2	Underlining mechanisms	2
1.3	State of the art	4
1.4	Motivation, goal and outline of the thesis	6
2	STATE OF THE ART	8
2.1	Statement of the problem	8
2.2	Overview of literatures	10
2.3	Unbounded linear shear flow	14
2.4	Linear shear flow with the wall lying in the inner region	21
2.5	Stagnant flow with the wall lying in the outer region	26
2.6	Linear shear flow with the wall lying in the outer region	31
2.7	Conclusions	39
3	NUMERICAL APPROACH AND PRELIMINARY TESTS	41
3.1	Numerical approach	41
3.2	Preliminary tests	43
4	CLEAN SPHERICAL BUBBLE IN WALL-BOUNDED FLOW	50
4.1	Characteristics of the flow field and fundamental mechanisms	50
4.2	Hydrodynamic forces on the bubble: fluid at rest at infinity	56
4.3	Hydrodynamic forces on the bubble: linear shear flow	60
4.4	Conclusions	69
5	RIGID SPHERE IN WALL-BOUNDED FLOW	72
5.1	Characteristics of the flow field and fundamental mechanisms	72
5.2	Hydrodynamic forces on the sphere: fluid at rest at infinity	78
5.3	Hydrodynamic forces on the sphere: Linear shear flow	83
5.4	Conclusions	90
6	CONCLUSIONS AND FUTURE WORK	93
6.1	Summary and conclusions	93
6.2	Future work	95
7	REFERENCE	97

Nomenclature

Symbols

a	maximum vorticity generated at the surface of a rigid sphere normalized by $2U_{\text{rel}}/d$
b	maximum vorticity generated at the surface of a clean bubble normalized by $2U_{\text{rel}}/d$
C	force coefficient ($C = 8F/\pi d^2 \rho U_{\text{rel}}^2$)
$C_{\text{L,Bi}}$	lift coefficient in the bifurcation condition
C_{D0}^{U}	drag coefficient in unbounded uniform flow
$C_{\text{D,Stokes}}$	Stokes drag
ΔC_{D}	drag change ($\Delta C_{\text{D}} = (C_{\text{D}} - C_{\text{D0}}^{\text{U}})/C_{\text{D0}}^{\text{U}}$)
c_{T1}, c_{T2}, c_{T3}	empirical functions proposed to glue together solutions that are valid in different Re -regimes
d	sphere diameter
$\mathbf{e}_x, \mathbf{e}_y, \mathbf{e}_z$	unit vectors in the x, y, z direction
$\mathbf{F}, F$	force
f	empirical function describing shear effects
$f_{\text{D}\infty}$	empirical function describing effects of slip-inertia on drag in unbounded flows
f'_{D}	empirical function describing effects of slip-inertia on drag in wall-bounded flows
f'_{L}	empirical function describing effects of slip-inertia on lift
h	empirical function describing wall effects
g	exponent describing the increase in the decay rate of the lift force with increasing Re
$\mathbf{I}$	Kronecker tensor
J	function defined by McLaughlin (1991, Eq. (3.20))
j^{W}	function defined by McLaughlin (1993, Eqs. (2.6), (2.7), (3.17))
L_{R}	wall distance normalized by the sphere radius
L_{u}	wall distance normalized by the Oseen length
L_{ω}	wall distance normalized by the Saffman length
$\tilde{L}$	wall distance measured from the sphere center
$\tilde{L}_{\text{u}}$	Oseen length ($\tilde{L}_{\text{u}} = \nu/U_{\text{rel}}$)
$\tilde{L}_{\omega}$	Saffman length ($\tilde{L}_{\omega} = (\nu/\omega_{\infty})^{1/2}$)
N	number of nodes used in the simulation
$\mathbf{n}$	outward unit normal to the sphere surface

$O(\quad)$	order of magnitude
p	disturbed pressure field
Re	Reynolds number based on relative velocity
$\mathbf{r}, r$	position vector and radial coordinate with origin at sphere center
$\bar{r}$	normalized radial position ($\bar{r} = 2r/d$)
Sr	dimensionless flow shear rate ($Sr = \gamma d/U_{\text{rel}}$)
$\mathbf{U}_{\text{rel}}, U_{\text{rel}}$	relative velocity
$U_{\text{rel},\perp}$	spanwise component of relative velocity
$U_{\text{rel},\parallel}$	streamwise component of relative velocity
$\mathbf{u}, u$	disturbed flow field
$\mathbf{u}_{\infty}, u_{\infty}$	undisturbed flow field
$\mathbf{V}, V$	sphere velocity
x	wall-normal coordinate
y	spanwise coordinate
z	stream-wise coordinate
∇	gradient operator
$^T \nabla \mathbf{u}$	transpose of $\nabla \mathbf{u}$
$\nabla \cdot$	divergence operator
$\nabla \times$	curl operator
∇^2	Laplacian operator
$\times$	vector cross product
Γ	sphere surface
β	constant depending on the type of the sphere ($\beta = 1$ for rigid spheres, $\beta = 2/3$ for clean bubbles)
γ	shear rate in unidirectional shear flow (in which case $\gamma = \omega_{\infty}$)
ε	ratio of Oseen to Saffman lengths $\tilde{L}_u/\tilde{L}_{\omega}$
η	radial coordinate
μ	fluid dynamic viscosity
ν	fluid kinematic viscosity
ξ	axial coordinate
ρ	fluid density
Σ	stress tensor ($\Sigma = -p\mathbf{I} + \rho\boldsymbol{\tau}$)
σ	empirical constant
$\boldsymbol{\tau}$	viscous part of the stress tensor Σ
φ	angular coordinate
$\boldsymbol{\omega}, \omega$	vorticity of disturbed flow ($\omega = \ \boldsymbol{\omega}\ $, $\boldsymbol{\omega} = \nabla \times \mathbf{u}$)
$\boldsymbol{\omega}_{\infty}, \omega_{\infty}$	vorticity of undisturbed flow

Superscripts

U	unbounded situation
W	wall-bounded situation
W-in	situation with the wall in the inner region
W-out	situation with wall in the outer-region

Subscripts

L	lift
D	drag
Lu, Du	wall-induced contributions
$L\omega, D\omega$	shear-induced contributions
P	particle

Abbreviations

BEM	boundary element method
Bub.	bubbles
DNS	direct numerical simulation
E-E	Eulerian-Eulerian approach
E-L	Eulerian-Lagrangian approach
Exp.	experiment
LA	lubrication analysis
Par.	particles
RPE	regular perturbation expansions
RT	reciprocal theorem
SPE	singular perturbation expansions

List of figures

- Figure 1.1. Wall- and shear-induced contributions to the lift force acting on a sphere (either a clean bubble or a rigid sphere) in the low-to-moderate Reynolds number regime. 2
- Figure 1.2. Wall- and shear-induced contributions to the lift force acting on a spherical bubble in the moderate-to-large Reynolds number regime. 3
- Figure 1.3. Wall- and shear-induced contributions to the lift force acting on a rigid sphere in the moderate-to-large Reynolds number regime. 3
- Figure 2.1. Schematic of a non-rotating sphere moving in a wall-bounded linear shear flow. 8
- Figure 2.2. $J(\varepsilon)$ predictions according to the present expression and the earlier ones from Legendre and Magnaudet (1998) and Mei (1992) as well as the asymptotic expressions from McLaughlin (1991) compared with a new numerical evaluation of the integral expression as well as the older evaluations of McLaughlin (1991) and Asmolov (1990): (a) $0 < \varepsilon \leq 0.25$; (b) $\varepsilon \geq 0.2$. 16
- Figure 2.3. $C_{L\omega}^U$ prediction according to the low- Re expression (2.7b) (represented by solid lines) compared with DNS data for (a) $0.02 \leq Re \leq 2$ and (b) $1 \leq Re \leq 200$. 18
- Figure 2.4. $C_{L\omega}^U$ predictions according to the correlation proposed in Loth (2008) for $50 < Re \leq 500$ compared with DNS data. 20
- Figure 2.5. C_L^{W-in} predictions according to the expressions of Cox and Hsu (1977), Cherukat and McLaughlin (1994), and Yahiaoui and Feuillebois (2010) for $1 \leq L_R \leq 100$ compared with numerical data concerning (a) a stagnant flow and (b) a stationary sphere. 24
- Figure 2.6. C_L^{W-in} predictions according to the expressions of Cox and Hsu (1977), Cherukat and McLaughlin (1994), and Yahiaoui and Feuillebois (2010) for $-10 \leq Sr \leq 10$ compared with numerical data under conditions of: (a) $L_R = 1, 1.1, 1.5$; (b) $L_R = 2, 3, 4$; (c) $L_R = 5, 10, 20$. 25
- Figure 2.7. f_D' and f_L' predictions according to the presently proposed expressions, (2.27), and the previous ones proposed in Vasseur and Cox (1977) and Takemura and Magnaudet (2003) compared with the present numerical evaluations of Eqs. (2.24) for $0.01 \leq L_u \leq 300$. 27
- Figure 2.8. C_{Lu}^W predictions according to the expressions of Takemura and Magnaudet (2003) and of Zeng et al. (2009) compared with (a) experimental data from Takemura and Magnaudet (2003) given in series at fixed value of Re for $1 < L_u \leq 200$, (b) DNS data from different sources as indicated in the legend given in series at fixed value of L_R for $1 \leq L_u \leq 1000$. 30
- Figure 2.9. $h_L(\varepsilon) \gg 1$ predictions according to the presently proposed expression and the earlier one from Takemura et al. (2009) as well as the asymptotic expressions including both the one from McLaughlin (1993) and the one from Cox and Hsu (1977) for $0.1 \leq L_\omega \leq 40$ compared with the numerical data from Drew (1988), Asmolov (1989), and McLaughlin (1993). 33

Figure 2.10. $\beta^{-1}C_L^{W-out}$ predictions according to the model, (2.37), with the h_L expression taken either as the presently proposed one, (2.42), or as the previous one from Takemura et al. (2009), (2.41), while keeping the rest involved expressions identical as summarized in Table 3 for $0.1 \leq L_\omega \leq 10$ compared with the numerical data for both situations where the sphere leads or lags the fluid. 35

Figure 2.11. $\beta^{-1}C_L^W$ prediction according to the model (2.37) and the wall-induced lift expression (i.e. without shear) of (2.27b) for $0.1 < L_u \leq 10$ compared with the experimental data from Takemura et al. (2009, clean bubble) and Takemura and Magnaudet (2009, rigid sphere). 37

Figure 2.12. $C_{L\omega}^W$ predictions according to the model (2.37) with the involved correlations summarized in Table 3 and the model of Zeng et al. (2009), (2.50), for $1 \leq L_u \leq 1000$ compared with the DNS data. 38

Figure 3.1. Illustration of the grid system. (a) Shape and size of the computational domain. (b) Definition of the number of nodes in the computational domain. (c) and (d) Partial view of the grid near the sphere with $L_R = 1.5$ and $2\delta/d = 0.01$ in (c), and $L_R = 2$ and $2\delta/d = 0.002$ in (d). 42

Figure 3.2. Numerical predictions ($\square$) for the wall-induced forces on a clean spherical bubble in a quiescent fluid at low-to-moderate Reynolds number. (a) ΔC_{Du}^W . (b) C_{Lu}^W . 44

Figure 3.3. Comparison of numerical predictions for C_{Lu}^W ($\square$) with the fit (2.28) of the asymptotic solution corresponding to conditions $Re = O(1 - 10)$ and the irrotational solution (2.30) for $1.5 \leq L_R \leq 8$ and $0.1 \leq Re \leq 500$. 45

Figure 3.4. Comparison of present numerical predictions with available numerical results and semi-expressions. (a) $C_{D\omega}^U$ compared with numerical results from Legendre and Magnaudet (1998) and semi-empirical correlation proposed in Mei et al. (1994). (b) $C_{L\omega}^U$ compared with numerical results and the composite fit (2.14) from Legendre and Magnaudet (1998). 46

Figure 3.5. Numerical predictions ($\square$) for the wall-induced forces on a rigid sphere in a quiescent fluid at low-to-moderate Reynolds number. (a) ΔC_{Du}^W . (b) C_{Lu}^W . 47

Figure 3.6. Comparison of present numerical results with the previous ones from Zeng et al. (2005, 2009). (a) C_{Du}^W . (b) C_{Lu}^W . 48

Figure 3.7. Comparison of present numerical predictions with available numerical results and semi-empirical expressions. (a) $C_{D\omega}^U$. (b) $C_{L\omega}^U$. 49

Figure 4.1. Distribution of the streamwise disturbance velocity $(\mathbf{u} - \mathbf{u}_\infty) \cdot \mathbf{e}_z / U_{rel}$ along the line ($y = 0, z = 0$). (a) Stagnant fluid ($Sr = 0$) for different separation distances; (b) Linear shear flow for $L_R = 4$. 51

Figure 4.2. Iso-contours of the normalized vorticity disturbance $d/(2U_{rel})(\boldsymbol{\omega} - \boldsymbol{\omega}_\infty) \cdot \mathbf{e}_y$ in the symmetry plane $y = 0$ at $L_R = 2$. Left column: $Sr = -0.5$ ($U_{rel} < 0$); central column: $Sr = 0$ ($U_{rel} > 0$); right column: $Sr = 0.5$ ($U_{rel} > 0$). 52

Figure 4.3. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the cross-sectional plane $z = d$ in an unbounded linear shear flow with $Sr = 0.5$. (a) $Re = 100$; (b) $Re = 500$. 53

Figure 4.4. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the equatorial plane $z = 0$ in a wall-bounded linear shear flow, with the bubble standing a distance $L_R = 1.5$ from the wall. 54

Figure 4.5. Wall-induced drag correction ΔC_{Du}^W for a bubble translating parallel to a wall in a fluid at rest. (a): high- Re regime; (b): entire Re -range investigated numerically. 56

Figure 4.6. Lift coefficient on a bubble translating parallel to a wall in a fluid at rest. (a) High-Reynolds-number range $100 \leq Re \leq 1000$. (b) Complete Re -range $0.1 \leq Re \leq 1000$. 59

Figure 4.7. Transverse force on a bubble translating parallel to a wall in a fluid at rest in the range $0.6 \leq Re \leq 300$ according to various sources. 60

Figure 4.8. Relative near-wall drag increase ΔC_D^W for a bubble translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. 61

Figure 4.9. Relative drag variation $\Delta C_{D\omega}^U$ for a bubble translating at moderate-to-high Re in an unbounded shear flow, with reference to the drag in a uniform stream. (a) Influence of the Reynolds number; (b) influence of the shear rate. 62

Figure 4.10. Difference in the high- Re range between the relative drag variation in the presence of wall and shear, ΔC_D^W , and the sum $\Delta C_{Du}^W + \Delta C_{D\omega}^U$ of the relative drag variation in the presence of the wall for $Sr = 0$, ΔC_{Du}^W , and the relative drag variation in an unbounded shear flow, $\Delta C_{D\omega}^U$. 63

Figure 4.11. Relative near-wall drag increase $\Delta C_D^W(Re, L_R, Sr)$ for a bubble translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. 64

Figure 4.12. Variations of the lift coefficient $C_L^W(Re, L_R, S)$ for a bubble translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. 65

Figure 4.13. (a) Effect of the shear-wall coupling on the lift force in the high Reynolds number regime. (b) Performance of the model (4.13). 67

Figure 4.14. Lift coefficient $C_L^W(Re, L_R, Sr)$ for a bubble translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. 68

Figure 5.1. Distribution of the streamwise disturbance velocity $(\mathbf{u} - \mathbf{u}_\infty) \cdot \mathbf{e}_z / U_{\text{rel}}$ along the line ($y = 0, z = 0$). (a) Stagnant fluid ($Sr = 0$) for different separation distances; (b) Linear shear flow for $L_R = 2$. 73

Figure 5.2. Iso-contours of the normalized vorticity disturbance $2/3 \times d/(2U_{\text{rel}}) (\boldsymbol{\omega} - \boldsymbol{\omega}_\infty) \cdot \mathbf{e}_y$ in the symmetry plane $y = 0$ at $L_R = 2$. Left column: $Sr = -0.5$ ($U_{\text{rel}} < 0$); central column: $Sr = 0$ ($U_{\text{rel}} > 0$); right column: $Sr = 0.5$ ($U_{\text{rel}} > 0$). 74

Figure 5.3. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the diametrical plane $z = 0$ in a wall-bounded linear shear flow, with the bubble standing at a distance $L_R = 1.5$ from the wall. 75

Figure 5.4. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the cross-sectional plane $z = d$ in a wall bounded stagnant flow with $L_R = 1.5$. (a) $Re = 50$; (b) $Re = 200$. 76

Figure 5.5. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the equatorial plane $z = 0$ in an unbounded linear shear flow with $Sr = 0.5$. (a) $Re = 50$; (b) $Re = 200$. 77

Figure 5.6. As Figure 5.5 but in the plane $z = d$. 77

Figure 5.7. Wall-induced drag correction ΔC_{Du}^W for a rigid sphere translating parallel to a wall in a fluid at rest. (a): high- Re regime; (b): entire Re -range investigated numerically. 79

Figure 5.8. Square of the maximum vorticity at the surface of a rigid sphere subjected to a uniform stream. 80

Figure 5.9. Lift coefficient on a rigid sphere translating parallel to a wall in a fluid at rest. 81

Figure 5.10. Relative near-wall drag increase ΔC_D^W for a rigid sphere translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime for (a) $Sr = \pm 0.2$, and (b) $Sr = \pm 0.5$. 84

Figure 5.11. Relative drag variation ΔC_D^W for a rigid sphere translating at moderate-to-high Re in an unbounded shear flow with reference to the drag in a uniform stream. 84

Figure 5.12. Difference in the moderate-to-high Re regime between the relative drag variation in the presence of wall and shear, ΔC_D^W , and the sum $\Delta C_{Du}^W + \Delta C_{D\omega}^U$ of the relative drag variation in the presence of the wall for $Sr = 0$, ΔC_{Du}^W , and the relative drag variation in an unbounded shear flow, $\Delta C_{D\omega}^U$. 85

Figure 5.13. Relative near-wall drag increase $\Delta C_D^W(Re, L_R, Sr)$ for a rigid sphere translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. 86

Figure 5.14. Variations of the lift coefficient $C_L^W(Re, L_R, Sr)$ for a rigid sphere translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. 87

Figure 5.15. Variations of the lift coefficient $C_L^W(Re, L_R, Sr)$ for a rigid sphere translating parallel to a wall in a linear shear flow in the low-to-moderate Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. 88

Figure 5.16. Variations of the lift coefficient $C_L^W(Re, L_R, Sr)$ for a rigid sphere translating parallel to a wall in a linear shear flow at moderate-to-high Reynolds number with (a) $L_R = 1.5$, (b) $L_R = 2.0$, and (c) $L_R = 4.0$. 89

List of tables

Table 1: Studies of the lift force acting on spheres in linear shear flows.	12
Table 2. Transitional Re for negative lift obtained in DNS studies	19
Table 3: Summary of expressions applied together with (2.37) in Figure 2.10	34
Table 4. Summary of data in Lee and Balachandar (2010, Table 2)	38
Table 5. Summary of suggested expressions as well as their range of applicability	40
Table 6. Effect of grid resolution on the drag and lift coefficients of a clean spherical bubble translating close to a wall ($L_R = 2$) in a stagnant fluid.	43
Table 7. Effect of grid resolution on the drag and lift coefficients of a rigid sphere translating close to a wall ($L_R = 2$) in a stagnant fluid.	47
Table 8. Total lift, vortical-induced lift, and the difference at $Re = 250$ for $L_R \geq 1.5$	82

1 INTRODUCTION

1.1 Background

The hydrodynamic force on bubbles and particles moving in wall-bounded flows is a problem of fundamental importance in fluid mechanics, which arises in a variety of technical and natural systems. Technical applications are abundant in microfluidics where the system dimensions are small e.g. inertial focusing (i.e., the alignment of spheres along a streamline of the flow field) (Hadikhani et al., 2018; Païè et al., 2017) and sorting (Kok et al., 2015; Chiu et al., 2016). Applications in larger scale systems are e.g. mixing (Risso, 2018) and erosive wear (Sinha et al., 2017). Similarly, relevant natural phenomena range from cavitation in choked flows (Brennen, 2014) to transport of sediment in rivers (Charru et al., 2013).

Generally speaking the hydrodynamic force acting on a sphere may be decomposed into components parallel and perpendicular to the direction of the relative motion between the body and the fluid surrounding it. The former is commonly referred to as the drag force, the latter as the lift force. For a non-spherical body some care needs to be taken as the above classification is strictly valid only if the body moves along an eigendirection of the tensorial drag coefficient. If the relative motion is not along such an eigendirection, the drag force needs not be aligned with it. In this case, drag is more precisely characterized by being expressed in terms of a symmetric tensor-coefficient (i.e. one with real eigenvalues), while lift is expressed in terms of an antisymmetric tensor-coefficient (i.e. one with imaginary eigenvalues). Since only spherical bubbles and particles are considered, this complication does not arise in the following discussion.

The presence of the wall tends to increase the drag force, but more importantly causes a transverse lift force acting on the sphere that can be directed either towards the wall or away from it depending on the detailed flow conditions. The lift force, although often much smaller in magnitude than the drag force, plays a crucial role in the accumulation of bubbles and particles either close to or away from the wall. This force also appears in the closure relations involved in the point-particle based Eulerian-Lagrangian approach (E-L, Subramaniam, 2013) or in an Eulerian-Eulerian approach based on the interpenetrating continua concept (E-E, Drew, 1983).

Asymptotic theories, laboratory experiments and direct numerical simulation (DNS) have been employed to determine near-wall hydrodynamic loads under various flow conditions. Asymptotic theories are suitable for studying low-Reynolds-number configurations (see Magnaudet et al. (2003) for a brief review). They may also be employed at very large Reynolds number for clean bubbles (Magnaudet, 2011). Asymptotic solutions are explicit but are valid only within a limited range of flow conditions. Experimental and DNS studies do not suffer from the same limitations and allow, in principle, rather arbitrary Reynolds numbers to be considered in a range of flow configurations. However, owing to mechanical limitations of the experimental devices (Takemura et al., 2003; Takemura et al., 2009; Takemura and Magnaudet, 2009) and numerical difficulties arising in DNS (Zeng et al., 2009; Lee and Balachandar, 2010; Shi et al., 2020), few studies to date provide reliable data describing the variations of the lift force acting on spheres moving in the vicinity of a wall as a function of the relevant parameters. In particular, no systematic investigation of shear- and wall-induced effects has been reported in the range of intermediate Reynolds numbers where inertial effects are dominant.

1.2 Underlining mechanisms

As discussed in the recent reviews (Shi and Rzehak 2019, 2020) and illustrated in Figure 1.1 below, the lift force acting on a sphere translating in a wall-bounded shear flow at low-to-moderate Reynolds numbers arises from two primary mechanisms. The first of these is the interaction between the wall and the vorticity produced at the sphere surface due to its translation with respect to the ambient fluid (hereafter referred to as the wall effect). When the undisturbed flow is stagnant (Figure 1.1 (a)), this contribution reduces to a wall-normal lift force (so-called vortical wall-induced lift) pointing into the flow (Vasseur and Cox, 1977; Takemura et al., 2002). The second mechanism is the asymmetric advection of the vorticity produced at the surface of the sphere by the ambient shear, which results in a force which is not aligned with the direction of the relative motion (the so-called Saffman-lift). When the sphere is far enough from the wall, as illustrated in Figure 1.1 (b), this contribution reduces to the shear-induced lift force in an unbounded flow, the asymptotic expression of which was derived in Saffman (1965) and Legendre and Magnaudet (1997) for a rigid sphere and a drop of arbitrary viscosity, respectively. In wall-bounded linear shear flows, both mechanisms are active. However, they do not combine linearly, as the entire flow disturbance is governed by the Oseen equation which prevents the linear superposition of individual disturbances. Moreover, the sphere may either lag or lead the fluid, which, as illustrated in Figure 1.1 (c) and (d), results in a cooperative or antagonistic combination of the wall- and shear-induced lift effects. In the low-to-moderate Reynolds number regime, bubbles behave similarly to rigid spheres, although the magnitude of the various contributions to the hydrodynamic force differs according to the viscosity ratio of the inner and outer fluids.

Figure 1.1. Wall- and shear-induced contributions to the lift force acting on a sphere (either a clean bubble or a rigid sphere) in the low-to-moderate Reynolds number regime. (a) Stagnant fluid in the presence of a wall, where only the vortical wall-induced lift exists and the sphere always leads the fluid. (b) Unbounded linear shear flow, where only the Saffman-lift exists; the force points away from the wall when the sphere lags behind the fluid, and its direction reverses if the sphere leads the fluid. (c), (d) Wall-bounded linear shear flow. The sphere lags the fluid in (c), where the two effects cooperate, while it leads the fluid in (d), making the two effects combine in an antagonistic manner.

The mechanisms governing the wall-induced lift force become different when the translational Reynolds number Re is large. This is because the vorticity produced at the surface of a clean bubble does not go on increasing with Re (Magnaudet et al., 1995), unlike for the case of a solid sphere, at the surface of which the no-slip condition applies and the surface vorticity grows like $Re^{1/2}$ when Re is large (Magnaudet and Mougin, 2007). Because of this saturation of the vorticity at the surface of a clean spherical bubble, the magnitude of the vortical wall-induced lift force at a given distance from the wall decreases as the Reynolds number increases. Then a second, inviscid mechanism takes over. Indeed, according to potential flow theory, a sphere translating parallel to a symmetry plane is attracted toward this plane because the fluid velocity reaches a maximum in the gap, thus inducing a pressure gradient directed away from the symmetry plane (van Wijngaarden, 1976; Miloh, 1977; Biesheuvel and van Wijngaarden, 1982; Kok, 1993). Hence, there is a critical gap-

dependent Reynolds number beyond which the transverse force acting on the bubble switches from repulsive (corresponding to the above vortical wall-induced lift mechanism) to attractive (corresponding to the above irrotational mechanism) (Takemura and Magnaudet, 2003) (see Figure 1.1(a) and Figure 1.2 (a)). No such reversal of the transverse force takes place in the case of a solid sphere (see Figure 1.1(a) and Figure 1.3 (a)), as the vortical wall-induced mechanism remains dominant no matter how large the Reynolds number.

Figure 1.2. Wall- and shear-induced contributions to the lift force acting on a spherical bubble in the moderate-to-large Reynolds number regime. (a) Stagnant fluid in the presence of a wall, where only the irrotational wall-induced lift exists. (b) Unbounded linear shear flow, where the Lighthill-Auton mechanism dominates; the force points away from the wall when the bubble lags behind the fluid, and its direction reverses if the bubble leads the fluid. (c), (d) Wall-bounded linear shear flow. The bubble lags the fluid in (c), where the two effects act in an antagonistic manner, while it leads the fluid in (d), where the two effects cooperate.

Figure 1.3. Wall- and shear-induced contributions to the lift force acting on a rigid sphere in the moderate-to-large Reynolds number regime. (a) Same as in Figure 1.1 (a). (b) Unbounded linear shear flow, where the viscous-weakening mechanism dominates; the force points towards the wall when the rigid sphere lags behind the fluid, and its direction reverses if the rigid sphere leads the fluid. (c), (d) Wall-bounded linear shear flow. The rigid sphere lags the fluid in (c), where the two effects act in an antagonistic manner, while it leads the fluid in (d), where the two effects cooperate.

Similar discrepancy regarding the mechanism governing the shear-induced lift force occurs at large Reynolds number. According to the low- Re asymptotic solution (Legendre and Magnaudet, 1997), the Saffman lift force rapidly decreases as the Reynolds number increases. Then a second vortical mechanism takes over. Indeed, according to the inviscid rotational flow theory (Lighthill, 1956), the distortion of the vorticity associated with the ambient shear by the sphere at high Reynolds number results in the generation of a nonzero stream-wise vorticity which is concentrated in the wake within two counter-rotating trailing vortices. The secondary velocity field induced by this stream-wise vorticity yields a second shear-induced lift force (Auton, 1987; so called Lighthill-Auton-lift), the direction of which was found identical with that of the Saffman-lift. At large-but-finite Reynolds number, viscous effects induce in the vicinity of the sphere a second stream-wise vorticity, the direction of which is antiparallel to the one due to the inviscid vortex tilting mechanism and thus weakens the Lighthill-Auton-lift. For a clean spherical bubble, this weakening effect never plays a significant role since the second stream-wise vorticity is always weak and decays rapidly with increasing Re (Legendre and Magnaudet, 1998). As a result, the direction of

the shear-induced lift force acting on a clean spherical bubble is independent of Re (see Figure 1.1(b) and Figure 1.2 (b)). In contrast, for a solid sphere at the surface of which the no-slip condition applies, the second stream-wise vorticity increases with increasing Re and overwhelms the outer vorticity in the mechanism generating the lift force when Re goes beyond some value. Hence, there is a critical shear-rate-dependent Reynolds number beyond which the shear-induced lift force acting on a rigid sphere switches from positive (corresponding to the above Lighthill-Auton mechanism) to negative (corresponding to the above viscous-weakening mechanism) (see Figure 1.1 (b) and Figure 1.3 (b)).

Due to the changes in the governing lift-generation mechanisms, the manner of interaction between the shear- and wall-induced lift forces at moderate-to-large Re behaves differently to that at low-to-moderate Re . For a clean spherical bubble, as illustrated in Figure 1.3 (c) (resp. Figure 1.3 (d)), the two effects are now antagonistic if the bubble lags (resp. leads) the fluid. The same behavior applies for a rigid sphere, while the directions of the shear- and wall-induced lift forces are usually antiparallel to those acting on a clean bubble (see Figure 1.3 (c) and (d)).

1.3 State of the art

Owing to its fore-aft symmetry, a sphere may only experience a lift force in the presence of finite inertial effects (Bretherton, 1962). In the low-but-finite Reynolds number regime, when the distance r to the sphere center increases, the magnitude of the translation-induced inertia term becomes comparable to the viscous term at a distance $r \sim O(\tilde{L}_u)$, where $\tilde{L}_u = \nu/U_{\text{rel}}$ is the Oseen length, ν and U_{rel} denoting the fluid kinematic viscosity and relative velocity between the body and fluid, respectively. Similarly, the shear-induced inertia term becomes comparable to the viscous term at a distance $r \sim O(\tilde{L}_\omega)$, where $\tilde{L}_\omega = (\nu/\omega_\infty)^{1/2}$ is the Saffman length, $\omega_\infty = \|\boldsymbol{\omega}_\infty\|$ denoting the norm of the vorticity $\boldsymbol{\omega}_\infty$ in the undisturbed flow. The parameter $\varepsilon = \tilde{L}_u/\tilde{L}_\omega$ determines whether the dominant inertial effect arises from shear ($\varepsilon > 1$) or slip ($\varepsilon < 1$). When the flow is bounded by a flat wall, the distance $\tilde{L}$ separating the sphere from the wall may be compared to the two inertial length scales through the ratios $L_u = \tilde{L}/\tilde{L}_u$ and $L_\omega = \tilde{L}/\tilde{L}_\omega$. Provided that $\max(L_u, L_\omega) \ll 1$, the wall is located in the inner region of the disturbance, while it stands in the outer region if $\max(L_u, L_\omega) \geq O(1)$.

The wall-induced lift force acting on rigid spheres in the low-Reynolds-number regime was considered in Cox and Hsu (1977) adapting the method of regular perturbation analysis. Their asymptotic expression was obtained for situations where the wall lies in the inner region of the disturbance. The case where the wall lies in the outer region was worked out in Vasseur and Cox (1977) adapting the method of singular perturbation analysis. In both cases, the wall-induced lift force was predicted to decrease with increasing wall distance L_u . The generalization of the two results above to spherical drops of arbitrary viscosity was achieved using similar approaches in Magnaudet et al. (2003) and Takemura et al. (2002), respectively. Their analyses indicate that, in both cases, the wall-induced lift force acting on a clean bubble (i.e. a spherical drop with a vanishing inner viscosity) differs from that on a rigid sphere only by a numerical factor of $(2/3)^2$. The wall lies usually in the outer region when the translational Reynolds number (based on the sphere diameter and relative velocity with respect to the ambient fluid) is larger than unity. For a clean bubble, experiments and DNSs performed in still fluid (Takemura and Magnaudet, 2003; Sugioka and Tsukada, 2015) revealed that the vortical mechanism responsible for the wall-induced lift force dominates the interaction process for $Re \lesssim 30$, while the irrotational mechanism becomes

dominant at higher Re , making bubbles tend to cluster at the wall. On the other hand, for the case of a rigid sphere, experiments and DNSs (Takemura and Magnaudet, 2003; Zeng et al., 2005, 2009) have shown that the vortical mechanism responsible for the wall-induced lift force at low Reynolds number still applies up to $Re \approx 100$, but the decay of the wall-induced lift force with increasing L_u was found faster than that obtained at low Re .

The analytical expression for the low-Reynolds-number shear-induced lift force acting on a rigid sphere moving in an unbounded flow domain was derived by Saffman (1965, 1968) in the strong shear limit ($\varepsilon \gg 1$), using the method of matched asymptotic expansions. Extension of Saffman's expression to finite ε , i.e. to conditions under which advective effects due to the sphere translation cannot be neglected with respect to those due to the shear, was later conducted independently in Asmolov (1989) and McLaughlin (1991) using a similar approach. These analyses indicate that the shear-induced lift force decreases with decreasing ε^* . The generalization of the above results to spherical drops of arbitrary viscosity was achieved in Legendre and Magnaudet (1997). This analysis indicates that the shear-induced lift force acting on a clean bubble differs from that on a rigid sphere only by a numerical factor of $(2/3)^2$, a ratio identical to the one found concerning the wall-induced lift force. At moderate Reynolds number, the vorticity generated at the bubble surface by the shear-free boundary condition and the vorticity present in the ambient shear flow both contribute to the lift force (Legendre and Magnaudet, 1998). The latter becomes dominant for $Re \gtrsim 30$ and the resulting lift force then approaches the inviscid prediction obtained by Auton (1987). On the other hand, for a rigid sphere, the stream-wise vorticity generated at the sphere surface by the no-slip boundary condition weakens the Lighthill-Auton mechanism. Instead of approaching the inviscid prediction in the limit $Re \rightarrow \infty$ the shear-induced lift force on a rigid sphere becomes negative beyond $Re \approx 60$ (Kurose and Komori, 1999; Lee and Wilczak, 2000; Bagchi and Balachandar, 2002).

Shear-induced and wall-induced lift effects combine in wall-bounded linear shear flows. In situations where the Reynolds number is small and the wall lies in the inner region, the lift force acting on a rigid sphere sitting on the wall was derived in Leighton and Acrivos (1985) and Krishnan and Leighton (1995) by using specific approximations taking into account the lubrication layer in the gap between the wall and the surface of the sphere. Situations with finite gaps (while the wall lies still in the inner region) have been investigated by Cox and Hsu (1977), Cherukat and McLaughlin (1994), and Yahiaoui and Feuillebois (2010) through a regular perturbation analysis. Their results indicate that, in situations where the wall lies in the inner region, the lift force results from two contributions. One is due to the wall effect and depends on the wall distance only. The other is due to the presence of the shear and depends linearly and quadratically on the shear rate (see e.g. Eq. (2.17a) in section 2.4). The generalization of the above results to spherical drops of arbitrary viscosity was achieved in Magnaudet et al. (2003). This analysis indicates that the $(2/3)^2$ factor mentioned above still applies concerning the leading order terms of the shear- and wall-contributions. The wall may lie in the outer region of the disturbance while the Reynolds number is still small, in which case the lift force may still be evaluated analytically through the method of matched asymptotic expansions. This problem was first considered in Drew (1988) in the strong shear limit for a rigid sphere, and revisited independently in Asmolov (1990) and McLaughlin

* McLaughlin (1991) has shown that for $\varepsilon < 0.22$ the direction of the lift is reversed. This feature is not confirmed in DNS study at small ε and likely caused by the neglect of higher order terms in the asymptotic expansion (Legendre and Magnaudet, 1998; Shi and Rzehak, 2019).

(1993) where the solution was extended to finite ε . Both concluded that the presence of the wall consistently reduces the shear-induced lift force, which agrees with the behavior predicted in Magnaudet et al. (2003) in the case where the wall lies in the inner region. In Asmolov (1990) and McLaughlin (1993), the solution for the lift force was obtained by a three-dimensional integral in Fourier space. In Takemura et al. (2009) it was assumed that, similar to the solutions derived in Magnaudet et al. (2003), the lift force may still be expressed as a superposition of the wall- and the (unbounded) shear-induced lift forces in physical space when the wall stands in the outer region, provided some modification due to the shear (resp. the presence of the wall) is introduced in the wall-induced (resp. shear-induced) contribution. This procedure yields an explicit approximate expression for the lift force as a function of the various physical parameters.

At finite Reynolds numbers, the wall lies usually in the outer region. Investigations in this case rely on experimental and DNS studies. Situations with bubbles and rigid spheres moving at low-but-finite Reynolds number along the wall of a wall-bounded linear shear flow, with the sphere either lagging or leading the fluid, were investigated experimentally in Takemura et al. (2009) and Takemura and Magnaudet (2009), respectively. This allowed the authors to explore the cooperative and antagonistic interactions between the wall- and shear-induced lift effects. Using an appropriate drag law modified by the presence of the wall and the influence of inertial effects, the resulting lift force was obtained from the measured migration velocity. A semi-empirical prediction for that force comparing well with the experimental data for $Re < 1.5$ was proposed. Situations with rigid spheres moving at moderate to high Reynolds numbers in wall bounded linear shear flows were investigated numerically by Zeng et al. (2009). Unfortunately, in all their simulations the sphere was considered to be stationary with respect to the bounding wall, which is only a special flow configuration where the sphere lags the fluid. Experimental or DNS study for either clean bubbles or rigid spheres moving at moderate-to-high Reynolds number in the same configuration as that of Takemura et al. (2009) and Takemura and Magnaudet (2009) is still unavailable.

1.4 Motivation, goal and outline of the thesis

Apart from the intrinsic fundamental interest in the study of the hydrodynamic loads on a sphere moving in a wall bounded flow, results obtained for this restricted problem also provide reliable closure models for the drag and lift forces, which are important inputs involved in both E-L and E-E approaches. Given that fully resolved simulations of bubbly or particulate flows remain challenging (Elghobashi, 2019; Maxey, 2017), simulations at industrial scale are only viable within these two frameworks.

The accuracy of the E-L and E-E approaches largely relies on the reliable approximate expressions for the interfacial forces especially the drag and lift, the development of which with a wider range of applicability requires the acquisition of new data and an identification of the underlying mechanisms involved in the different flow regimes. In particular the proposal of Lee and Balachandar (2010) to conduct simulations in a moving coordinate frame to account for the translation of the body with respect to the wall possesses further potential to make progress in this direction. This idea is applied in the present work, in which results of a systematic numerical study performed with spheres translating in a wall-bounded linear shear flow with the sphere either leading or lagging the fluid are reported. Variations of the stationary drag and lift forces are presented over a wide range of Reynolds number, wall distance, and shear rate. The results are compared with available theoretical or semi-empirical expressions. Based on this comparison, new approximate expressions for the force components are proposed.

The remainder of this thesis is organized as follows. In chapter 2, the problem is formulated and the scope of the work is made precise together with basic definitions used throughout the thesis. Expressions for the drag and lift forces available in the literature are then summarized. To get the best currently available description, alternative expressions are critically assessed by comparison to data from analytical, experimental, and DNS studies. The results reported in this chapter are mainly based on Shi and Rzehak (2019, 2020), while those reported in the followings are mainly based on Shi et al. (2020a, 2020b). Chapter 3 gives a short description of the numerical procedure and results for preliminary tests conducted to validate the numerical method and setup. Chapters 4 and 5 discuss physical features and hydrodynamic mechanisms revealed by the flow field around a clean spherical bubble and a rigid sphere, respectively. Results for the hydrodynamic forces are presented and analyzed in these two chapters as well. Conclusions and directions for future work are finally provided in section 6.

2 STATE OF THE ART

2.1 Statement of the problem

Throughout the present work, a Cartesian coordinate system ($Oxyz$) with the origin located at the center of the sphere is used, as illustrated in Figure 2.1. It is assumed that the non-rotating sphere moves with a velocity $\mathbf{V} = V\mathbf{e}_z$ parallel to a single planar wall. The wall is located at $x = -\tilde{L}$ and $\mathbf{e}_x$ denotes the wall-normal unit vector pointing into the fluid. In the reference frame translating with the sphere, the unperturbed flow is a one-dimensional linear shear flow with a velocity profile $\mathbf{u}_\infty = [\gamma(\tilde{L} + x) - V]\mathbf{e}_z$, and a nonzero spanwise vorticity $\boldsymbol{\omega}_\infty = -\gamma\mathbf{e}_y$. The relative (or slip) velocity between the fluid with respect to the bubble is then $\mathbf{U}_{\text{rel}} = (\gamma\tilde{L} - V)\mathbf{e}_z$. The fluid velocity and the pressure field in the presence of the sphere are denoted by $\mathbf{u}$ and p , respectively, and $\boldsymbol{\omega} = \nabla \times \mathbf{u}$ denotes the vorticity.

Figure 2.1. Schematic of a non-rotating sphere moving in a wall-bounded linear shear flow.

The surrounding fluid is assumed to be Newtonian and the flow is considered as incompressible. The continuity and Navier-Stokes equations thus take the form

$$\nabla \cdot \mathbf{u} = 0; \quad \frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho} \nabla p + \nabla \cdot \boldsymbol{\tau}, \quad (2.1a,b)$$

where $\boldsymbol{\tau} = \nu[\nabla \mathbf{u} + {}^T \nabla \mathbf{u}]$ is the viscous part of the stress tensor $\boldsymbol{\Sigma} = -p\mathbf{I} + \rho\boldsymbol{\tau}$ and ρ is the density of the liquid, $\mathbf{I}$ denoting the Kronecker tensor. In the reference frame attached to the sphere center, boundary conditions at the wall and in the far field are

$$\mathbf{u} = \begin{cases} -V\mathbf{e}_z & \text{for } x = -\tilde{L}, \\ [\gamma(\tilde{L} + x) - V]\mathbf{e}_z & \text{for } r \rightarrow \infty. \end{cases} \quad (2.2a,b)$$

where $r = (x^2 + y^2 + z^2)^{1/2}$ denotes the position with respect to the sphere center.

On the bubble surface, the normal velocity must vanish, owing to the non-penetration condition. Moreover, the dynamic viscosity of the gas within the bubble is assumed to be much smaller than that of the suspending liquid and the bubble surface is considered to be free of any surfactant, so that the outer fluid obeys a shear-free condition at the interface. Last, surface tension is assumed to be strong enough for the capillary force to be able to maintain the bubble spherical whatever the

local strength of the hydrodynamic stresses. Under such conditions, the boundary conditions at the bubble surface are

$$\left. \begin{array}{l} \mathbf{u} \cdot \mathbf{n} = 0 \\ \mathbf{n} \times (\boldsymbol{\tau} \cdot \mathbf{n}) = 0 \end{array} \right\} \quad \text{for} \quad r = \frac{d}{2}. \quad (2.3)$$

where $\mathbf{n}$ denotes the outward unit normal to the bubble surface. On other hand, for a rigid sphere, the non-penetration and no-slip boundary conditions applying at the sphere surface yield

$$\mathbf{u} = 0 \quad \text{for} \quad r = \frac{d}{2}. \quad (2.4)$$

With the above boundary conditions, the parameters governing the steady flow field past the sphere may be stated as the Reynolds number Re , the non-dimensional shear rate Sr , and the wall distance L_R . These are defined as

$$Re = \frac{U_{\text{rel}} d}{\nu}, \quad Sr = \frac{\gamma d}{U_{\text{rel}}}, \quad L_R = \frac{2\tilde{L}}{d}, \quad (2.5)$$

with $U_{\text{rel}} = \mathbf{U}_{\text{rel}} \cdot \mathbf{e}_z$. A positive (resp. negative) sign of Sr indicates that the sphere lags (resp. leads) the fluid.

In the more general case, any three independent parameters may be chosen from the set of dimensionless variables $L_R, L_u, L_\omega, Re, Sr$ and ε as the governing parameters. In special cases, some of the variables may be irrelevant and a certain choice for the relevant ones be most obvious. This will be discussed in the respective part of the rest sections within this chapter.

As stated in the introduction, the particular interest here is the hydrodynamic force acting on the sphere. This force may be split into its drag component $\mathbf{F}_D$ parallel to $\mathbf{U}_{\text{rel}}$, and its lift or transverse component, $\mathbf{F}_L$, parallel to $\mathbf{e}_x$, namely

$$\mathbf{F}_D = \frac{U_{\text{rel}}}{\|\mathbf{U}_{\text{rel}}\|} \cdot \int_{\Gamma} \boldsymbol{\Sigma} \cdot \mathbf{n} \, d\Gamma, \quad \mathbf{F}_L = \mathbf{e}_x \cdot \int_{\Gamma} \boldsymbol{\Sigma} \cdot \mathbf{n} \, d\Gamma, \quad (2.6)$$

where Γ is the sphere surface. Results concerning these forces will be expressed in terms of the dimensionless lift and drag coefficients C_L and C_D , obtained by dividing the corresponding component of the force by $\pi d^2 \rho U_{\text{rel}}^2 / 8$. Note that a negative (resp. positive) value of the lift coefficient corresponds to an attractive (resp. repulsive) force with respect to the wall. the notations C_D^W (resp. C_L^W) and C_D^U (resp. C_L^U) are introduced to denote the drag (resp. lift) coefficients in wall-bounded and unbounded flows, respectively. Situations where the wall lies in the inner or outer region of the disturbance will be distinguished by the superscripts W-in and W-out, respectively. To appreciate the modification of the drag force due to the wall and shear effects, results for the drag coefficient are usually given in the form of the relative change $\Delta C_D = (C_D - C_{D0}^U) / C_{D0}^U$, where C_{D0}^U denotes the drag coefficient on a sphere moving in an unbounded uniform stream. Drag (resp. lift) contributions corresponding to the wall-induced effect are denoted with the subscript Du (resp. Lu), while those corresponding to the shear-induced effect are denoted with the subscript Dw (resp. Lw).

The situations considered in the present review comprise a sphere translating in the following flow configurations:

- (a) unbounded linear shear flow, i.e. $L_R \rightarrow \infty$, $L_u \rightarrow \infty$, and $L_\omega \rightarrow \infty$;
- (b) linear shear flow with the wall lying in the inner region;
- (c) stagnant flow with the wall lying in the outer region;
- (d) linear shear flow with the wall lying in the outer region;

2.2 Overview of literatures

The literature review covers all four cases, a through d, described in the previous section. Only works concerned with spheres in laminar flows of Newtonian fluids have been taken into account. No distinction has been made whether the fluid is a liquid or a gas, but only studies up to $Re = O(10^2)$ are included. Also only the steady hydrodynamic force is considered.

An overview of all reviewed works is given in Table 1 in chronological order. In addition to the cases treated, limits on the validity of the results are listed in terms of the pertinent dimensionless variables. A brief description of the results obtained is included in the table, while a more detailed discussion will be presented in the following sections organized into a number of different topics. Relevant research methods include theoretical study mainly by means of the method of either regular or singular expansion analyses, experiment, and DNS. Different solutions for the hydrodynamic force based on perturbation theory at low Reynolds numbers can be found in the literature. These solutions are analytical and explicit but are valid in only a limited range of normalized wall distances. Experimental and DNS studies are not limited in this way, but provide only approximations to the idealized conditions stipulated in the previous section and introduce measurement or numerical errors.

For unbounded flows, analytical solution of the Navier–Stokes equations is straightforward for creeping flow conditions, i.e. $Re = 0$, in which case the problem becomes linear. For small but non-zero Re an approximate solution may be obtained the method of matched asymptotic expansions (Kaplun and Lagerstrom, 1957; Proudman and Pearson, 1957). The difficulty in this case is due to the fact that convective inertia represent a singular perturbation of the creeping-flow problem. To deal with this situation, two perturbation expansions in terms of the small parameter $\epsilon \propto Re$ are formed, an inner and an outer one. The inner expansion is expressed in terms of the usual spatial coordinate $\bar{r} = 2r/d$ and satisfies the boundary condition on the surface of the sphere, but not the far-field condition to match the unperturbed flow. The outer expansion is expressed in terms of the scaled coordinate $\epsilon\bar{r}$ and satisfies the far field condition, but treats the effect of the sphere only as a point force which can be modeled by a Dirac source term. At zero order, both expansions directly combine to the creeping flow solution, while at higher orders the expansion coefficients are determined by matching the inner and the outer solutions in an intermediate region where both the solutions are supposed to be valid (Hinch, 1991, section 5.3).

When the bounding wall is involved and lies in the inner region of the disturbance (i.e. when $\max(L_u, L_\omega) \ll 1$), the inertial effects affecting the hydrodynamic force at various order of approximation (with respect to L_R^{-1}) may be obtained through a regular perturbation expansion because wall-induced corrections make the velocity disturbance decay as $\bar{r}^{-2}$ (Cox and Brenner, 1968) in the far field of the sphere instead of decaying as $\bar{r}^{-1}$ in the classical unbounded case.

When the sphere's radius is negligible compared to the wall distance, i.e. $L_R \gg 1$, its presence may be treated as a point-force to obtain the hydrodynamic force at zeroth-order. In contrast, situations where the sphere is moving close to a wall, i.e. $(L_R - 1) \sim O(1)$, require its finite size to be taken into account. The integrals required to obtain the hydrodynamic force then can be formulated analytically by means of either the reciprocal theorem or the boundary element method, but in most circumstances have to be evaluated numerically. In the limit that the wall distance comes down to the lubrication region, i.e. $(L_R - 1) \ll 1$ (O'Neill and Stewartson, 1967), both the reciprocal theorem and the boundary element method break down and the leading-order terms must be evaluated by using specific approximations taking into account the lubrication layer in the gap (this is labeled as 'lubrication analysis' in Table 1).

When the characteristic lengths become large enough such that $\max(L_u, L_\omega) \geq O(1)$, the wall lies in the outer region of the disturbance and a singular perturbation problem has to be solved to determine the hydrodynamic force. This requires the use of matched asymptotic expansions. The presence of the sphere in the flow field is always treated as a point-force due to the fact that $L_R = 2L_u/Re = 2L_\omega/(SrRe)^{1/2} \gg 1$. In the shearless case ($L_\omega = 0$), the hydrodynamic force is a function of L_u only and the matching procedure results in a simple two-dimensional integral in Fourier space, which in general has to be evaluated numerically. Analytical solutions can be obtained in the limits of both $L_u \gg 1$ and $L_u \ll 1$. In the presence of shear, the matching procedure yields a fourth-order ordinary equation for a partial Fourier transform, which may be solved either by numerical means or through analytical calculation taking advantage of Airy functions.

Most of the experimental studies of the inertial lift in wall-bounded flows reported to date pertain to axisymmetric or plane two-dimensional Poiseuille flows. Only few detailed experiments devoted to the lateral migration of spheres in wall-bounded stagnant or linear shear flows have been reported. A pioneering experiment was conducted by Vasseur and Cox (1977) concerning the lateral migration behavior of rigid spheres in a planar Couette flow. Due to the experimental uncertainty, their theory in the case where the wall is located in the Oseen region was confirmed only qualitatively. The recent experiments of Takemura and co-authors (Takemura et al., 2002, 2009; Takemura and Magnaudet, 2003, 2009) provide, to our knowledge, the only reliable measurement of wall-bounded lift force over a wide range of Reynolds numbers. In situations with spheres moving in stagnant flow, measurements are available even up to a Reynolds number of one hundred, whereas in situations concerning a linear shear flow, only moderate Reynolds number ($Re \sim O(1)$) and fairly weak shear rate ($\gamma \sim O(1) \text{ s}^{-1}$) have been achieved so far owing to mechanical limitations of the experimental devices in realizing a linear shear flow. Lastly, it has to be noted that for all experiments the immediately accessible parameter is the sphere terminal and migration velocities. Transformation from a migration (resp. terminal) velocity to the corresponding lift (resp. drag) force is straightforward, provided that the drag law is known. This, however, is not straightforward to obtain as corrections to the Stokes drag due to the ambient shear, translational inertia, and the wall have to be considered. A brief discussion on the drag law corrections will be given in section 2.6.2.

Available DNS studies are usually restricted to situations with moderate Reynolds numbers. As discussed above, studying the inertial contribution to the hydrodynamic force at low Reynolds number needs the implementation of a rather large computational domain to reduce effects of the numerical boundary on the ideally unbounded side, which may result in unaffordable CPU times. Compared with experiment, DNS allows to closely match the desired idealized conditions and the hydrodynamic force can be evaluated directly without needing to refer to the drag law. Reynolds

numbers of several hundreds are feasible and rather arbitrary shear rates can be specified. The only restriction of DNS compared with experimental study seems that, if such computations are to be performed in a frame of reference fixed to the wall, the numerical methodology must be capable of handling the translational motion of the sphere and this results in rather high computational cost. Most DNS studies employing such a reference frame therefore consider only a stationary sphere (so that no translation occurs), which corresponds to the special condition that $Sr = 2L_R^{-1}$. As pointed out by Lee and Balachandar (2010), a more promising way would be to perform the simulations in a frame moving with the sphere. However, this has hardly been carried out yet such that systematic DNS study of a sphere translating in wall-bounded flows involving both positive and negative Sr is still unavailable.

Table 1: Studies of the lift force acting on spheres in linear shear flows.

Reference	Method 1)	Cases considered 2)				Scope of application	Results 3)
		a	b	c	d		
Saffman (1965, 1968)	SPE	×	-	-	-	$Re \ll 1, \varepsilon \gg 1$	Par.: analytical solution for lift
Cox and Brenner (1968)	RPE	-	×	-	-	$Re \ll 1, L_R \gg 1$	Par.: lift expressions in terms of Green's functions
Cox and Hsu (1977)	RPE	×	×	-	-	$Re \ll 1, L_R \gg 1$	Par.: analytical solution for lift with leading order only
Vasseur and Cox (1977)	SPE	-	-	×	-	$Re \ll 1, Sr = 0$	Par.: lift expressions in form of 2d Fourier integral
	Exp	-	-	×	-	$0.026 \leq Re \leq 0.26, 5 < L_R < 50$	Par.: data for migration velocity
Leighton and Acrivos (1985)	LA	-	×	-	-	$Re \ll 1, L_R = 1, Sr = 2L_R^{-1}$	Par.: $C_{L\omega}^W(L_R = 1) = 5.87$
Auton (1987)	perturbed potential flow	×	-	-	-	$Re \rightarrow \infty, Sr \ll 1$	Bub.: analytical solution $C_{L\omega}^U = 2Sr/3$
Fischer and Rosenberger (1987)	BEM	-	×	-	-	$Re \ll 1, 1.2 \leq L_R \leq 10, Sr = 0, 2L_R^{-1}$	Par.: data for lift
Drew (1988)	SPE	-	-	×	-	$Re \ll 1, L_R \gg 1, \varepsilon \gg 1$	Par.: data for lift; wall enhances Saffman-lift for $L_\omega > 3$
Asmolov (1989, 1990)	SPE	×	-	×	-	$Re \ll 1, L_R \gg 1, \varepsilon \geq 0.5$	Par.: lift expression in form of 3d Fourier integral; wall inhibits Saffman-lift for whatever L_ω
Cherukat and McLaughlin (1990)	Exp	-	-	×	-	$0.1 \leq Re \leq 10, 3 < L_R < 13$	Par.: data for migration velocity with uncertainty $\leq 15\%$
Dandy and Dwyer (1990)	DNS	×	-	-	-	$0.1 \leq Re \leq 100, 0.2 \leq Sr \leq 0.8$	Par.: data for drag and lift; data were found unreliable
McLaughlin (1991, 1993)	SPE	×	-	×	-	$Re \ll 1, L_R \gg 1, \varepsilon \sim O(1)$	Par.: lift expressions in form of 3d Fourier integral; wall inhibits Saffman-lift for whatever L_ω

Mei (1992)	Review	×	-	-	-	$Re \leq 100,$ $0.2 \leq Sr \leq 0.8$	Par.: correlation for lift; no negative lift can be produced for $Re \geq 50$
Cherukat and McLaughlin (1994)	RT	-	×	-		$Re \ll 1,$ $1.1 \leq L_R \leq 20,$ $-10 \leq Sr \leq 10$	Par.: data and correlation for lift
Cherukat et al. (1994)	Exp	×	-	-	-	$0.2 < Re \leq 3.0,$ $0.15 \leq \varepsilon \leq 1.6$	data for lift; data suffers wall effect
Lovalenti (1994)	RPE	-	×	-	-	$Re \ll 1,$ $L_R \gg 1$	Par.: analytical solution for lift with leading order term only
Krishnan and Leighton (1995)	LA	-	×	-		$Re \ll 1,$ $L_R = 1,$ $Sr = 0, 2L_R^{-1}$	Par.: $C_{Lu}^W(L_R = 1) = 1.12,$ $C_{Lo}^W(L_R = 1) = 5.89$
Legendre and Magnaudet (1997)	SPE	×	-	-	-	$Re \ll 1,$ $\varepsilon \sim O(1)$	Bub.: analytical solution for lift
Legendre and Magnaudet (1998)	DNS	×	-	-	-	$0.1 \leq Re \leq 500,$ $Sr \leq 1$	Bub.: data and expression for drag (high Re) and lift
Salem and Oesterle (1998)	DNS	×	-	-	-	$Re = 0.1,$ $Sr \leq 0.4$	Par.: data for lift
Takagi and Matsumoto (1998)	DNS	×	-	-	-	$0.1 \leq Re \leq 200,$ $Sr = 0.2$	Bub.: data for lift
Cherukat et al. (1999)	DNS	×	-	-	-	$0.02 \leq Re \leq 2,$ $Sr \leq 0.4$	Par.: data for lift
Kurose and Komori (1999)	DNS	×	-	-	-	$0.5 \leq Re \leq 500,$ $Sr \leq 0.8$	Par.: data for drag and lift
Lee and Wilczak (2000)	DNS	×	-	-	-	$20 \leq Re \leq 500,$ $0.025 \leq Sr \leq 0.2$	Par.: data for lift
Bagchi and Balachandar (2002)	DNS	×	-	-	-	$0.5 \leq Re \leq 200,$ $Sr \leq 0.4$	Par.: data for drag and lift
Takemura et al. (2002)	Exp	-	-	×	-	$0.6 \leq Re \leq 4.4,$ $2.8 < L_R < 13,$ $Sr = 0$	Bub.: data for lift with uncertainty $\leq 5\%$
	SPE	-	-	×	-	$Re \ll 1,$ $Sr = 0$	Bub.: lift expressions in form of 2d Fourier integral
Magnaudet et al. (2003)	RT	-	×	-	-	$Re \ll 1,$ $L_R > 1$	Bub. & Par.: analytical solution for drag and lift involving higher order terms with respect to L_R^{-1}
Takemura and Magnaudet (2003)	Exp	-	-	×	-	$0.96 \leq Re \leq 92,$ $2.6 < L_R < 10;$ $Sr = 0$	Bub. & Par.: data and empirical expression for lift; Exp uncertainty $\leq 5\%$
Kim et al. (2005)	DNS	×	-	-	-	$300 \leq Re \leq 480,$ $0.05 \leq Sr \leq 0.15$	Par.: data for drag and lift
Zeng et al. (2005)	DNS	-	-	×	-	$0.5 \leq Re \leq 300,$ $1.5 \leq L_R \leq 8$	Par.: data for drag and lift; imperfect bifurcation occurs beyond $Re = 150$
Kim (2006)	DNS	×	-	-	-	$5 \leq Re \leq 200,$	Par.: data for lift

						$0.1 \leq Sr \leq 0.3$	
Bluemink et al. (2008)	DNS	×	-	-	-	$Re = 20, 50,$ $Sr = 0.1$	Par.: data for lift
Loth (2008)	Review	×	-	-	-	$0 < Re \leq 500,$ $0.2 \leq Sr \leq 0.8$	Par.: correlation for lift
Hölzer and Sommerfeld (2009)	DNS	×	-	-	-	$0.003 \leq Re \leq 480,$ $Sr = 0.16, 0.32$	Par.: data for drag and lift
Sugioka and Komori (2009)	DNS	×	-	-	-	$1 \leq Re \leq 300,$ $Sr \leq 0.4$	Bub.: data for drag and lift
Takemura et al. (2009)	Exp	-	-	-	×	$0.55 \leq Re \leq 3.5,$ $1 < L_R < 6,$ $-0.12 < Sr < 0.14$	Bub.: data and empirical expression for drag and lift; Exp uncertainty $\leq 5\%$
Takemura and Magnaudet (2009)	Exp	-	-	-	×	$0.20 \leq Re \leq 1.7,$ $1 < L_R < 5,$ $-0.09 < Sr < 0.13$	Par.: data for migration velocity; Exp uncertainty $\leq 5\%$
Zeng et al. (2009)	DNS	-	-	×	-	$2 \leq Re \leq 250,$ $1.01 \leq L_R \leq 8,$ $Sr = 0, 2L_R^{-1}$	Par.: data and empirical expression for lift
Lee and Balachandar (2010)	DNS	-	×	×	-	$5 \leq Re \leq 100,$ $1.01 \leq L_R \leq 2,$ $Sr = 0, 2L_R^{-1}, 0.5, 2$	Par.: data for drag and lift
Yahiaoui and Feuillebois (2010)	RT	-	×	-	-	$Re \ll 1,$ $1.2 \leq L_R \leq 100,$ $Sr = 0, 2L_R^{-1}$	Par.: data and empirical expression for lift
Homann et al. (2013)	DNS	×	-	-	-	$10 \leq Re \leq 200,$ $Sr = 0.2$	Par.: data for lift
Santarelli and Fröhlich (2015, 2016)	DNS	×	-	-	-	$Re = 260, 420,$ $Sr = 0.2$	Par.: data for lift
Sugioka and Tsukada (2015)	DNS	-	-	×	-	$1 \leq Re \leq 300,$ $L_R = 2,$ $Sr = 0$	Bub. & Par.: data for drag and lift
Zhou et al. (2017)	DNS	-	-	×	-	$0.5 \leq Re \leq 250,$ $3 \leq L_R \leq 4$	Par.: data for lift; imperfect bifurcation occurs beyond $Re = 150$
Candelier et al. (2019)	SPE	×	-	-	-	$Re \ll 1, \varepsilon \gg 1$	Bub. & Par.: analytical solution for drag and lift

1) BEM, boundary element method; Exp, experiment; LA, lubrication analysis; RPE, regular perturbation expansions; RT, reciprocal theorem; SPE, singular perturbation expansions.

2) ×, considered; -, not considered.

3) Par., study concerned with rigid spheres; Bub., study concerned with clean spherical bubbles.

2.3 Unbounded linear shear flow

2.3.1 Analytical solution at low- Re

At low-but-finite Reynolds number, the presence of a uniform shear tends to increase the drag, and simultaneously causes a transverse or lift force in the direction of $\mathbf{U}_{\text{rel}} \times \boldsymbol{\omega}$. Both forces are

proportional to $(|Sr|Re)^{1/2}$. They may be expressed in terms of the drag and lift coefficients in the form

$$\begin{aligned} C_{D\omega}^U(Re \ll 1) - C_{D0}^U(Re \rightarrow 0) &= \frac{18}{\pi^2} \beta^2 \varepsilon J_D(\varepsilon), \\ C_{L\omega}^U(Re \ll 1) &= \frac{18}{\pi^2} \beta^2 \frac{Sr}{|Sr|} \varepsilon J_L(\varepsilon), \end{aligned} \quad (2.7a,b)$$

where $C_{D0}^U(Re \rightarrow 0)$ denotes the drag coefficient in the creeping flow limit, i.e. $C_{D0}^U(Re \rightarrow 0) = 24\beta/Re$, $\varepsilon = \tilde{L}_u/\tilde{L}_\omega = (|Sr|Re)^{1/2}$ is the ratio of the Oseen and Saffman lengths scales, and $\beta = 2/3$ (resp. $\beta = 1$) for a clean bubble (resp. rigid sphere). The function $J_L(\varepsilon)$ was derived for arbitrary values of ε in McLaughlin (1991, Eq. (3.20)). In the limit $\varepsilon \rightarrow \infty$, one has (Candelier et al., 2019)

$$J_D(\infty) = 0.485, \quad J_L(\infty) = 2.254. \quad (2.8a,b)$$

The way the function $J_D(\varepsilon)$ tends to zero as ε decreases is still unknown, but this is of little importance since the relative magnitude of the shear-induced correction to the drag is small whatever ε in this regime. Thus for convenience, the subscript ‘ L ’ will be dropped hereafter and $J(\)$ will always stand for $J_L(\)$. At finite ε the function J_L was evaluated numerically in Asmolov (1990) and McLaughlin (1991). Their results are shown, respectively, as the red crosses and open circles in Figure 2.2. According to the numerical data of McLaughlin (1991), $J(\varepsilon)$ decreases as ε becomes smaller and even changes its sign for $\varepsilon < 0.22$. In the limiting cases of very large and very small ε , explicit expressions for $J(\varepsilon)$ were found by McLaughlin (1991) as

$$J(\varepsilon) = \begin{cases} 2.255 - 0.6463\varepsilon^{-2} & \text{for } \varepsilon \gg 1 \\ -32\pi^2\varepsilon^5 \ln(1/\varepsilon^2) & \text{for } \varepsilon \ll 1 \end{cases}, \quad (2.9)$$

which are shown as the dashed lines in Figure 2.2.

A comparison of the results for $J(\varepsilon)$ obtained by both authors in Figure 2.2 (b) shows that for moderate ε , McLaughlin (1991) obtained systematically higher values of $J(\varepsilon)$ than Asmolov (1990), while both results approach McLaughlin’s analytical expression for $\varepsilon > 5$. The deviations are likely due to different numerical methods and error tolerances employed in evaluating the integral expression for $J(\varepsilon)$.

Based on McLaughlin’s numerical data Mei (1992) proposed an empirical fit function for $J(\varepsilon)$:

$$J(\varepsilon) = 0.6765\{1 + \tanh[2.5(\lg \varepsilon + 0.191)]\}\{0.667 + \tanh[6(\varepsilon - 0.32)]\}, \quad (2.10)$$

which appears as the short dashed lines in Figure 2.2.

Legendre and Magnaudet (1998) attempted to evaluate the $J(\varepsilon)$ function by DNS for a clean spherical bubble. Based on their DNS data in the range $0.2 \leq \varepsilon < 0.6$ and McLaughlin’s asymptotic solution for $\varepsilon > 0.8$ a fit function was proposed as

$$J(\varepsilon) = 2.255(1 + 0.20\varepsilon^{-2})^{-3/2}, \quad (2.11)$$

which appears as the dash dotted lines in Figure 2.2.

Figure 2.2. $J(\varepsilon)$ predictions according to the present expression, (2.12), and the earlier ones from Legendre and Magnaudet (1998), (2.11), and Mei (1992), (2.10), as well as the asymptotic expressions from McLaughlin (1991), (2.9), (represented by solid, dash-dotted, short-dashed, and dashed lines, respectively) compared with a new numerical evaluation of the integral expression as well as the older evaluations of McLaughlin (1991) and Asmolov (1990) (represented by open squares, red crosses, and open circles, respectively): (a) $0 < \varepsilon \leq 0.25$; (b) $\varepsilon \geq 0.2$.

As illustrated in Figure 2.2, none of the available formulae for $J(\varepsilon)$ gives good agreement with the numerical evaluation of McLaughlin (1991) especially in the region of negative lift (see Figure 2.2 (a)). Moreover, the deviations between the available numerical results obtained by different authors makes the reliability of all the aforementioned correlations even more questionable. To fill these gaps, the defining integral ((3.20) in McLaughlin (1991)) has been reevaluated by an adaptive integration approach (Shampine, 2008) with finer resolution and an absolute error tolerance of $1\text{E-}10$. The result shown by the open squares in Figure 2.2 agrees well with the previous one from McLaughlin (1991) (red cross symbols in Figure 2.2). A 4th order polynomial fit shows perfect agreement with the numerical data in the range $\varepsilon \leq 0.23$. For $\varepsilon > 0.23$ a fit function of similar form as suggested by Legendre and Magnaudet (1998) but with optimized values of the fit parameters captures the behavior in this region very well. Together, the following fit function for $J(\varepsilon)$ is proposed here:

$$J(\varepsilon) = \begin{cases} -0.04\varepsilon + 2.05\varepsilon^2 - 32.2\varepsilon^3 + 106.8\varepsilon^4 & \text{for } \varepsilon \leq 0.23 \\ 2.255(1 + 0.02304\varepsilon^{-2})^{-12.77} & \text{for } \varepsilon > 0.23 \end{cases} \quad (2.12)$$

This is shown as the solid lines in Figure 2.2.

It remains to discuss the differences between the expression (2.12), which is based on the theoretical analysis of McLaughlin (1991) and the correlation (2.11) proposed by Legendre and Magnaudet (1998) based on their DNS simulations. The former gives negative values of the shear-lift coefficient for $\varepsilon < 0.22$ while the latter does not show this region of negative lift coefficient. The result obtained by McLaughlin (1991) is analytical but involves an assumption that amounts to neglecting the lift contribution from the sub-Oseen-region, i.e. an interval between $O(\tilde{L}_u)$ and

$O(\tilde{L}_\omega)$ (see discussion after (4.2) in McLaughlin (1991)). This means their results are strictly valid only if $\tilde{L}_\omega < \tilde{L}_u$ or $\varepsilon > 1$. The DNS simulations by Legendre and Magnaudet (1998) of course does not contain such an assumption, but is subject to errors due to a still insufficient domain size (100 particle radii). Only positive lift coefficients were found also for values of ε where a negative lift would occur according to the results of McLaughlin (1991). Revisiting these simulations (Shi and Magnaudet, private communication, 2019) but with larger domain size (up to 300 sphere radii) indicates that their findings remain valid. Therefore, presently the $J(\varepsilon)$ correlation proposed by Legendre and Magnaudet (1998), i.e. (2.11), will be applied.

2.3.2 Approximate expression at moderate-to-large Reynolds number

Concerning a spherical bubble, the lift force in the inviscid limit was determined analytically in Auton (1987) for a vanishingly small shear ($Sr \rightarrow 0$). The high-Reynolds-number behavior was investigated numerically in Legendre and Magnaudet (1998), where it was found that[†]

$$\Delta C_{D\omega}^U(Re \gg 1) \approx 0.55Sr^2, \quad (2.13a)$$

$$C_{L\omega}^U(Re \gg 1) = \frac{2}{3}Sr(1 - 0.07|Sr|)\frac{1 + 16Re^{-1}}{1 + 29Re^{-1}}, \quad (2.13b)$$

where $\Delta C_{D\omega}^U = (C_{D\omega}^U - C_{D0}^U(Re))/C_{D0}^U(Re)$, and $C_{L\omega}^U = \frac{2}{3}Sr$ is the asymptotic value of the lift coefficient found in the limit $Sr \rightarrow 0, Re \rightarrow \infty$ in Auton (1987). The fit (2.13a) for the shear-induced drag increase was confirmed in subsequent numerical studies (Kurose and Komori, 1999; Sugioka and Komori, 2009).

At moderate Reynolds number, the lift force may be described by the composite fit proposed in Legendre and Magnaudet (1998), namely

$$C_{L\omega}^U(Re, Sr) \approx \frac{Sr}{|Sr|} \left\{ [C_{L\omega}^U(Re \ll 1)]^2 + [C_{L\omega}^U(Re \gg 1)]^2 \right\}^{1/2}, \quad (2.14)$$

which combines the low- and high- Re results (2.7b) and (2.13b). The adequacy of (2.14) in describing the lift force at moderate Reynolds number has been confirmed in subsequent numerical studies of Takagi and Matsumoto (1998, Figure 7) and Sugioka and Komori (2009, Figure 10).

Unfortunately, due to the continuous increase of the surface vorticity generated by the no-slip boundary condition at the sphere's surface, Auton's solution cannot be used to describe the limiting behavior of $C_{L\omega}^U$ for a solid sphere at very large Re . In fact, as revealed in all DNS studies below, instead of approaching a constant positive value, the lift coefficient of a solid sphere becomes negative and depends strongly on the shear rate beyond a certain value of Re .

A first DNS study concerning a rigid sphere was conducted by Dandy and Dwyer (1990), but the employed computational domain (20 sphere radii) was criticized to be too small in subsequent DNS

[†] The finite- Sr correction does not appear explicitly in Legendre and Magnaudet (1998). It was obtained by fitting the results provided in table 6 of this reference.

studies[‡]. Further DNS studies with larger computational domain were later conducted by Salem and Oesterle (1998, 27 sphere radii) with $Re = 0.1$ and by Cherukat et al. (1999, 75 sphere radii) with $0.02 \leq Re \leq 2$. A comparison of $C_{L\omega}^U$ prediction according to (2.7b) (using (2.11) for $J(\varepsilon)$) with DNS data for $Re \leq 2$ is given in Figure 2.3 (a). The agreement is as expected for $Re \gtrsim 0.1$, smaller than which (2.7b) gives increasingly higher $C_{L\omega}^U$ with decreasing Re . This mismatch may be ascribed to the size of the computational domain employed in the DNS, which may be insufficient to eliminate the confinement effect appearing at low Re . The perturbation analysis in section 2.3.1 shows that the inertia and viscous effects induced by the sphere become comparable at a distance of $O(2(ReSr)^{-1/2})$. In cases considered in Cherukat et al. (1999) one gets $O(2(ReSr)^{-1/2}) \approx 10$, a result suggesting that a domain size of 75 sphere radii is almost free of confinement effect. Shi and Rezhak (2019) ascribed this mismatch to the negative contribution from the small term of the Saffman-lift (see (2.17) in Saffman (1965)), which might be non-negligible at finite ε . This explanation will be examined in 3.2.2 when discussing the preliminary results.

Figure 2.3. $C_{L\omega}^U$ prediction according to the low- Re expression (2.7b) (represented by solid lines) compared with DNS data (represented by different symbols) for (a) $0.02 \leq Re \leq 2$ and (b) $1 \leq Re \leq 200$.

A comparison of (2.7b) with all other DNS data for $1 \leq Re \leq 200$ is given in Figure 2.3 (b). For $Re < 50$ the predicted lift is always larger than the DNS data of Kurose and Komori (1999) but smaller than the data in other sources. The inconsistencies between DNS data from different sources are likely due to the different size of the computational domains that were employed. In particular the results of Kim (2006) show significantly larger values of $C_{L\omega}^U$ than other data at comparable values of Sr , which could be due to the relatively larger domain size that was employed (see Table 2). In fact, Kim (2006, Figure 2 (b)) observed an increase of $C_{L\omega}^U$ when the domain size increases from 21 to 101 sphere radii. On the other hand Homann et al. (2013, Figure 4 (a)) claimed

[‡] The problem of Dandy and Dwyer's DNS study is not only the domain size. Subsequent DNS studies (Takagi and Matsumoto, 1998; Legendre and Magnaudet, 1998) have shown that the shear-induced lift coefficient is monotonically increase with increasing domain size, while Dandy and Dwyer's result indicated opposite tendency. As a consequence, the correlation proposed in Mei (1992) by fitting the results to Dandy and Dwyer (1990) should be used with caution.

a reverse trend when the cross-stream domain size increases from 128 to 256 particle radii. Overall, the low- Re expression (2.7b) is still reasonable within this range of Re , since for the most part only small values are found.

Table 2. Transitional Re for negative lift obtained in DNS studies

Reference (cross-stream domain size)	Sr	Transitional Re
Kurose and Komori (1999, 10 sphere radii)	0.4	57.1
	0.6	53.8
	0.8	58.7
Lee and Wilczak (2000, 16 sphere radii)	0.025	53.9
	0.05	55.0
	0.1	55.0
	0.2	52.1
Bagchi and Balachandar (2002, 30 sphere radii)	0.2	55.6
	0.4	54.5
Kim (2006, 101 sphere radii)	0.1	75.7
	0.2	80.3
	0.3	80.5
Hölzer and Sommerfeld (2009, 12.4 sphere radii)	0.16	60.1
	0.32	59.2
Homann et al. (2013, 216 sphere radii)	0.2	84.7

At moderate to higher Reynolds numbers the shear-induced lift force on a rigid sphere changes its sign at $Re \approx 60$. The cause for the occurrence of negative $C_{L\omega}^U$ values can be elucidated by the individual contributions of viscous and pressure forces. As stated in DNS studies, the pressure contribution is always positive for Re but the viscous contribution becomes negative for roughly $Re \geq 10$. The lift changes its sign once the viscous contribution outweighs that of the pressure, which takes place at a value of Re between 50 and 100. This transition from positive to negative lift coefficient was first observed by Kurose and Komori (1999) with the transitional Reynolds number determined roughly as $Re \approx 55$. Different values were reported later as shown in Table 2. It is apparent that DNS studies with larger computational domains (e.g. Kim (2006), Homann et al. (2013)) show a larger transitional Re (around 80) compared with those employing a smaller computational domain. Regardless of this difference all studies found a weak dependence of the transitional Re on the shear rate Sr .

For $Re > 100$, the pressure contribution also turns negative and its magnitude increases with increasing Re_p such that it dominates the viscous contribution at $Re > 200$ (Kurose and Komori, 1999; Lee and Wilczak, 2000). For $Re \geq 300$, $C_{L\omega}^U$ becomes less dependent on Re and approaches a constant value that is positively correlated to Sr . Based on the DNS data of Kurose and Komori

(1999) and Bagchi and Balachandar (2002), Loth (2008) proposed the following $C_{L\omega}^U$ correlation for $Re > 50$:

$$C_{L\omega}^U = -Sr^{1/3}\{0.0525 + 0.0575\tanh[5 \lg(Re/120)]\}. \quad (2.15)$$

Figure 2.4. $C_{L\omega}^U$ predictions according to the correlation proposed in Loth (2008), (2.15), (represented by solid lines) for $50 < Re \leq 500$ compared with DNS data (represented by symbols). The range of Re has been splitted into two panels for better visibility.

As can be seen from Figure 2.4, For $Re \geq 300$ Loth's correlation shows fair agreement with the DNS data provided that $Sr \geq 0.2$ but underestimates the lower shear rate data. For flows that involve very weak shear (i.e. $Sr \rightarrow 0$), the shear may be considered as a perturbation to the uniform base flow, which as discussed in Shi and Rzehak (2019, section 4.2.1) becomes unstable at a value of Re in the present range. It is thus conceivable that an imperfect bifurcation lift would be recovered in this condition. The direction of the lift force is then fixed by the imposed shear while its magnitude is given by the lift coefficient in the bifurcation condition, i.e.:

$$C_{L\omega}^U(Re \geq 300, Sr \rightarrow 0) = C_{L,Bi}, \quad (2.16)$$

where a constant value of $C_{L,Bi} = 0.064$ is suggested (Shi and Rzehak (2019)).

For $50 \leq Re < 300$ significant inconsistency of different DNS data makes a reliable correlation hard to obtain.

2.4 Linear shear flow with the wall lying in the inner region

Recalling the requirement $\max(L_\omega, L_u) \ll 1$ for the wall to be lying in the inner region, it is seen that the Reynolds numbers in this case are necessarily small since $Re = 2L_u/L_R$, which restricts the practical value of the results for this case. The hydrodynamic force then depends on two parameters, namely the wall distance normalized by the sphere radius, L_R , and the non-dimensional shear rate, Sr . Note that the limit $L_R \rightarrow \infty$ in this situation means that the wall lies on the outer boundary of the inner region, which coincides with the inner boundary of the outer region, rather than the unperturbed far field. Thus the hydrodynamic force in this limit cannot not approach the unbounded, low-Reynolds number result from Shi and Rzehak (2019).

The theoretical study of sphere migration in wall-bounded flows originates from Cox and Brenner (1968). A crucial point recognized in their investigation is that with the wall lying in the inner region, the hydrodynamic force to zeroth order in L_R^{-1} may be obtained through a regular expansion with respect to Re . This idea was applied in Magnaudet et al. (2003), in which the finite-size effects were accounted by means of the reciprocal theorem. The analytical solutions for the drag and lift forces on a clean spherical bubble were found to be[§]

$$\begin{aligned} \Delta C_D^{W-in}(Sr, L_R) &= \underbrace{\left(\frac{3}{8} L_R^{-1} + \frac{3}{64} L_R^{-4} \right) \left(1 - \frac{3}{8} L_R^{-1} - \frac{3}{64} L_R^{-4} \right)^{-1}}_{\Delta C_{Du}^{W-in}} \\ &\quad - \underbrace{\frac{1}{16} \left(L_R^{-2} + \frac{3}{8} L_R^{-3} \right) Sr}_{\Delta C_{D\omega}^{W-in}}, \\ C_L^{W-in}(Sr, L_R) &= \underbrace{\frac{1}{2} \left(1 + \frac{1}{8} L_R^{-1} - \frac{33}{64} L_R^{-2} \right)}_{C_{Lu}^{W-in}} \\ &\quad + \underbrace{\frac{11}{24} \left(L_R + \frac{9}{8} - \frac{1271}{3520} L_R^{-1} \right) Sr + \frac{11}{144} \left(1 + \frac{3}{8} L_R^{-1} \right) Sr^2}_{C_{L\omega}^{W-in}}. \end{aligned} \tag{2.17a,b}$$

where $\Delta C_D^{W-in}(Sr, L_R) = \left(C_D^{W-in}(Sr, L_R) - C_{D0}^U(Re \rightarrow 0) \right) / C_{D0}^U(Re \rightarrow 0)$.

(2.17a,b) make it clear that the drag modification and the lift force result from two contributions. One, denoted as ΔC_{Du}^{W-in} (resp. C_{Lu}^{W-in}), is due to the wall effect and depends on L_R only. The other, denoted as $\Delta C_{D\omega}^{W-in}$ (resp. $C_{L\omega}^{W-in}$), is due to the presence of the shear and depends linearly and quadratically on Sr , although it is also altered by the wall proximity. The drag modification vanishes in the limit of large separations. In the same limit, the lift force becomes entirely governed by the shear effect which grows linearly with L_R . Since $L_\omega = \frac{1}{2} L_R (|Sr|Re)^{1/2}$ the term proportional to L_R in the $C_{L\omega}^{W-in}$ -contribution differs from the lift coefficient $C_{L\omega}^U$ in (2.7b) for the

[§] In Eq. (43a) of Magnaudet et al. (2003), there should be a minus sign in front of the L_R^{-2} -term involved in (2.17b), in line with Eqs. (44a, b). Also, the pre-factor of the $L_R^{-1}Sr$ -term is error in Eq. (45b) of the same reference. All pre-factors involved in (2.17b) were re-computed in the framework of the present study.

unbounded case by a factor of $\frac{11}{96} \pi^2 L_\omega / J_L(\varepsilon)$, which indicates that the two expressions reach a similar magnitude for some finite value of L_ω .

The case concerning a rigid sphere was also considered in Magnaudet et al. (2003), in which the analytical solution for the drag force were found to be**

$$\Delta C_D^{W-in}(Sr, L_R) = \frac{\left(\frac{9}{16} L_R^{-1} - \frac{1}{8} L_R^{-3} + \frac{45}{256} L_R^{-4} + \frac{1}{16} L_R^{-5} \right)}{\underbrace{\left(1 - \frac{9}{16} L_R^{-1} + \frac{1}{8} L_R^{-3} - \frac{45}{256} L_R^{-4} - \frac{1}{16} L_R^{-5} \right)}_{\Delta C_{Du}^{W-in}}} - \underbrace{\frac{5}{32} \left(L_R^{-2} + \frac{9}{16} L_R^{-3} \right) Sr}_{\Delta C_{D\omega}^{W-in}}. \quad (2.18)$$

Explicit lift expression concerning a rigid sphere was first obtained by Cox and Hsu (1977), in which the Green's functions obtained by Cox and Brenner (1968) were evaluated analytically. Furthermore, some minor corrections were provided by Lovalenti in the Appendix of Cherukat and McLaughlin (1994). The final analytical result, which is valid under the assumptions $Re \ll 1$, $L_R \gg 1$, and $\max(L_u, L_\omega) \ll 1$, reads

$$C_L^{W-in} = \frac{9}{8} + \frac{33}{32} \left(L_R + \frac{17}{48} \right) Sr + \frac{61}{192} Sr^2. \quad (2.19)$$

Cox and Hsu (1977) treated the presence of the sphere as a point-force, which is reasonable only for large wall distances. Situations concerned with smaller wall distances were later considered by Fischer and Rosenberger (1987) and by Cherukat and McLaughlin (1994) by numerical evaluation of the sphere's surface stress integral. Based on their numerical data for $1.1 \leq L_R \leq 20$ and $-10 \leq Sr \leq 10$, Cherukat and McLaughlin (1994) proposed the fitted correlation

$$C_L^{W-in} = \sum_{i=1}^3 \sum_{j=1}^5 a_{i,j} Sr^{i-1} L_R^{2-j} \quad (2.20a)$$

with

$$a_{i,j} = \begin{bmatrix} 0.0000 & 1.1278 & 0.1375 & -0.4642 & 0.3090 \\ 1.0312 & 0.3645 & 0.6634 & -0.2884 & 0.0000 \\ 0.0000 & 0.3194 & 0.1683 & -0.3821 & 0.2097 \end{bmatrix}. \quad (2.20b)$$

The limiting condition where the sphere is in contact with the wall, i.e. $L_R = 1$, was investigated using the lubrication approximation by Leighton and Acrivos (1985) and Krishnan and Leighton (1995). Their investigations showed that the lift force can be separated into three contributions: one due to the translational motion, one due to the ambient shear, and one due to the coupling of shear and translation, i.e.

** Solution (2.18) applies for torque-free rotating spheres (Magnaudet et al., 2003).

$$C_L^{W-\text{in}} = C_{Lu}^{W-\text{in}} \left(1 - \frac{1}{2} L_R Sr\right)^2 + C_{Lu\omega}^W \left(\frac{1}{2} L_R Sr\right) \left(1 - \frac{1}{2} L_R Sr\right) + C_{L\omega}^W \left(\frac{1}{2} L_R Sr\right)^2. \quad (2.21)$$

Here C_{Lu}^W and $C_{L\omega}^W$ denote the coefficients of the wall-lift force (here describing the contribution of the translational motion) and the lift force of a stationary sphere (here describing the shear contribution), respectively. The coupling between both effects is represented by the term involving $C_{Lu\omega}^W$ which vanishes when either $Sr = 0$ or $Sr = 2L_R^{-1}$. Values of $C_{Lu}^{W-\text{in}}$, $C_{L\omega}^W$, and $C_{Lu\omega}^W$ at $L_R = 1$ were evaluated as 1.117, 5.893, and 5.759, respectively.

Yahiaoui and Feuillebois (2010) extended Krishnan and Leighton's analysis to finite gaps between the wall and the surface of the sphere employing a method similar to the one used by Cherukat and McLaughlin (1994). A range of $1.01 \leq L_R \leq 100$ was considered and the range of shear rates contains the values $Sr = 0$ and $Sr = 2L_R^{-1}$ but was not specified precisely. Their fitted results for the three lift coefficients in Eq. (2.21) read

$$C_{Lu}^{W-\text{in}} = \frac{2}{\pi} \sum_{i=1}^6 a_i^u L_R^{4-i} \bigg/ \sum_{i=1}^6 b_i^u L_R^{4-i}, \quad (2.22a)$$

$$C_{L\omega}^W = \frac{2}{\pi} L_R^{-2} \exp \left[\sum_{i=1}^6 a_i^\omega (\ln L_R)^{6-i} \bigg/ \sum_{i=1}^6 b_i^\omega (\ln L_R)^{6-i} \right], \quad (2.22b)$$

and

$$C_{Lu\omega}^W = \begin{cases} \frac{2}{\pi} \sum_{i=1}^6 a_i^{u\omega 1} L_R^{5-i} \bigg/ \sum_{i=1}^6 b_i^{u\omega 1} L_R^{5-i} & \text{for } L_R < 2 \\ \frac{2}{\pi} \sum_{i=1}^6 a_i^{u\omega 2} L_R^{5-i} \bigg/ \sum_{i=1}^6 b_i^{u\omega 2} L_R^{5-i} & \text{for } L_R \geq 2 \end{cases} \quad (2.22c)$$

with

$$\begin{pmatrix} a_i^u \\ b_i^u \\ a_i^\omega \\ b_i^\omega \\ a_i^{u\omega 1} \\ b_i^{u\omega 2} \\ a_i^{u\omega 1} \\ b_i^{u\omega 2} \end{pmatrix} = \begin{bmatrix} 1.77 & 14.48 & 45.52 & -42.67 & 9.243 & 0 \\ 1 & 8.14 & -23.59 & -16.54 & 0 & 0 \\ 2.0172 & 3.4562 & 3.9608 & 2.6728 & -0.15728 & 0.01386 \\ 0 & 1 & 0.96328 & 1.264 & -0.07648 & 0.006228 \\ 5.661 & 179.4 & 126.4 & -704.5 & -8.393 & -815.4 \\ 1 & 32.18 & -36.26 & 10.58 & -124.8 & 0 \\ 0 & 9.288 & 1.407 & -3.606 & -3.431 & -1.401 \\ 1 & 1.902 & 3.712 & 0.9578 & -7.088 & 0 \end{bmatrix}. \quad (2.22d)$$

The expressions for C_{Lu}^{W-in} and $C_{L\omega}^W$ show good agreement with Krishnan and Leighton's results in the limit $L_R = 1$ while the $C_{Lu\omega}$ correlation approaches 6.604 at $L_R = 1$ which is 15% higher than the value determined by Krishnan and Leighton (1995).

Figure 2.5. C_L^{W-in} predictions according to the expressions of Cox and Hsu (1977), (2.19), Cherukat and McLaughlin (1994), (2.20), and Yahiaoui and Feuillebois (2010), (2.21) & (2.22), (represented by dashed, solid, and dotted lines, respectively) for $1 \leq L_R \leq 100$ compared with numerical data (represented by symbols) concerning (a) a stagnant flow and (b) a stationary sphere.

Comparisons of predictions of C_{Lu}^{W-in} and $C_{L\omega}^W$ with numerical data are shown in Figure 2.5, recalling from Krishnan and Leighton (1995) that conditions to obtain these special cases are $Sr = 0$ and $Sr = 2L_R^{-1}$, respectively. The numerical data for C_{Lu}^{W-in} and $C_{L\omega}^W$ obtained by Cherukat and McLaughlin (1994) and Yahiaoui and Feuillebois (2010) show good agreement with each other. However, values of the C_{Lu}^{W-in} data from Fischer and Rosenberger (1987) are always larger than those found by the other two groups, which is likely due to an insufficient implementation of the Gauss-Legendre product formula (for details, see Fischer and Rosenberger (1987, section 4.2)). As for the predictions, there is hardly any difference between those of Cherukat and McLaughlin (1994) and those of Yahiaoui and Feuillebois (2010). Both agree well with the numerical data for C_{Lu}^{W-in} and $C_{L\omega}^W$ as functions of L_R (excluding the probably unreliable ones from Fischer and Rosenberger (1987)). Cox and Hsu's first order C_L^{W-in} formula gives a value of $C_{Lu}^{W-in} = 1.125$ independent of L_R . Although it neglects the correction due to finite particle size, the maximum deviation from the numerical data is less than 5% and in particular in the limits of small and large L_R good agreement is found. On the other hand, their predicted $C_{L\omega}^W$ suffers an underestimation compared with the

numerical data for $L_R < 10$. The deviation is largest at $L_R = 1$ reaching roughly 10% and decreases with increasing L_R . In the limit $L_R \rightarrow \infty$, the analytical solution of Cox and Hsu (1977) yields $C_{L\omega}^W \rightarrow 3.1875$, which agrees very well with the numerical data obtained by Yahiaoui and Feuillebois (2010) at $L_R = 100$.

Figure 2.6. C_L^{W-in} predictions according to the expressions of Cox and Hsu (1977), (2.19), Cherukat and McLaughlin (1994), (2.20), and Yahiaoui and Feuillebois (2010), (2.21) & (2.22), (represented by dashed, solid, and dotted lines, respectively) for $-10 \leq Sr \leq 10$ compared with numerical data (represented by symbols) under conditions of: (a) $L_R = 1, 1.1, 1.5$; (b) $L_R = 2, 3, 4$; (c) $L_R = 5, 10, 20$.

Figure 2.6 compares the full C_L^{W-in} predictions with the numerical data for $1 \leq L_R \leq 20$ and $-10 \leq Sr \leq 10$. The numerical data comprise those provided by Cherukat and McLaughlin (1994, Tables 1 and 2) and the data series $C_L^{W-in}(L_R = 1, Sr)$ generated by Krishnan and Leighton's analytical solution. The correlation proposed by Cherukat and McLaughlin (1994) shows excellent agreement with their own numerical data, i.e. for $1.1 \leq L_R \leq 20$, which is of course not surprising, but also with those obtained from Krishnan and Leighton's analytical solution, i.e. at $L_R = 1$. Cox and Hsu's expression shows nearly the same accuracy as that of Cherukat and McLaughlin (1994) for $L_R \geq 5$. However, for $L_R \leq 4$ it overpredicts the numerical data where the deviation increases both with decreasing L_R and increasing $|Sr|$. This may be expected since contributions of the higher order terms neglected in Cox and Hsu's analysis become more significant under these conditions. Yahiaoui and Feuillebois's expression shows good agreement with the numerical data

for $0 \leq Sr \leq 2/L_R$. However, outside this range, i.e. for negative and large positive values of Sr , the agreement rapidly deteriorates, which is likely due to the restricted range of the numerical data (unfortunately not specified in their paper) used to fit the expressions.

The comparisons above show that the fitted expression proposed by Cherukat and McLaughlin (1994) is the most accurate one. Combining the leading-order solution obtained in Cox and Hsu (1977), (2.19), with this fitted expression, (2.20), a semi-empirical expression for the lift force on a rigid sphere formulated in a form similar as (2.17b) reads:

$$\begin{aligned}
C_L^{W-in}(Sr, L_R) = & \underbrace{\frac{9}{8}(1 + 0.1222L_R^{-1} - 0.4126L_R^{-2} + 0.2701L_R^{-3})}_{C_{Lu}^{W-in}} \\
& + \frac{33}{32} \left(L_R + \frac{17}{48} + 0.6433L_R^{-1} - 0.2797L_R^{-2} \right) Sr \\
& + \underbrace{\frac{61}{192}(1 + 0.5269L_R^{-1} - 1.1963L_R^{-2} + 0.6565L_R^{-3})}_{C_{L\omega}^{W-in}} Sr^2.
\end{aligned} \tag{2.23}$$

2.5 Stagnant flow with the wall lying in the outer region

As discussed in section 2.2, the wall lies in the outer region for $L_u = L_R Re/2 \geq O(1)$, with either finite Re or with $Re \ll 1$ but $L_R \geq O(Re^{-1})$. This case is likely more relevant for practical purposes than the one where the wall lies in the inner region as discussed in the previous sections. The condition of a stagnant flow is expressed as $Sr = 0$. The wall effects become unimportant in the limit $L_R \rightarrow \infty, L_u \rightarrow \infty$, which due to the absence of the shear flow means that no lift force exists.

2.5.1 Analytical solution at low- Re

In this case the lift force depends only on the wall distance normalized by the Oseen length, L_u . Vasseur and Cox (1977) considered the case of a solid sphere translating in a stagnant flow in the low-but-finite Reynolds number limit using the method of matched asymptotic expansions. The generalization of the above results to spherical drops of arbitrary viscosity was achieved in Takemura et al. (2002). The relevant solutions are found in the form of double integrals which cannot be evaluated in closed form, namely^{††}

$$\begin{aligned}
\Delta C_{Du}^{W-out} &= \frac{3\beta}{4\pi L_R L_u} \int_0^{2\pi} \int_0^\infty \left\{ \frac{[\chi + \lambda]e^{-2\lambda} + 2\chi e^{-2\chi} - 4\chi e^{-(\chi+\lambda)}}{\chi - \lambda} + \frac{i\lambda \cos\phi - L_u}{\chi} \lambda e^{-2\chi} \right\} d\lambda d\phi, \\
C_{Lu}^{W-out} &= \frac{9\beta^2}{\pi L_u^2} \int_0^{2\pi} \int_0^\infty \frac{\chi + \lambda}{\chi - \lambda} (e^{-\lambda} - e^{-\chi})^2 \lambda d\lambda d\phi,
\end{aligned} \tag{2.24a,b}$$

^{††} In Eq. (8.22) of Vasseur and Cox (1977) a necessary multiplier λ within the second integral of (2.24a) was missing.

where $\Delta C_{Du}^{W-out}(Re \ll 1) = (C_{Du}^{W-out}(L_u, L_R) - C_{D0}^U(Re \rightarrow 0))/C_{D0}^U(Re \rightarrow 0)$, $\beta = 2/3$ (resp. $\beta = 1$) for a clean bubble (resp. rigid sphere), and $\chi^2 = \lambda^2 + i\lambda L_u \cos\phi$ with $i^2 = -1$.

For the present work, (2.24a,b) have been evaluated numerically by an adaptive integration approach (Shampine, 2008). The results with a relative error tolerance of 10^{-4} are shown as the square symbols in Figure 2.7.

Figure 2.7. f'_D and f'_L predictions according to the presently proposed expressions, (2.27), and the previous ones proposed in Vasseur and Cox (1977), (2.25), and Takemura and Magnaudet (2003), (2.26), (represented by solid, dashed, and short dashed lines, respectively) compared with the present numerical evaluations of Eqs. (2.24) (represented by symbols) for $0.01 \leq L_u \leq 300$. (a) f'_D , (b) f'_L .

In the limits of $L_u \ll 1$ and $L_u \gg 1$ explicit expressions were found by Vasseur and Cox (1977) as

$$\begin{aligned} \frac{16}{9}\beta^{-1}L_R\Delta C_{Du}^{W-out} = f'_D &= \begin{cases} 1 & \text{for } L_u \ll 1 \\ -0.338L_u^{-3/2} & \text{for } L_u \gg 1 \end{cases} \\ \frac{8}{9}\beta^{-2}C_{Lu}^{W-out} = f'_L &= \begin{cases} 1 & \text{for } L_u \ll 1 \\ 4(L_u^{-2} + 2.21901L_u^{-5/2}) & \text{for } L_u \gg 1 \end{cases} \end{aligned} \quad (2.25a,b)$$

where, f'_D and f'_L describe how the wall-induced drag modification and the lift force relax to zero as inertial effects in the bulk become dominant. In the limit $L_u \rightarrow 0$, expressions (2.25a,b) match the inner solutions described in the last section taken at $Sr = 0$ in the limit $L_R \rightarrow \infty$. (2.25a,b) appear as the dashed lines in Figure 2.7 (a) and (b), respectively.

Based on the numerical data from Takemura et al. (2002, unfortunately not given in their paper), Takemura and Magnaudet (2003) proposed the fitted expression for the lift force

$$f'_L = \begin{cases} (1 + 5.14 \times 10^{-6}L_u^{4.58})e^{-0.292 L_u} & \text{for } L_u < 10 \\ 7.95L_u^{-2.09} & \text{for } L_u \geq 10 \end{cases} \quad (2.26)$$

which appears as the short-dashed line in Figure 2.7 (b).

As seen in Figure 2.7 (b), Takemura and Magnaudet's expression shows good agreement with the present highly accurate numerical data for $L_u \geq 3$ but underestimates these for $L_u < 3$. In fact, a fit based on the constant / quadratic rational function given below shows better agreement compared with Eq. (2.26) for $L_u < 10$:

$$f'_D = \frac{1}{1 + 0.16L_u(L_u + 4)}, \quad f'_L = \begin{cases} \frac{1}{1 + 0.13L_u(L_u + 0.53)} & \text{for } L_u < 10 \\ 7.95L_u^{-2.09} & \text{for } L_u \geq 10 \end{cases} \quad (2.27a,b)$$

(2.27) appear as the solid lines in Figure 2.7 and approach the analytical solutions in the limit $L_u \ll 1$. The agreement concerning the drag force is as expected as well.

2.5.2 Approximate expression for the lift force at moderate-to-large Reynolds number

No theoretical solution for the hydrodynamic forces may be obtained when inertial effects become dominant. Reliable extensions of the low-Reynolds-number and inviscid solutions (when available) to this intermediate regime may however be achieved provided that sufficient and accurate data are available.

Experimental and numerical studies (Takemura et al., 2002; Takemura and Magnaudet, 2003; Sugioka and Tsukada, 2015) devoted to the rise of a clean spherical bubble close to a wall revealed that, for $Re = O(10)$, the lift force exhibits a faster decay with increasing L_u compared to the low- Re solution. In Takemura and Magnaudet (2003), experimental observations performed with bubbles such that $Re < 30$ and theoretical considerations about the nature of the bubble-wall interaction could be summarized through the following semi-empirical relation

$$C_{Lu}^W(Re = O(1 - 10)) \approx b^2(L_R/3)^g C_{Lu}^{W-out}(Re \ll 1), \quad (2.28)$$

with

$$b = 1 + 2 \tanh(0.17Re^{0.4} - 0.12Re^{0.05}) \quad \text{and} \quad g = -2 \tanh(0.01Re). \quad (2.29a,b)$$

The factor b expresses the increase of the vorticity at the bubble surface with Re . Indeed the maximum of the surface vorticity is three times larger in the limit $Re \rightarrow \infty$ than in the zero- Re limit (Batchelor, 1967, p. 366). The exponent g accounts for the increase of the decay rate of the lift force with L_u as Re increases, from L_u^{-2} at low-but-finite Re to L_u^{-4} in the inviscid limit (Takemura and Magnaudet, 2003).

At higher Reynolds numbers, the irrotational mechanism illustrated in Figure 1.2 (a) becomes dominant. In the inviscid limit, the transverse force becomes identical to that experienced by each of the two bubbles in a pair rising perpendicular to its line of centers. The corresponding coefficient is obtained in the form of an infinite series with respect to the inverse of the separation distance, the first terms of which are (van Wijngaarden, 1976; Miloh, 1977; Legendre et al., 2003)

$$C_{Lu}^W(Re \rightarrow \infty) = -\frac{3}{8}L_R^{-4} \left[1 + \frac{1}{8}L_R^{-3} + \frac{1}{6}L_R^{-5} \right] + O(L_R^{-10}). \quad (2.30)$$

Still for a clean bubble pair rising in the above configuration, the transverse interaction yields an asymmetry of the vorticity distribution within the boundary layer surrounding each bubble. For this reason, a viscous correction arises in the transverse force at large-but-finite Re , yielding (Legendre et al., 2003; Magnaudet, 2011)

$$C_{Lu}^W(Re \gg 1) \approx C_{Lu}^W(Re \rightarrow \infty) + 15Re^{-1}L_R^{-4}. \quad (2.31)$$

Returning to the problem of a single bubble translating parallel to a wall, the transition from the low-to-moderate Re regime corresponding to Figure 1.1 (a) to the high- Re regime illustrated in Figure 1.2 (a) was discussed in Takemura and Magnaudet (2003). It was shown that the two driving mechanisms superimpose almost linearly, so that this transition is correctly captured by the empirical expression

$$\begin{aligned} C_{Lu}^W &\approx C_{Lu}^W(Re = O(1 - 10)) + c_{T\infty} C_{Lu}^W(Re \rightarrow \infty), \quad \text{with} \\ c_{T\infty} &= 1 - e^{-0.22Re^{0.45}}. \end{aligned} \quad (2.32a,b)$$

As figure 8 of Takemura and Magnaudet (2003) shows, predictions based on this linear fit compare well with the experimental values of the lift coefficient determined for $L_R \geq 4$ up to $Re = 10^2$, the largest Reynolds number considered in that study.

Turning to the problem of a rigid sphere translating parallel to a wall, experimental study performed with fully contaminated spherical bubbles such that $1 \lesssim Re \lesssim 100$ (Takemura and Magnaudet, 2003) has revealed that, for $Re = O(10)$, the lift coefficient exhibits a faster decay with increasing L_u compared to the low- Re solution. Experimental observations could be summarized in a similar way as the one for a clean bubble, namely:

$$C_{Lu}^W(Re = O(1 - 10)) \approx C_{Lu}^{W-out}(Re \ll 1) a^2 (L_R/\sigma)^g \quad (2.33)$$

with

$$\sigma = 3, \quad a = 1 + 0.6Re^{0.5} - 0.55Re^{0.08}, \quad (2.34a,b)$$

where σ is an empirical constant, a expresses the surface vorticity generated by the no-slip boundary condition at finite Re . Expression (2.34b) was obtained based on the data provided in Magnaudet et al. (1995), in which a rigid sphere subjected to an unbounded uniform flow was considered. The exponent g appearing in (2.33) accounts for the increase of the decay rate of the lift force with L_u as Re increases and takes the form of (2.29b).

The first DNS study of the wall-induced lift was conducted in Zeng et al. (2005, 2009) with $1.01 \leq L_R \leq 8$ and $0.5 \leq Re \leq 300$. Their data for $Re \leq 100$ show a similar tendency for $C_{Lu}^W(L_u)$ as the experimental ones obtained by Takemura and Magnaudet (2003). An interesting finding of their study is that, due to the occurrence of an imperfect bifurcation, the wall-induced lift coefficient increases substantially with increasing Re beyond a value of about 150. Based on their data with $L_R \geq 1.5$ and $Re \lesssim 150$ Zeng et al. (2009) proposed an expression similar as (2.33) but with^{‡‡}

^{‡‡} In Zeng et al. (2009) also a different $g(Re)$ expression was proposed (see their Eq. (34)). This expression, however, does not satisfy the L_u^{-4} -decay law in the inviscid limit (Takemura and Magnaudet, 2003).

$$\sigma = 2 \quad \text{and} \quad a = \sqrt{1 + 0.33Re + 0.0049Re^2}. \quad (2.35a,b)$$

The reliability of the DNS data obtained by Zeng et al. (2005, 2009) as well as their interesting finding of the imperfect bifurcation phenomenon were confirmed by subsequent DNS studies, e.g. Lee and Balachandar (2010), Sugioka and Tsukada (2015), and Zhou et al. (2017), each of which employed different DNS methods. No empirical expression for $C_{Lu}^W(Re = O(100))$ is available in the literature.

Figure 2.8. C_{Lu}^W predictions according to the expressions of Takemura and Magnaudet (2003), (2.23) & (2.24), and of Zeng et al. (2009), (2.33) & (2.35), (represented by dashed and solid lines, respectively) compared with (a) experimental data from Takemura and Magnaudet (2003) given in series at fixed value of Re for $1 < L_u \leq 200$, (b) DNS data from different sources as indicated in the legend given in series at fixed value of L_R for $1 \leq L_u \leq 1000$.

Comparison between the two predictions for C_{Lu}^W and the experimental data from Takemura and Magnaudet (2003) is shown in Figure 2.8 (a) as a function of L_u for fixed values of Re . The value of L_R varies along each curve as $L_R = 2L_u Re^{-1}$. For $Re \gtrsim 25$, predictions of both expressions show good agreement with each other and with the experimental data. For lower Re the expression of Takemura and Magnaudet (2003) overestimates (resp. underestimates) the measurements somewhat for $2.5 \lesssim Re \lesssim 25$ (resp. $Re \lesssim 2.5$) while that of Zeng et al. still gives a good match. Figure 2.8 (b) compares the two predictions with the DNS data again as a function of L_u , but now for fixed values of L_R . Hence, now the value $Re = 2L_u L_R^{-1}$ varies along each curve. Takemura and Magnaudet's expression is in good agreement with the DNS data provided that $10 \leq Re \leq 100$. At smaller values of Re it fails to approach a constant value as seen in the DNS data. Zeng et al.'s expression in contrast gives good agreement with the DNS data for $Re \leq 100$. At larger values of Re both suffer a too fast decay compared to the DNS data. According to Figure 2.8 (b) $Re \approx 150$ roughly corresponds to the minimum of the lift coefficient before it begins to rise again due to the occurrence of the already mentioned imperfect bifurcation.

2.6 Linear shear flow with the wall lying in the outer region

The presence of shear in the undisturbed flow makes the resulting hydrodynamic force more difficult to obtain theoretically compared with the condition of a stagnant flow. This is due to the fact that, as discussed in section 1.2, any sphere moving in a wall-bounded shear flow experiences two different types of lift forces which generally combine nonlinearly. One of these is due to the shear, while the other results directly from the presence of the wall. Cox and Hsu (1977) considered this problem with the wall lying in the inner region. Their solution (2.19) can be re-written in terms of the parameters, ε and L_ω , by replacing Sr with $2\varepsilon L_\omega/L_R \operatorname{sgn}(Sr)$. In the limit $L_R \rightarrow \infty$, one obtains the following expression for the lift coefficient which is valid on the boundary between the inner and outer regions:

$$\beta^{-1} C_L^{W-out} = \frac{9}{8} + \frac{33}{16} \frac{Sr}{|Sr|} \varepsilon L_\omega. \quad (2.36)$$

The first and second terms on the right hand indicate the lift contributions due to, respectively, the presence of the wall and the ambient shear. The factor $Sr/|Sr|$ implies that the shear-induced lift changes sign when the direction of the relative velocity $\mathbf{U}_{rel}$ reverses. The wall-induced lift keeps a positive sign independent of the sign of $\mathbf{U}_{rel}$. When the wall is lying in the outer region, corrections due to the finite values of L_u and L_ω should be considered for both contributions. An expression suggested by Takemura, Magnaudet and Dimitrakopoulos (2009) reads:

$$C_L^{W-out} \approx C_{Lu}^{W-out} f_L(\varepsilon, L_\omega) + C_{L\omega}^U h_L(\varepsilon, L_\omega), \quad (2.37)$$

where, as explained in section 2.3, $C_{L\omega}^U$ denotes the coefficient of the lift force acting on a sphere translating in an unbounded linear shear flow. f_L and h_L are empirical functions describing the modifications due to the shear and the presence of the wall to each of the two lift force contributions, respectively. As before, the wall effects become unimportant in the limit $L_R \rightarrow \infty$, $L_u \rightarrow \infty$, $L_\omega \rightarrow \infty$, and the unbounded result is approached.

2.6.1 Approximate expression for the lift force at low- Re

In the limits of small and large values of ε , (2.37) is simplified since one of the two additive terms drops out. For $\varepsilon \gg 1$ the translation-induced inertia term, which is essential for the generation of the wall-induced lift, becomes negligible compared with the shear-induced inertia term (see Eq. (3) in Shi and Rzehak (2020) for the expressions of the two terms), which is essential for the generation of shear-induced lift. Hence in this condition f_L vanishes and h_L may be evaluated individually. For $\varepsilon \ll 1$, conversely, the shear-lift becomes negligible such that h_L vanishes. However without shear, the wall-induced lift remains unchanged such that one immediately finds

$$f_L(\varepsilon \ll 1) = 1. \quad (2.38)$$

In the remainder of this section, first a corresponding expression for $h_L(\varepsilon \gg 1)$ is considered, which is then extended to intermediate values of ε . Finally, this is combined with a correlation for f_L at intermediate values of ε to obtain predictions for C_L^{W-out} that can be compared with numerical data.

The case concerning a solid sphere translating in a wall-bounded linear shear flow with the wall lying in the outer region was investigated originally by Drew (1988) using the method of matched asymptotic expansions. Drew considered the problem in the limit $\varepsilon \gg 1$ such that the form of $h_L(\varepsilon \gg 1)$ may be found. In his analysis, the Fourier transform of the migration velocity, which is essential for the determination of the lift force, was evaluated numerically. According to Drew's results, the wall reduces the shear-induced lift for $L_\omega < 3$ (i.e. $h_L(\varepsilon \gg 1, L_\omega < 3) < 1$) while for $L_\omega \geq 3$ the shear-induced lift is enhanced by the wall (i.e. $h_L(\varepsilon \gg 1, L_\omega \geq 3) \geq 1$). Since the latter is at variance with other works (see below), only the numerical data for $h_L(\varepsilon \gg 1, L_\omega < 3)$ are shown as the “+” symbols in Figure 2.9.

Drew's analysis was re-visited by Asmolov (1989) and independently by McLaughlin (1993), again using the method of matched asymptotic expansions. However, instead of evaluating the Fourier transform numerically, both succeeded to obtain an analytical solution which is expressed in terms of Airy functions and their derivatives. The Airy functions and their derivatives were calculated in terms of their Taylor series expansions for values of the argument smaller in magnitude than a certain threshold, and in terms of their asymptotic series for values of the argument larger in magnitude than the threshold. Asmolov (1989) set the threshold to 5 while McLaughlin (1993) used a value of 4. According to the results obtained, both concluded that the presence of the wall reduces the shear-induced lift consistently for any value of L_ω . Specifically, the resulting lift force would increase monotonically from zero at $L_\omega = 0$ to the value obtained by Saffman (1965, 1968) when $L_\omega \rightarrow \infty$. Their numerical data include cases where the sphere leads or lags the fluid corresponding to different signs of Sr . In the limit of $\varepsilon \rightarrow \infty$ there is no difference between both cases and the corresponding numerical data are shown in Figure 2.9 as circle and square symbols, respectively.

In addition, McLaughlin (1993) derived that, for $L_\omega \gg 1$ and $\varepsilon \geq 1$ but not necessarily large, the amount of reduction of the shear-induced lift due to the wall decreases as $L_\omega^{-5/3}$, i.e.

$$h_L(L_\omega \gg 1) = 1 - 1.8778 L_\omega^{-5/3} / J(\varepsilon). \quad (2.39)$$

Here, as mentioned in section 2.3, $J(\varepsilon)$ describes the shear-induced lift in an unbounded condition and its form is discussed in detail by Shi and Rzehak (2019).

According to the theory of matched asymptotic expansions, the outer-region lift force in the limit $L_\omega \ll 1$ must agree with the inner-region lift force in the limit $L_R \gg 1$. The latter is given by Cox and Hsu's solution (i.e. Eq. (2.36)), which yields the value of $h_L(L_\omega \ll 1)$ as

$$h_L(L_\omega \ll 1) = \frac{11}{96} \pi^2 L_\omega / J(\varepsilon). \quad (2.40)$$

In the limit $\varepsilon \gg 1$ Eq. (2.39) and (2.40) are shown as the dashed lines in Figure 2.9.

Based on the numerical data tabulated in McLaughlin (1993, Tables 1 and 2) and the limiting solution of $h_L(L_\omega \ll 1)$ (i.e. Eq. (2.40)), Takemura et al. (2009) proposed a semi-empirical expression for h_L in the form

$$h_L(\varepsilon, L_\omega) = 1 - e^{-\frac{11}{96} \pi^2 L_\omega / J(\varepsilon)}. \quad (2.41)$$

In the limit $\varepsilon \gg 1$ Eq. (2.41) appears as the dotted line in Figure 2.9.

Figure 2.9. $h_L(\varepsilon \gg 1)$ predictions according to the presently proposed expression, (2.42), and the earlier one from Takemura et al. (2009), (2.41), as well as the asymptotic expressions including both the one from McLaughlin (1993) for $L_\omega \gg 1$, (2.39), and the one from Cox and Hsu (1977) for $L_\omega \ll 1$, (2.40), (represented by solid, short dashed, and dashed lines, respectively) for $0.1 \leq L_\omega \leq 40$ compared with the numerical data from Drew (1988), Asmolov (1989) and McLaughlin (1993) (represented by cross, circle, and square symbols, respectively).

As shown in Figure 2.9, Drew's numerical data deviate strongly from both the numerical data obtained by the other authors and the analytical solution $h_L(L_\omega \ll 1)$. On the other hand, the numerical data obtained by Asmolov (1989) and McLaughlin (1993) show quantitative agreement with each other and approach the analytical solution in the limit $L_\omega \ll 1$. Data for $L_\omega > 6$ are available only from the study of McLaughlin (1993). These data show good agreement with the analytical solution in the limit $L_\omega \gg 1$. For $L_\omega \leq 1$, the expression proposed for h_L in Takemura, Magnaudet and Dimitrakopoulos (2009) shows quite good agreement with the numerical data provided by Asmolov (1989) and McLaughlin (1993) and the analytical solution $h_L(L_\omega \ll 1)$. However, for larger L_ω , their expression increasingly underestimates the reduction of the shear-induced lift due to the wall and deviates from the analytical solution $h_L(L_\omega \gg 1)$.

An improved expression in the same spirit as Eq. (2.41) is proposed to better approach the analytical solutions and the numerical data of Asmolov (1989) and McLaughlin (1993) as^{§§}

$$h_L(\varepsilon, L_\omega) = \begin{cases} 1 - e^{-\frac{11}{96}\pi^2 \frac{70}{70+L_\omega^{1.38}} L_\omega / |J(\varepsilon)|} & \text{for } L_\omega < 15 \\ 1 - 1.8778 L_\omega^{-5/3} / |J(\varepsilon)| & \text{for } L_\omega \geq 15 \end{cases} \quad (2.42)$$

In the limit $\varepsilon \rightarrow \infty$ Eq. (2.42) appears as the solid line in Figure 2.9.

^{§§} The analysis of McLaughlin (1991) showed that $J(\varepsilon)$ becomes negative when $\varepsilon < 0.22$; this is why the modulus of $J(\varepsilon)$ is used in Eq. (2.42).

An empirical expression for $f_L(\varepsilon, L_\omega)$ respecting the limit Eq. (2.38) was proposed by Takemura et al. (2009) as

$$f_L(\varepsilon, L_\omega) = e^{-0.22\varepsilon^{0.8}L_\omega^{2.5}}, \quad (2.43)$$

such that the entire numerical data obtained by McLaughlin (1993) was reproduced well.

Prediction of the lift coefficient $\beta^{-1}C_L^{W-out}$ is facilitated by application of (2.37) together with Eqs. (2.42) and (2.43) for h_L and f_L , respectively. Other necessary correlations are listed in Table 3. Note that Takemura et al (2009) used (2.26) for C_{Lu}^{W-out} , while here (2.27b) is applied since the comparison in Figure 2.7 (b) has confirmed the superiority of (2.27b) over (2.26). For the function $J(\varepsilon)$ appearing in (2.42), the accurate fit to the results from McLaughlin (1991, Table 1), (2.12), is employed to achieve consistency with the approximations on which the numerical data are based. In particular, the negative sign of J for the smallest value $\varepsilon = 0.2$ must be captured to achieve agreement with the numerical data as the unbounded case $L_\omega \rightarrow \infty$ is approached. The predicted lift coefficient appears as the solid lines in Figure 2.10.

Table 3: Summary of expressions applied together with (2.37) in Figure 2.10

parameter	equation
C_{Lu}^{W-out}	(2.27b)
$C_{L\omega}^U$	(2.7b)
f_L	(2.43)
$J(\varepsilon)$	(2.12)

The numerical data of both Asmolov (1990) and McLaughlin (1993), resulting from evaluation of the Airy functions, are represented by different symbols in Figure 2.10. The slight difference between their results is probably due to the different values of the threshold used when evaluating the Airy functions. In addition to varying the values of ε and L_ω , they consider both situations where the particle leads ($Sr > 0$) or lags ($Sr < 0$) the fluid.

The good agreement between the prediction and the numerical data confirms the reliability of the f_L correlation Eq. (2.43) as well as the reasonability of the assumption (2.37). For practical purpose, it remain necessary to discuss the prediction of the model (2.37) with (2.41) for h_L , which has a simpler form. As seen in Figure 2.10, although (2.41) clearly overestimate the shear-induced lift in the limit $\varepsilon \gg 1$, the deviation from the numerical data at finite ε is not obvious. In most cases no clear distinction from the prediction by implementing (2.42) as the h_L expression could be observed. Therefore, presently the h_L expression proposed by Takemura et al. (2009) will be applied in the following sections.

Figure 2.10. $\beta^{-1} C_L^{W-out}$ predictions according to the model, (2.37), with the h_L expression taken either as the presently proposed one, (2.42), or as the previous one from Takemura et al. (2009), (2.41), while keeping the rest involved expressions identical as summarized in Table 3 (represented by solid and dashed lines, respectively) for $0.1 \leq L_\omega \leq 10$ compared with the numerical data (represented by symbols) for both situations where the sphere leads ($Sr > 0$) or lags ($Sr < 0$) the fluid.

2.6.2 Approximate expression for the lift force at low-but-finite Reynolds number

Experimental investigation of the migration of spheres translating in a wall-bounded linear shear flow at low-but-finite Reynolds number was conducted by Takemura et al. (2009) for clean bubbles and by Takemura and Magnaudet (2009) for rigid spheres. Since the actually measured quantities are the transverse migration velocity and the terminal velocity of the sphere relative to the fluid, $U_{rel,\perp}$ and $U_{rel,\parallel}$, a theoretical input needed to estimate the lift coefficient is the drag law modified by the presence of wall and shear, $C_D(L_R, L_u, L_\omega)$. Given the relative velocity in the streamwise direction, $U_{rel,\parallel} \approx U_{rel}$, since drag forces are typically much larger than lift forces, the lift coefficient can be obtained by the relation

$$C_L^W = \frac{U_{rel,\perp}}{U_{rel,\parallel}} C_D(L_R, L_u, L_\omega). \quad (2.44)$$

The drag coefficient C_D may be expressed by the result for Stokes flow modified by ambient shear, translational inertia and the presence of the wall. Since the shear rate in all the experiments remains fairly weak, the shear-induced correction, and hence the dependency on L_ω , is neglected. The procedures suggested by Takemura et al. (2009) and Takemura and Magnaudet (2009) are applied in the following.

Assuming that the wall-induced and translational inertial corrections superimpose linearly one can write

$$C_D = C_{D,\text{Stokes}}[f_{D\infty}(Re) + h_D(L_R, L_u)], \quad (2.45)$$

where $C_{D,\text{Stokes}}$ denotes the Stokes drag, $f_{D\infty}$ denotes the drag correction in an unbounded condition, h_D denotes the wall-induced drag correction. For a clean bubble, a semi-empirical expression for $f_{D\infty}$ proposed by Mei, Klausner and Lawrence (1994) reads

$$f_{D\infty}(Re) = 1 + [8Re^{-1} + 0.5(1 + 3.315Re^{-1/2})]^{-1}. \quad (2.46)$$

The wall-induced drag correction h_D for a clean bubble was investigated theoretically by Magnaudet et al. (2003). Based on their numerical data, Takemura et al. (2009) proposed

$$h_D(L_R, L_u) = L_R^{-1}[3/4 + 1.52 \times 10^{-5}(2L_u)^{3.82}]e^{-0.624L_u}. \quad (2.47)$$

For a rigid sphere, a widely used expression for $f_{D\infty}$ was proposed by Schiller and Naumann (1933), namely

$$f_{D\infty}(Re) = 1 + 0.15Re^{0.687}. \quad (2.48)$$

According to Takemura (2004), the wall-induced drag correction h_D for a solid sphere can be approximated in the form

$$h_D = \begin{cases} \left(1 - \frac{9}{8}L_R^{-1} + \frac{1}{2}L_R^{-3} - \frac{135}{256}L_R^{-4} + \frac{39}{256}L_R^{-5}\right)^{-1} - 1 & \text{for } L_u < 1. \\ 9L_R^{-1}(8 + 4.24L_u + 1.31L_u^2 + 0.478L_u^3 + 0.0718L_u^4)^{-1} & \text{for } L_u \geq 1 \end{cases} \quad (2.49)$$

The lift coefficient can be estimated based on the above correlations and the experimental determination of L_R , U_{rel} , and $U_{\text{rel},\perp}$. A summary of the experimental data for the lift coefficient as a function of L_u obtained in the two studies mentioned at the beginning of this section is given in Figure 2.11. There are two series for rigid spheres and seven series for clean bubbles with Reynolds numbers less than 3.5. The experimental data are compared with the predictions by (2.37), where the wall-induced lift is given by (2.28) and (2.33) for clean bubbles and rigid spheres, respectively, and the unbounded shear-induced lift by (2.7b).

In addition to the combined model just described, the wall-induced lift curve calculated by (2.27b) appears as the dashed line in Figure 2.11, which separates the whole data set into two parts: one with positive Sr and the other with negative Sr . It is seen that for positive Sr (i.e. the sphere lagging the flow) the lift is increased compared with a stagnant flow, while it is reduced for negative Sr (i.e. the sphere leading the flow).

Considering the many approximations that had to be made, the predictions of (2.37) agree reasonably well with the experimental data. A previous comparison was made by Takemura et al. (2009, Figure 6) based on a similar model, which however used the low Reynolds number expressions for both the unbounded shear-induced lift coefficient $C_{L\omega}^U$ and the wall-induced lift coefficient $C_{L_u}^W$. These authors found similar agreement with the experimental data up to $Re \approx 2$

but an underestimate for larger values of Re , which is not surprising in view of the neglect of finite Re corrections (Legendre and Magnaudet, 1998; Takemura and Magnaudet, 2003).

The fair agreement with the data suggests that the decomposition of (2.37) is applicable at least up to Reynolds numbers of around 4. For the various submodels, improved expressions might be sought, including also (2.45) to (2.49) that were necessary to obtain the measured lift coefficients. Results from DNS studies that circumvent the use of these models would be highly desirable.

Figure 2.11. $\beta^{-1}C_L^W$ prediction according to the model (2.37) and the wall-induced lift expression (i.e. without shear) of (2.27b) (represented by solid lines and dashed line, respectively) for $0.1 < L_u \leq 10$ compared with the experimental data from Takemura et al. (2009, clean bubble) and Takemura and Magnaudet (2009, rigid sphere) (represented by circle and square symbols, respectively).

2.6.3 Approximate expression for the lift force at moderate-to-large Reynolds number

DNS study of the lift force acting on a rigid sphere subjected to a wall-bounded linear shear flow was conducted by Zeng et al. (2009). Only a stationary sphere was considered, which means that shear rate and wall distance are related as $Sr = 2L_R^{-1}$. The Reynolds number ranged from 2 to 250, and the wall distance L_R ranged from 1.01 to 8. Zeng et al. (2009) summarized their DNS results with the following correlation:

$$C_{L\omega}^W = C_{L\omega}^W(L_R = 1.01)\exp[-0.5\delta(Re/250)^{4/3}][\exp(\alpha\delta^{\beta'}) - \lambda] \quad (2.50)$$

with

$$\begin{aligned} C_{L\omega}^W(L_R = 1.01) &= 3.663(Re + 0.1173)^{-0.22}, \\ \alpha &= -e^{-0.3+0.025Re}, \\ \beta' &= 0.8 + 0.01Re, \\ \lambda &= (1 - e^{-\delta})(Re/250)^{5/2}. \end{aligned} \quad (2.51a-d)$$

Here, as mentioned in section 2.4, $C_{L\omega}^W$ corresponds to the coefficient of the lift force acting on a stationary sphere. In the limit $L_R \rightarrow 1$ this correlation reduces to (2.51a), which approaches the inner-region solution of Leighton and Acrivos (1985) at $Re \rightarrow 0$.

The predictions of (2.50) are shown in Figure 2.12 with the curves given for fixed values of L_R , i.e. the value $Re = 2L_u L_R^{-1}$ varies along each curve. As expected, Zeng's correlation shows good agreement with their DNS data. Comparison concerning the prediction of (2.37) (with all necessary correlations as listed in Table 3) is made in Figure 2.12 as well. Compared with the DNS data the predictions of (2.37) show only mediocre agreement as soon as Re assumes values larger than about 4. For the few data points with $Re < 4$ the agreement is quite good. In this light, Zeng's prediction at large L_R but small L_u appears questionable.

Figure 2.12. $C_{L\omega}^W$ predictions according to the model (2.37) with the involved correlations summarized in Table 3 and the model of Zeng et al. (2009), (2.50), (represented by dashed and solid lines, respectively) for $1 \leq L_u \leq 1000$ compared with the DNS data (represented by square symbols).

Table 4. Summary of data in Lee and Balachandar (2010, Table 2)***

Re	Sr	L_R	C_L	C_L	C_L	C_L
			from DNS	from (2.37)	from (2.50) using Sr and L_R	from (2.50) using Re and L_R
5	2	2	1.64	1.33	0.796	1.13
20	0.5	2	0.334	0.0243	0.796	0.527
50	2	2	0.764	0.0600	0.0157	0.218

The restriction of a stationary sphere was removed by Lee and Balachandar (2010) in their DNS study by conducting the computation in a reference frame that translates with the sphere. However, they conducted the simulation with $L_R = 2$ only. A summary of their results consisting of three data points is given in Table 4. The prediction of (2.37) is given as well. It shows acceptable

*** Note that here a different definition of the relevant velocity scale is used, thus the resulting Reynolds numbers and lift coefficients are different from those given in Lee and Balachandar (2010, Table 2).

agreement with the DNS data at $Re = 5$ but suffers a severe underestimation at both $Re = 20$ and $Re = 50$. This deviation is in accordance with the comparison shown in Figure 2.12. To show the effect of sphere motion, the predictions of Zeng et al., (2.50), are given in the last two columns of Table 4 using the values for L_R and Sr as well as those for Re and L_R . Both deviate significantly from the DNS results for all conditions, the latter being somewhat closer. For the lowest value of Re , both predictions are even lower than that of (2.37). Note that in Table 4 $SrL_R > 2$ indicates that the sphere moves antiparallel to the flow and vice versa. Compared with the case of a stationary sphere, the resulting lift force would increase (resp. decrease) if the sphere moves antiparallel (resp. parallel) to the flow. This trend is clearly seen for both sets of parameters used.

2.7 Conclusions

A review has been presented of the available results on the hydrodynamic force experienced by a sphere translating in unbounded and wall-bounded linear shear flows. As much as results are available, both clean spherical bubbles and rigid spheres have been considered. Expressions based on analytical calculations as well as obtained empirically have been compared against the available data from analytical, experimental, and DNS studies. The suggested correlations for the drag and lift coefficients in different cases are summarized in Table 5.

Different situations can be distinguished based on the wall distance $\tilde{L}$ normalized by the Saffman length $\tilde{L}_\omega$, the Oseen length $\tilde{L}_u$, and the sphere radius $d/2$, i.e. $L_\omega = \tilde{L}/\tilde{L}_\omega$, $L_u = \tilde{L}/\tilde{L}_u$, and $L_R = 2\tilde{L}/d$. For unbounded linear shear flows (termed case a), the composite fit for the lift force proposed in Legendre and Magnaudet (1998) was found to be applicable for clean spherical bubbles translating at rather arbitrary Reynolds numbers and moderate shear rate (i.e. $Sr \leq O(1)$). Unfortunately, this expression does not apply for a rigid sphere. In this case the low- Re expression proposed in Legendre and Magnaudet (1998) was shown to be applicable for $Re \lesssim 50$ and $Sr \leq O(1)$. At higher Reynolds number the direction of the shear-induced lift reverses. There, the agreement achieved by the expression proposed in Loth (2008) was only mediocre.

Conditions where the wall lies in the inner region, i.e. $\max(L_\omega, L_u) \ll 1$, (termed case b) are restricted to small Reynolds number conditions for which DNS and experimental data are so far not available. On the basis of comparisons with available numerical data that were obtained by various perturbation methods, the analytical solutions obtained in Magnaudet et al. (2003) for a clean spherical bubble and the fitted expression proposed in Cherukat and McLaughlin (1994) for a rigid sphere have been shown to be the most accurate. Both are valid for arbitrary shear rate and rather wide range of wall distances. For the latter the validity of the expression of Cherukat and McLaughlin (1994) extends to $L_R = 1$ (i.e. the situation where a sphere is in contact with the wall).

Conditions where the wall lies in the outer region, i.e. $\max(L_\omega, L_u) \geq O(1)$, (termed case c and d) are more relevant to applications, but also significantly more complex. For stagnant flow (case c), the resulting lift force can be obtained by singular perturbation expansions provided that the particle Reynolds number is small. Based on a re-evaluation of the defining integral with high numerical accuracy, the expression of Takemura and Magnaudet (2003) has been improved in the range of $L_u \leq 3$. The modified expression approaches analytical solutions in the limits of both $L_u \gg 1$ and $L_u \ll 1$. For finite Reynolds numbers, the composite fit proposed in Takemura and Magnaudet (2003) has been shown to be accurate for $L_R \gtrsim 4$ and $Re \lesssim 300$. On the other hand, for a rigid sphere, comparisons with available DNS and experimental data showed the expression of Zeng et al. (2009) to be applicable for a broader range, i.e. for $1.01 \leq L_R \leq 8$ and $Re \lesssim 100$, than the one

proposed by Takemura and Magnaudet (2003). Some data for still higher particle Reynolds numbers have been obtained in DNS studies. However, although each of them confirmed the onset of an imperfect bifurcation, a systematic study on the resulting lift force is still unavailable.

Table 5. Summary of suggested expressions as well as their range of applicability

case	sphere type	range of Re	range of wall distances	range of Sr	equation
a	clean bubble	arbitrary	$L_R, L_u, L_\omega \rightarrow \infty$	$Sr \leq O(1)$	lift: (2.14) along with (2.13b) (2.11) and (2.7b)
	rigid sphere	$Re \lesssim 50$	$L_R, L_u, L_\omega \rightarrow \infty$	$Sr \leq O(1)$	lift: (2.7b) along with (2.11)
b	clean bubble	$Re \ll 1$	$L_R^{-3} \ll 1$	arbitrary	drag: (2.17a) lift: (2.17b)
	rigid sphere	$Re \ll 1$	arbitrary L_R	arbitrary	drag: (2.18) lift: (2.23)
c	clean bubble	$Re \lesssim 300$	$1 \lesssim L_u \lesssim 10^3$	$Sr = 0$	lift: (2.32) along with (2.31), (2.30), (2.28), and (2.27b)
	rigid sphere	$Re \lesssim 100$	$1 \lesssim L_u \lesssim O(10^2)$	$Sr = 0$	lift: (2.33) along with (2.35a,b), and (2.27b)
d	both	$Re \lesssim 4$	$10^{-1} \leq \max(L_u, L_\omega) \lesssim 10^1$	$ Sr \lesssim O(10^{-1})$	lift: (2.37) along with expressions listed in Table 3
	rigid sphere	$4 \leq Re \leq 250$	$1 \lesssim L_u \lesssim 10^3$	$Sr = 2L_R^{-1}$	lift: (2.50) along with (2.51a-d)

For linear shear flow (case d), the situation becomes yet more involved since the shear- and wall-induced lift forces combine nonlinearly. At Reynolds numbers up to $Re \approx 4$ the decomposition proposed by Takemura, Magnaudet, and Dimitrakopoulos (2009) gives fair agreement with the available numerical data from evaluation of matched asymptotic expansions and with their experimental data concerning both clean bubbles and rigid spheres. In the range $4 \leq Re \leq 250$ the correlation of Zeng et al. (2009) may be used to evaluate the lift force on a rigid sphere provided that the position of the sphere is kept fixed with respect to the bounding wall. A highly accurate model applicable over a wide range of parameters and confirmed by data from different sources is not yet available for this case.

3 NUMERICAL APPROACH AND PRELIMINARY TESTS

3.1 Numerical approach

The computational results discussed below are carried out using the JADIM code developed at IMFT. This code solves the three-dimensional unsteady Navier-Stokes equations with a finite-volume discretization and, in the version used here, makes use of a boundary-fitted staggered grid. Spatial derivatives are approximated using second-order centered schemes. The velocity field is advanced in time with a third-order Runge-Kutta algorithm for the advective term, together with a Crank-Nicolson semi-implicit algorithm for viscous terms. Incompressibility is satisfied at the end of each time step through a projection technique which yields a Poisson equation for the pressure correction. Details about this code can be found in previous publications, especially Calmet and Magnaudet (1997) for most algorithmic aspects, and Magnaudet et al. (1995) (resp. Legendre et al. (2003)) for specific aspects concerned with curvilinear grids in unbounded (resp. wall-bounded) flows.

The grid system used in this study is identical with the one developed in Legendre et al. (2003), based on which two spherical bubbles rising side by side in a viscous liquid was simulated. A two-dimensional grid is first built on the streamlines $\eta = \text{const.}$ and the equipotential lines $\xi = \text{const.}$ of the potential flow around two circular cylinders moving in line along the x -axis. Then this grid is rotated about the x -axis with an angle $\varphi = \pi$ or 2π . The first choice, which was used in certain runs, exploits the planar symmetry of the problem geometry with respect to the plane $y = 0$, reducing the computational domain to a half-space by imposing a symmetry condition in this plane. Other computations were run in the full domain $0 \leq \varphi \leq 2\pi$, because there is a priori no guarantee that the flow keeps its planar symmetry at high Reynolds number, owing to the combined presence of wall and shear. The resulting computational domain, shown in Figure 3.1 (a), has an inner boundary that coincides with the sphere surface and a cylindrical outer boundary of radius R_∞ . Its height in between the sphere center and the wall (resp. the outer boundary) is $\tilde{L}$ (resp. R_∞). The (ξ, η, φ) grid is made of $(N_W + N_p + N_\infty) \times N_\eta \times N_\varphi$ nodes as defined in Figure 3.1 (b). Here N_W is the number of nodes between the wall $x = -\tilde{L}$ and the sphere, N_p is the number of nodes along half of the sphere circumference (from $x = -d/2$ to $x = d/2$), N_∞ is the number of nodes between the sphere and the outer boundary in the x -direction, N_η and N_φ are the number of nodes along the radial (η) and azimuthal (φ) directions, respectively. The sphere surface is thus discretized with $N_p \times N_\varphi$ nodes.

In Legendre et al. (2003) it was found that the length R_∞ and the distance δ from the sphere surface to the first node above it near the singular point $x = 0$ of the x -axis are critical for an accurate calculation of the transverse force. To reduce the effect of the other boundary, R_∞ is selected such that $2R_\infty/d = 100$ for $Re < 1$, $2R_\infty/d = 80$ for $Re < 100$, and $2R_\infty/d = 40$ for $Re \geq 100$. To improve accuracy in the high-Reynolds-number regime, the dimensionless distance $2\delta/d$ is set to 0.01 for $Re < 10$ and to 0.002 for $Re \geq 10$. A constant spacing of nodes is chosen in the φ -direction with $N_\varphi = 128$ (resp. 64) in the case of a full (resp. half) domain. In the ξ - and η -directions, a geometrical progression ensuring that the widths ratio between two successive cells is less than 1.15 is applied with $N_\infty = 58$ and $N_\eta = 54$. Some tests were carried out at large Reynolds number with a finer resolution in the radial direction, namely $N_\eta = 80$ and 108. Differences on the drag and lift coefficients were found to be less than 0.4% in all cases, from which it is concluded

that $N_\eta = 54$ is sufficient throughout the range of flow conditions considered here. In Legendre et al. (2003) it was shown that numerical results are not weakly sensitive to the number of nodes on the sphere surface, N_p , and in between the bubble and the wall, N_W . Regarding the former number, the configuration considered here does not differ much from that in Legendre et al. (2003). Hence this reference was followed and N_p was set as 30. The situation is different regarding N_W , since the plane $x = -\tilde{L}$ corresponds to a rigid wall with a no-slip condition here, whereas it was only a symmetry plane in Legendre et al. (2003). For this reason, more grid points are required near the wall when the Reynolds number becomes large to properly capture the corresponding boundary layer. For $Re \leq 10$ it was found convenient to employ $N_W = 10$ for $L_R \leq 2$, $N_W = 15$ for $2 < L_R \leq 4$, and $N_W = 20$ for $L_R > 4$. At larger Reynolds numbers, the results to be discussed later show that effects of the boundary layer are ‘felt’ by the bubble only at short separation distances, typically $L_R \leq 2$. N_W was increased up to 40 (resp. 60) for $L_R = 1.5$ (resp. 2) and it was found that results are grid-independent for $N_W \geq 30$ (resp. 40) up to $Re = 10^3$. Therefore the latter values were adopted, which allow to cluster approximately 10 grid points within the $O(d/(2Re^{1/2}))$ wall boundary layer^{†††} for $Re = 1000$, guaranteeing a proper capture of the corresponding effects. Two examples of the near-sphere cell distribution at low-to-moderate Reynolds numbers are provided in Figure 3.1. The adequacy of the resulting resolution is established in the following sections where results for the drag and lift forces in the wall-bounded configuration with the fluid at rest at infinity, as well as predictions for the drag and lift forces and in an unbounded shear flow at low-to-high Reynolds numbers were discussed.

Figure 3.1. Illustration of the grid system. (a) Shape and size of the computational domain. (b) Definition of the number of nodes in the computational domain. (c) and (d) Partial view of the grid near the sphere with $L_R = 1.5$ and $2\delta/d = 0.01$ in (c), and $L_R = 2$ and $2\delta/d = 0.002$ in (d).

The velocity is assumed to correspond to the unperturbed flow (2.2b) on the top plate $x = R_\infty$ and the cylindrical surface $(y^2 + z^2)^{1/2} = R_\infty$. On the bottom plate $x = -\tilde{L}$ the no-slip condition in the moving frame, $\mathbf{u} = -V\mathbf{e}_z$, is applied. Note that the $\mathbf{e}_x$ -symmetry axis of the grid system introduces an artificial singularity, since a given point $(x = x_0, y = 0, z = 0)$ on this axis is

^{†††} At high- Re , the flow about a clean spherical bubble is almost irrotational. For this reason, the disturbance decays as $(2r/d)^{-3}$ (Magnaudet, 2011), where r denotes the distance to the bubble center. Consequently, the tangential velocity on the plane $x = -L_R$ would only be $U_W = L_R^{-3}U_{rel}$ if the wall were replaced by a symmetry plane. Hence the Reynolds number Re_W that determines the wall boundary layer thickness is approximately $Re_W = U_W d/\nu = L_R^{-3}Re$.

associated with different values of φ . A specific condition described in Legendre and Magnaudet (1998) is used to overcome this problem. The techniques used to evaluate the various contributions to the hydrodynamic force experienced by the sphere may be found in the same reference.

3.2 Preliminary tests

The capability of the JADIM code to accurately compute three-dimensional flows past clean bubbles and rigid spheres over a wide range of Reynolds number has already been proved in various contexts, (see e.g. Legendre and Magnaudet (1998), Magnaudet and Mougin (2007), and Auguste and Magnaudet (2018)). The (ξ, η, φ) grid system used here was also shown to be suitable to obtain accurate grid-independent results regarding the hydrodynamic interaction between two spherical bubbles rising side-by-side in a stagnant liquid (Legendre et al., 2003). Therefore, here it is necessary to check grid effects in wall-bounded flows and in an unbounded linear shear flow, respectively. The following discussion is separated into two sections with section 3.2.1 on clean spherical bubbles and section 3.2.2 on rigid spheres.

3.2.1 Clean spherical bubble

In a first series of tests the forces on a clean bubble translating at finite Reynolds number in a wall-bounded stagnant flow were computed. To obtain some insight into the adequacy of the grid resolution, this test was carried out first at $Re = 0.1, 100$, and 500 with $L_R = 2$. Note that for $Re = 0.1$ and $L_R = 2$, the normalized wall distance L_u is $L_u = ReL_R/2 = 0.1$. Thus, the wall lies in the inner region of the disturbance and the solution (2.17a,b) applies. The corresponding asymptotic drag and lift coefficients predicted are 197.6 and 0.467, respectively. At $Re = 500$, the resulting lift coefficient should be close to the irrotational prediction (2.30), i.e. $C_{Lu}^W = -0.024$.

Table 6. Effect of grid resolution on the drag and lift coefficients of a clean spherical bubble translating close to a wall ($L_R = 2$) in a stagnant fluid.

		$128 \times 54 \times 64$	$128 \times 54 \times 128$	$152 \times 78 \times 128$	analytical solution
$Re = 0.1$	C_{Du}^W	196.4	196.9	197.7	197.6
	C_{Lu}^W	0.470	0.468	0.469	0.467
$Re = 100$	C_{Du}^W	0.392	0.391	0.392	-
	C_{Lu}^W	-0.016	-0.016	-0.016	-
$Re = 500$	C_{Du}^W	0.092	0.092	0.092	-
	C_{Lu}^W	-0.023	-0.023	-0.023	-0.024

Computational results obtained with three different grid resolutions are listed in Table 6. The obtained drag and lift coefficients show good agreement with the analytical solution at $Re = 0.1$. At $Re = 500$ the deviation from (2.30) is approximately 4%. This deviation is likely due to the viscous correction proportional to $Re^{-1}L_R^{-4}$ in (2.31). For all three Reynolds numbers considered in this test, the numerical predictions only exhibit slight variations with the resolution, the

differences between the results obtained with the coarsest ($128 \times 54 \times 64$) grid and those provided by the most refined one ($152 \times 78 \times 128$) being less than 1%.

Figure 3.2. Numerical predictions ($\square$) for the wall-induced forces on a clean spherical bubble in a quiescent fluid at low-to-moderate Reynolds number. (a) ΔC_{Du}^W . (b) C_{Lu}^W (with C_{Lu}^W multiplied by L_R^{-1} for better readability). Dashed lines: asymptotic solution (2.17a,b) corresponding to conditions $L_u \ll 1, L_\omega \ll 1$; dotted lines: asymptotic solution (2.27a,b) corresponding to conditions $L_u \gg 1, L_\omega \gg 1$; solid lines: semi-empirical model (3.1a,b).

A second series of tests, still with the fluid at rest far from the bubble was carried out on the $128 \times 54 \times 128$ grid with $0.1 \leq Re \leq 500$ and $1.5 \leq L_R \leq 8$. The drag and lift coefficients obtained in the range $0.1 \leq Re \leq 2$ are compared with available analytical solutions in Figure 3.2. The computational results at $Re = 0.1$ show good agreement with the inner solution (2.17a,b)^{†††}. On the other hand, the results agree well with the outer solution (2.27a,b) for $L_R = 4$ and 8, i.e. for $L_u \gtrsim O(1)$. When $L_R \leq 2$, the results deviate somewhat from both the inner and outer solutions for $Re \gtrsim 0.5$. This is no surprise, as in these cases the wall lies in the intermediate region where none of these solutions is valid (Takemura and Magnaudet, 2009). More precisely, the outer solution is obtained by considering that the sphere is shrunk to a point, whereas a uniformly valid approximation could only be obtained by taking into account its finite size in the Oseen equation. On a purely heuristic basis, the inner and outer solutions may be combined into expressions tending toward each of them in the appropriate limit, namely

$$\Delta C_{Du}^W(Re \ll 1) \approx f_D' \Delta C_{Du}^{W-in}, \quad C_{Lu}^W(Re \ll 1) \approx f_L' C_{Lu}^{W-in} \quad (3.1a,b)$$

with f_D' and f_L' (resp. ΔC_{Du}^{W-in} and C_{Lu}^{W-in}) as given in (2.27a) and (2.27b) (resp. (2.17a) and (2.17b)), respectively. Based on these semi-empirical expressions, (3.1a,b) approach the inner and outer solutions in the limits $L_u \rightarrow 0$ and $L_R \rightarrow \infty$ combined with $L_u \geq O(1)$, respectively. Predictions provided by these approximations are displayed with solid lines in Figure 3.2 and show good agreement with the numerical results.

^{†††} The slight difference observed for $L_R = 1.5$ is presumably due to the limited accuracy of (2.17a,b) when the normalized separation distance becomes of $O(1)$, as lubrication effects not accounted for by the expansion in powers of L_R^{-1} become significant in this limit.

At moderate Reynolds number, the calculated C_{Lu}^W may be compared with the fit (2.28), under conditions $L_R \geq 4$. As shown in Figure 3.3, the agreement is excellent for $Re \leq 20$, beyond which both the numerical data and the prediction indicate vanishingly small values of C_{Lu}^W . Numerical predictions in the range $20 \leq Re \leq 500$ are compared with the potential flow solution (2.30) at small wall distances, namely $L_R = 1.5$ and 2.0 . As seen in Figure 3.3, the deviation from the irrotational solution becomes negligible beyond $Re \approx 300$. At moderate Re , the computed lift coefficient becomes negative for $Re \approx 35$ (based on linear interpolation), which agrees well with the critical value found in Takemura and Magnaudet (2003) and Sugioka and Tsukada (2015).

Figure 3.3. Comparison of numerical predictions for C_{Lu}^W ($\square$) with the fit (2.28) of the asymptotic solution corresponding to conditions $Re = O(1 - 10)$ (dashed lines), and the irrotational solution (2.30) (short-dashed lines), for $1.5 \leq L_R \leq 8$ and $0.1 \leq Re \leq 500$.

In a further series of tests, the flow field with the $98 \times 54 \times 128$ grid in situations where the normalized wall distance L_R is very large, more specifically $\tilde{L} = R_\infty$, was computed. For this purpose, the grid system is adjusted such that $N_W = N_\infty$. The unperturbed flow is a one-dimensional linear shear flow $\mathbf{u}_\infty = (U_{rel} + \gamma x)\mathbf{e}_z$ and the forces experienced by the bubble are expected to correspond to the unbounded shear flow configuration. This test was carried out for $0.1 \leq Re \leq 200$ with two different shear rates, namely $Sr = 0.02$ and $Sr = 0.2$. Note that these simulations differ from those carried out in Legendre and Magnaudet (1998) only with respect to the flow direction: there, the undisturbed flow was set as $\mathbf{u}_\infty = (U_{rel} + \gamma y)\mathbf{e}_x$ (in current notations), i.e. the flow was primarily along the grid symmetry axis, whereas it stands in a plane perpendicular to this axis in the present case.

The comparison of the calculated drag coefficient with values obtained in Legendre and Magnaudet (1998) and with a semi-empirical fit proposed in Mei et al. (1994) is shown in Figure 3.4 (a). As the shear has virtually no effect on the drag for $Sr \lesssim 0.2$, only numerical data obtained for $Sr = 0.2$ in Legendre and Magnaudet (1998) are presented. Results deviate from those of Legendre and Magnaudet (1998) by less than 2% for all values of Re and Sr . Figure 3.4 (b) compares the computed lift coefficient with those obtained in Legendre and Magnaudet (1998) and with the composite fit (2.14). Again, the agreement with these earlier predictions is good. Some tiny differences may be noticed for $Sr = 0.02$ when $Re \lesssim 2$. They are likely due to the difference in the two numerical settings. Indeed, compared with Legendre and Magnaudet (1998), the current grid

is somewhat more refined ($98 \times 54 \times 128$ instead of $90 \times 45 \times 64$), especially near the sphere surface ($2\delta/d = 0.002$ instead of $2\delta/d = 0.01$).

Figure 3.4. Comparison of present numerical predictions with available numerical results and semi-expressions. (a) C_{D0}^U compared with numerical results from Legendre and Magnaudet (1998) and semi-empirical correlation $\frac{Re}{16} C_{D0}^U = 1 + \left[\frac{8}{Re} + \frac{1}{2} (1 + 3.315 Re^{-1/2}) \right]^{-1}$ proposed in Mei et al. (1994). (b) C_{L0}^U compared with numerical results and the composite fit (2.14) from Legendre and Magnaudet (1998).

3.2.2 Rigid sphere

Like in the case concerning a clean spherical bubble, in a first series of tests the forces on a rigid sphere translating at finite Reynolds number in a wall-bounded stagnant flow were computed. To obtain some insight into the adequacy of the grid resolution, this test was carried out first at $Re = 0.1, 100$, and 200 ^{§§§} with $L_R = 2$. At $Re = 0.1$ the wall lies in the inner region of the disturbance and the solution (2.18) and (2.23) applies. The corresponding asymptotic drag and lift coefficients predicted are 336.8 and 1.119, respectively. At $Re = 100$ and 200 the DNS results from Zeng et al. (2009) using the spectral element methods may be treated as a reference.

Computational results obtained with three different grid resolutions are listed in Table 7. The obtained drag and lift coefficients show good agreement with the analytical solution at $Re = 0.1$. At $Re = 100$ and 200 the deviations from the results of Zeng et al. (2009) are often less than 3%, except for the lift coefficients obtained with the coarsest grid at $Re = 200$. There, the deviation amounts to 8%. For the first two Reynolds numbers considered in this test, the numerical predictions only exhibit slight variations with the resolution, differences between results obtained with the normal grid and the most refined one being less than 1%. For all three Reynolds numbers

^{§§§} Unlike in the case concerning a clean spherical bubble, in which the flow field is always steady whatever Re , the flow field around a rigid sphere becomes unsteady for $Re \approx 212.6$ due to the onset of bifurcation (Citro et al., 2016); this is why the highest Reynolds number is set as 200.

considered in this test, the numerical predictions obtained with the normal and the most refined grids only exhibit slight variations with the resolution, the differences being less than 2%.

Table 7. Effect of grid resolution on the drag and lift coefficients of a rigid sphere translating close to a wall ($L_R = 2$) in a stagnant fluid.

		$128 \times 54 \times 64$	$128 \times 54 \times 128$	$172 \times 78 \times 128$	analytical solution	Zeng et al. (2009)
$Re = 0.1$	C_{Du}^W	334.8	336.2	336.8	336.8	-
	C_{Lu}^W	1.106	1.109	1.109	1.119	-
$Re = 100$	C_{Du}^W	1.163	1.140	1.143	-	1.164
	C_{Lu}^W	0.042	0.043	0.043	-	0.042
$Re = 200$	C_{Du}^W	0.817	0.812	0.814	-	0.816
	C_{Lu}^W	0.064	0.060	0.059	-	0.059

A second series of tests, still with the fluid at rest far from the rigid sphere but now with $1.5 \leq L_R \leq 8$ was carried out. The adopt grid is $128 \times 54 \times 128$. The drag and lift coefficients obtained in the range $0.1 \leq Re \leq 2$ are compared with the inner solution and the presently proposed semi-empirical low- Re expression (3.1a,b) (but now with ΔC_{Du}^{W-in} and C_{Lu}^{W-in} given by (2.18) and (2.23), respectively). The computational results at $Re = 0.1$ show good agreement with the inner solution. Beyond $Re = 0.1$ the computational results decrease with increasing Reynolds number, which agrees well the low- Re expression (3.1a,b).

Figure 3.5. Numerical predictions ($\square$) for the wall-induced forces on a rigid sphere in a quiescent fluid at low-to-moderate Reynolds number. (a) ΔC_{Du}^W . (b) C_{Lu}^W (with C_{Lu}^W multiplied by L_R^{-1} for better readability). Dashed lines: asymptotic solution (2.18) and (2.23) corresponding to conditions $L_u \ll 1, L_\omega \ll 1$; solid lines: semi-empirical model (3.1a,b).

At moderate-to-high Reynolds numbers ($0.5 \leq Re \leq 200$) the calculated results may be compared to the data from Zeng et al. (2005, 2009). As shown in Figure 3.6 (a), the drag results deviate from the previous ones by less than 3% for all values of Re and L_R . Figure 3.6 (b) compares the calculated lift coefficients with those obtained in Zeng et al. (2005, 2009). Again, the agreement with these earlier data is good. Some small differences may be noticed at $Re = 200$ when $L_R \geq 4$. This is likely due to the relatively small lift coefficients under these conditions, in which it is difficult to exclude the numerical inaccuracy. According to the results at $Re = 200$ listed in Table 7, the lift coefficient decreases with increasing grid resolution indicating that the deviation from the previous ones is not a consequence of insufficient grid resolution.

Figure 3.6. Comparison of present numerical results with the previous ones from Zeng et al. (2005, 2009). (a) C_{Du}^W . (b) C_{Lu}^W . Both are multiplied by L_R^{-1} for better readability.

In a further series of tests the flow field in situations where the wall lies in the unperturbed far field was computed. This test was carried out for $0.1 \leq Re \leq 200$ with two different shear rates, namely $Sr = 0.2$ and 0.5 .

The comparison of the calculated drag coefficients with values obtained in Kurose and Komori (1999) and with the empirical expression proposed in Schiller and Naumann (1933) is shown in Figure 3.7 (a). At $Sr = 0.2$, our results deviate from the expression by less than 3% for $0.1 \leq Re \leq 5$ and from those of Kurose and Komori (1999) by less than also 3% for $10 \leq Re \leq 200$. At $Sr = 0.5$, the calculated drag coefficients for $Re < 50$ show virtually no difference from those obtained at $Sr = 0.2$. On the other hand, for $Re \geq 50$ the obtained values are always larger than those at $Sr = 0.2$. These features agree qualitatively with those shown in Kurose and Komori (1999, Figure 6). Figure 3.7 (b) compares the calculated lift coefficients with those previously obtained and with the low- Re expression (2.7b). In contrast to the comparison discussed in section 2.3.2, where (2.7b) always overestimates the numerical results obtained previously, the agreement between (2.7b) and the present numerical results for $Re \lesssim 5$ is always acceptable. For $Re \geq 10$ (2.7b) can no longer be taken for granted. Compared with the present DNS results it gives a too faster decay. The deviation between the present and the previous DNS results at $Sr = 0.2$ is likely a consequence of insufficient computational domain adopt in previous studies (see the discussion below). Since this artificial confinement effects decays with increasing Reynolds number (Legendre and Magnaudet,

1998). Beyond $Re = 50$ quite good agreement between the numerical results at $Sr = 0.2$ from different studies can be observed. Moreover, the present numerical results indicate that the lift coefficient becomes negative for $Re \gtrsim 50$ and increases with increasing Sr which agrees with the behaviors revealed in previous studies (see Figure 2.4).

Figure 3.7. Comparison of present numerical predictions with available numerical results and semi-empirical expressions. (a) C_{D0}^U compared with numerical results from Kurose and Komori (1999) and expression $C_{D0}^U = \frac{24}{Re}(1 + 0.15Re^{0.687})$ proposed in Schiller and Naumann (1933). (b) $C_{L\omega}^U$ compared with numerical results and the low- Re expression (2.7b).

It remains necessary to discuss the deviation between the low- Re expression (2.7b) and the previous numerical results as already shown in Figure 2.3. As the size of computational domain R_∞ used here**** ($2R_\infty/d = 100$, see section 3.1) is larger than those used in previous studies (see Table 2), it may thus be concluded that the mismatch with the low- Re expression (2.7b) revealed in previous studies is a consequence of confinement effects rather the negative contribution from the small term of the Saffman-lift (see (2.17) in Saffman (1965)) as explained in Shi and Rzehak (2019). Moreover, the experiment of Takemura et al. (2009) concerning clean spherical bubbles moving at low- Re and low ε already gave the evidence that the small term of the Saffman-lift does not play a significant role.

In summary, the tests reported in this chapter prove that the wall and shear effects are both accurately captured by the present numerical procedure throughout the range of Reynolds number $0.1 \leq Re \leq O(10^2)$.

**** To ensure that the numerical results are not influenced by artificial confinement effects, the size of the computational domain was increased up to $2R_\infty/d = 300$. This did not produce any change in the values of $C_{L\omega}^U$.

4 CLEAN SPHERICAL BUBBLE IN WALL-BOUNDED FLOW

This chapter first describes the flow field and the underling mechanisms. The variations of the drag and lift forces on the bubble revealed by numerical data in the light of the basic mechanisms described in section 4.1 are then discussed. Most of the results cover the range $0.1 \leq Re \leq 500$, $|Sr| \leq 0.5$, but some correspond to higher Reynolds number or shear rate. Such larger values were found useful to determine the dependence of several contributions with respect to Re , Sr and L_R in the high-Reynolds number range. Note that, following earlier studies aimed at revealing fundamental mechanisms rather than sticking to specific experimental conditions, Re , Sr , and L_R are varied arbitrarily without considering whether or not a real bubble would remain approximately spherical in a given fluid under such conditions. In all cases, the numerical data are used to derive semi-empirical models valid either in the low-to-moderate or moderate-to-large Re -range. Then these models are combined to propose empirical fits valid at arbitrary Reynolds number.

4.1 Characteristics of the flow field and fundamental mechanisms

4.1.1 Velocity field

Figure 4.1 (a) shows the computed profiles of the streamwise velocity disturbance along the line ($y = 0, z = 0$) perpendicular to the wall (x -axis) when the bubble translates in a stagnant fluid, for different separation distances and Reynolds numbers ranging from 0.1 to 500. Note that U_{rel} is negative if the bubble rises towards positive z , so that negative (resp. positive) fluid velocities normalized by U_{rel} in this figure correspond to an upward (resp. downward) fluid motion with respect to the bubble. At high Reynolds number ($Re = 500$) the disturbance decreases rapidly as the distance to the bubble increases. In the gap $-L_R < 2x/d \leq -1$, this decrease results in a pressure gradient directed towards the bubble, hence a transverse force toward the wall, in line with the mechanism illustrated in Figure 1.2 (a). Due to the L_R^{-4} -decay of the wall-induced pressure asymmetry (the footprint of which directly appears in (2.30)), wall effects are almost negligible for $L_R = 4$ but are well visible for $L_R = 2$. Compared to the former case, the disturbance is larger in the gap in the latter one, except within the thin boundary layer adjacent to the wall, in which it vanishes rapidly to satisfy the no-slip condition. When the Reynolds number decreases, so does the magnitude of the disturbance close to the bubble, owing to the growing influence of the boundary layer that develops at its surface (compare the profiles found for $Re = 500$ and 100). This boundary layer is totally distinct from the one that develops at the wall, being a direct consequence of the shear-free condition at a curved interface (Batchelor, 1967). At $Re = 10$, the disturbance changes sign close to the bubble, within a layer whose thickness is of the order of the bubble radius. At small Reynolds number ($Re = 0.1$) it is negative everywhere along the line ($y = 0, z = 0$), i.e. directed along the direction of the bubble rise. The wall proximity significantly decreases the disturbance in the gap, as may be seen by comparing its magnitude on the left and right halves of the red and green lines at a given distance from the bubble center.

The influence of the shear is illustrated in Figure 4.1 (b), based on the results obtained with two opposite shear rates, $Sr = \pm 0.5$, for a separation distance $L_R = 4$. At high enough Reynolds number ($Re = 500$ or 100), the presence of a positive (resp. negative) shear, corresponding to a configuration where the bubble lags (resp. leads) the fluid, increases (resp. decreases) the magnitude of the disturbance in the gap, while it decreases (resp. increases) it on the opposite side. At moderate Reynolds number ($Re = 10$), this behavior subsists outside the boundary layer surrounding the bubble, within which only a tiny influence of Sr can be observed. In contrast, effects of the shear

are detected only close the bubble when the Reynolds number is low ($Re = 0.1$). There, a positive (resp. negative) shear decreases (resp. increases) the magnitude of the disturbance in the gap, while it increases (resp. decreases) it on the opposite side.

Figure 4.1. Distribution of the streamwise disturbance velocity $(\mathbf{u} - \mathbf{u}_\infty) \cdot \mathbf{e}_z / U_{\text{rel}}$ along the line ($y = 0, z = 0$). (a) Stagnant fluid ($Sr = 0$) for different separation distances; (b) Linear shear flow for $L_R = 4$. The wall stands at position $2x/d = -2$ (resp. -4) for $L_R = 2$ (resp. 4).

4.1.2 Vorticity field

Some aspects of these variations, and complementary features of the bubble-wall interaction, may be better understood by examining the distribution of the y -component of the vorticity disturbance in the symmetry plane $y = 0$. This distribution is displayed in Figure 4.2 for the specific separation $L_R = 2$. Vorticity is generated both at the bubble surface (due to the shear-free condition) and at the wall (due to the no-slip condition). In what follows, the contributions provided by these two distinct boundaries are referred to as surface vorticity and wall vorticity, respectively. The surface vorticity diffuses around the bubble and is advected downstream in the wake. When the fluid is at rest at infinity, the vorticity distribution in the high-Reynolds-number regime ($Re = 500$, Figure 4.2 (k)), is almost symmetric with respect to the plane $x = 0$. Negative vorticity (see the sign convention in the caption of Figure 4.2) is generated at the wall, owing to the weakening of the disturbance by the no-slip condition. However, in the high- Re regime, the wall shear layer is too thin to affect the distribution of the surface vorticity, the iso-contours of which would be virtually unchanged, when the bubble rising in an unbounded expanse of fluid. Because of this almost symmetrical vorticity

distribution, it may be inferred that the asymmetry of the disturbance velocity observed in Figure 4.1 (a) is mostly due to the irrotational mechanism illustrated in Figure 1.2 (a). When the Reynolds

Figure 4.2. Iso-contours of the normalized vorticity disturbance $d/(2U_{\text{rel}}) (\boldsymbol{\omega} - \boldsymbol{\omega}_{\infty}) \cdot \mathbf{e}_y$ in the symmetry plane $y = 0$ at $L_R = 2$. Left column: $Sr = -0.5$ ($U_{\text{rel}} < 0$); central column: $Sr = 0$ ($U_{\text{rel}} > 0$); right column: $Sr = 0.5$ ($U_{\text{rel}} > 0$). The wall is at the bottom of each panel. The relative flow with respect to the bubble is from left to right, i.e. in the z - (resp. $-z$)-direction for $Sr = 0.5$ (resp. $Sr = 0$ and -0.5).

number decreases, the thickness of the two boundary layers increases ($Re = 100$, Figure 4.2 (h)). Then they start to interact, making the asymmetry between the surface vorticity iso-contours in the gap ($x < 0$) and those on the opposite side of the bubble ($x > 0$) more prominent ($Re = 10$, Figure 4.2 (e)). At low Reynolds number ($Re = 0.1$, Figure 4.2 (b)), the region containing positive vorticity originating at the bubble surface and that containing negative wall vorticity interpenetrate each other, making the resulting vorticity magnitude in the gap weaker than on the opposite side, especially around the mid-plane $z = 0$. This asymmetry is responsible for the drag enhancement described by the contribution ΔC_{Du}^{W-in} in (2.17a). In contrast it is not directly responsible for the transverse force on the bubble, owing to the reversibility of the flow in the Stokes region of the disturbance. The crucial process responsible for this force component is the gradual slowing down of the fluid displaced along the wall by the bubble translation as the downstream distance increases. This slowing down corresponding to a negative $\partial_z u_z$ near the wall, continuity implies the generation of a transverse flow with a positive $\partial_x u_x$. As $u_x = 0$ at the wall, this tiny transverse flow is directed away from the wall, yielding a pressure decrease as x increases. At downstream distances larger than the Oseen length L_u (here $L_u \approx 10d$), this process is no longer reversible, yielding a repulsive net transverse force on the bubble.

Figure 4.3. Iso-contours of the normalized stream-wise vorticity $d/(2U_{rel}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the cross-sectional plane $z = d$ in an unbounded linear shear flow with $Sr = 0.5$. (a) $Re = 100$; (b) $Re = 500$. The main flow is going inwards, along the z -axis.

The interaction between a uniformly sheared flow in an unbounded fluid and a three-dimensional bluff body is well understood in the inviscid limit (e.g. Magnaudet and Eames (2000) and references therein). A key result of this interaction is the tilting of the upstream vorticity, $\boldsymbol{\omega}_\infty \cdot \mathbf{e}_y = -\gamma$, by the transverse gradients of the streamwise velocity, $\partial_y u_z$, resulting from the flow around the body. This tilting mechanism yields the generation of a nonzero streamwise (or trailing) vorticity component in the wake, concentrated within the two threads of a horseshoe vortex. Figure 4.3 shows how the streamwise vorticity ω_z is distributed within a cross-sectional (x, y) plane located in the near wake of the bubble. Since $\boldsymbol{\omega}_\infty \cdot \mathbf{e}_y < 0$ and $U_{rel} > 0$, the resulting ω_z is positive (resp. negative) for $y < 0$ (resp. $y > 0$) if Sr is positive; the sign of ω_z in each thread of the vortex

reverses if Sr is negative. Consequently, the fluid located in between the two threads is entrained downwards (resp. upwards) if $Sr > 0$ (resp. $Sr < 0$), while the fluid located outside the double-threaded wake is entrained in the opposite direction. This is the classical mechanism responsible for the inviscid lift force on a three-dimensional body, illustrated in Figure 1.2 (b), which yields the result (2.13b) for a sphere (Auton, 1987). The footprint of this mechanism may be found in Figure 4.2 (j) and (l), where it is seen that the spanwise vorticity generated at the bubble surface is advected asymmetrically with respect to the plane $x = 0$. Indeed, at such large Reynolds number ($Re = 500$), the aforementioned downward (resp. upward) flow generated in the mid-plane $y = 0$ by the double-threaded wake bends the iso-contours of the spanwise vorticity in the wake towards the $x < 0$ (resp. $x > 0$) direction when the bubble lags (resp. leads) the fluid. Although this asymmetry arises in the wall vicinity in the present case, the wall plays no role in the underlying process.

Figure 4.4. Iso-contours of the normalized stream-wise vorticity $d/(2|U_{\text{rel}}|) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the equatorial plane $z = 0$ in a wall-bounded linear shear flow, with the bubble standing a distance $L_R = 1.5$ from the wall. The main flow is going inwards, along the z (resp. $-z$)-direction for $Sr = 0.5$ (resp. $Sr \leq 0$).

Figure 4.4 reveals the spatial structure of the streamwise vorticity distribution in the presence of a nearby wall. Close to the bubble, the two threads of the horseshoe vortex are already visible in the selected diametrical plane, and the sign of ω_z within each of them reverses with the sign of Sr as expected. When $Sr = 0$, two thin threads with significant values of ω_z develop close to the lower half of the bubble surface. This is because the fluid velocity u_z increases with the distance from the wall within the wall boundary layer, so that the lower part of the bubble is still submitted to a nonzero shear ($\partial_x u_z \neq 0$), even though there is no shear in the upstream flow. The larger the Reynolds number, the thinner the wall boundary layer, which explains why the two threads are much thinner and the magnitude of ω_z within each of them is significantly weaker when $Re = 500$. This mechanism subsists when $Sr \neq 0$, and then combines with the tilting mechanism associated with the outer shear. When Sr is positive, they cooperated, yielding a constant sign of ω_z on each side of the bubble. In contrast, they induce opposite signs of ω_z when Sr is negative. This is visible in Figure 4.4 (a), where a thin near-surface layer with $\omega_z < 0$ (resp. > 0) is encapsulated within a

thicker layer of positive (resp. negative) ω_z in the half-plane $y > 0$ (resp. $y < 0$). Clearly the inner layer results from the positive near-wall shear, while the outer layer is due to the negative upstream shear. A salient feature in Figure 4.4 is the presence of two counter-rotating ‘pancake’ streamwise vortices within the wall boundary layer. These structures merely result from the spanwise displacement of near-wall fluid particles as the bubble moves parallel to the wall. Indeed, whatever the sign of Sr , fluid particles standing in between the bubble and the wall are displaced towards positive (resp. negative) y -positions in the half-plane $y > 0$ (resp. $y < 0$), implying positive (resp. negative) spanwise local velocities. Owing to the no-slip condition, $u_y = 0$ at the wall, so that $\partial_x u_y$ is positive (resp. negative) near the wall in the half-plane $y > 0$ (resp. $y < 0$), which yields $\omega_z > 0$ (resp. < 0). Clearly this process is independent from the outer shear, as the constant sign of ω_z in each half-plane irrespective of Sr confirms. Since the horseshoe vortex past the bubble results from a Sr -dependent mechanism while the pair of ‘pancake’ vortices at the wall is driven by a Sr -independent process, ω_z keeps a constant sign within each half-plane for $Sr < 0$, while it changes sign in between the two types of structures for $Sr \geq 0$.

The generation of the surface vorticity is also modified by the shear. Indeed, for the shear-free condition to be satisfied at the bubble surface in the presence of an outer shear, a shear-flow type correction has to take place within the boundary layer. Compared to the un-sheared case, this correction yields an additional positive vorticity component therein when the bubble lags the fluid. Hence this vorticity correction cooperates with the primary positive vorticity in the part of the bubble boundary layer corresponding to $x < 0$, whereas it mitigates the primary negative vorticity on the opposite side. Consequently, the intensity of the overall vorticity round the bubble is increased for $x < 0$ and decreased for $x > 0$, as Figure 4.2 (l) indicates, and the same happens to the disturbance flow close to the bubble surface (see e.g. the profile corresponding to $Re = 100$ in Figure 4.1 (b)). These conclusions reverse when the bubble leads the fluid, so that the surface vorticity and streamwise velocity disturbance are lowered for $x < 0$ and enhanced for $x > 0$, in line with the distributions displayed in Figure 4.2 (j) and Figure 4.1 (b). Again, the wall plays little role in these mechanisms as far as the Reynolds number is large. More specifically, for $Re = 500$, Figure 4.2 (j) indicates that the flow region in which the vorticity originating from the bubble surface is significantly disconnected from the wall shear layer when Sr is negative, while there may be some weak connection between the two regions when Sr is positive (Figure 4.2 (l)), owing to the bending of the wake toward the wall.

As the Reynolds number decreases, viscous effects tend to attenuate the efficiency of the inviscid vortex tilting mechanism described above. This is why the bending of the surface vorticity distribution in the wake becomes weaker at $Re = 100$ (Figure 4.2 (g) and (i)). At the same time, the boundary layers thicken, so that the flow near the lower edge of the vertical region in the near wake starts to interact significantly with the wall shear layer, just as it does in the un-sheared case. This interaction strengthens as the Reynolds number decreases ($Re = 10$ and 0.1), making the situation combine effects of the wall-induced asymmetry with those of the shear-induced asymmetry within the wake itself. As the wall-induced and shear-induced lift mechanisms both result in a force directed toward $x > 0$ if Sr is positive (Figure 1.1 (c)), they act together to yield an enhanced repulsive force in this case, as reflected in (2.17b). Conversely, they produce antagonistic effects if Sr is negative (Figure 1.1 (d)), which yields a reduced transverse force. Regarding viscous effects, the mechanisms described above indicate that the wall interaction tends to reduce the spanwise vorticity in the gap, while the excess surface vorticity resulting from the presence of the shear tends to enhance (resp. reduce) it when Sr is positive (resp. negative). The two effects just do the opposite

on the free side of the bubble. For this reason, the top-bottom asymmetry of the ω_y -vorticity distribution existing in the un-sheared case is lowered (enhanced) by the shear if the bubble lags (resp. leads) the fluid. This is why the drag is decreased (resp. increased) by the shear for positive (resp. negative) Sr , as (2.17a) confirms.

4.2 Hydrodynamic forces on the bubble: fluid at rest at infinity

4.2.1 Drag

The validity of the low- Re approximation for the wall-induced drag correction in the low-but-finite Re regime was confirmed during the validation of the numerical approach (see (3.1a) and Figure 3.2 (a) in section 3.2.1). Hence the primary focus here is on the behavior of the drag coefficient $C_{Du}^W(Re, L_R)$ at moderate-to-high Re . To appreciate the modification of the drag force due to the wall influence, C_{Du}^W is compared to its counterpart in an unbounded flow, C_{D0}^U . The drag change ratio $\Delta C_{Du}^W = (C_{Du}^W - C_{D0}^U)/C_{D0}^U$ is plotted in Figure 4.5.

Figure 4.5. Wall-induced drag correction ΔC_{Du}^W for a bubble translating parallel to a wall in a fluid at rest. (a): high- Re regime; (b): entire Re -range investigated numerically. Symbols: numerical data; solid lines: high- Re prediction (4.1); dash-dotted lines: low- Re prediction (3.1a); dashed lines: low-to-moderate- Re prediction (4.3); dotted lines: composite fit (4.4).

This figure reveals that, beyond $Re = 100$, there is a clear increase, with both the Reynolds number and the inverse of the separation distance, L_R^{-1} , of the relative influence of the wall on the drag. In that range of Reynolds number, the relative drag increase becomes significant only for $L_R \lesssim 2$. Theoretical prediction for ΔC_{Du}^W in the limit of very large Reynolds number is still unavailable. In contrast, the case of a spherical bubble rising along the axis of a circular pipe was considered in Sherwood (2001), where it was established asymptotically (for both $L_R \gg 1$ and $Re \gg 1$) that $\Delta C_{Du}^W \approx 1.6L_R^{-3} + 0.2Re^{1/2}L_R^{-9/2}$. The L_R^{-3} -drag increase is a confinement effect, the vanishing of the fluid normal velocity at the pipe wall enhancing the local strain in the flow disturbance throughout the fluid. The $Re^{1/2}L_R^{-9/2}$ -increase results from the wall boundary layer within which the dominant velocity gradient varies as $Re^{1/2}$. Due to the sharp decrease of the latter contribution with L_R , its influence is significant for large enough Re only. Conversely, it eventually becomes dominant whatever L_R provided Re is large enough. Although the geometrical configuration

considered here differs from that in Sherwood (2001), the physical mechanisms responsible for the drag increase remain qualitatively unchanged. For this reason, an empirical expression for ΔC_{Du}^W in the above form, adjusting both the pre-factors and the exponents to the numerical data was proposed. Fitting the numerical results independently in the range $20 \leq Re \leq 50$ (resp. $Re > 50$) to determine the Re -independent (resp. dependent) contribution, yielded

$$\Delta C_{Du}^W(Re \gg 1) \approx 0.47L_R^{-4} + 0.0055L_R^{-6}Re^{3/4}. \quad (4.1)$$

Figure 4.5 (a) shows that (4.1) compares well with the DNS data for $Re \gtrsim 50$. The surprising feature in (4.1) is that the separation distance and Reynolds number appear with exponents significantly different from those found in Sherwood (2001). Extensive tests were carried out to make sure that these findings are not due to an insufficient grid resolution. In particular the number of nodes N_W between the bubble and the wall was increased up to 40 (resp. 60) for $L_R = 1.5$ (resp. 2), and the number of nodes N_η in the radial direction up to 108 without observing any significant change in the drag and lift forces. This confirms that the results displayed in Figure 4.5 (a) are truly grid-independent. Also, since the relative drag variation induced by the wall boundary layer is still small for $L_R = 2$ and 1.5 (it only amounts to 7% for $L_R = 1.5$ and $Re = 10^3$), Additional computations were ran for $L_R = 1.25$, a shorter separation distance at which this effect is significantly larger. As the brown line in Figure 4.5 (a) reveals, (4.1) still closely follows the corresponding data, confirming that this fit is robust whatever L_R within the range of Reynolds number explored. This does not imply that it is asymptotically correct in the limit $Re \rightarrow \infty$, and there are indications that it is not. Consider the situation in which the wall is replaced by a symmetry plane, which corresponds to the case of a pair of identical bubbles rising side by side. No boundary layer exists along the symmetry plane, and the drag modification in the limit $Re \rightarrow \infty$ is then just a consequence of the non-penetration condition across this plane. In the inviscid limit, this condition generates an $O(L_R^{-3})$ -increase in the relative velocity U_{rel} , which in turn yields an $O(L_R^{-3})$ relative drag increase (Legendre et al., 2003). However, numerical data provided in Legendre et al. (2003) show that, for $L_R \lesssim 1.5$ ΔC_{Du}^W still increases with the Reynolds number up to $Re = 500$ before becoming Re -independent. Consequently the asymptotic regime in which ΔC_{Du}^W no longer depends on Re is only reached for very large Reynolds numbers. Here, as previously mentioned, the “ Re -independent” contribution to (4.1) was determined from data corresponding to Reynolds numbers of some tens because this is the range where the wall boundary layer effect is still negligibly small. However, viscous effects are still present in this Re -range, as the above example revealed. This is confirmed by Figure 4.2 (h) and Figure 4.4 (b) which show that, for $L_R \leq 2$, the vortical region round the bubble directly interacts with the wall boundary layer at such moderate Reynolds numbers. This interaction is much weaker when $Re = 500$ (Figure 4.2 (k) and Figure 4.4 (e)), suggesting that the ultimate behavior corresponding to Figure 4.4 is only reached for $Re \gtrsim 500$.

Figure 4.5 (b) displays the relative drag increase throughout the range of Reynolds number explored in the simulations. Examination of the low-to-moderate- Re range in Figure 4.5 (b) indicates that (3.1a) under-predicts the drag increase at small separations as soon as the Reynolds number is beyond the range 0.2-0.5 (see also Figure 3.2 (a)). Following Takemura et al. (2002), this prediction may be improved by noting that the drag increase at low-to-moderate- Re is proportional to the square of the maximum vorticity at the bubble surface. Variations of this quantity with the Reynolds number are empirically expressed by the fitting function $b(Re)$ in

(2.29a). However, it was found that a more accurate fit of the DNS data reported in Magnaudet et al. (1995) is provided by

$$b(Re) = 1 + \tanh(0.012Re^{0.8}) + \tanh(0.07Re^{0.8}). \quad (4.2)$$

Making use of (4.2), (3.1a) was then extended toward moderate Reynolds numbers by expressing the drag increase in the form

$$\Delta C_{Du}^W(Re = O(1)) \approx f_D' b^2(Re) \Delta C_{Du}^{W-in}, \quad (4.3)$$

with ΔC_{Du}^{W-in} and f_D' as given in (2.17a) and (2.27a), respectively. As Figure 4.5 (b) shows, this expression allows an accurate prediction of ΔC_{Du}^W up to $Re \approx 2$. Obviously neither (4.3) nor (4.1) is accurate in the intermediate range $2 \lesssim Re \lesssim 10$. Nevertheless, an empirical fit may be obtained by combining the above two models in the form

$$\begin{aligned} \Delta C_{Du}^W(Re) &\approx \Delta C_{Du}^W(Re = O(1)) + c_{Du\infty} \Delta C_{Du}^W(Re \gg 1), \text{ with} \\ c_{Du\infty} &= 1 - e^{-0.07Re}. \end{aligned} \quad (4.4a,b)$$

As Figure 4.5 (b) shows, this composite expression correctly reproduces the computed drag variations throughout the entire range of Reynolds number.

4.2.2 Lift

Similar to wall-induced drag variations, the validity of the solution based on the combination of (2.17b) and (2.27b) for the transverse (lift) force coefficient in the low-but-finite Re regime was confirmed during the validation of the numerical approach (see (3.1b) and Figure 3.2 (b) in section 3.2.1). For this reason, the behavior of $C_{Lu}^W(Re, L_R)$ in the high- Re range $10^2 \leq Re \leq 10^3$ is discussed first, before examining the variations of the transverse force at arbitrary Reynolds number. Figure 4.6 (a) compares the numerical data obtained for C_{Lu}^W in that range with the irrotational prediction (2.30). The agreement is excellent as soon as the Reynolds number is large enough ($Re \gtrsim 300$) and the separation distance is small enough ($L_R \lesssim 4$). The viscous effect associated with the asymmetry of the boundary layer surrounding the bubble, which yields the correction (2.31), becomes significant at smaller Re , where it lowers the negative (i.e. attractive) transverse force. Numerical results also confirm the sharp decay of the transverse force when L_R increases, as predicted by (2.30), which makes the attractive effect negligibly small for dimensionless separations larger than a few units.

Figure 4.6 (b) shows how $C_{Lu}^W(Re, L_R)$ varies with the Reynolds number throughout the range $10^{-1} \leq Re \leq 10^3$. In line with experiments reported in Takemura and Magnaudet (2003), the transverse force is found to switch from positive (i.e. repulsive) to negative (i.e. attractive) in the range $40 \leq Re \leq 60$, depending on L_R ; the smaller L_R the lower the critical Reynolds number at which C_{Lu}^W changes sign. At low Reynolds number, numerical data indicate that $C_{Lu}^W \rightarrow 1/2$ for $L_R \gtrsim 4$, in agreement with the asymptotic prediction (2.17b). Higher-order terms in (2.17b), which represent effects of the bubble finite size, tend to lower the transverse force when the bubble gets very close to the wall; numerical results confirm this trend (see especially the data set corresponding to $L_R = 1.5$). In Takemura and Magnaudet (2003), the semi-empirical expression

(2.28) was proposed to estimate the transverse force for moderate separations and Reynolds numbers, typically $L_R \gtrsim 2$ and $Re = O(10)$. This expression accounts for the variations of the vorticity magnitude at the bubble surface as a function of Re through the empirical function $b(Re)$ given in (2.29a). In contrast, it does not account for the aforementioned finite-size effects which become important for small separations, as it makes use of the prediction for $C_{Lu}^{W-out}(Re \ll 1)$ resulting from (2.24b), in which the bubble is treated as a point-force. To improve this aspect, $C_{Lu}^{W-out}(Re \ll 1)$ in (2.28) is heuristically replaced by $C_{Lu}^W(Re \ll 1) \approx f'_L C_{Lu}^{W-in}$ as given in (3.1b), so that (2.28) becomes

$$C_{Lu}^W(Re = O(1 - 10)) \approx b^2(L_R/3)^g f'_L C_{Lu}^{W-in}, \quad (4.5)$$

with C_{Lu}^{W-in} , f'_L , b , and g , as given in (2.17b), (2.27b), (4.2), and (2.29b), respectively.

Figure 4.6. Lift coefficient on a bubble translating parallel to a wall in a fluid at rest. (a) High-Reynolds-number range $10^2 \leq Re \leq 10^3$. Comparison of numerical results (symbols) with the potential flow prediction (2.30) (solid lines), and the high- Re prediction (2.31) including the Re^{-1} vortical contribution (dotted lines). (b) Complete Re -range $10^{-1} \leq Re \leq 10^3$. Comparison of numerical results (symbols) with the low-to-moderate Re semi-empirical model (4.5) (dashed lines), the high- Re prediction (2.31) (dotted lines), and the composite model (solid lines).

The prediction of (4.5) (dashed lines in Figure 4.6 (b)) is found to agree well with the numerical results up to $Re \approx 10$. For practical purpose, an empirical composite model similar in essence to (2.32), capable of fitting the variations of C_{Lu}^W throughout the explored range of Reynolds number was proposed. In (2.32), the high- Re viscous contribution which makes $C_{Lu}^W(Re \gg 1)$ differ from $C_{Lu}^W(Re \rightarrow \infty)$ (see (2.30) and (2.31)) was not considered, since the experiments reported in Takemura and Magnaudet (2003) were all run at Reynolds numbers less than 100. However, as Figure 4.6 (a) shows, this viscous effect is significant for $Re = O(10^2)$. It was found that the simplest way in which the various contributions may be combined while respecting the proper asymptotic behaviors and having a limited impact out of their own range of validity reads

$$C_{Lu}^W \approx C_{Lu}^W(Re = O(1 - 10)) + c_{T1} [C_{Lu}^W(Re \rightarrow \infty) + c_{T2} Re^{-1} L_R^{-4}], \quad \text{with} \quad (4.6a,b,c)$$

$$c_{T1}(Re) = 1 - e^{-0.22Re^{0.6}}, \quad c_{T2}(Re) = 15 \tanh(0.01Re).$$

As shown by the solid lines in Figure 4.6 (b), this empirical fit agrees well with the numerical data throughout the explored range of parameters.

To further test the capabilities of the above composite model, Figure 4.7 compares its predictions with available numerical and experimental data taken from other sources. These data were obtained by considering bubbles with different diameters and changing the separation distance for each of them. This is why each series plotted in the figure corresponds to a fixed Reynolds number and varying $L_u = (Re/2)L_R$. As expected, low- Re data approach the outer solution (2.27b) as L_u becomes of $O(1)$ (consider especially the series corresponding to $Re = 0.6$). The transverse force decays more slowly than predicted by this solution when the Reynolds number is of $O(1-10)$. As discussed in Takemura and Magnaudet (2003), this is primarily an effect of the finite- Re increase of the vorticity produced at the bubble surface, which is reflected in the above fitting function $b(Re)$. Last, the transverse force changes sign for a critical Reynolds number of some tens, as it becomes dominated by the irrotational mechanism when viscous effects are small enough. The composite model (4.6), which improves over the original model (2.32) proposed in Takemura and Magnaudet (2003), is seen to properly capture these successive features.

Figure 4.7. Transverse force on a bubble translating parallel to a wall in a fluid at rest in the range $0.6 \leq Re \leq 300$ according to various sources. Solid line: composite model (4.6) involving the low-to-moderate- Re model (4.5) and (4.2); dashed line: low-but-finite- Re outer solution (2.27b); $\square$: experimental data from Takemura et al. (2002) and Takemura and Magnaudet (2003); *: numerical data from Sugioka and Tsukada (2015).

4.3 Hydrodynamic forces on the bubble: linear shear flow

We now perform the same type of analysis in the more complex situation where the effects of a constant shear combine with those of the wall.

4.3.1 Drag

Results for the drag change ratio $\Delta C_D^W = (\Delta C_D^W - \Delta C_{D0}^U) / \Delta C_{D0}^U$ obtained in the low-but-finite Reynolds number regime, $0.1 \leq Re \leq 2$, are plotted in Figure 4.8 for different shear rates and separation distances. Clearly, the shear-induced drag modification is negligibly small compared with that due to the wall effect when L_R exceeds a few units. For the smallest two separations, the shear is found to increase (resp. reduce) the drag when the bubble leads (resp. lags) the fluid, in line with the qualitative discussion provided at the end of section 4.1. The solution (2.17a) assuming that the wall stands in the inner region of the disturbance shows good agreement with

numerical results at $Re = 0.1$ but, not surprisingly, overestimates them at higher Reynolds number. No explicit counterpart of the theoretical solution (2.24a) exists when the shear is nonzero and the wall stands in the outer region of the disturbance. However the relative influence of the shear is always small under the conditions considered here (at $Re = 0.1$, the relative variation of ΔC_D^W is approximately 8% for $Sr = \pm 0.5$ compared to the un-sheared case $Sr = 0$). For this reason, the arguments employed in the un-sheared configuration to derive (3.1a) and (4.3) is merely duplicated empirically, in order to obtain an estimate of the drag variation valid up to Reynolds numbers of $O(1)$. This yields

$$\Delta C_D^W(Re = O(1)) \approx f_D'(L_u) b^2(Re) \Delta C_D^{W-in}, \quad (4.7)$$

with ΔC_D^{W-in} , $f_D'(L_u)$, and b as given in (2.17a), (2.27a) and (4.2), respectively. As the solid lines in Figure 4.8 show, the corresponding predictions properly follow the numerical data up to $Re \approx 2$.

Figure 4.8. Relative near-wall drag increase ΔC_D^W for a bubble translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. Symbols: numerical results for $Sr > 0$ ($\square$), and $Sr < 0$ ($\circ$). Dashed lines: asymptotic solution (2.27a) corresponding to conditions $L_u \gg 1, L_\omega \gg 1$; solid lines: semi-empirical model (4.7). Thick (resp. thin) lines correspond to positive (resp. negative) Sr .

To analyze results obtained in the moderate-to-high- Re range, the unbounded configuration in which the generation of the lift force is dominated by the inviscid vortex tilting mechanism described in section 4.1 is considered first. Figure 4.9 shows how the relative drag change $\Delta C_{D\omega}^U(Sr, Re) = (C_{D\omega}^U(Sr, Re) - C_{D0}^U(Re)) / C_{D0}^U(Re)$ varies with both the Reynolds number and the dimensionless shear rate. Symmetry considerations imply that $\Delta C_{D\omega}^U(Sr, Re)$ cannot depend on the sign of Sr , which numerical results confirm. If the carrying flow were irrotational, one would expect the relative drag increase to be proportional to Sr^2 and independent of Re in the limit $Re \rightarrow \infty$, since boundary layer effects are negligibly small in this limit. This may be confirmed by evaluating theoretically the drag experienced by a spherical bubble translating in a pure axisymmetric straining flow of the form $\mathbf{u}_\infty = -\frac{\gamma}{2}(x\mathbf{e}_x + y\mathbf{e}_y) + (\gamma z - V)\mathbf{e}_z$. As there is no

wake in that case in the limit $Re \rightarrow \infty$, the work produced by the drag force exactly balances the dissipation in the entire flow (Batchelor, 1967). Evaluating this dissipation yields $\Delta C_{D\omega}^U(Re \rightarrow \infty, Sr) = \frac{2}{9}Sr^2$. The situation is drastically different in the linear shear flow of interest here, since the disturbance is not irrotational and a wake made of the two counter-rotating trailing vortices discussed in section 4.1 extends to infinity downstream of the bubble. This configuration is similar to that of a wing of finite span, on which the trailing vortices are known to produce a lift-induced drag force proportional to the square of the lift force (Batchelor, 1967). This additional drag is a second-order effect due to the interaction between the upstream vorticity and the vortex-induced velocity disturbance induced by the trailing vortices, here proportional to γd . Consequently, it is proportional to $\rho d^4 \gamma^2$, yielding an increase in the drag force proportional to $Sr^2 \rho d^2 U_{rel}^2$, hence a relative drag variation $\Delta C_{D\omega}^U$ proportional to $Sr^2 Re$ since $C_{D0}^U \propto Re^{-1}$ in this regime. Based on this analogy, a fit of the results displayed in Figure 4.9 was sought in the form $\Delta C_{D\omega}^U \propto |Sr|^m Re^n$, which results in

$$\Delta C_{D\omega}^U(Re \gg 1) \approx 2 \times 10^{-3} |Sr|^{1.9} Re, \quad (4.8)$$

which is seen to properly capture the trends revealed by numerical results. The fact that the exponents in (4.8) are slightly lower than predicted in the inviscid lift-induced drag scenario is presumably a finite-Reynolds number effect that subsists in the limited Re -range considered in present simulations.

Figure 4.9. Relative drag variation $\Delta C_{D\omega}^U$ for a bubble translating at moderate-to-high Re in an unbounded shear flow, with reference to the drag in a uniform stream. (a) Influence of the Reynolds number; (b) influence of the shear rate. In (a): numerical results for $Sr > 0$ ($\square$), and $Sr < 0$ ($\circ$). In (b) numerical results for $Re = 500$ ($\square$), and $Re = 300$ ($\circ$). Solid line: prediction of (4.8); dashed line: prediction of (2.13a) taken from Legendre and Magnaudet (1998); $\times$: numerical results from Legendre and Magnaudet (1998).

Now it is necessary to evaluate how much the above results are altered when the bubble gets close to the wall. Based on Figure 4.2 (j) and (l), one expects this alteration to be fairly weak, since the wall boundary layer is thin in the considered Re -range, and to depend on the sign of Sr , owing to the bending of the bubble wake towards (resp. away from) the wall for positive (resp. negative) Sr . To clarify the magnitude of the wall-shear interaction, the difference between the actual drag variation in the near-wall configuration, $\Delta C_D^W(Re, Sr, L_R)$, and the sum $\Delta C_{Du}^W(Re, L_R) +$

$\Delta C_{D\omega}^U(Re, Sr)$ of the two contributions discussed above was computed. This difference, say $\Delta C_{D\omega}^{W-U}$, is displayed in Figure 4.10. The results show that it is negligibly small whatever the Reynolds number and for both shear rates for $L_R \geq 2$. In addition to $L_R = 1.5$, computations for $L_R = 1.25$ were ran in order to determine the sharp decrease of $\Delta C_{D\omega}^{W-U}(Re \gg 1)$ as the separation increases. Figure 4.10 indicates that $\Delta C_{D\omega}^{W-U}(Re \gg 1)$ grows linearly with Sr and is positive (resp. negative) when the bubble lags (resp. leads) the fluid. This was expected on the basis of Figure 4.2 (j) and (l), since the interaction between the wake and the wall is stronger when Sr is positive, due to the bending of the wake towards the wall. Based on DNS data, the variation of $\Delta C_{D\omega}^{W-U}(Re \gg 1)$ with L_R and Re are found to be correctly fitted in the form

$$\Delta C_{D\omega}^{W-U}(Re \gg 1) \approx 0.05 L_R^{-7/2} Sr Re^{1/3}. \quad (4.9)$$

Again, the above fit is grounded on a limited set of data obtained in the range $50 \leq Re \leq 10^3$. Hence it is presumably not relevant in the limit $Re \rightarrow \infty$. Nevertheless, up to $Re \approx 10^3$, the above decomposition allows to model the entire wall-induced drag correction in the moderate-to-high- Re regime in the form

$$\Delta C_D^W(Re \gg 1) \approx \Delta C_{Du}^W(Re \gg 1) + \Delta C_{D\omega}^U(Re \gg 1) + \Delta C_{D\omega}^{W-U}(Re \gg 1), \quad (4.10)$$

where the three contributions in the right-hand side are provided by (4.1), (4.8) and (4.9), respectively.

Figure 4.10. Difference in the high- Re range between the relative drag variation in the presence of wall and shear, ΔC_D^W , and the sum $\Delta C_{Du}^W + \Delta C_{D\omega}^U$ of the relative drag variation in the presence of the wall for $Sr = 0$, ΔC_{Du}^W , and the relative drag variation in an unbounded shear flow, $\Delta C_{D\omega}^U$.

Finally, Figure 4.11 presents all numerical results obtained throughout the range $10^{-1} \leq Re \leq 10^3$ together with the corresponding predictions based on the semi-empirical expressions established above. Comparing the two panels, which only differ by the magnitude of Sr , reveals that the shear has only a secondary influence on the drag increase up to Reynolds numbers of $O(10^2)$. In that range, shear-induced drag variations do not exceed 10% of the total drag increase for $|Sr| = 0.5$. This is in contrast with the behavior observed at higher Reynolds number, where $\Delta C_D^W(Re = 500)$

is found to be twice as large for $Sr = \pm 0.5$ than for $Sr = \pm 0.2$, owing to the large influence of the lift-induced-drag contribution (4.8). Clearly, the sign of Sr has only a small influence on ΔC_D^W at moderate-to-large Re , as the shear is seen to increase the drag in all cases. In other words the sign-dependent correction $\Delta C_{D\omega}^{W-U}$ resulting from the wall-shear interaction is always small compared to the lift-induced-drag contribution $\Delta C_{Du}^W(Re \gg 1)$. Interestingly, comparing ΔC_D^W in two configurations differing only by the sign of Sr , it turns out that the drag increase is slightly larger at low Reynolds number when the bubble leads the fluid ($Sr < 0$), in agreement with (2.17a). However, the reverse holds at large (and even moderate) Reynolds number, although this is only a secondary effect in the high- Re regime, as discussed above. In a way similar to (4.6), an empirical expression combining linearly $\Delta C_{Du}^W(Re = O(1))$ and $\Delta C_D^W(Re \gg 1)$, as respectively given by (4.7) and (4.10), may be designed to improve the estimate of the drag increase in the intermediate range $1 \leq Re \leq 10^2$. As the dash-dotted lines in Figure 4.11 show, the composite expression form

$$\Delta C_D^W(Re) \approx \Delta C_D^W(Re = O(1)) + c_{D\omega\infty} \Delta C_D^W(Re \gg 1), \text{ with} \quad (4.11a,b)$$

$$c_{D\omega\infty} = 1 - e^{-0.07Re}.$$

correctly fits the DNS data throughout the entire range of Reynolds number.

Figure 4.11. Relative near-wall drag increase $\Delta C_D^W(Re, L_R, Sr)$ for a bubble translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. $\square$ and $\circ$: numerical data for $Sr > 0$ and $Sr < 0$, respectively. Thick (resp. thin) solid lines: high- Re prediction (4.11) for positive (resp. negative) Sr ; thick (resp. thin) dashed lines: low- Re prediction (4.7) for positive (resp. negative) Sr ; thick (thin) dash-dotted lines: composite expression (4.11) for positive (resp. negative) Sr .

4.3.2 Lift

The computed lift coefficient $C_L^W(Re, Sr, L_R)$ in the low-but-finite Reynolds number regime is plotted in Figure 4.12 for various normalized shear rates and separation distances. Numerical values corresponding to $L_R \leq 2$ only slightly change with increasing Re up to $Re \approx 0.5$, which provides an indication that the wall lies in the inner region of the disturbance in the corresponding (Re, L_R) -range. To properly interpret variations of C_L^W at larger Reynolds numbers and separation distances, it is important to keep in mind that, since Sr is kept constant, increasing Re makes $\varepsilon = (Sr/Re)^{1/2}$ decrease from left to right in each series. Consequently, for a given L_R , the larger Re

the smaller the shear-induced lift force. The wall-induced contribution is also a decreasing function of the Reynolds number, since it depends directly on $L_u = (Re/2)L_R$ and sharply decreases when L_u becomes of $O(1)$ or larger in the shearless case, as shown in Figure 2.7. Since the two contributions cooperate when the bubble lags the fluid, their variations as Re increases reinforce each other, making the total lift force decrease sharply as soon as the wall stands in the outer region (see e.g. the data sets corresponding to $L_R = 4$ and 8 in the top left panel of Figure 4.12). Conversely, these variations tend to compensate when the bubble leads the fluid, which mitigates the C_L^W variations (consider the same two data sets in the bottom left panel, where these variations virtually cancel each other up to $Re \approx 1$, resulting in an almost Re -independent total lift force).

Figure 4.12. Variations of the lift coefficient $C_L^W(Re, L_R, Sr)$ for a bubble translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. $\square$ (resp. $\circ$): numerical data for $Sr > 0$ (resp. $Sr < 0$). Dashed lines: asymptotic prediction (2.17b) corresponding to conditions $L_u \ll 1, L_w \ll 1$; dotted lines: fit (2.37) of the asymptotic prediction corresponding to conditions $L_u \gg 1, L_w \gg 1$; solid lines: semi-empirical model (4.12) taking into account finite-size effects.

Keeping Re and Sr constant, the influence of the separation distance is closely related to the successive behaviors of the shear-induced contribution as L_u and L_w increase. Indeed, as (2.17b) shows, this contribution grows linearly with L_R when the wall stands in the inner region. It grows more slowly when it stands in the outer region, until it reaches a constant value for large enough separations (this evolution is reflected in the h_L function involved in (2.41); see also Figures 4, 6,

and 8 in McLaughlin (1993)). Because of this gradual evolution, different behaviors of the total lift force are observed in Figure 4.12. As far as the wall stands in the inner region or close to it, variations of C_L^W with L_R are dominated by the nearly linear growth of the shear-induced contribution. Consequently, the lift force increases (resp. decreases, possibly changing sign) with increasing L_R when $Sr > 0$ (resp. < 0). This is the behavior observed for $Re \lesssim 0.5$ (resp. $\lesssim 0.8$) with $Sr = \pm 0.2$ (resp. ± 0.5). For larger Reynolds numbers, variations of the shear-induced contribution (which depends on L_R through L_u and L_ω) become weaker, so that the overall variation of the total lift force with L_R is mostly controlled by that of the wall-induced contribution (which depends on L_R through L_u). Since this contribution weakens dramatically as L_u increases, the magnitude of the total lift force decreases, irrespective of its sign. When Re , Sr and L_R (hence L_u and L_ω) are large enough, the wall-induced contribution becomes negligibly small, so that the total lift force reduces to the shear-induced contribution. In this situation, C_L^W takes opposite values when the sign of Sr is reversed while Re and L_R are kept constant. This is what happens when the three parameters in Figure 4.12 reach their maximum, i.e. $L_R = 8$, $Re = 2$, and $Sr = \pm 0.5$. Indeed, the corresponding DNS data in the right two panels indicate $C_L^W \approx \pm 0.54$, depending on the sign of Sr . Interestingly, Figure 18 of Legendre and Magnaudet (1998) indicates $C_{L\omega}^U(Re = 2, Sr = 0.5) \approx 0.56$ in an unbounded flow. Thus it can be concluded that the wall virtually no longer influences the lift force for the considered set of parameters, i.e. $L_u = 8$ and $L_\omega = 4$.

The asymptotic expression (2.17b) corresponding to situations in which the wall stands in the inner region of the disturbance (dashed lines in Figure 4.12) closely predicts the computed lift force for small enough L_R and Re , typically $L_R < 4$ and $Re \leq 0.2$ for both shear rates. Not surprisingly, the agreement deteriorates as L_R or Re increases, owing to the increasing influence of inertial effects through L_u and L_ω . Overall, the approximate fit (2.37) (along with (2.41) and (2.43) for h_L and f_L) of the asymptotic solution obtained in the case the wall stands in the outer region of the disturbance (dotted lines in Figure 4.12) properly accounts for these effects. A closer look reveals that the corresponding prediction is in good agreement with the DNS data obtained for $L_R = 8$, at least up to $Re = 1$, but increasingly deviates from the computational results as L_R decreases. This is no surprise, as (2.41) and (2.43) are based on the outer solution of McLaughlin (1993), which is valid only in the limit of large separations. Indeed, with (2.41) and (2.43), (2.17b) approaches the leading-order expression of the asymptotic solution (2.17b) in the double limit $L_u \rightarrow 0$ and $L_\omega \rightarrow 0$, but does not account for the finite-size effects which affect both the wall-induced and the shear-induced contributions. This limitation may be overcome by modifying heuristically (2.37) in a way similar to that employed to obtain (4.5) in the un-sheared case. That is, the outer solution for the wall effect may be replaced in (2.37) by the mixed expression $C_{Lu}^W(Re \ll 1) \approx f_L' C_{Lu}^{W-in}$ (see (3.1b)), and the $h_L(L_\omega, \varepsilon)$ weighting function in (2.41) may be substituted by a function $h_L(L_\omega, \varepsilon, L_R)$ incorporating finite-size effects and tending towards $h_L(L_\omega, \varepsilon)$ for large separations. Instead of (2.37)-(2.41) one then has

$$C_L^W(Re \ll 1) \approx f_L C_{Lu}^W(Re \ll 1) + h_L' C_{L\omega}^U(Re \ll 1), \text{ with} \quad (4.12a,b)$$

$$h_L'(L_\omega, \varepsilon, L_R) = 1 - e^{-\frac{11}{96}\pi^2 \frac{L_\omega}{J(\varepsilon)} \left(1 + \frac{9}{8}L_R^{-1} - \frac{1271}{3520}L_R^{-2}\right)},$$

with $f_L(L_\omega, \varepsilon)$ still given by (2.43). With these modifications, the semi-empirical model (4.12) approaches the complete asymptotic solution (2.17b) when $L_u \rightarrow 0$ and $L_\omega \rightarrow 0$ (with the exception of the Sr^2 -term, usually much smaller than the Sr -term as far as $Sr \lesssim 1$), while the initial

approximation (2.41) of the outer solution is recovered in the limit $L_R \gg 1$. Compared to (2.37)-(2.41), the predictions of (4.12) (solid lines in Figure 4.12) exhibit a significantly better agreement with numerical results when L_R and Re decrease.

Figure 4.13. (a) Effect of the shear-wall coupling on the lift force in the high Reynolds number regime. (a) Symbols: $\Delta C_L^W(Re, L_R, Sr) = C_L^W(Re, L_R, Sr) - C_{L\omega}^U(Re \gg 1) - C_{Lu}^W(Re \gg 1)$. (b) Performance of the model (4.13) estimated by the difference $\epsilon_{WS} = [C_L^W(Re, L_R, Sr) - C_L^W(Re \gg 1)] / [|C_{L\omega}^U(Re \gg 1)| + |C_{Lu}^W(Re \gg 1)|]$.

The behavior of the lift force in the high-Reynolds-number range is then examined. At large enough separations, the wake past the bubble does not interact significantly with the wall, so that the lift coefficient must approach $C_{L\omega}^U(Re \gg 1)$ as given in (2.13b). When the bubble gets close to the wall, two distinct interaction mechanisms come into play. One is due to the bubble translation, and would yield the attractive transverse force discussed in section 4.2.2 in the absence of shear. The other is due to the interaction of the shear-induced vortex structure past the bubble, especially the trailing vortices which dominate the wake, with the wall. This is similar to the ground effect known to increase the lift force on an aircraft flying very close to the ground. To quantify this second effect, the difference between the actual lift coefficient $C_L^W(Re, Sr, L_R)$ and the sum $C_{L\omega}^U(Re \gg 1) + C_{Lu}^W(Re \gg 1)$ (the latter as given in (2.31)) is plotted in Figure 4.13 (a). This figure shows that this difference, say ΔC_L^W , is small for $L_R \geq 4$ but becomes significant at smaller separations, sharply increasing as L_R reduces. As expected from the above analogy, ΔC_L^W is positive (resp. negative) for $Sr > 0$ (resp. $Sr < 0$) and is linearly proportional to Sr . Note that the sign of ΔC_L^W is in line with what may physically be expected from Figure 4.2 (j-1), given the direction in which the wake bends for positive and negative Sr , respectively. ΔC_L^W is also seen to be a slowly decreasing function of Re , an effect which may be attributed to the wall boundary layer. Based on these observations, and fitting the numerical data of Figure 4.13 (a), the total lift coefficient is modeled in the form

$$C_L^W(Re \gg 1) \approx C_{Lu}^W(Re \gg 1) + C_{L\omega}^U(Re \gg 1) + \Delta C_L^W(Re \gg 1), \text{ with} \quad (4.13a,b)$$

$$\frac{\Delta C_L^W(Re \gg 1)}{C_{Lu}^U(Re \gg 1)} = I_{WS} \approx a_G L_R^{-7/2} (1 + b_G Re^{-1/2}),$$

where $a_G \approx 0.23$ and $b_G \approx 13$. The performance of this model is assessed in Figure 4.13 (b) by computing the difference $C_L^W(Re, Sr, L_R) - C_L^W(Re \gg 1)$ between the numerical value of the lift

coefficient and the estimate provided by the model (4.13). This difference is normalized by $|C_{L\omega}^U|(Re \gg 1) + |C_{Lu}^W|(Re \gg 1)$, the sum of the estimated magnitudes of the two dominant contributions to the transverse force. The normalized difference, ϵ_{WS} , is found to be only a few percent in all cases, confirming that the above model captures the main characteristics of this interaction mechanism.

Figure 4.14. Lift coefficient $C_L^W(Re, L_R, Sr)$ for a bubble translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. $\square$ (resp. $\circ$) : numerical data for $Sr > 0$ (resp. $Sr < 0$). Solid lines: high- Re prediction (4.13); dashed lines: low- Re prediction (4.12); black dash-dotted line: moderate-to-high- Re behavior predicted by (2.13b) in an unbounded shear flow; short dashed lines: composite model (4.14).

Figure 4.14 gathers the complete set of numerical results for the lift coefficient C_L^W obtained in the range $10^{-1} \leq Re \leq 10^3$. Clearly, most of the variations of the lift force with respect to both the Reynolds number and the separation distance take place for $Re \lesssim 10$. At higher Reynolds numbers, discernible variations with the separation distance only subsist for $L_R \leq 2$. For larger separations, the magnitude of the lift force becomes close to that found in an unbounded flow, as predicted by (2.13b). Interestingly, for $Sr = -0.2$, the lift force changes sign for a critical Reynolds number in the range $3 \lesssim Re \lesssim 15$ when the separation decreases from $L_R = 4$ to $L_R = 1.5$. This feature implies the existence of an equilibrium position of the bubble, resulting from a balance between the wall- and shear-induced lift components. Indeed, only the repulsive transverse force associated with the low-to-moderate- Re wall effect produces a positive transverse force in this case. This force may dominate the attractive shear-induced lift, provided L_R and Sr are small enough, which yields the above change of sign. No such feature is observed for $Sr = -0.5$, since the negative shear-induced component is always dominant, even at small separations. Note that another equilibrium

position, not encountered in Figure 4.14, exists at large Reynolds number with weak positive shears and small separations. Indeed, balancing the dominant contributions in (2.30) and (2.13b) in the limit $Sr \rightarrow \infty, Re \rightarrow \infty$ implies that the transverse force vanishes for $L_R \approx (3/4)^{1/2} Sr^{-1/4}$, i.e. $L_R \approx 1.3$ for $Sr = 0.2$. The predictors of this equilibrium position may be discerned in the panel of Figure 4.14 corresponding to $Sr = 0.2$, as the lift coefficient exhibits only small positive values at large Reynolds number, and these values are significantly decreasing with L_R .

Predictions based on the low- Re model (4.12) and the high- Re model (4.13) are displayed in Figure 4.14. These predictions are seen to properly follow numerical results for $Re \lesssim 2$ and $Re \gtrsim 20$, respectively. To fill the gap in which none of these models apply, the composite model (4.6) for the wall-induced transverse force is empirically combined linearly with a second composite model for the shear-induced contribution, inspired from (2.14) and providing a smooth variation from the low- Re prediction (4.12) to the high- Re prediction (4.13). Following this approach, the resulting composite model reads

$$C_L^W(Re, Sr, L_R) \approx C_{Lu}^W(Re, Sr, L_R) + C_{L\omega}^W(Re, Sr, L_R), \quad (4.14)$$

with

$$\begin{aligned} C_{Lu}^W(Re, Sr, L_R) &\approx f_L f_L' b^2 (L_R/3)^g C_{Lu}^{W-in} + c_{T1} [C_{Lu}^W(Re \rightarrow \infty) + c_{T2} Re^{-1} L_R^{-4}], \\ C_{L\omega}^W(Re, Sr, L_R) &\approx h_L' C_{L\omega}^U(Re \ll 1) + c_{T3}(Re)(1 + I_{WS}) C_{L\omega}^U(Re \gg 1) \text{ with} \\ c_{T3}(Re) &= 1 - e^{-0.3Re}, \end{aligned} \quad (4.15a,b)$$

where I_{WS} is given in (4.13b). Figure 4.14 shows that this model (represented by short dashed lines) properly fits the variations of the lift coefficient throughout the range of Re , Sr , and L_R covered by the simulations. Although it involves several empirical functions which depend on L_R , L_u , L_ω , and Re , it properly reduces to the relevant asymptotic expression in the various possible limits $Sr \rightarrow 0$, $Re \ll 1$, $Re \gg 1$, and $L_R \gg 1$.

4.4 Conclusions

This chapter reported on a numerical study of the drag and lift forces acting on clean spherical bubbles rising along the wall of a wall-bounded linear shear flow. Flow configurations with the bubble either lagging or leading the fluid were considered, so as to explore cooperative and antagonistic interactions between the wall- and shear-induced effects. With the selected range of wall distances, situations with the wall lying in either the inner or the outer region of the disturbance were both covered in the low-Reynolds-number regime. The selected Reynolds number range allowed to consider situations dominated by viscous effects as well as nearly inviscid flows. In both asymptotic regimes, systematic comparisons with available analytical solutions were carried out.

For bubbles rising in a fluid at rest, low-Reynolds-number asymptotic solutions indicate an increase of the drag due to the presence of the wall. Additionally, a repulsive transverse force takes place, due to the interaction between the wall and the wake resulting from the vorticity generated at the bubble surface by the shear-free condition. For a given separation distance, the magnitude of this repulsive force decreases with the Reynolds number when the wall lies in the outer region of the

disturbance. At low-but-finite Reynolds number, both the drag increase and the transverse force are proportional to the square of the maximum vorticity at the bubble surface, which increases with the Reynolds number. Present computational results confirm these predictions, and support the model proposed in Takemura and Magnaudet (2003) for the prediction of the transverse force at low-to-moderate Reynolds number, albeit with some changes in the empirical coefficients. At higher Reynolds number, the boundary layers originating at the bubble surface and wall become thin and no longer interact significantly. This makes the flow in the gap almost irrotational, which results in an attractive transverse force as predicted by potential flow theory. However, an $O(Re^{-1}L_R^{-4})$ viscous correction remains, and present results show that it significantly reduces the attractive transverse force for Reynolds numbers of $O(10^2)$. A drag increase also exists in the high-Reynolds-number regime but is significant only when the separation distance is small, typically $L_R \lesssim 2$. This increase results from two separate mechanisms. On the one hand there is a “confinement” effect imposed by the non-penetration condition at the wall which induces an increase of the bubble relative velocity, hence a Re -independent relative drag increase when the Reynolds number is large enough. On the other hand, the wall boundary layer resulting from the no-slip condition provides a Re -dependent relative drag increase. In the limited Re -range considered here ($Re \leq 10^3$), these two effects were found to be proportional to L_R^{-4} and $L_R^{-6}Re^{3/4}$, respectively. A point of caution, however, is that although these scalings accurately fit the numerical data in the moderate-to-large Re -range investigated here, various arguments suggest that they do not hold in the limit $Re \rightarrow \infty$.

Interactions between shear and wall effects have essentially been considered in the low-Reynolds-number range in the available literature. In this regime, the solution of Magnaudet et al. (2003) valid when the wall stands in the inner region of the disturbance indicates a decrease (resp. an increase) of the drag due to shear effects when the bubble lags (resp. leads) the fluid, while the reverse holds for the transverse force. For this reason, the latter may switch from positive to negative at a given L_R if the bubble leads the fluid and the magnitude of the shear is large enough. Computational results fully confirm these predictions, both qualitatively and quantitatively. When the wall stands in the outer region of the disturbance, they also confirm the corresponding theoretical predictions and their fit as proposed in Takemura et al. (2009). Empirical expressions taking into account finite-size effects have been established to estimate the drag increase and the lift force irrespective of the wall position in the low-but-finite Reynolds number regime. Comparison with numerical results indicates that they provide reliable predictions up to $Re = O(1)$.

To disentangle the various effects at play in a wall-bounded shear flow at moderate-to-high Reynolds number, first the well-documented unbounded configuration was considered. The underlying idea was to superimpose linearly the corresponding results with those obtained in the wall-bounded situation in the absence of shear, in order to determine the strength of interactions not taken into account in this crude superposition scheme. In the inviscid limit, the lift and lift-induced drag forces on a bubble translating in an unbounded linear shear flow have the same origin as those experienced by a wing with a finite span. The tilting of the upstream spanwise vorticity past the body results in a horseshoe vortex in the wake, which, in the case of a sphere, yields a lift force with a coefficient of $\frac{2}{3}Sr$ in the weak-shear limit (Auton, 1987). Similarly, the drag increase due to the interaction between the upstream vorticity and the vortex-induced velocity disturbance in the wake causes a relative drag variation proportional to Sr^2Re . Computational results in the range $10^2 \leq Re \leq 10^3$ essentially confirm these predictions, although finite- Re effects are still

present at such Reynolds numbers and somewhat decrease the Sr -exponent involved in the lift-induced drag correction.

When a nearby wall is involved, the presence of the horseshoe vortex makes the wall-shear interaction dependent on the sign of Sr . Indeed, this vortex deflects the fluid located within the wake towards the wall or away from it, depending on whether the bubble lags or leads the fluid. Since the interaction between the wake and wall is stronger in the former case, the drag and total lift force are both increased (resp. decreased) when the bubble lags (resp. leads) the fluid. Computational results confirm the various aspects of this scenario. They indicate that, for moderate-to-large Reynolds numbers, say $Re \gtrsim 100$, the wall-shear interaction is significant only when the bubble moves very close to the wall, typically for $L_R \leq 2$. As the Reynolds number decreases down to $Re \approx 50$, viscous effects gradually inhibit the bending of the wake, reducing the overall repulsive (resp. attractive) force for $Sr > 0$ (resp. $Sr < 0$). At somewhat lower Reynolds numbers, say $5 \lesssim Re \lesssim 50$, the two boundary layers thicken, strengthening the interaction between the wake and the wall shear layer if the separation distance is small. This results in an enhanced repulsive wall-induced contribution to the transverse force, which increases (resp. decreases) the magnitude of this force when $Sr > 0$ (resp. $Sr < 0$). For $Re \lesssim 5$, the picture becomes more complex because several mechanisms combine. First, the Saffman and Oseen length scales grow as Re decreases in such a way that their ratio, ε , also grows. For a given Sr , this variation tends to increase the shear-induced lift force in the unbounded configuration (see Figure 3.4 (b)), because the role of the shear increases at the expense of that of the relative velocity in the transport of the disturbance downstream of the bubble. Then, in the wall-bounded configuration, the wake and wall shear layer are thick enough that they interpenetrate each other some distance downstream from the bubble, even for separation distances as large as $L_R = 8$. Keeping Sr and Re constant, the shear-induced lift mechanism experiences little change compared to the unbounded configuration if L_R is large, and essentially combines linearly with the wall-induced effect corresponding to the shearless configuration. Combining the above two arguments explains why, for a given Re , the lift coefficient experiences large variations when Sr changes sign and L_R is large (consider the pink symbols corresponding to $L_R = 8$ in Figure 4.14). However, as L_R is decreased, the wall tends to inhibit the tilting of the upstream vorticity past the bubble. Hence the shorter the separation distance, the smaller the fraction of the transverse force provided by the shear-induced contribution, so that this force becomes dominated by the repulsive wall-induced contribution. This is why, if the bubble leads the fluid, the shear has to be large for the transverse force to remain attractive (i.e. $C_L^W < 0$) when Re is of order unity or less and L_R is small (red circles corresponding to $L_R = 1.5$ in Figure 4.14).

Present numerical results help rationalize and quantify the various mechanisms reviewed above and the way they interact. From a practical point of view, they also result in several models for the drag correction and transverse force. Models grounded on asymptotic predictions established in the low- or high-Reynolds number limit have been proposed, especially by incorporating relevant empirical finite- Re -corrections. Then these models have been combined to obtain composite fits valid throughout the range of parameters explored numerically. Fits (4.4) and (4.6) may be used to predict the wall-induced drag correction and transverse force in a fluid at rest, respectively. Similarly, fits (4.11) and (4.14)-(4.15), which reduce to the former set for $Sr = 0$, apply in wall-bounded shear flows irrespective of the sign of the shear rate and relative fluid-bubble velocity.

5 RIGID SPHERE IN WALL-BOUNDED FLOW

This chapter discusses the numerical results obtained concerning a rigid sphere. Similar to the last chapter, first the flow field and the underlying mechanisms are described. The variations of the drag and lift forces on the sphere revealed by numerical data in the light of the basic mechanisms are then discussed. The results cover the range $0.1 \leq Re \leq 250$ and $|Sr| \leq 0.5$, within which the flow field in the moving frame remains steady whatever L_R . Note that, in all calculations the sphere was not allowed to rotate. The numerical data are used to derive semi-empirical models valid either in the low-to-moderate or moderate-to-large Re range. Then these models are combined to propose empirical fits valid thoroughly the considered range of Reynolds number.

5.1 Characteristics of the flow field and fundamental mechanisms

5.1.1 Velocity field

Figure 5.1 (a) shows the computed profiles of the streamwise velocity disturbance along the line ($y = 0, z = 0$) perpendicular to the wall (x -axis) when the sphere translates in a stagnant fluid, for different separation distances and Reynolds numbers ranging from 0.1 to 200. Note that U_{rel} is negative if the sphere moves towards positive z , so that negative (resp. positive) fluid velocities normalized by U_{rel} in this figure correspond to an upward (resp. downward) fluid motion with respect to the sphere. At high Reynolds number ($Re = 200$), the no-slip boundary condition on the sphere surface results in a thin layer round the sphere, within which the disturbance is always negative. This feature differs from what has been seen in the case of a clean bubble (Figure 4.1 (a)). There, the disturbance at high Re is always positive whatever the distance from the sphere. The thickness of this layer on the wall-bounded side decreases with increasing wall proximity. On the other hand, for a given separation distance, the disturbance decreases rapidly as the distance to the sphere increases and changes sign beyond a critical distance d_c , forming an accelerating gap $-L_R < 2x/d < -(d_c + 1)$ within which near-wall fluid particles gets accelerated in the moving frame. In the boundary layer around the sphere, the decrease of the disturbance results in a pressure gradient directed towards the wall, hence a transverse force towards the sphere, in line with the vortical mechanism illustrated in Figure 1.3 (a). Since at high Re the boundary layer around the sphere exhibits an asymmetry only at $O(L_R^{-4})$ (the footprint of which may be seen in (2.29b)), wall effects are almost negligible for $L_R = 4$ but are well visible for $L_R = 2$. Compared to the former case, the disturbance is larger in the accelerating gap in the latter one, except within the thin boundary layer adjacent to the wall, in which it vanishes rapidly to satisfy the no-slip condition. When the Reynolds number decreases, the accelerating gap gets thinner, owing to the growing influence of the boundary layer that develops at the sphere surface (compare the profiles found for $Re = 200$ and 100). At $Re = 10$, it almost vanishes, resulting in similar disturbance profiles in the case of a clean bubble (see Figure 4.1 (a)). At small Reynolds number ($Re = 0.1$) the disturbance is negative everywhere along the line ($y = 0, z = 0$), i.e. directed along the direction of the sphere translation. Since at low Re the interaction of a Stokeslet with a wall induces an asymmetric flow about the sphere at $O(L_R^{-2})$, wall effects are still visible for $L_R = 4$. Comparing the magnitude of the disturbance on both side of the sphere at a given L_R , the wall proximity significantly decreases the disturbance in the gap.

The influence of the shear is illustrated in Figure 5.1 (b), based on the results obtained with two opposite shear rates, $Sr = \pm 0.5$, for a separation distance $L_R = 2$. Similar to the case of a clean bubble, in the moving frame the presence of a positive (resp. negative) shear, corresponding to a

configuration where the sphere lags (resp. leads) the fluid, accelerates (resp. decreases) the near-wall fluid particles, while it decelerates (resp. increases) those on the opposite side. Consequently, at high Reynolds number ($Re = 200$ or 100), the disturbance in the accelerating gap is enhanced (resp. inhibited) by a positive (resp. negative) shear, while the reverse occurs on the unbounded side. At moderate Reynolds number ($Re = 10$), the accelerating gap almost vanishes, on which only a tiny influence of Sr can be observed. However, on the unbounded side the acceleration and deceleration effects are still obvious. When the Reynolds number is low ($Re = 0.1$), the disturbance becomes everywhere negative and the aforementioned shear effects are subside within the thick boundary layer round the sphere.

Figure 5.1. Distribution of the streamwise disturbance velocity $(\mathbf{u} - \mathbf{u}_\infty) \cdot \mathbf{e}_z / U_{\text{rel}}$ along the line ($y = 0, z = 0$). (a) Stagnant fluid ($Sr = 0$) for different separation distances; (b) Linear shear flow for $L_R = 2$. The wall stands at position $2x/d = -1.5, -2$, and -4 for $L_R = 1.5, 2$, and 4 , respectively.

5.1.2 Vorticity field

Some aspects of the variations of the velocity disturbance, and complementary features of the sphere-wall interaction, may be better understood by examining the distribution of the y -component of the vorticity disturbance in the symmetry plane $y = 0$. This distribution is displayed in Figure 5.2 for the specific separation $L_R = 2$. Vorticity is generated both at the sphere surface and at the wall due to the no-slip condition applied on the two surfaces. In what follows, the contributions provided from these two surfaces are referred to as surface vorticity and wall vorticity, respectively. The surface vorticity diffuses around the sphere and is advected downstream in the wake. When the fluid is at rest at infinity, as revealed from the second column of Figure 5.2, it continuously increases with increasing Re . At high Reynolds number ($Re = 200$, Figure 5.2 (k)), it is obviously

thicker than that in the case of a clean bubble (Figure 4.2 (k)) and is advected asymmetrically with a preference towards the wall. Although the wall shear layer is as thin as it is in the case of a clean bubble, interaction between the two vorticities is still visible.

Figure 5.2. Iso-contours of the normalized vorticity disturbance $2/3 \times d/(2U_{\text{rel}}) (\boldsymbol{\omega} - \boldsymbol{\omega}_{\infty}) \cdot \mathbf{e}_y$ in the symmetry plane $y = 0$ at $L_R = 2$. Left column: $Sr = -0.5$ ($U_{\text{rel}} < 0$); central column: $Sr = 0$ ($U_{\text{rel}} > 0$); right column: $Sr = 0.5$ ($U_{\text{rel}} > 0$). The wall stands at the bottom of each panel. The relative flow with respect to the sphere is from left to right, i.e. in the z - (resp. $-z$)-direction for $Sr = 0.5$ (resp. $Sr = 0$ and -0.5).

It may thus be inferred that the asymmetry of the disturbance velocity observed in Figure 5.1 (a) at high Re is still due to the vortical mechanism illustrated in Figure 1.1 (a). Another interesting feature is the onset of flow separation (Figure 5.2 (k)), which results in the presence in the wake a recirculation region. Taken the unbounded case as a reference, the wall proximity slightly shifts the rear stagnant point towards the wall, agree with the observation in Zeng et al. (2005, Figure 3). When the Reynolds number decreases, the thickness of the two boundary layers increases ($Re = 50$, Figure 5.2 (h)), making the interaction between them more intensive and the asymmetry between the surface vorticity iso-contours in the gap ($x < 0$) and those on the opposite side of the sphere ($x > 0$) more prominent. At moderate-to-low Reynolds number ($Re = 10$ and 0.1 , Figure 5.2 (e) and (b)), the vorticity structure becomes almost identical with that in the case of a clean bubble (see Figure 4.2 (e) and (b)), except that the vorticity round the sphere is about 1.5 times that round a clean bubble (note the multiplier $2/3$ used in obtaining the vorticity structure). Thus, the underlining mechanism responsible for the drag enhancement and the lift force at low Reynolds number is similar to what has been stated in the case of a clean bubble. On the one hand, the competition between the two vorticities in the gap enhances the asymmetry of the vorticity round the sphere, resulting in a drag enhancement described by the contribution ΔC_{Du}^{W-in} in (2.18). On the other hand, the gradual slowing down of the fluid displaced along the wall induces of a transverse flow directed away from the wall, yielding a pressure decrease as x increases and consequently a repulsive net transverse force on the sphere.

Figure 5.3. Iso-contours of the normalized stream-wise vorticity $d/(2U_{rel}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the diametrical plane $z = 0$ in a wall-bounded linear shear flow, with the bubble standing at a distance $L_R = 1.5$ from the wall. The main flow is going inwards, along the z (resp. $-z$)-direction for $Sr > 0$ (resp. $Sr \leq 0$).

The asymmetric advection of the surface vorticity (Figure 5.2 (k)) at high Reynolds number does not take place in the case of a clean bubble (Figure 4.2 (h) and (k)). This distinction may be understood by examining the distribution of the streamwise vorticity, the structure of which in the

equatorial plane $z = 0$ is revealed in Figure 5.3 (b) and (e). Similar to the case of a clean bubble (Figure 4.2 (b) and (e)), two threads with significant value of ω_z develop close to the lower half of the sphere surface. This is certainly due to the presence of a local shear in the gap, owing to the translation of the sphere with respect to the wall. Unlike for the case of a clean bubble, where only the wall boundary layer play a significant role, making ω_z decays rapidly as the Reynolds number increases, here the boundary layer at the sphere surface comes into play as well. Since the surface vorticity continuously increases with increasing Reynolds number, the resulting ω_z increases as well. Figure 5.4 shows that, downstream of the sphere, the significant values of ω_z are concentrated within the two threads of a horseshoe vortex whose centres are located very close to the x -axis. At moderate Reynolds number ($Re = 50$, Figure 5.4 (a)) the maximum of ω_z is small because viscous effects quickly diffuses the streamwise vorticity once it has been produced around sphere. This maximum increases very strongly with Re and becomes comparable to the typical value $d/(2U_{rel})$ at $Re = 200$ (Figure 5.4 (b)). Like in the case with a clean spherical bubble subjected to an unbounded linear shear flow with $Sr > 0$, the fluid located in between the two threads is entrained downwards, bending the iso-contours of the spanwise vorticity in the wake towards the $x < 0$ direction. Similar vorticity structure also appear if the rigid sphere is replaced by a clean bubble, but at high Re the vorticity is in most cases an order of magnitude smaller than it is here.

Figure 5.4. Iso-contours of the normalized stream-wise vorticity $d/(2U_{rel}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the cross-sectional plane $z = d$ in a wall bounded stagnant flow with $L_R = 1.5$. (a) $Re = 50$; (b) $Re = 200$. The main flow is going inwards, along the $-z$ direction.

The interaction between a uniformly sheared flow in an unbounded fluid and a three-dimensional bluff body generates a nonzero streamwise (or trailing) vorticity component in the wake in the inviscid limit. At large-but-finite Re and for a clean bubble (Legendre and Magnaudet, 1998), the velocity gradients close to the sphere induced by viscous effects produce counter-rotating streamwise vorticity, which partially cancels those generated by the inviscid vortex stretching mechanism. Figure 5.5 shows how the streamwise vorticity ω_z round a rigid sphere is distributed in the equatorial plane $z = 0$ in an unbounded linear shear flow with $Sr = 0.5$. The spatial structure of the ω_z distribution is similar to that round a clean bubble: while ω_z is negative (for $y < 0$) close to the sphere, an outer region of positive values appears at $Re = 50$. When the Reynolds number increases, unlike for the case of a clean bubble, where the negative values disappear rapidly, the region containing negative values of ω_z round a rigid sphere shrinks while the maximum value rapidly increases. Downstream of the sphere, the negative vorticity dominates, resulting in the generation of a double-threaded wake as shown in Figure 5.6. The sign of ω_z in each thread of the

vortex is opposite to that in the classical trailing vorticity, and reverses if Sr is negative. The footprint of this viscous-weakening mechanism may be found in Figure 5.2 (h) and (l), where it is seen that the spanwise vorticity generated at the sphere surface is advected asymmetrically with respect to the plane $x = 0$. Indeed, at this Reynolds number ($Re = 200$), the aforementioned double-threaded wake entrains the fluid in the mid-plane $y = 0$ upwards (resp. downwards), bending the the rear stagnant point and the spanwise vorticity in the wake towards the $x > 0$ (resp. $x < 0$) direction when the sphere lags (resp. leads) the fluid. Since the presence of the wall always bends the spanwise vorticity downwards, the asymmetry is more pronounced when Sr is negative.

Figure 5.5. Iso-contours of the normalized stream-wise vorticity $d/(2U_{\text{rel}}) \boldsymbol{\omega} \cdot \mathbf{e}_z$ in the equatorial plane $z = 0$ in an unbounded linear shear flow with $Sr = 0.5$. (a) $Re = 50$; (b) $Re = 200$.

Figure 5.6. As Figure 5.5 but in the plane $z = d$.

Figure 5.3 reveals the spatial structure of the streamwise vorticity distribution in the presence of a nearby wall in the diametrical plane $z = 0$. In the case where the sphere lags the fluid, the aforementioned negative vorticity (for $y < 0$) close to the sphere and the presence of an outer region containing positive ω_z are already visible at $Re = 200$, and the sign of ω_z within each of them reverses with the sign of Sr as expected. In the lower half of the sphere surface, this negative vorticity partially cancels the two threads of vortex generated due to the presence of the wall, while they tend to compensate when the sphere leads the fluid. Within the wall boundary layer, two counter-rotating ‘pancake’ streamwise vortices appear, the intensity of which is much larger than it is in the case of a clean bubble. These structures merely result from the spanwise displacement of near-wall fluid particles as the sphere moves parallel to the wall, and is independent from the outer shear, as the constant sign of ω_z in each half-plane irrespective of Sr confirms.

The generation of the surface vorticity is also modified by the shear. Indeed, for the no-slip condition to be satisfied at the sphere surface in the presence of an outer shear, a shear-flow type correction has to take place within the boundary layer. Different from the correction appearing in the case of a clean bubble, the correction here yields an additional negative vorticity component therein when the sphere lags the fluid. Hence this vorticity correction cooperates with the primary negative vorticity on the isolated side, whereas it mitigates the primary positive vorticity in the part of the sphere boundary layer corresponding to $x < 0$. Consequently, the intensity of the overall vorticity round the sphere is increased for $x > 0$ and decreased for $x < 0$, as Figure 5.2 (i) indicates, and the same happens to the disturbance flow round the sphere (see e.g. the profile corresponding to $Re = 50$ and 200 in Figure 5.1 (b)). These conclusions reverse when the sphere leads the fluid, so that the surface vorticity and streamwise velocity disturbance round the sphere are lowered for $x > 0$ and enhanced for $x < 0$, in line with the distributions displayed in Figure 5.2 (g) and Figure 5.1 (b). The wall plays little role in these mechanisms as far as the Reynolds number is large, but the wall vorticity in the shear layer is also modified by the shear: it significantly increases (decreases) when the sphere lags (resp. leads) the fluid (see Figure 5.2 (j) and (l)). Consequently, for $Re = 200$, a weak connection between the two regions can be observed at both negative and positive Sr . In the former case it is due to the bending of the wake toward the wall, while in the latter it is due to the thickening of the wall vorticity.

As the Reynolds number decreases, the surface vorticity gets smaller, attenuating the efficiency of the viscous-weakening mechanism described above. At $Re = 50$, the two threads of vortex behind the sphere is vanishingly small (Figure 5.6 (a)), which explains why the bending of the surface vorticity distribution in the wake becomes weaker at $Re = 50$ (Figure 4.2 (g) and (i)). At the same time, the boundary layers thicken, so that the flow near the lower edge of the vertical region in the near wake starts to interact significantly with the wall shear layer, just as it does in the un-sheared case. This interaction strengthens as the Reynolds number decreases ($Re = 10$ and 0.1), making the situation combine effects of the wall-induced asymmetry with those of the shear-induced asymmetry within the wake itself. As the wall-induced and shear-induced lift mechanisms both result in a force directed toward $x > 0$ if Sr is positive (Figure 1.1 (c)), they act together to yield an enhanced repulsive force in this case, as reflected in (2.23). Conversely, they produce antagonistic effects if Sr is negative (Figure 1.1 (d)), which yields a reduced transverse force. Regarding viscous effects, the mechanisms described above indicate that the wall interaction tends to reduce the spanwise vorticity in the gap, while the excess surface vorticity resulting from the presence of the shear tends to enhance (resp. reduce) it when Sr is positive (resp. negative). The two effects just do the opposite on the free side of the sphere. For this reason, the top-bottom asymmetry of the ω_y -vorticity distribution existing in the un-sheared case is lowered (enhanced) by the shear if the sphere lags (resp. leads) the fluid. This is why the drag is decreased (resp. increased) by the shear for positive (resp. negative) Sr , as (2.18) confirms.

5.2 Hydrodynamic forces on the sphere: fluid at rest at infinity

5.2.1 Drag

The validity of the low- Re approximation for the wall-induced drag correction in the low-but-finite Re regime was confirmed during the validation of the numerical approach (see (3.1a) and Figure 3.5 (a) in section 3.2.2). Hence the primary focus here is on the behavior of the drag coefficient $C_{Du}^W(Re, L_R)$ at moderate-to-high Re . To appreciate the modification of the drag force due to the

wall influence, C_{Du}^W is compared to its counterpart in an unbounded flow, C_{D0}^U . The drag change ratio $\Delta C_{Du}^W = (C_{Du}^W - C_{D0}^U)/C_{D0}^U$ is plotted in Figure 5.7 (a). This figure reveals that, beyond $Re = 100$, the drag increase is only weakly dependent on Re . Instead, there is a clear increase with the inverse of the separation distance, L_R^{-1} , which is significant only for $L_R \lesssim 2$. Theoretical prediction for ΔC_{Du}^W in the limit of large-but finite Reynolds number is still unavailable. Fitting the numerical results at $Re = 250$ yields

$$\Delta C_{Du}^W(Re = O(100)) \approx 0.40 L_R^{-3}. \quad (5.1)$$

Figure 5.7 (a) shows that (5.1) compares well with the numerical data for $Re \geq 200$. Also, since the relative drag variation induced by the wall boundary layer is still small for $L_R = 2$ and 1.5 (it only amounts to 13% for $L_R = 1.5$ and $Re = 250$), additional computations were ran for $L_R = 1.25$, a shorter separation distance at which this effect is significantly larger. As the brown line in Figure 5.7 (a) reveals, (5.1) still closely follows the corresponding data, confirming that this fit is robust whatever L_R within the range of Reynolds number explored. Interestingly, in (5.1) the separation distance appears with exponent identical with that obtained in Legendre et al. (2003). There, the confinement effect is induced by a symmetric plane. In the inviscid limit, the non-penetration condition across this plane generates an $O(L_R^{-3})$ -increase in the relative velocity U_{rel} , which in turn yields an $O(L_R^{-3})$ relative drag increase. However, this agreement should be treated as merely a coincidence. On the one hand, numerical data provided in Legendre et al. (2003) show that such an asymptotic regime in which ΔC_{Du}^W no longer depends on Re is only reached for very large Reynolds numbers ($Re \gtrsim 500$). On the other hand, viscous effects are still present in this Re -range, as the above example revealed. This is confirmed by Figure 5.3 (b) and (e) which show that, for $L_R \leq 1.5$, the vortical region round the sphere directly interacts with the wall boundary layer at such moderate Reynolds numbers.

Figure 5.7. Wall-induced drag correction ΔC_{Du}^W for a rigid sphere translating parallel to a wall in a fluid at rest. (a): high- Re regime; (b): entire Re -range investigated numerically. Symbols: numerical data; thin solid lines: high- Re prediction (5.1); dash-dotted lines: low- Re prediction (3.1a); dashed lines: low-to-moderate- Re prediction (5.3) with $a(Re)$ given by (5.2); thick solid lines: low-to-moderate- Re prediction (5.3) with $a(Re)$ given by (5.2); short dashed lines: composite fit (5.5).

Examination of the low-to-moderate- Re range indicates that (3.1a) under-predicts the drag increase at small separations as soon as the Reynolds number is beyond 1 (see also Figure 3.5 (a)). Following

Vasseur and Cox (1977), this prediction may be improved by noting that the drag increase at low-to-moderate- Re is proportional to the square of the maximum vorticity at the sphere surface. Variations of this quantity with the Reynolds number were empirically expressed by the fitting function $a(Re)$ in (2.34b) and (2.25b). Based on the present numerical data and those in Magnaudet et al. (1995) and the fact that $a(Re)$ increases with $Re^{1/2}$ at high Re , it was found more accurate to estimate $a(Re)$ in an unbounded uniform stream by

$$a^U(Re) = \sqrt{1 - 0.12Re^{1/2} + 0.37Re}. \quad (5.2)$$

Making use of (5.2), extend (3.1a) is then extended toward moderate Reynolds numbers by expressing the drag increase in the form

$$\Delta C_{Du}^W(Re = O(1)) \approx f_D' a^2(Re) \Delta C_{Du}^{W-in}, \quad (5.3)$$

with ΔC_{Du}^{W-in} and f_D' given by (2.18) and (2.27a), respectively. As Figure 5.7 (b) shows, this expression allows an accurate prediction of ΔC_{Du}^W at $Re = O(10)$ but clearly overestimates the numerical data at lower Reynolds number especially when $L_R \leq 2$. This deviation is likely due to a possible suppression of the surface vorticity due to the wall proximity. To take this suppression into account it was found appropriate to modify (5.2) by

$$a^W(Re) = \sqrt{1 + \tanh(0.05ReL_R^2)(0.37Re - 0.12Re^{1/2})}. \quad (5.4)$$

Figure 5.8. Square of the maximum vorticity at the surface of a rigid sphere subjected to a uniform stream. $\square$: present numerical data; $\circ$: data in Magnaudet et al. (1995); solid line: present fit (5.2); dashed line: high- Re expression $a(Re \gg 1) \approx \sqrt{0.37Re}$.

As the dashed lines in Figure 5.7 (b) shows, with this modification (5.3) accurately matches the numerical data up to $Re = 20$. Obviously neither (5.3) nor (5.1) is accurate in the intermediate range $20 \lesssim Re \lesssim 150$. Nevertheless, an empirical fit may be obtained by combining the above two models in the form

$$\Delta C_{Du}^W(Re) \approx \Delta C_{Du}^W(Re = O(1)) + c_{Du\infty} \Delta C_{Du}^W(Re = O(100)), \text{ with} \quad (5.5a,b)$$

$$c_{Du\infty} = 1 - e^{-0.035Re^{0.75}}.$$

As Figure 5.7 (b) shows, this composite expression correctly reproduces the computed drag variations throughout the entire range of Reynolds number.

5.2.2 Lift

Similar to wall-induced drag variations, the validity of the solution based on the combination of (2.23) and (2.27b) for the transverse (lift) force coefficient in the low-but-finite Re regime was confirmed during the validation of the numerical approach (see (3.1b) and Figure 3.5 (b) in section 3.2.2). More specifically, it was shown that (3.1b) allows an accurate prediction of C_{Lu}^W up to $Re \approx 1$ (see also Figure 5.9). Here, first the appropriate extension of (3.1b) to moderate Reynolds number is considered.

Following Takemura and Magnaudet (2003), a preliminary extension may be obtained by noting that the lift force at low-to-moderate- Re is proportional to the square of the maximum vorticity at the sphere surface. Making use of (5.4), the improved expression takes the form:

$$C_{Lu}^W(Re = O(1 - 10)) \approx a^2 f_L' C_{Lu}^{W-in}, \quad (5.6)$$

with C_{Lu}^{W-in} , f_L' , and a as given in (2.23), (2.27b), and (5.4) respectively.

Figure 5.9. Lift coefficient (multiplied by L_R^{-1} for better readability) on a rigid sphere translating parallel to a wall in a fluid at rest. Symbols: numerical data; dash-dotted lines: low- Re prediction (3.1b); solid lines: low-to-moderate- Re prediction (5.6); dashed lines: low-to-moderate- Re prediction (5.7).

The prediction of (5.6) (solid lines in Figure 5.9) is found to agree well with the numerical results up to $Re \approx 10$. The agreement even extends up to $Re = 100$ provided that $L_R \geq 4$. At smaller separation, a clear underestimation appears for $Re > 10$. This underestimation increases with

decreasing L_R and increasing Re . This is likely due to the presence of a local shear in the gap between the wall and the sphere surface, resulting in the presence of two threads of vortex in the wake at moderate Reynolds number (see Figure 5.4). Indeed, according to the inviscid rotational flow theory (Lighthill, 1956; Auton, 1987), the secondary velocity field induced by this stream-wise vorticity yields a lift force pointing away from the wall. Noting also that the decay rate of the lift force with L_u as Re increases varies from L_u^{-2} at low-but-finite Re to L_u^{-4} in the inviscid limit (Takemura and Magnaudet, 2003), (5.6) is further improved by

$$C_{Lu}^W(Re = O(1 - 100)) \approx a^2 f_L' C_{Lu}^{W-in}(\min(1, L_R/3))^g \quad (5.7)$$

with $g(Re)$ as given in (2.29b).

As shown by the dashed lines in Figure 5.9, this empirical fit agrees well with the numerical data for $Re \leq 100$, beyond which the agreement deteriorates.

In an unbounded uniform ambient flow, the flow around a rigid sphere experiences a steady state bifurcation at $Re = Re^{SS} \approx 212.6$ (Citro et al., 2016) which leads from an axisymmetric state with zero lift to a mirror-symmetric state with non-zero lift. The type of this bifurcation is a pitchfork in the presence of $O(2)$ symmetry (Fabre et al., 2008). As noted by Johnson and Patel (1999) in this case there is no physically preferred direction of the lift force and the observed results are due to unavoidable perturbations. With the presence of a nearby wall, the flow undergoes an imperfect bifurcation with the plane of symmetry being fixed to be wall normal (Zeng et al., 2005), and as a result the transverse force induced is pointing away from the wall. In the limit $L_R \gg 1$, analytical solution for the lift force may be obtained by conducting weakly non-linear analysis in the bifurcation region $\frac{1}{Re^{SS}} - \frac{1}{Re} \ll 1$.

Table 8. Total lift, vortical-induced lift, and the difference at $Re = 250$ for $L_R \geq 1.5$

L_R	total C_L from DNS	vortical-induced C_L from (5.7)	difference
1.5	1.061×10^{-1}	5.59×10^{-2}	5.02×10^{-2}
2	8.043×10^{-2}	1.76×10^{-2}	6.28×10^{-2}
4	6.345×10^{-2}	1.89×10^{-3}	6.16×10^{-2}
8	6.165×10^{-2}	4.44×10^{-4}	6.12×10^{-2}
∞	6.089×10^{-2}	-	-

As the vortical mechanism is weakening with increasing Reynolds number (see the dashed lines in Figure 5.9), the increase in the lift coefficient beyond $Re = 100$ observed in Figure 5.9 appears due to the imperfect bifurcation mentioned above. This could be confirmed by comparing the numerical results with those obtained using weakly nonlinear approaches. An alternative indication is to compare the difference between the total lift force and the vortical-induced lift to the magnitude of the lift force in an imperfect bifurcation condition. The latter is considered here at $Re = 250$. As Table 8 shows, the difference has a magnitude of about 0.06 which agrees with the value obtained

in an imperfect bifurcation condition in present and previous studies (Johnson and Patel, 1999; Kim and Choi, 2002; Giacobello et al., 2009).

5.3 Hydrodynamic forces on the sphere: Linear shear flow

We now perform the same type of analysis in the more complex situation where the effects of a constant shear combine with those of the wall.

5.3.1 Drag

Results for the drag change ratio $\Delta C_D^W = (\Delta C_D^W - \Delta C_{D0}^U) / \Delta C_{D0}^U$ obtained in the low-but-finite Reynolds number regime, $0.1 \leq Re \leq 2$, with two dimensionless shear rates, $Sr = \pm 0.2$ and ± 0.5 , are plotted in Figure 5.10 for different separation distances. Like in the case of a clean spherical bubble (Figure 4.8), the shear-induced drag modification is negligibly small compared with that due to the wall effect when L_R exceeds a few units. For the smallest two separations, the shear is found to increase (resp. reduce) the drag when the sphere leads (resp. lags) the fluid, in line with the qualitative discussion provided at the end of section 5.1. The solution (2.18) assuming that the wall stands in the inner region of the disturbance shows good agreement with numerical results at $Re = 0.1$ but, not surprisingly, overestimates them at higher Reynolds number. No explicit counterpart of the theoretical solution (2.24a) exists when the shear is nonzero and the wall stands in the outer region of the disturbance. However the relative influence of the shear is always small under the conditions considered here (at $Re = 0.1$, the relative variation of ΔC_D^W is approximately 8% for $Sr = \pm 0.5$ compared to the un-sheared case $Sr = 0$). For this reason, the arguments employed in the case of a clean bubble is followed, in order to obtain an estimate of the drag variation valid up to Reynolds numbers of $O(1)$. This yields

$$\Delta C_D^W(Re = O(1)) \approx f_D'(L_u) a^2(Re) \Delta C_D^{W-in} \quad (5.8)$$

with ΔC_D^{W-in} , $f_D'(L_u)$, and a as given in (2.18), (2.27a) and (5.4), respectively. As the solid lines in Figure 5.10 show, the corresponding predictions properly follow the numerical data up to $Re \approx 2$.

To analyze results obtained in the moderate-to-high- Re range, first the unbounded configuration is considered. Figure 5.11 shows how the relative drag change $\Delta C_{D\omega}^U(Sr, Re) = (C_{D\omega}^U(Sr, Re) - C_{D0}^U(Re)) / C_{D0}^U(Re)$ varies with both the Reynolds number and the dimensionless shear rate. Within the ranges of Sr and Re considered, $\Delta C_{D\omega}^U$ slightly increases as Re increases and depends almost linearly on $|Sr|$, in agreement with the tendency obtained in Kurose and Komori (1999, Figure 6). Although similar behavior appears in the case of a clean bubble (see Figure 4.9), the relative increase obtained is much larger than it is here. Specifically, in all considered cases here $\Delta C_{D\omega}^U$ never exceeds 4 percent. Fitting the numerical results at $Re = 250$ yields

$$\Delta C_{D\omega}^U(Re = O(100)) \approx 0.075|Sr|. \quad (5.9)$$

Figure 5.10. Relative near-wall drag increase ΔC_D^W for a rigid sphere translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime for (a) $Sr = \pm 0.2$, and (b) $Sr = \pm 0.5$. Symbols: DNS results for positive ($\square$) and negative ($\circ$) Sr . Dashed lines: asymptotic prediction (2.18) corresponding to conditions $L_u \ll 1$, $L_\omega \ll 1$; solid lines: semi-empirical model (5.8). Thick (resp. thin) lines correspond to positive (resp. negative) Sr .

Figure 5.11. Relative drag variation $\Delta C_{D_\omega}^U$ for a rigid sphere translating at moderate-to-high Re in an unbounded shear flow, with reference to the drag in a uniform stream.

Now it is necessary to evaluate how much the above results are altered when the sphere gets closer to the wall. Based on Figure 5.2 (j) and (l), one expects this alteration to be fairly weak, since the wall boundary layer is thin in the considered Re -range, and to depend on the sign of Sr , owing to the bending of the sphere wake towards (resp. away from) the wall for negative (resp. positive) Sr . To clarify the magnitude of the wall-shear interaction, we computed the difference between the actual drag variation in the near-wall configuration, $\Delta C_D^W(Re, Sr, L_R)$, and the sum $\Delta C_{Du}^W(Re, L_R) + \Delta C_{D_\omega}^U(Re, Sr)$ of the two contributions discussed above. This difference, say $\Delta C_{D_\omega}^{W-U}(Re \gg 1)$, is displayed in Figure 5.12. The results show that it is negligibly small whatever the Reynolds number and for both shear rates for $L_R \geq 1.5$. Since only a weak connection between the boundary layers round the sphere and near the wall can be observed even at $L_R = 1.5$, we ran additional computations for $Sr = \pm 0.5$ at $L_R = 1.25$, a shorter separation distance at which the

connection may be stronger. As the brown symbols in Figure 5.12 reveals, the difference is still negligible within the range of Reynolds number we explored.

Figure 5.12. Difference in the moderate-to-high Re regime between the relative drag variation in the presence of wall and shear, ΔC_D^W , and the sum $\Delta C_{Du}^W + \Delta C_{D\omega}^U$ of the relative drag variation in the presence of the wall for $Sr = 0$, ΔC_{Du}^W , and the relative drag variation in an unbounded shear flow, $\Delta C_{D\omega}^U$.

Based on the above observations, it seems appropriate to model the entire wall-induced drag correction in the moderate-to-high Re regime in the form

$$\Delta C_D^W(Re = O(100)) \approx \Delta C_{Du}^W(Re = O(100)) + \Delta C_{D\omega}^U(Re = O(100)), \quad (5.10)$$

where the two contributions in the right-hand side are provided by (5.1) and (5.9), respectively.

Finally, Figure 5.13 presents all numerical results obtained throughout the range $10^{-1} \leq Re \leq 250$ together with the corresponding predictions based on the semi-empirical expressions established above. Comparing the two panels, which only differ by the magnitude of Sr , reveals that the shear has only a secondary influence on the drag within the range of Reynolds number explored. In the moderate-to-high- Re range, shear-induced drag variations do not exceed 10% of the total drag increase for $|Sr| = 0.5$. This is in contrast with the behavior observed in the case of a clean bubble, where $\Delta C_D^W - \Delta C_{Du}^W$ already exceeds 20% at $Re = 250$ for $|Sr| = 0.5$, owing to the large influence of the lift-induced-drag contribution (4.8). Interestingly, comparing ΔC_D^W in two configurations differing only by the sign of Sr , it turns out that the drag increase is slightly larger at low Reynolds number when the sphere leads the fluid ($Sr < 0$), in agreement with (2.18). However, no clear dependence on the sign of Sr can be observed at moderate-to-large Reynolds number. In a way similar to (5.5), an empirical expression combining linearly $\Delta C_D^W(Re = O(1))$ and $\Delta C_D^W(Re = O(100))$, as respectively given by (5.8) and (5.10), may be designed to improve the estimate of the drag increase in the intermediate range $2 \leq Re \leq 10^2$. As the short dashed lines in Figure 5.13 show, the composite expression

$$\Delta C_D^W(Re) \approx \Delta C_D^W(Re = O(1)) + c_{D\omega\infty} \Delta C_D^W(Re = O(100)) \text{ with} \quad (5.11a,b)$$

$$c_{D\omega\infty} = c_{Du\infty} = 1 - e^{-0.035Re^{0.75}}$$

correctly fits the DNS data throughout the entire range of Reynolds number.

Figure 5.13. Relative near-wall drag increase $\Delta C_D^W(Re, L_R, Sr)$ for a rigid sphere translating parallel to a wall in a linear shear flow throughout the Re -range investigated numerically. (a) $Sr = \pm 0.2$; (b) $Sr = \pm 0.5$. $\square$ and $\circ$: numerical data for $Sr > 0$ and $Sr < 0$, respectively. Thick (resp. thin) solid lines: moderate-to-high- Re prediction (5.10) for positive (resp. negative) Sr ; thick (resp. thin) dashed lines: low- Re prediction (5.8) for positive (resp. negative) Sr ; thick (thin) dash-dotted lines: composite expression (5.11a,b) for positive (resp. negative) Sr .

5.3.2 Lift

Figure 5.14 shows the computed lift coefficient $C_L^W(Re, Sr, L_R)$ in the low-but-finite Reynolds number regime at various normalized shear rates and separation distances. Variations of C_L^W with increasing Re and L_R as well as the form of the interplay between the shear- and wall-induced contributions are consistent with those observed in the case of a clean bubble (see the discussion in section 4.3.2), which agrees with the behavior predicted in Legendre and Magnaudet (1998), Takemura et al. (2002), and Magnaudet et al. (2003). Specifically, these work indicate that, to leading order, shear- and wall-induced lift forces acting on a rigid sphere differ from those on a clean bubble only by a numerical factor of $(3/2)^2$. This is confirmed by comparing data shown here to their counterpart shown in Figure 4.12 at $Re = 0.1$.

The asymptotic expression (2.23) corresponding to situations in which the wall stands in the inner region of the disturbance (dashed lines in Figure 5.14) closely predicts the computed lift force for small enough L_R and Re , typically $L_R < 4$ and $Re \leq 0.2$ for both shear rates. Not surprisingly, the agreement deteriorates as L_R or Re increases, owing to the increasing influence of inertial effects through L_u and L_ω . The approximate fit (2.37) (along with (2.41) and (2.43) for h_L and f_L) of the asymptotic solution obtained in the case the wall standing in the outer region of the disturbance (dotted lines in Figure 5.14) properly accounts for these effects. The quantitative agreement is good for $L_R \geq 4$, at least up to $Re = 1$, but increasingly deteriorates as L_R decreases. Like in the case of a clean bubble, this deviation is certainly due to the fact that (2.41) and (2.43) are based on the outer solution of McLaughlin (1993), which is valid only in the limit of large separations. This limitation may be overcome by modifying heuristically (2.37) in a way similar to that employed to obtain (4.12) in the case of a clean bubble. That is, the outer solution for the wall effect may be replaced

in (2.37) by the mixed expression $C_{Lu}^W(Re \ll 1) \approx f_L' C_{Lu}^{W-in}$ (see (3.1b)), and the $h_L(L_\omega, \varepsilon)$ weighting function in (2.41) may be substituted by a function $h_L(L_\omega, \varepsilon, L_R)$ incorporating finite-size effects and tending towards $h_L(L_\omega, \varepsilon)$ for large separations. Instead of (2.37)-(2.41) one then has

Figure 5.14. Variations of the lift coefficient $C_L^W(Re, Sr, L_R)$ for a rigid sphere translating parallel to a wall in a linear shear flow in the low-but-finite Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. $\square$ (resp. $\circ$): numerical data for $Sr > 0$ (resp. $Sr < 0$). Dashed lines: asymptotic prediction (2.23) corresponding to conditions $L_u \ll 1, L_\omega \ll 1$; dotted lines: fit (2.37) of the asymptotic prediction corresponding to conditions $L_u \gg 1, L_\omega \gg 1$; solid lines: semi-empirical model (5.12) taking into account finite-size effects.

$$C_L^W(Re \ll 1) \approx f_L C_{Lu}^W(Re \ll 1) + h_L' C_{L\omega}^U(Re \ll 1), \text{ with} \quad (5.12a,b)$$

$$h_L'(L_\omega, \varepsilon, L_R) = 1 - e^{-\frac{11}{96}\pi^2 \frac{L_\omega}{J(\varepsilon)} \left(1 + \frac{17}{48}L_R^{-1} + 0.6433L_R^{-2} - 0.2797L_R^{-3}\right)},$$

with $f_L(L_\omega, \varepsilon)$ still given by (2.43). With these modifications, the semi-empirical model (5.12) approaches the complete asymptotic solution (2.23) when $L_u \rightarrow 0$ and $L_\omega \rightarrow 0$ (with the exception of the Sr^2 -term, usually much smaller than the Sr -term as far as $Sr \lesssim 1$), while the initial approximation (2.41) of the outer solution is recovered in the limit $L_R \gg 1$. Compared to (2.37)-

(2.41), the predictions of (5.12) (solid lines in Figure 5.14) exhibit a significantly better agreement with numerical results when L_R and Re decrease.

Figure 5.15. Variations of the lift coefficient $C_L^W(Re, Sr, L_R)$ for a rigid sphere translating parallel to a wall in a linear shear flow in the low-to-moderate Reynolds number regime with (a) $Sr = \pm 0.2$ and (b) $Sr = \pm 0.5$. $\square$ (resp. $\circ$): numerical data for $Sr > 0$ (resp. $Sr < 0$). Dashed lines: low- Re expression (5.12); short dashed lines: low-to-moderate- Re expression (5.13); black solid lines: lift coefficient obtained in an unbound flow; red solid lines: lift coefficient obtained in the shearless condition at $L_R = 1.5$.

Results obtained in the moderate Reynolds number regime are then presented. Figure 5.15 summarizes the computed lift coefficient $C_L^W(Re, Sr, L_R)$ for $0.1 \leq Re \leq 100$ at various normalized shear rates and separation distances. Clearly, most of the variations of the lift coefficient with respect to both the Reynolds number and the separation distance take place for $Re \lesssim 10$. At higher Reynolds numbers, discernible variations with the separation distance only subsist for $L_R \lesssim 2$. For larger separations, the magnitude of the lift force becomes close to that found in an unbounded flow, as represented by the black solid lines (obtained based on a spline interpolation of the data shown in Figure 3.7 (b)). This is no surprising, as the thickness of the boundary layers round the sphere and near the wall decreases as Re increases (see Figure 5.2), making the wall effects vanishingly small beyond a certain Reynolds number. The effects caused by the presence of the shear may be examined by comparing $C_L^W(Re, Sr, L_R)$ to its counterpart obtained in the shearless

situation, namely $C_{Lu}^W(Re, L_R)$. The latter at $L_R = 1.5$ appears in Figure 5.15 as the red solid lines (obtained based on a spline interpolation of the data shown in Figure 5.9). The influence of shear is pronounced only for $Re \lesssim 10$. There, clearly a positive Sr contributes positively to the resulting lift force and vice versa. Since at higher Reynolds number the shear-induced lift becomes vanishingly small even in an unbounded flow (see Figure 3.7 (b)), the low- Re expression (5.12) may be extend to moderate Reynolds number simply by:

$$C_L^W(Re = O(1 - 100)) \approx f_L C_{Lu}^W(Re = O(1 - 100)) + h'_L C_{L\omega}^U(Re \ll 1) \quad (5.13a, b)$$

with

$$f_L(\varepsilon, L_\omega, Re) = e^{-0.22\varepsilon^{0.8} L_\omega^{2.5} \exp(-0.01Re^2)},$$

with h'_L and $C_{Lu}^W(Re = O(1 - 100))$ given by (5.12b) and (5.7), respectively. Note that the previous f_L expression (2.43) gives a too fast decay of the wall-induced contribution at moderate Reynolds number for $Sr = O(1)$. For instance, it decreases to 0.4 at $Re = 50$ for $Sr = 0.5$ and $L_R = 1.5$ while data shown in Figure 5.15 suggest $f_L \approx 1$. This limitation may be overcome by modifying the f_L expression via (5.13b). No such modification is necessary in the case of a clean bubble, as there the vortical mechanism dramatically vanishes beyond $Re \approx 30$. As shown in Figure 5.15, (5.13) matches well with all numerical data in the range $0.1 \leq Re \leq 100$.

Figure 5.16. Variations of the lift coefficient $C_L^W(Re, Sr, L_R)$ for a rigid sphere translating parallel to a wall in a linear shear flow at moderate-to-high Reynolds number with (a) $L_R = 1.5$, (b) $L_R = 2.0$, and (c) $L_R = 4.0$.

For $Re \gtrsim 100$, the picture becomes more complex because several mechanisms combine. First, the viscous-weakening mechanism (see Figure 1.3 (b)) activates, resulting in the generation of a shear-induced lift force, which, in the unbounded configuration, is always antiparallel to that of the Saffman-lift. On the other hand, the discussion in section 5.2.2 indicates that the vortical mechanism responsible for the wall-induced lift at low Reynolds number remains non-negligible up to $Re = 250$ provided that $L_R \lesssim 2$. In the combined situation, these two mechanisms act in an antagonistic (resp. cooperate) manner when Sr is negative (resp. positive). This may be qualitatively seen in Figure 5.16, where, taken the results at $Sr = 0$ as a reference, clearly a negative Sr contributes positively to the resulting lift force and vice versa. A closer look reveals that usually the difference between $C_L^W(Re, Sr, L_R)$ and $C_{Lu}^W(Re, L_R)$ does not equal to the shear-induced lift in an unbounded configuration, namely $C_L^W(Re, Sr, L_R) - C_{Lu}^W(Re, L_R) \neq C_{L\omega}^U(Re, Sr)$. This may be understood by noting that, beyond a certain Reynolds number, the flow undergoes an imperfect

bifurcation, enhancing both $C_{L\omega}^U(Re, Sr)^{\dagger\dagger\dagger}$ and $C_{Lu}^W(Re, L_R)$. In the combined situation, the onset of bifurcation enhances either the viscous-weakening or the vortical mechanism depending on the relative intensity of the perturbation induced by the shear and that due to the wall, but not both. Hence, in situations where the two mechanisms act antagonistically, i.e. when Sr is positive, there is a critical shear-rate-dependent separation distance larger than which the onset of an imperfect bifurcation is always perturbed by the shear. Interestingly, our computational results at $L_R = 1.5$ indicate that the perturbation induced by the wall surpasses that induced by the shear at $Sr = 0.2$, while at $Sr = 0.5$ the latter overwhelms the former in perturbing the imperfect bifurcation. Since the wall-induced perturbation rapidly decays as L_R increases, at larger separation distances usually it is the shear-induced perturbation that responsible for the onset of an imperfect bifurcation as Figure 5.16 (b) and (c) confirm.

5.4 Conclusions

This chapter reported on a numerical study of the drag and lift forces acting on a rigid sphere moving along the wall of a wall-bounded linear shear flow. Flow configurations with the sphere either lagging or leading the fluid were considered, so as to explore cooperative and antagonistic interactions between the wall- and shear-induced effects. With the selected range of wall distances, situations with the wall lying in either the inner or the outer region of the disturbance were both covered in the low-Reynolds-number regime. The selected Reynolds number range allowed to consider situations with either vanishingly small or pronounced inertial effects. In the former asymptotic regime, systematic comparisons with available analytical solutions were carried out.

For spheres moving in a fluid at rest, low-Reynolds-number asymptotic solutions indicate an increase of the drag due to the presence of the wall. Additionally, a repulsive transverse force takes place, due to the interaction between the wall and the wake resulting from the vorticity generated at the sphere surface by the no-slip condition. For a given separation distance, the magnitude of this repulsive force decreases with the Reynolds number when the wall lies in the outer region of the disturbance. At low-but-finite Reynolds number, both the drag increase and the transverse force are proportional to the square of the maximum vorticity at the sphere surface, which increases with the Reynolds number. Present computational results confirm these predictions, and support the model proposed in Takemura and Magnaudet (2003) for the prediction of the transverse force at low-to-moderate Reynolds number, albeit with some changes in describing the modification of the surface vorticity due to the wall proximity. At moderate-to-high Reynolds number, the boundary layer originating at the wall becomes thin, while the thickness of the one at the sphere surface hardly changes as Re increases. Due to the continuous increase of the surface vorticity, vortical interaction between the wall and the wake remains considerable. Indeed, the transverse force predicted by the vortical mechanism applies up to $Re = 100$ provided that $L_R \gtrsim 4$. At smaller separation distances, two threads with significant value of streamwise vorticity develop close to the lower half of the sphere surface, owing to the translation of the sphere with respect to the wall. This results in, on the one hand, two threads of a horseshoe vortex in the wake, which increases the transverse force, and, on the other hand, an enhancement of the asymmetry of the vorticity round

^{††††} Note that, in the unbounded configuration, the presence of a weak shear ($Sr \rightarrow 0$) may be considered as a perturbation to the uniform base flow, which undergoes an imperfect bifurcation with the plane of symmetry being parallel to $\boldsymbol{\omega} \times \boldsymbol{U}_{\text{rel}}$.

the sphere, which increases the drag. For the latter, the increase was found to be proportional to L_R^{-3} .

Interactions between shear and wall effects have essentially been considered in the low-Reynolds-number range in the available literature. In this regime, the solution of Magnaudet et al. (2003) is valid when the wall stands in the inner region of the disturbance and indicates a decrease (resp. an increase) of the drag due to shear effects when the sphere lags (resp. leads) the fluid, while the reverse holds for the transverse force. For this reason, the latter may switch from positive to negative at a given L_R if the sphere leads the fluid and the magnitude of the shear is large enough. Computational results fully confirm these predictions, both qualitatively and quantitatively. When the wall stands in the outer region of the disturbance, they also confirm the corresponding theoretical predictions and their fit as proposed in Takemura et al. (2009). Empirical expressions taking into account finite-size effects have been established to estimate the drag increase and the lift force irrespective of the wall position in the low-but-finite Reynolds number regime. Comparison with numerical results indicates that they provide reliable predictions up to $Re = O(1)$.

To disentangle the various effects at play in a wall-bounded shear flow at moderate-to-high Reynolds number, first the well-documented unbounded configuration was considered in the range $50 \leq Re \leq 250$. The underlying idea was to superimpose linearly the corresponding results with those obtained in the wall-bounded situation in the absence of shear, in order to determine the strength of interactions not taken into account in this crude superposition scheme. Computational results reveal the presence of a double-threaded wake, in which the sign of the streamwise vorticity is opposite to that in the wake behind a clean bubble. As a result, the shear-induced lift is opposite to that corresponding to the inviscid vortex tilting mechanism and increases with increasing Re and Sr . Meanwhile, the drag force is hardly influenced by the shear, although a slight increase (less than 4%) with increasing Re and Sr is also observed. These observations agree well with those found in previous studies (Kurose and Komori, 1999; Bagchi and Balachandar, 2002).

When a nearby wall is involved, the wall-shear interaction depends on the following distinct processes. First, the spanwise vorticity in the vicinity of the wall is increased (resp. decreased) when the sphere lags (resp. leads) the fluid, enhancing (resp. lightening) the wall-shear interaction. Besides, the double-threaded wake caused by the ambient shear acts antagonistically (resp. cooperatively) with that caused by the local shear appearing in the gap in bending the surface vorticity towards the wall, lightening (resp. enhancing) the wall-shear interaction. A combination of these two effects results in an increase of drag, which only depends weakly on the sign of Sr . Concerning the lift force, the picture becomes more complex. First, the double-threaded wake caused by the ambient shear results in the generation of a shear-induced lift force, which, in the unbounded configuration, is always antiparallel to that corresponding to the inviscid mechanism. Besides, the vortical mechanism responsible for the wall-induced lift at low Reynolds number remains considerable. In the combined situation, these two mechanisms act in an antagonistic (resp. cooperate) manner when Sr is positive (resp. negative). Moreover, the onset of bifurcation in the moderate-to-high Re regime enhances either of the two mechanisms depending on the relative intensity of the perturbation induced by the shear and that due to the wall, but not both. Present computational results indicate that the wall-induced perturbation decays rapidly as L_R increases. Beyond $L_R \approx 2$ usually it is the shear-induced perturbation that is responsible for the onset of an imperfect bifurcation.

As the Reynolds number decreases down to $Re \approx 50$, viscous effects gradually inhibit the double-threaded vortex in the wake, reducing the negative (resp. positive) lift-contribution for $Sr > 0$ (resp. $Sr < 0$). At somewhat lower Reynolds numbers, say $5 \lesssim Re \lesssim 50$, the two boundary layers thicken, strengthening the interaction between the wake and the wall shear layer if the separation distance is small. This results in an enhanced repulsive wall-induced contribution to the transverse force. Since now the tiny shear-induced lift is mainly due to the asymmetric advection of the surface vorticity, it acts cooperatively (resp. antagonistically) with the wall-induced lift when $Sr > 0$ (resp. $Sr < 0$). For $Re \lesssim 5$, the picture becomes identical with that in cases concerning a clean bubble. That is, the shear-induced effects essentially combines linearly with the wall-induced effect corresponding to the shearless configuration provided that L_R is large. However, as L_R is decreased, the wall tends to inhibit the tilting of the upstream vorticity past the sphere. Hence the shorter the separation distance, the smaller the fraction of the transverse force provided by the shear-induced contribution, so that this force becomes dominated by the repulsive wall-induced contribution.

Present numerical results help rationalize and quantify the various mechanisms reviewed above and the way they interact. From a practical point of view, they also result in several models for the drag correction and transverse force. Models grounded on either asymptotic predictions established in the low-Reynolds-number limit or purely empirical basis in the moderate-to-high Reynolds number range have been proposed. Then these models have been combined to obtain composite fits valid throughout the range of parameters explored numerically. Fits (5.5) and (5.7) may be used to predict the wall-induced drag correction and transverse force in a fluid at rest, respectively. Similarly, fits (5.11) and (5.13), which reduce to the former set for $Sr = 0$, apply in wall-bounded shear flows irrespective of the sign of the shear rate and relative fluid-sphere velocity.

6 CONCLUSIONS AND FUTURE WORK

6.1 Summary and conclusions

Interactions between a stream-wise translating sphere and a wall-bounded linear shear flow are numerically investigated in this thesis. Boundary conditions on the sphere's surface correspond to either a clean spherical bubble or a rigid sphere. Meanwhile, the flow configurations considered allow the sphere either lagging or leading the fluid, so as to explore cooperative and antagonistic interactions between the wall- and shear-induced effects. The sphere Reynolds number considered ranges from 0.1 to several hundreds, allowing to explore situations with either vanishingly small or pronounced inertial effects. The JADIM code developed at IMFT is used to perform direct numerical simulations. The body-fitted grid round the sphere allows to accurately calculate the forces on the sphere and capture the detailed flow features. Concluding remarks on the main findings obtained in the case concerning a clean bubble and a rigid sphere have been stated in sections 4.4 and 5.4, respectively. To conclude this work, it appears worthwhile to clarify the main similarities and differences between the results obtained in these two cases, particularly the governing mechanisms at work and their interactions, in the specified flow configurations.

6.1.1 Unbounded linear shear flow

The maximum of the vorticity originating at the sphere surface plays a crucial role in most of the governing mechanisms. The past works have shown that this maximum is $2U_{\text{rel}}/d$ (resp. $3U_{\text{rel}}/d$) for a clean spherical bubble (resp. rigid sphere) moving in a stagnant fluid at low Reynolds number, typically $Re \lesssim 0.1$. This maximum gradually increases as Re increases: for a clean bubble, it approaches $6U_{\text{rel}}/d$ in the inviscid limit; for a rigid sphere, it increases as $Re^{1/2}$ beyond $Re \approx 50$. Present computational results confirm these behaviors. For practical purposes, accurate fit-formulas for the above variations ((4.2) and (5.2)) based on the present numerical data and the previous ones in Magnaudet et al. (1995) are also provided.

The surface vorticity is advected asymmetrically in the wake when an ambient shear is present, yielding at low Reynolds number a correction to the drag force in the direction $\mathbf{U}_{\text{rel}} \times \boldsymbol{\omega}$, namely a transverse or (shear-induced) lift force (the so-called Saffman-lift). The asymptotic expression of the shear-induced lift was derived in Legendre and Magnaudet (1997) for a drop of arbitrary viscosity. Specifically, their analysis indicates that the shear-induced lift acting on a clean bubble differs from that on a rigid sphere only by a numerical factor of $(2/3)^2$ (i.e. the square of ratio of the surface vorticity). Present computational results confirm these behaviors and show that the applicability of their asymptotic expression extends up to $Re \lesssim 1$.

The Saffman lift rapidly decreases as the Reynolds number increases. Then a second vortical mechanism takes over. For a clean bubble, due to the saturation of the vorticity at the surface, the inviscid mechanism gradually dominates. Specifically, in the inviscid limit the distortion of the vorticity associated with the ambient shear by the sphere results in the generation of a nonzero stream-wise vorticity in the wake, which is concentrated within two counter-rotating trailing vortices. The secondary velocity field induced by this stream-wise vorticity yields a second shear-induced lift force (Auton, 1987), the direction of which was found parallel to the Saffman-lift. For a rigid sphere, due to the continuous increase of the surface vorticity, the inviscid mechanism never plays a significant role. Indeed, present computational results reveal the presence of a second stream-wise vorticity in the vicinity of the sphere, owing to the velocity gradient induced by viscous

effects. Its direction is opposite to that due to the inviscid vortex tilting mechanism mentioned above, while its intensity is always larger than the latter. Downstream of the sphere, the two vortices partially cancel, forming a narrow trailing vorticity in the wake. The sign of ω_z in each thread of the vortex is opposite to that in the classical trailing vorticity, and reverses if Sr is negative. Accordingly, the direction of the resulting shear-induced lift is opposite to that due to the inviscid vortex tilting mechanism.

The drag force in the low-to-moderate- Re regime is hardly affected by the shear. In the inviscid limit, the configuration considered here is similar to that of a wing of finite span, on which the trailing vortices are known to produce a lift-induced drag force proportional to the square of the lift force (Batchelor, 1967). The relative drag variation due to the interaction between the upstream vorticity and the vortex-induced velocity disturbance in the wake is proportional to $Sr^2 Re$. This prediction is essentially confirmed by the present computational results in the range $10^2 \leq Re \leq 10^3$ concerning a clean spherical bubble. Not surprisingly, it does not apply in cases concerning a rigid sphere, owing to the continuous increase of the surface vorticity. Indeed, these cases indicate that the drag increase caused by the shear with $Sr = O(1)$ is generally negligible provided that $Re \leq 250$.

6.1.2 Wall-bounded stagnant flow

The wall proximity significantly inhibits the increase of the surface vorticity as Re increases, especially in cases concerning a rigid sphere moving at low-to-moderate Reynolds number. Based on the present computational results, the inhibited vorticity may be described by the modified expression (5.4), which significantly improves the agreement in predicting the drag and lift forces at low-to-moderate Reynolds number.

The interaction between the surface vorticity and the wall tends to increase the drag. Additionally, it causes a repulsive transverse force. At low Reynolds number, the asymptotic expressions of the drag increase and the transverse force were derived in Takemura et al. (2002) and Magnaudet et al. (2003) for a drop of arbitrary viscosity. Their analyses indicate that the drag increase and the wall-induced lift acting on a clean bubble differ from their counterpart on a rigid sphere only by a numerical factor of $(2/3)^2$. At low-but-finite Reynolds number, the analysis in Takemura and Magnaudet (2003) indicates that both the drag increase and the transverse force are proportional to the square of the maximum vorticity at the sphere surface, which increases with the Reynolds number. Present computational results confirm these predictions, both qualitatively and quantitatively.

At higher Reynolds number, the boundary layers originating at the bubble surface and wall become thin and no longer interact significantly. This makes the flow in the gap almost irrotational, which results in an attractive transverse force as predicted by potential flow theory. However, for a rigid sphere, the thickness of the boundary layer originating at its surface hardly changes beyond $Re \approx 50$. Due to the continuous increase of the surface vorticity, vortical interaction between the wall and the wake remains considerable. Indeed, present computational results indicate that the transverse force acting on a rigid sphere never reverses. Moreover, Predictions according to the vortical mechanism match well with the numerical data up to $Re = 100$ provided that $L_R \gtrsim 4$.

At smaller separation distances, two threads with significant value of streamwise vorticity develop close to the lower half of the sphere surface, owing to the local shear arising from the translation of the sphere with respect to the wall. Downstream of the sphere, they are concentrated into two

threads of a horseshoe vortex, causing a repulsive transverse force. Consequently, for a clean bubble the attractive transverse force for Reynolds numbers of $O(10^2)$ is significantly decreased. In contrast, for a rigid sphere, the decay of the transverse force generated by the vortical mechanism as Re increases is partially compensated.

6.1.3 Wall-bounded linear shear flow

When an ambient shear is involved, the interaction between the boundary layers originating at the sphere surface and wall at high Reynolds number is affected by the following distinct processes. First, the shear induces a horseshoe vortex in the wake, making the interaction dependent on the sign of Sr and the nature of the sphere surface. Indeed, this vortex deflects the fluid located within the wake towards (resp. away from) the wall provided that the sphere lags the fluid and the sphere surface obeys a free-slip (resp. no-slip) condition, enhancing (resp. lightening) the interaction. Besides, the generation of the surface vorticity is also modified by the shear. Indeed, for the specified boundary condition to be satisfied at the sphere surface in the presence of an ambient shear, a shear-flow type correction has to take place within the boundary layer. For a clean spherical bubble (resp. rigid sphere), at the surface of which the free-slip (resp. no-slip) condition applies, the correction yields an additional positive (resp. negative) vorticity component therein when the sphere lags the fluid. Hence this vorticity correction cooperates with (resp. mitigates) the primary positive vorticity on the wall-bounded side. Consequently, the intensity of the overall vorticity there is increased (decreased), enhancing (resp. lightening) the interaction. Lastly, the intensity of the vorticity within the shear layer at the wall is also modified by the shear, owing to the shift of the surface vorticity by the shear. Unlike the two processes mentioned above, this process depends solely on the sign of Sr . It results in an increase (resp. decrease) of the vorticity within the shear layer at the wall if the sphere lags (resp. leads) the fluid, enhancing (resp. lightening) the interaction. Not surprisingly, this shift is more pronounced in cases concerning a rigid sphere, owing to the significantly higher value of surface vorticity than that around a clean bubble. Most of the variations of the drag and lift forces at high Reynolds number could be understood by a combination of the processes mentioned above, except for the variation of the lift acting on a rigid sphere beyond $Re \approx 100$. There, the onset of an imperfect bifurcation pumps extra energy into the generation of the transverse force, the direction of which depends on the relative intensity of the perturbation induced by the shear and that due to the wall. No such bifurcation occurs in the case of a clean bubble, as the flow field in situations with a clean bubble subjected to the uniform stream remains axisymmetric however large the Reynolds number.

These deviations gradually vanish as the Reynolds number decreases. In the low-Reynolds-number range, the inner-region solution in Magnaudet et al. (2003) indicates that the drag modification and the lift force result from two contributions. One is due to the wall effect and depends on L_R only. The other is due to the presence of the shear and depends linearly and quadratically on Sr , although it is also altered by the wall proximity. Specifically, their analysis indicates that the leading-order terms of the forces acting on a clean bubble differ from those on a rigid sphere only by a numerical factor of $(2/3)^2$. Present computational results confirm these predictions.

6.2 Future work

One of the future goals of the investigation on wall-bounded multiphase flows is to gain the insight into the effects on the dispersed phase caused by the wall and the ambient flow as well as the wall-

shear interactions. Present work is restricted to situations with spheres moving stream-wise in wall-bounded linear shear flows. Two possible research directions closely related to the present work are:

(i) Cross-stream moving sphere in a wall-bounded linear shear flow. This future work together with the present one would facilitate a general understanding of the near-wall interactions with the sphere moving in arbitrary directions. In the unbound limit, the general solution was considered in Candelier et al. (2019). Meanwhile, an asymptotic solution in situations where the wall lies in the inner region of the disturbance has been obtained by Magnaudet et al. (2003). Practical situations always lay between the two limits, in which DNS and experimental investigation would be highly appreciated.

(ii) Stream-wise moving sphere in a parabolic shear flow. Practical flows are always pressure driven, not moving-wall driven. For practical purposes, it is necessary to take into account the effects caused by the curvature of the unperturbed velocity. In the unbounded limit, the general solution was considered in Asmolov (1999). Meanwhile, an asymptotic solution in situations where the wall lies in the inner region of the disturbance has been obtained by Yahiaoui and Feuillebois (2010). Practical situations always lay between the two limits, in which DNS and experimental investigation would be highly appreciated.

7 REFERENCES

- Asmolov, E.S., 1989. Lift force exerted on a spherical particle in a laminar boundary layer. *Fluid Dynamics* 24, 710–714.
- Asmolov, E.S., 1990. Dynamics of a spherical particle in a laminar boundary layer. *Fluid Dynamics* 25, 886–890.
- Asmolov, E.S., 1999. The inertial lift on a spherical particle in a plane Poiseuille flow at large channel Reynolds number. *Journal of Fluid Mechanics* 381, 63–87.
- Auguste, F. and Magnaudet, J., 2018. Path oscillations and enhanced drag of light rising spheres. *Journal of Fluid Mechanics* 841, 228–266.
- Auton, T. R., 1987. The lift force on a spherical body in a rotational flow. *Journal of Fluid Mechanics* 183, 199–218.
- Bagchi, P., and Balachandar, S., 2002. Effect of free rotation on the motion of a solid sphere in linear shear flow at moderate Re. *Physics of Fluids* 14, 2719–2737.
- Batchelor, G.K., 1967. *An introduction to fluid dynamics*. Cambridge University Press.
- Biesheuvel, A. and Van Wijngaarden, L., 1982. The motion of pairs of gas bubbles in a perfect liquid. *Journal of Engineering Mathematics* 16, 349–365.
- Bluemink, J. J., Lohse, D., Prosperetti, A., and Van Wijngaarden, L., 2008. A sphere in a uniformly rotating or shearing flow. *Journal of Fluid Mechanics* 600, 201–233.
- Brennen, C.E., 2014. *Cavitation and bubble dynamics*. Cambridge University Press.
- Bretherton, F.P., 1962. The motion of rigid particles in a shear flow at low Reynolds number. *Journal of Fluid Mechanics* 14, 284–304.
- Calmet, I. and Magnaudet, J., 1997. Large-eddy simulation of high-Schmidt number mass transfer in a turbulent channel flow. *Physics of Fluids* 9, 438–455.
- Candelier, F., Mehlig, B. and Magnaudet, J., 2019. Time-dependent lift and drag on a rigid body in a viscous steady linear flow. *Journal of Fluid Mechanics* 864, 554–595.
- Charru, F., Andreotti, B. and Claudin, P., 2013. Sand ripples and dunes. *Annual Review of Fluid Mechanics* 45, 469–493.
- Cherukat, P. and McLaughlin, J.B., 1990. Wall-induced lift on a sphere. *International Journal of Multiphase Flow* 16, 899–907.
- Cherukat, P. and McLaughlin, J.B., 1994. The inertial lift on a rigid sphere in a linear shear flow field near a flat wall. *Journal of Fluid Mechanics* 263, 1–18 (and Corrigenda 1995. *Journal of Fluid Mechanics* 285, 407).
- Cherukat, P., McLaughlin, J. B., and Dandy, D. S., 1999. A computational study of the inertial lift on a sphere in a linear shear flow field. *International Journal of Multiphase Flow* 25, 15–33.
- Cherukat, P., McLaughlin, J.B. and Graham, A.L., 1994. The inertial lift on a rigid sphere translating in a linear shear flow field. *International Journal of Multiphase Flow* 20, 339–353.
- Chiu, Y.-Y., Huang, C.-K. and Lu, Y.-W., 2016. Enhancement of microfluidic particle separation using cross-flow filters with hydrodynamic focusing. *Biomicrofluidics* 10, 011906.

- Citro, V., Tchoufag, J., Fabre, D., Giannetti, F. and Luchini, P., 2016. Linear stability and weakly nonlinear analysis of the flow past rotating spheres. *Journal of Fluid Mechanics* 807, 62–86.
- Cox, R.G. and Brenner, H., 1968. The lateral migration of solid particles in Poiseuille flow—I Theory. *Chemical Engineering Science* 23, 147–173.
- Cox, R.G. and Hsu, S.K., 1977. The lateral migration of solid particles in a laminar flow near a plane. *International Journal of Multiphase Flow* 3, 201–222.
- Dandy, D. S., and Dwyer, H. A., 1990. A sphere in shear flow at finite Reynolds number: effect of shear on particle lift, drag, and heat transfer. *Journal of Fluid Mechanics* 216, 381–410.
- Drew, D. A., 1983. Mathematical modeling of two-phase flow. *Annual Review of Fluid Mechanics* 15, 261–291.
- Drew, D.A., 1988. The lift force on a small sphere in the presence of a wall. *Chemical Engineering Science* 43, 769–773.
- Elghobashi, S., 2019. Direct numerical simulation of turbulent flows laden with droplets or bubbles. *Annual Review of Fluid Mechanics* 51, 217–244.
- Fabre, D., Auguste, F. and Magnaudet, J., 2008. Bifurcations and symmetry breaking in the wake of axisymmetric bodies. *Physics of Fluids* 20, 051702.
- Fischer, T.M. and Rosenberger, R., 1987. A boundary integral method for the numerical computation of the forces exerted on a sphere in viscous incompressible flows near a plane wall. *Zeitschrift für angewandte Mathematik und Physik ZAMP* 38, 339–365.
- Giacobello, M., Ooi, A. and Balachandar, S., 2009. Wake structure of a transversely rotating sphere at moderate Reynolds numbers. *Journal of Fluid Mechanics* 621, 103–130.
- Hadikhani, P., Hashemi, S.M.H., Balestra, G., Zhu, L., Modestino, M.A., Gallaire, F. and Psaltis, D., 2018. Inertial manipulation of bubbles in rectangular microfluidic channels. *Lab on a Chip* 18, 1035–1046.
- Hinch, E.J., 1991. Perturbation methods. Cambridge University Press.
- Homann, H., Bec, J., and Grauer, R., 2013. Effect of turbulent fluctuations on the drag and lift forces on a towed sphere and its boundary layer. *Journal of Fluid Mechanics* 721, 155–179.
- Hölzer, A., and Sommerfeld, M., 2009. Lattice Boltzmann simulations to determine drag, lift and torque acting on non-spherical particles. *Computers and Fluids* 38, 572–589.
- Johnson, T.A. and Patel, V.C., 1999. Flow past a sphere up to a Reynolds number of 300. *Journal of Fluid Mechanics* 378, 19–70.
- Kaplun, S., and Lagerstrom, P. A., 1957. Asymptotic expansions of Navier-Stokes solutions for small Reynolds numbers. *Journal of Mathematics and Mechanics* 6, 585–593.
- Kim, D. and Choi, H., 2002. Laminar flow past a sphere rotating in the streamwise direction. *Journal of Fluid Mechanics* 461, 365–386.
- Kim, D., Choi, H., and Choi, H., 2005. Characteristics of laminar flow past a sphere in uniform shear. *Physics of Fluids* 17, 103602.

- Kim, I., 2006. Forces on a spherical particle in shear flow at intermediate Reynolds numbers. *International Journal of Computational Fluid Dynamics* 20, 137–141.
- Kok, J.B., 1993. W. Dynamics of a pair of gas bubbles moving through liquid part I. Theory. *European Journal of Mechanics - B/Fluids* 12, 515–540.
- Kok, M.P., Segers, T. and Versluis, M., 2015. Bubble sorting in pinched microchannels for ultrasound contrast agent enrichment. *Lab on a Chip* 15, 3716–3722.
- Krishnan, G.P. and Leighton Jr, D.T., 1995. Inertial lift on a moving sphere in contact with a plane wall in a shear flow. *Physics of Fluids* 7, 2538–2545.
- Kurose, R., and Komori, S., 1999. Drag and lift forces on a rotating sphere in a linear shear flow. *Journal of Fluid Mechanics* 384, 183–206.
- Lee, H. and Balachandar, S., 2010. Drag and lift forces on a spherical particle moving on a wall in a shear flow at finite Re. *Journal of Fluid Mechanics* 657, 89–125.
- Lee, S., and Wilczak, J. M., 2000. The effects of shear flow on the unsteady wakes behind a sphere at moderate Reynolds numbers. *Fluid Dynamics Research* 27, 1–22.
- Legendre, D., and Magnaudet, J., 1997. A note on the lift force on a spherical bubble or drop in a low-Reynolds-number shear flow. *Physics of Fluids* 9, 3572–3574.
- Legendre, D., and Magnaudet, J., 1998. The lift force on a spherical bubble in a viscous linear shear flow. *Journal of Fluid Mechanics* 368, 81–126.
- Leighton, D. and Acrivos, A., 1985. The lift on a small sphere touching a plane in the presence of a simple shear flow. *Zeitschrift für angewandte Mathematik und Physik ZAMP* 36, 174–178.
- Lighthill, M. J., 1956. Drift. *J. Fluid Mech. Journal of Fluid Mechanics* 1, 31–53 (and Corrigenda 1957. *Journal of Fluid Mechanics* 2, 311).
- Loth, E., 2008. Lift of a spherical particle subject to vorticity and/or spin. *AIAA Journal* 46, 801–809.
- Lovalenti, P.M., 1994. The force on a sphere in a simple shear flow. Appendix A to Cherukat & McLaughlin. *Journal of Fluid Mechanics* 263, 1–18.
- Magnaudet, J. and Eames, I., 2000. The motion of high-Reynolds-number bubbles in inhomogeneous flows. *Annual Review of Fluid Mechanics* 32, 659–708.
- Magnaudet, J. and Mougin, G., 2007. Wake instability of a fixed spheroidal bubble. *Journal of Fluid Mechanics* 572, 311–337.
- Magnaudet, J., Rivero, M. and Fabre, J., 1995. Accelerated flows past a rigid sphere or a spherical bubble. Part 1. Steady straining flow. *Journal of Fluid Mechanics* 284, 97–135.
- Magnaudet, J., Takagi, S., and Legendre, D., 2003. Drag, deformation and lateral migration of a buoyant drop moving near a wall. *Journal of Fluid Mechanics* 476, 115–157.
- Magnaudet, J., 2011. A ‘reciprocal’ theorem for the prediction of loads on a body moving in an inhomogeneous flow at arbitrary Reynolds number. *Journal of Fluid Mechanics* 689, 564–604.
- Maxey, M., 2017. Simulation methods for particulate flows and concentrated suspensions. *Annual Review of Fluid Mechanics* 49, 171–193.

- McLaughlin, J. B., 1991. Inertial migration of a small sphere in linear shear flows. *Journal of Fluid Mechanics* 224, 261–274.
- McLaughlin, J.B., 1993. The lift on a small sphere in wall-bounded linear shear flows. *Journal of Fluid Mechanics*, 246, 249–265.
- Mei, R., 1992. An approximate expression for the shear lift force on a spherical particle at finite Reynolds number. *International Journal of Multiphase Flow* 18, 145–147.
- Mei, R., Klausner, J.F. and Lawrence, C.J., 1994. A note on the history force on a spherical bubble at finite Reynolds number. *Physics of Fluids* 6, 418–420.
- Miloh, T., 1977. Hydrodynamics of deformable contiguous spherical shapes in an incompressible inviscid fluid. *Journal of Engineering Mathematics* 11, 349–372.
- O'Neill, M.E. and Stewartson, K., 1967. On the slow motion of a sphere parallel to a nearby plane wall. *Journal of Fluid Mechanics* 27, 705–724.
- Paiè, P., Bragheri, F., Di, D.C. and Osellame, R., 2017. Particle focusing by 3D inertial microfluidics. *Microsystems & Nanoengineering* 3, 17027.
- Proudman, I., and Pearson, J. R. A., 1957. Expansions at small Reynolds numbers for the flow past a sphere and a circular cylinder. *Journal of Fluid Mechanics* 2, 237–262.
- Risso, F., 2018. Agitation, mixing, and transfers induced by bubbles. *Annual Review of Fluid Mechanics* 50, 25–48.
- Saffman, P. G. T., 1965. The lift on a small sphere in a slow shear flow. *Journal of Fluid Mechanics* 22, 385–400 (and Corrigenda 1968. *Journal of Fluid Mechanics* 31, 624).
- Salem, M. B., and Oesterle, B., 1998. A shear flow around a spinning sphere: numerical study at moderate Reynolds numbers. *International Journal of Multiphase Flow* 24, 563–585.
- Santarelli, C., and Fröhlich, J., 2015. Direct numerical simulations of spherical bubbles in vertical turbulent channel flow. *International Journal of Multiphase Flow* 75, 174–193.
- Santarelli, C., and Fröhlich, J., 2016. Direct Numerical Simulations of spherical bubbles in vertical turbulent channel flow. Influence of bubble size and bidispersity. *International Journal of Multiphase Flow* 81, 27–45.
- Schiller, L. and Naumann, A., 1933. On the Basic Calculations of Gravity Processing. *Z. Vereines German Inge.* 77, 318–321.
- Shampine, L. F., 2008. Vectorized adaptive quadrature in MATLAB. *Journal of Computational and Applied Mathematics* 211, 131–140.
- Sherwood, J.D., 2001. Steady rise of a small spherical gas bubble along the axis of a cylindrical pipe at high Reynolds number. *European Journal of Mechanics-B/Fluids* 20, 399–414.
- Shi, P. and Rzehak, R., 2019. Lift Forces on Solid Spherical Particles in Unbounded Flows. *Chemical Engineering Science* 208, 115145.
- Shi, P. and Rzehak, R., 2020. Lift Forces on Solid Spherical Particles in Wall-bounded Flows, *Chemical Engineering Science* 211, 115264.

- Shi, P., Rzehak, R., Lucas, D., and Magnaudet, J., 2020a. Hydrodynamic forces on a clean spherical bubble translating in a wall-bounded linear shear flow, *Physical Review Fluids*, in revision.
- Shi, P., Rzehak, R., Lucas, D., and Magnaudet, J., 2020b. Hydrodynamic forces on a rigid sphere translating in a wall-bounded linear shear flow, *Physical Review Fluids*, to be submitted.
- Sinha, S.L., Dewangan, S.K. and Sharma, A., 2017. A review on particulate slurry erosive wear of industrial materials: In context with pipeline transportation of mineral– slurry. *Particulate Science and Technology* 35, 103–118.
- Subramaniam, S., 2013. Lagrangian-Eulerian methods for multiphase flows. *Progress in Energy and Combustion Science* 39, 215–245.
- Sugioka, K.I. and Komori, S., 2009. Drag and lift forces acting on a spherical gas bubble in homogeneous shear liquid flow. *Journal of Fluid Mechanics* 629, 173–193.
- Sugioka, K.I. and Tsukada, T., 2015. Direct numerical simulations of drag and lift forces acting on a spherical bubble near a plane wall. *International Journal of Multiphase Flow* 71, 32–37.
- Takagi, S. and Matsumoto, Y., 1998. Numerical study on the forces acting on a bubble and particle. *Proceedings of the 3rd International Conference on Multiphase Flow*. Lyon, France.
- Takagi, S. and Matsumoto, Y., 2011. Surfactant effects on bubble motion and bubbly flows. *Annual Review of Fluid Mechanics* 43, 615–636.
- Takemura, F., 2004. Migration velocities of spherical solid particles near a vertical wall for Reynolds number from 0.1 to 5. *Physics of Fluids* 16, 204–207.
- Takemura, F. and Magnaudet, J., 2003. The transverse force on clean and contaminated bubbles rising near a vertical wall at moderate Reynolds number. *Journal of Fluid Mechanics* 495, 235–253.
- Takemura, F. and Magnaudet, J., 2009. Lateral migration of a small spherical buoyant particle in a wall–bounded linear shear flow. *Physics of Fluids* 21, 083303.
- Takemura, F., Magnaudet, J. and Dimitrakopoulos, P., 2009. Migration and deformation of bubbles rising in a wall–bounded shear flow at finite Reynolds number. *Journal of Fluid Mechanics* 634, 463–486.
- Takemura, F., Takagi, S., Magnaudet, J. and Matsumoto, Y., 2002. Drag and lift forces on a bubble rising near a vertical wall in a viscous liquid. *Journal of Fluid Mechanics* 461, 277–300.
- Vasseur, P. and Cox, R.G., 1977. The lateral migration of spherical particles sedimenting in a stagnant bounded fluid. *Journal of Fluid Mechanics* 80, 561–591.
- van Wijngaarden, L. and Jeffrey, D.J., 1976. Hydrodynamic interaction between gas bubbles in liquid. *Journal of Fluid Mechanics* 77, 27–44.
- Yahiaoui, S. and Feuillebois, F., 2010. Lift on a sphere moving near a wall in a parabolic flow. *Journal of Fluid Mechanics* 662, 447–474.
- Zeng, L., Balachandar, S. and Fischer, P., 2005. Wall–induced forces on a rigid sphere at finite Reynolds number. *Journal of Fluid Mechanics* 536, 1–25.
- Zeng, L., Najjar, F., Balachandar, S. and Fischer, P., 2009. Forces on a finite–sized particle located close to a wall in a linear shear flow. *Physics of Fluids* 21, 033302.

Zhou, Z., Jin, G., Tian, B. and Ren, J., 2017. Hydrodynamic force and torque models for a particle moving near a wall at finite particle Reynolds numbers. *International Journal of Multiphase Flow* 92, 1–19.